

Device	Password Type	Purpose	Value
R-Annex	Enable secret	Privileged EXEC access	Ann3x!Rtr25
R-Annex	Console password	Local console (line con 0) login	C0ns!Annex
R-Annex	SSH local user	Remote access (VTY, login local)	netadmin / Annex@SSH25
Annex-L3	Enable secret	Privileged EXEC access	L3Annex!25
Annex-L3	Console password	Local console (line con 0) login	C0nsL3!Annex
Annex-L3	SSH local user	Remote access (VTY, login local)	netadmin / L3Annex@SSH25
Annex-L3	VTP password	VLAN database sync (VTP client)	AITC@vTp25
SW-IT	Enable secret	Privileged EXEC access	ITOff!Sw25
SW-IT	Console password	Local console (line con 0) login	C0ns!ITOff
SW-IT	SSH local user	Remote access (VTY, login local)	netadmin / ITOff@SSH25
SW-IT	VTP password	VLAN database sync (VTP client)	AITC@vTp25
SW-Faculty	Enable secret	Privileged EXEC access	Fac!Sw25
SW-Faculty	Console password	Local console (line con 0) login	C0ns!Fac
SW-Faculty	SSH local user	Remote access (VTY, login local)	netadmin / Fac@SSH25
SW-Faculty	VTP password	VLAN database sync (VTP client)	AITC@vTp25

SWA-TR1	Enable secret	Privileged EXEC access	TR1!Sw25
SWA-TR1	Console password	Local console (line con 0) login	C0ns!TR1
SWA-TR1	SSH local user	Remote access (VTY, login local)	netadmin / TR1@SSH25
SWA-TR1	VTP password	VLAN database sync (VTP client)	AITC@vTp25
SWA-TR2	Enable secret	Privileged EXEC access	TR2!Sw25
SWA-TR2	Console password	Local console (line con 0) login	C0ns!TR2
SWA-TR2	SSH local user	Remote access (VTY, login local)	netadmin / TR2@SSH25

ACLS:

NAT Annex Inside: (R-Annex)

- Internal subnets that are eligible for NAT/PAT translation when leaving through the WAN interface.
- Standard ACL

```
ip access-list standard
NAT-ANNEX-INSIDE permit 192.168.0.0
0.0.1.255
```

```
ip nat inside source list NAT-ANNEX-INSIDE int gig0/0/0 overload
```

Internet-IN: (R-Annex - g0/0/0)

- Internet hosts may only send traffic into the Annex network if it is a response to a session initiated internally.
- ICMP diagnostics needed for outbound ping/traceroute to function are explicitly permitted back in.
- Extended ACL

```
ip access-list extended
INTERNET-IN permit tcp any any
established permit icmp any any
echo-reply permit icmp any any
ttl-exceeded permit icmp any
any unreachable deny ip any any
```

```
int gig0/0/0
ip access-group INTERNET-IN in
exit
```

ANNEX-L3:

```
ip access-list extended STUDENTS-ACL
  deny ip 192.168.0.0 0.0.0.127
192.168.0.128 0.0.0.31
  permit ip any any
```

```
ip access-list extended
INSTRUCTORS-ACL
  deny ip 192.168.0.160
0.0.0.15 192.168.0.128
0.0.0.31
  permit ip any any
```

```
int vlan 10
  ip access-group STUDENTS-ACL
in
exit
```

```
int vlan 20
  ip access-group
INSTRUCTORS-ACL in
exit
```