

QA test credentials

Support Ticketing System — ITG Group

One account per role, for testing what each role can and cannot reach. All seven share the same password.

These accounts exist only in Development. They are created by RoleAccountSeeder, which refuses to run under any other environment name, and the application refuses to start in Production if the flag that enables them is switched on. Do not create equivalents on a live system: one shared password written down in a document is exactly the arrangement this system is built to prevent everywhere else.

Sign in

Address `http://localhost:5173`

Password `TestDesk!Pass#2026`

Organization ITG Group (ITG)

Accounts

Role	Email	Perms	Should be able to
Super Admin	<code>superadmin@itg.test</code>	55	Everything, including deleting users and editing system settings.
Administrator	<code>administrator@itg.test</code>	17	Users, roles, teams, categories and SLA policies. Not reporting.
Manager	<code>manager@itg.test</code>	42	Reports, the audit log and every ticket in the organization. No administration.
Team Lead	<code>lead@itg.test</code>	35	Their team's queue, assignment and escalation, plus reports.
Technical Specialist	<code>specialist@itg.test</code>	25	Tickets assigned to their team, including internal notes.
Support Agent	<code>agent@itg.test</code>	23	Their team's tickets: comment, resolve, log work.
Requester	<code>requester@itg.test</code>	10	Only tickets they raised. Must never see an internal note.

Permission counts are the seeded defaults. They change the moment an administrator edits a role, so a count here that no longer matches Administration → Roles is a sign the role was edited, not that this sheet is broken.

Worth checking first

These are the behaviours most likely to be wrong in a system of this kind, and the quickest to confirm.

1. Scope is enforced, not hidden

Sign in as the Requester and open a ticket ID raised by somebody else. The answer must be 404, not 403 — a 403 would confirm the ticket exists.

2. Internal notes stay internal

As an Agent, add a comment marked internal. Sign in as the Requester who raised that ticket. The note must not appear, in the page or in the network response.

3. Administration is closed to Managers

As the Manager, open Administration → Users. Expect to be refused; the Manager role carries reporting, not user management.

4. A deleted person keeps their history

As Super Admin, delete an account that raised a ticket. The ticket must survive and read “Deleted user” rather than disappearing.

5. Passwords are not recoverable

Create a user in Administration. The temporary password is shown once. Reload before using it and it is gone — reset it rather than guessing.

Notes

Team-scoped roles see nothing until they are on a team. Team Lead, Technical Specialist and Support Agent have a Team data scope, so their queues are empty until an administrator adds them to a team under Administration → Teams. An empty queue for those three is configuration, not a defect.

Sign-ins are rate limited to ten per minute from one address. Switching between all seven accounts in quick succession will start returning 401 — wait a minute rather than concluding a password is wrong.

Deleting an account is permanent. There is no restore. To recreate these seven after deleting one, restart the API: the seeder adds only what is missing and leaves existing passwords alone.