

Ombre Paints

Sequence of Colors



PRIMER · PUTTY · EMULSIONS · WEATHER COATS · ENAMELS

PRODUCT CATALOGUE

Sequence of Colours

2026

WELCOME, OMBRÉ PAINTS

Welcome to Ombré Paints, where a sequence of colours meets lasting protection. From the first coat of primer to the final stroke of enamel, our range is built to take every surface from raw to remarkable.

Our portfolio follows the way a wall is actually painted: Wall Primer and Wall Putty prepare the surface, Super and Luxury Emulsions bring interiors to life, Weather Shield and Weather Pro defend exteriors against sun and rain, and Matt and Synthetic Enamels finish doors, windows and metalwork.

Whether you are a contractor, a dealer or a homeowner, every Ombré product is formulated for smooth application, rich colour and dependable performance.



Wall Primer



Wall Putty



Super Emulsion



Luxury Emulsion



Weather Shield



Weather Pro



Matt Enamel



Synthetic Enamel

TABLE OF CONTENTS

Primer to Enamel

01 PRIMER

- **Wall Primer** **04**
For interior walls · 100% acrylic based

02 PUTTY

- **Wall Putty** **06**
For interior walls · 100% acrylic based

03 EMULSIONS

- **Super Emulsion** **08**
For interior walls · Smooth finish walls
- **Luxury Emulsion** **10**
For interior walls · Extra coverage

04 WEATHER COATS

- **Weather Shield** **12**
For exterior walls · 100% acrylic based
- **Weather Pro** **14**
For exterior walls · Beauty that protects

05 ENAMELS

- **Matt Enamel** **16**
All-in-one acrylic / sealer / undercoat
- **Synthetic Enamel** **18**
High gloss finish for wood and metal

Wall Primer

For interior walls · 100% acrylic based

GENERAL DESCRIPTION

Ombré Wall Primer is a 100% acrylic, water-based undercoat for interior walls. It seals porous plaster and cement surfaces, evens out suction and creates a uniform, high-adhesion base so that emulsion topcoats achieve better coverage, truer colour and a smoother finish.

PACK SIZE

3.64 Litres and 18.2 Litres.

COLOUR RANGE

White (can be tinted)

FINISH

Flat matt

VOLUME SOLIDS

32 ± 2% (nominal)

FILM THICKNESS / COAT

Dry: 25–30 Micrometers

TOUCH DRY

30–60 Minutes

RECOAT

2–4 Hours

THEORETICAL COVERAGE

A guide to the theoretical coverage which can be achieved under normal conditions is 10–12 m²/litre/coat.

APPLICATION

Brush, Roller or Spray

THINNING

10–20% with clean water.

CLEANING UP

Wash all equipment with clean water immediately after use.

SURFACE PREPARATION

Surfaces must be clean, dry and free from dust, grease, oil, loose paint and efflorescence. Repair cracks and holes, then apply one to two coats of Ombré Wall Primer and allow to dry fully before the putty or emulsion coat.

SAFETY, HEALTH & ENVIRONMENT

Keep out of reach of children. Avoid contact with skin and eyes; if contact occurs, rinse with plenty of water. Ensure good ventilation during application and drying. Do not empty residues into drains or watercourses; dispose of waste responsibly.



Wall Primer

CODE : 0001

High durable · Water based · Excellent opacity · Good flow

Wall Putty

For interior walls · 100% acrylic based

02

GENERAL DESCRIPTION	Ombré Wall Putty is a ready-to-use, 100% acrylic based smoothing compound for interior walls. It fills pores, hairline cracks and surface imperfections, spreads easily, sands to a fine finish and leaves a flat, level base for primer and emulsion.
PACK SIZE	5 kg and 20 kg.
COLOUR RANGE	White
FINISH	Flat, sandable
VOLUME SOLIDS	65 ± 2% (nominal)
FILM THICKNESS / COAT	Dry: 0.5-1.0 mm per coat
TOUCH DRY	1-2 Hours
RECOAT	4-6 Hours (before sanding)
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 2-3 m ² /kg/coat.
APPLICATION	Putty Knife / Trowel
THINNING	Ready to use. Do not add water unless advised.
CLEANING UP	Wash tools with clean water before the putty hardens.
SURFACE PREPARATION	Remove loose material, dust, oil and old flaking paint. Dampen very dry surfaces lightly. Apply in thin, even coats, let each coat dry completely and sand smooth with fine abrasive paper. Prime before painting.
SAFETY, HEALTH & ENVIRONMENT	Keep out of reach of children. Avoid contact with skin and eyes; if contact occurs, rinse with plenty of water. Ensure good ventilation during application and drying. Do not empty residues into drains or watercourses; dispose of waste responsibly.



Wall Putty

CODE : 0002

High durable · Water based · Excellent opacity · Good flow

Super Emulsion

For interior walls · Smooth finish walls

03

GENERAL DESCRIPTION	Ombré Super Emulsion is a 100% acrylic based, water-borne paint for interior walls and ceilings. It delivers a smooth, uniform matt finish with good opacity and flow, in a wide range of shades from the Ombré colour system.
PACK SIZE	3.64 Litres and 18.2 Litres.
COLOUR RANGE	Wide range of shades via the Ombré colour system
FINISH	Smooth matt
VOLUME SOLIDS	38 ± 2% (nominal)
FILM THICKNESS / COAT	Dry: 30-40 Micrometers
TOUCH DRY	30-60 Minutes
RECOAT	2-4 Hours
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 11-13 m ² /litre/coat.
APPLICATION	Brush, Roller or Spray
THINNING	10-20% with clean water.
CLEANING UP	Wash all equipment with clean water immediately after use.
SURFACE PREPARATION	Surfaces must be clean, dry, sound and free from dust, grease and loose paint. Apply Ombré Wall Primer (and Wall Putty where needed) first. Apply two coats of Super Emulsion, allowing each coat to dry before the next.
SAFETY, HEALTH & ENVIRONMENT	Keep out of reach of children. Avoid contact with skin and eyes; if contact occurs, rinse with plenty of water. Ensure good ventilation during application and drying. Do not empty residues into drains or watercourses; dispose of waste responsibly.



Super Emulsion

CODE : 0003

High durable · Water based · Scratch-resistant quality · Good flow

Luxury Emulsion

For interior walls · Extra coverage

04

GENERAL DESCRIPTION	Ombré Luxury Emulsion is a premium, extra-coverage interior emulsion with excellent flow and levelling. It gives a rich, luxurious smooth finish with long-lasting colours, strong durability and resistance to hairline cracking.
PACK SIZE	3.64 Litres and 18.2 Litres.
COLOUR RANGE	Wide range of shades via the Ombré colour system
FINISH	Silk / soft sheen
VOLUME SOLIDS	42 ± 2% (nominal)
FILM THICKNESS / COAT	Dry: 35-45 Micrometers
TOUCH DRY	30-60 Minutes
RECOAT	2-4 Hours
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 12-14 m ² /litre/coat.
APPLICATION	Brush, Roller or Spray
THINNING	10-15% with clean water.
CLEANING UP	Wash all equipment with clean water immediately after use.
SURFACE PREPARATION	Surfaces must be clean, dry, sound and free from dust, grease and loose paint. Prime with Ombré Wall Primer, fill with Wall Putty where needed and sand smooth. Apply two coats of Luxury Emulsion, allowing each coat to dry before the next.
SAFETY, HEALTH & ENVIRONMENT	Keep out of reach of children. Avoid contact with skin and eyes; if contact occurs, rinse with plenty of water. Ensure good ventilation during application and drying. Do not empty residues into drains or watercourses; dispose of waste responsibly.



Luxury Emulsion

CODE : 0004

Excellent flow & levelling · Long-lasting colours · Hairline crack resistant

Weather Shield

For exterior walls · 100% acrylic based

GENERAL DESCRIPTION	Ombré Weather Shield is a 100% acrylic based exterior emulsion that protects walls against sun, rain and dust while keeping colours fresh. It forms a flexible, water-resistant film with a smooth finish on cement plaster, concrete and masonry.
PACK SIZE	3.64 Litres and 18.2 Litres.
COLOUR RANGE	Wide range of shades via the Ombré colour system
FINISH	Smooth matt
VOLUME SOLIDS	42 ± 2% (nominal)
FILM THICKNESS / COAT	Dry: 35-45 Micrometers
TOUCH DRY	30-60 Minutes
RECOAT	3-4 Hours
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 9-11 m ² /litre/coat.
APPLICATION	Brush, Roller or Spray
THINNING	10-15% with clean water.
CLEANING UP	Wash all equipment with clean water immediately after use.
SURFACE PREPARATION	Remove algae, efflorescence, dirt and loose paint. Surfaces must be clean, dry and sound. Repair cracks, apply a suitable exterior primer, then two coats of Weather Shield. Do not apply in rain or on damp walls.
SAFETY, HEALTH & ENVIRONMENT	Keep out of reach of children. Avoid contact with skin and eyes; if contact occurs, rinse with plenty of water. Ensure good ventilation during application and drying. Do not empty residues into drains or watercourses; dispose of waste responsibly.



Weather Shield

CODE : 0005

100% acrylic based · Eco-friendly · Smooth finish walls

Weather Pro

For exterior walls · Beauty that protects

GENERAL DESCRIPTION	Ombré Weather Pro is our premium exterior wall coating: beauty that protects. Its advanced acrylic formulation offers long-lasting protection against harsh weather, UV exposure and fading, keeping facades looking new for years.
PACK SIZE	3.64 Litres and 18.2 Litres.
COLOUR RANGE	Wide range of shades via the Ombré colour system
FINISH	Smooth satin
VOLUME SOLIDS	46 ± 2% (nominal)
FILM THICKNESS / COAT	Dry: 40–50 Micrometers
TOUCH DRY	30–60 Minutes
RECOAT	3–4 Hours
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 10–12 m ² /litre/coat.
APPLICATION	Brush, Roller or Spray
THINNING	5–10% with clean water.
CLEANING UP	Wash all equipment with clean water immediately after use.
SURFACE PREPARATION	Remove algae, efflorescence, dirt and loose paint. Surfaces must be clean, dry and sound. Repair cracks, apply a suitable exterior primer, then two coats of Weather Pro. Do not apply in rain or on damp walls.
SAFETY, HEALTH & ENVIRONMENT	Keep out of reach of children. Avoid contact with skin and eyes; if contact occurs, rinse with plenty of water. Ensure good ventilation during application and drying. Do not empty residues into drains or watercourses; dispose of waste responsibly.



Weather Pro

CODE : 0006

Long lasting protection · Beauty that protects

Matt Enamel

All-in-one acrylic / sealer / undercoat

GENERAL DESCRIPTION	Ombré Matt Enamel is an all-in-one acrylic, sealer and undercoat with excellent hiding power. It gives a smooth, durable matt finish with extra coverage, UV protection and resistance to colour fading, mould and dirt.
PACK SIZE	0.9l Litre and 3.64 Litres.
COLOUR RANGE	Wide range of shades via the Ombré colour system
FINISH	Matt
VOLUME SOLIDS	40 ± 2% (nominal)
FILM THICKNESS / COAT	Dry: 30-40 Micrometers
TOUCH DRY	1 Hour
RECOAT	4 Hours
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 11-13 m ² /litre/coat.
APPLICATION	Brush, Roller or Spray
THINNING	5-10% with clean water.
CLEANING UP	Wash all equipment with clean water immediately after use.
SURFACE PREPARATION	Surfaces must be clean, dry and free from wax, dust, rust, grease and loose paint. Sand glossy surfaces lightly. Apply two coats of Matt Enamel, allowing each coat to dry before the next.
SAFETY, HEALTH & ENVIRONMENT	Keep out of reach of children. Avoid contact with skin and eyes; if contact occurs, rinse with plenty of water. Ensure good ventilation during application and drying. Do not empty residues into drains or watercourses; dispose of waste responsibly.



Matt Enamel

CODE : 0007

UV protection · Resists colour fading · Resists mould & dirt · Easy to apply

Synthetic Enamel

High gloss finish for wood and metal

08

GENERAL DESCRIPTION	Ombré Synthetic Enamel is a solvent-based, high gloss finish for wood and metal. It offers extra coverage, a hard-wearing and easy-to-clean film, UV protection and resistance to fading, mould and weathering. Ideal for doors, windows, grills and railings.
PACK SIZE	0.9l Litre and 3.64 Litres.
COLOUR RANGE	Wide range of shades via the Ombré colour system
FINISH	High gloss
VOLUME SOLIDS	48 ± 2% (nominal)
FILM THICKNESS / COAT	Dry: 30-35 Micrometers
TOUCH DRY	3-4 Hours
RECOAT	16-24 Hours
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 12-14 m ² /litre/coat.
APPLICATION	Brush, Roller or Spray
THINNING	5-10% with Ombré thinner or mineral turpentine.
CLEANING UP	Clean all equipment with mineral turpentine immediately after use.
SURFACE PREPARATION	Surfaces that are new, bare, old or previously painted must be clean, dry and free from wax, dust, rust and any other unwanted material. Apply a suitable primer on bare wood or metal. After each coat, lightly sand with abrasive paper.
SAFETY, HEALTH & ENVIRONMENT	Highly flammable; keep container sealed, upright and away from children, ignition sources, food and extreme temperatures. Wear protective gear during use, avoid inhalation and contact with skin or eyes, and ensure good ventilation. Dispose of waste responsibly.



Synthetic Enamel

CODE : 0008

UV protection · Resists colour fading · Resists mould & dirt · Easy to apply



Ombré Paints

Sequence of Colors

Colour that protects. Finishes that last.

Thank you for choosing Ombré Paints. Our team is ready to help with product selection, colour guidance and dealer enquiries.

GET IN TOUCH

2026

PHONE

0334-9739730

EMAIL

shafaykazmi5@gmail.com

ADDRESS

Sihala, Islamabad, Pakistan