

Wall Primer

For interior walls · 100% acrylic based

GENERAL DESCRIPTION

Ombré Wall Primer is a 100% acrylic, water-based undercoat for interior walls. It seals porous plaster and cement surfaces, evens out suction and creates a uniform, high-adhesion base so that emulsion topcoats achieve better coverage, truer colour and a smoother finish.

PACK SIZE

3.64 Litres and 18.2 Litres.

COLOUR RANGE

White (can be tinted)

FINISH

Flat matt

VOLUME SOLIDS

32 ± 2% (nominal)

FILM THICKNESS / COAT

Dry: 25–30 Micrometers

TOUCH DRY

30–60 Minutes

RECOAT

2–4 Hours

THEORETICAL COVERAGE

A guide to the theoretical coverage which can be achieved under normal conditions is 10–12 m²/litre/coat.

APPLICATION

Brush, Roller or Spray

THINNING

10–20% with clean water.

CLEANING UP

Wash all equipment with clean water immediately after use.

SURFACE PREPARATION

Surfaces must be clean, dry and free from dust, grease, oil, loose paint and efflorescence. Repair cracks and holes, then apply one to two coats of Ombré Wall Primer and allow to dry fully before the putty or emulsion coat.

SAFETY, HEALTH & ENVIRONMENT

Keep out of reach of children. Avoid contact with skin and eyes; if contact occurs, rinse with plenty of water. Ensure good ventilation during application and drying. Do not empty residues into drains or watercourses; dispose of waste responsibly.



Wall Primer

CODE : 0001

High durable · Water based · Excellent opacity · Good flow