

Wall Putty

For interior walls · 100% acrylic based

02

GENERAL DESCRIPTION	Ombré Wall Putty is a ready-to-use, 100% acrylic based smoothing compound for interior walls. It fills pores, hairline cracks and surface imperfections, spreads easily, sands to a fine finish and leaves a flat, level base for primer and emulsion.
PACK SIZE	5 kg and 20 kg.
COLOUR RANGE	White
FINISH	Flat, sandable
VOLUME SOLIDS	65 ± 2% (nominal)
FILM THICKNESS / COAT	Dry: 0.5-1.0 mm per coat
TOUCH DRY	1-2 Hours
RECOAT	4-6 Hours (before sanding)
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 2-3 m ² /kg/coat.
APPLICATION	Putty Knife / Trowel
THINNING	Ready to use. Do not add water unless advised.
CLEANING UP	Wash tools with clean water before the putty hardens.
SURFACE PREPARATION	Remove loose material, dust, oil and old flaking paint. Dampen very dry surfaces lightly. Apply in thin, even coats, let each coat dry completely and sand smooth with fine abrasive paper. Prime before painting.
SAFETY, HEALTH & ENVIRONMENT	Keep out of reach of children. Avoid contact with skin and eyes; if contact occurs, rinse with plenty of water. Ensure good ventilation during application and drying. Do not empty residues into drains or watercourses; dispose of waste responsibly.



Wall Putty

CODE : 0002

High durable · Water based · Excellent opacity · Good flow