

Synthetic Enamel

High gloss finish for wood and metal

08

GENERAL DESCRIPTION	Ombré Synthetic Enamel is a solvent-based, high gloss finish for wood and metal. It offers extra coverage, a hard-wearing and easy-to-clean film, UV protection and resistance to fading, mould and weathering. Ideal for doors, windows, grills and railings.
PACK SIZE	0.9l Litre and 3.64 Litres.
COLOUR RANGE	Wide range of shades via the Ombré colour system
FINISH	High gloss
VOLUME SOLIDS	48 ± 2% (nominal)
FILM THICKNESS / COAT	Dry: 30-35 Micrometers
TOUCH DRY	3-4 Hours
RECOAT	16-24 Hours
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 12-14 m ² /litre/coat.
APPLICATION	Brush, Roller or Spray
THINNING	5-10% with Ombré thinner or mineral turpentine.
CLEANING UP	Clean all equipment with mineral turpentine immediately after use.
SURFACE PREPARATION	Surfaces that are new, bare, old or previously painted must be clean, dry and free from wax, dust, rust and any other unwanted material. Apply a suitable primer on bare wood or metal. After each coat, lightly sand with abrasive paper.
SAFETY, HEALTH & ENVIRONMENT	Highly flammable; keep container sealed, upright and away from children, ignition sources, food and extreme temperatures. Wear protective gear during use, avoid inhalation and contact with skin or eyes, and ensure good ventilation. Dispose of waste responsibly.



Synthetic Enamel

CODE : 0008

UV protection · Resists colour fading · Resists mould & dirt · Easy to apply