

Wood Dyer

Wood Colour

GENERAL DESCRIPTION

WOOD DYER Wood Colour is a premium-quality, fast-drying, highly transparent wood stain formulated to enhance and highlight the natural grain patterns of all types of wood surfaces. It provides deep penetration and rich coloration without obscuring the wood's inherent beauty. It is ideal for use on soft wood, hard wood, plywood, furniture, doors, windows, and high-end cabinetry

PACK SIZE

0.91 Litre and 3.64 Litres.

COLOUR RANGE

Available in a wide range of standard wood shades

WATER RESISTANCE

Designed to be over-coated; provides excellent structural stability against normal atmospheric humidity when sealed.

VOLUME SOLIDS

12± 2% (nominal)

FILM THICKNESS/COAT

Wet: 30-45 Micrometers

Dry: 17-25 Micrometers

DRYING TIMES

Depends on temperature, humidity, air movements and film thickness.

TOUCH DRY

15-20 Minutes

RECOAT

20-30 Minutes

THEORETICAL COVERAGE

A guide to the theoretical coverage which can be achieved under normal conditions is 12-14m²/litre/coat.

APPLICATION

Spray, Ragging, or Brush

CONVENTIONAL SPRAY

100-150% with WOOD DYER's Wood Thinner.

CLEANING UP

Clean all equipment with WOOD DYER's Wood Thinner immediately after use.

SURFACE PREPARATION

Surfaces that are new, bare, old, or previously painted need to be clean, dry, and free from wax, dust, rust, and any other unwanted materials. Apply WOOD DYER's Wood Lacquer to the surfaces and let them dry. After each coat, lightly sand the surface with abrasive paper.

SAFETY HEALTH AND ENVIRONMENTAL FORMATION

Highly flammable; keep container sealed, upright, and away from children, ignition sources, food, and extreme temperatures. Wear protective gear during use, avoid inhalation and contact with skin or eyes, and ensure good ventilation. Dispose of waste responsibly; toxic to aquatic life and may cause long-term harm.



Wood Color

CODE NA : 0003