

Wood Dyer

Wood Lacquer

GENERAL DESCRIPTION

WOOD DYER Lacquer is high quality, fast drying, clear topcoat lacquer for wooden surfaces. It gives beautiful Matt finish without hiding the wood grains. It is used on soft wood, hard wood, plywood, furniture, timber works such as doors, windows, tables, cupboards etc. It gives slip effects on the surface applied.

PACK SIZE

0.91 Litre and 3.64 Litres.

COLOUR RANGE

Clear

WATER RESISTANCE

Resistant to the levels of atmospheric humidity present in normal environment.

VOLUME SOLIDS

32± 2% (nominal)

FILM THICKNESS/COAT

Wet: 50-75 Micrometers

Dry: 17-25 Micrometers

DRYING TIMES

Depends on temperature, humidity, air movements and film thickness.

TOUCH DRY

15-20 Minutes

RECOAT

1-1.5 Hours

THEORETICAL COVERAGE

A guide to the theoretical coverage which can be achieved under normal conditions is 11-13m²/litre/coat.

APPLICATION

Spray

CONVENTIONAL SPRAY

100-150% with WOOD DYER's Wood Thinner.

CLEANING UP

Clean all equipment with WOOD DYER's Wood Thinner immediately after use.

SURFACE PREPARATION

Surfaces that are new, bare, old, or previously painted need to be clean, dry, and free from wax, dust, rust, and any other unwanted materials. Apply WOOD DYER's Wood Lacquer to the surfaces and let them dry. After each coat, lightly sand the surface with abrasive paper.

SAFETY HEALTH AND ENVIRONMENTAL FORMATION

Highly flammable; keep container sealed, upright, and away from children, ignition sources, food, and extreme temperatures. Wear protective gear during use, avoid inhalation and contact with skin or eyes, and ensure good ventilation. Dispose of waste responsibly; toxic to aquatic life and may cause long-term harm.



Wood Lacquer

CODE NA : 0002