

Wood Dyer

Wood Sealer

GENERAL DESCRIPTION

WOOD DYER Sealer penetrates and seals wood grain fibers for easy sanding. It enhances and warms the grain giving the look of natural wood. It is nitrocellulose based fast drying and bonding undercoat. Sanding Sealer can be used on plywood, furniture and bare timber work over new or previously finished surface.

PACK SIZE

0.91 Litre and 3.64 Litres.

COLOUR RANGE

Clear

WATER RESISTANCE

Resistant to the levels of atmospheric humidity present in normal environment.

VOLUME SOLIDS

32± 2% (nominal)

FILM THICKNESS/COAT

Wet: 50-75 Micrometers

Dry: 17-25 Micrometers

DRYING TIMES

Depends on temperature, humidity, air movements and film thickness.

TOUCH DRY

15-20 Minutes

RECOAT

1-1.5 Hours

THEORETICAL COVERAGE

A guide to the theoretical coverage which can be achieved under normal conditions is 11-13m²/litre/coat.

APPLICATION

Spray

CONVENTIONAL SPRAY

100-150% with WOOD DYER's Wood Thinner.

CLEANING UP


Clean all equipment with WOOD DYER's Wood Thinner immediately after use.

SURFACE PREPARATION

Surfaces that are new, bare, old, or previously painted need to be clean, dry, and free from wax, dust, rust, and any other unwanted materials. Apply WOOD DYER's Wood Sealer to the surfaces and let them dry. After each coat, lightly sand the surface with abrasive paper.

SAFETY HEALTH AND ENVIRONMENTAL FORMATION

Highly flammable; keep container sealed, upright, and away from children, ignition sources, food, and extreme temperatures. Wear protective gear during use, avoid inhalation and contact with skin or eyes, and ensure good ventilation. Dispose of waste responsibly; toxic to aquatic life and may cause long-term harm.



Wood Sealer

CODE NA : 0001