

Weather Shield

For exterior walls · 100% acrylic based

GENERAL DESCRIPTION	Ombré Weather Shield is a 100% acrylic based exterior emulsion that protects walls against sun, rain and dust while keeping colours fresh. It forms a flexible, water-resistant film with a smooth finish on cement plaster, concrete and masonry.
PACK SIZE	3.64 Litres and 18.2 Litres.
COLOUR RANGE	Wide range of shades via the Ombré colour system
FINISH	Smooth matt
VOLUME SOLIDS	42 ± 2% (nominal)
FILM THICKNESS / COAT	Dry: 35-45 Micrometers
TOUCH DRY	30-60 Minutes
RECOAT	3-4 Hours
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 9-11 m ² /litre/coat.
APPLICATION	Brush, Roller or Spray
THINNING	10-15% with clean water.
CLEANING UP	Wash all equipment with clean water immediately after use.
SURFACE PREPARATION	Remove algae, efflorescence, dirt and loose paint. Surfaces must be clean, dry and sound. Repair cracks, apply a suitable exterior primer, then two coats of Weather Shield. Do not apply in rain or on damp walls.
SAFETY, HEALTH & ENVIRONMENT	Keep out of reach of children. Avoid contact with skin and eyes; if contact occurs, rinse with plenty of water. Ensure good ventilation during application and drying. Do not empty residues into drains or watercourses; dispose of waste responsibly.



Weather Shield

CODE : 0005

100% acrylic based · Eco-friendly · Smooth finish walls