

Roads and Highways Department

API Documentation

Vehicle Information for Bank User

API BASE URL: <baseUrl>

The context 'baseUrl' contains http, server IP address and server Port number.
IP address and Port number may vary. Please confirm from the document provider.

Example = "http://" + "10.110.10.110" + ":8090"

Current Application baseUrl = <http://10.110.10.110:8090>

Steps:

1. Login (to get the token)
2. Set the token in the Authorization as Bearer Token (For every API request). The token will expire within 12 hours.
3. Fetch Vehicle Information
4. Register Vehicle
5. Unregister Vehicle (Inactivate wallet status when required)

Login:

API URL - {baseUrl}/api/v2/login

HTTP REQUEST METHOD - POST

APPLICATION CONTENT TYPE - application/json

Payload to login

SL	Parameter Name	Data Type	Parameter Type
01	username	String	Required
02	password	String	Required

Sample Request 1:

```
{  
  "username" : "addUsername",  
  "password" : "addPassword"  
}
```

Sample response 1:

Response status: 200 - OK

```
{  
  "token": "eyJhbG.eyJzdWU4N30.xNML3t-HgpN8_I2v9Q5K6sktdr0-DxltcwC6cl8r3VE"  
}
```

NB: The token will expire within 12 hours. Set the token for every API request.

Fetch Vehicle Information:

API URL - {baseUrl}/api/v2/wallet/vehicle-info

HTTP REQUEST METHOD - POST

APPLICATION CONTENT TYPE - application/json

AUTHORIZATION TYPE - Bearer Token

Payload to fetch vehicle info

SL	Parameter Name	Data Type	Parameter Type
01	vehicleRegistrationNumber / rfid	String	Required
02	companyOid	Integer	Required

Sample Request 1:

```
{  
  "vehicleRegistrationNumber": "DHAKA METRO-GA-37-1933",  
  "companyOid": "bankUserCompanyOid"  
}
```

NB: Replace the fields according to your information.

Sample Response 1: When there is an active wallet by your company (and the provided vehicle registration number)

Response status: 200 - OK

```
{  
  "vehicleRegistrationNumber": "DHAKA METRO-GA-26-6824",  
  "chassisNo": "NZ****1961",  
  "brtaClass": "MOTOR CAR (LARGE)",  
  "rhdClass": "MOTOR CAR (LARGE)",  
  "vehicleCC": "1500",  
  "vehicleColour": "WHITE",  
  "wallet": {  
    "vehicleRegistrationNumber": "DHAKA METRO-GA-26-6824",  
    "companyName": "Agrani Bank PLC",  
    "type": "BANK",  
    "status": 1  
  },  
  "walletMessage": null  
}
```

NB: Response wallet will be the active wallet.

Sample Response 2: When there is an active wallet by another company (and the provided vehicle registration number). The wallet response will be null and the walletMessage will be as follows.

Response status: 200 - OK

```
{
  "vehicleRegistrationNumber": "DHAKA METRO-GA-26-6824",
  "chassisNo": "NZ****1961",
  "brtaClass": "MOTOR CAR (LARGE)",
  "rhdClass": "MOTOR CAR (LARGE)",
  "vehicleCC": "1500",
  "vehicleColour": "WHITE",
  "wallet": null,
  "walletMessage": "No active wallet found with the vehicle registration number."
}
```

NB: There will be only one active wallet in the database. If there is no active wallet, the wallet response will be null and the walletMessage will be as follows (Sample response 3).

Sample Response 3:

Response status: 200 - OK

```
{
  "vehicleRegistrationNumber": "DHAKA METRO-GA-26-6824",
  "chassisNo": "NZ****1961",
  "brtaClass": "MOTOR CAR (LARGE)",
  "rhdClass": "MOTOR CAR (LARGE)",
  "vehicleCC": "1500",
  "vehicleColour": "WHITE",
  "wallet": null,
  "walletMessage": "No active wallet found with the vehicle registration number."
}
```

NB: For the next request (register-vehicle api), must ensure that the response wallet info matched with the user's wallet info or the wallet response will be null. Otherwise the user must inactive the activated wallet by the unregister-vehicle api.

Register Vehicle:

API URL - {baseUrl}/api/v2/wallet/register-vehicle

HTTP REQUEST METHOD - **POST**

APPLICATION CONTENT TYPE - **application/json**

AUTHORIZATION TYPE - **Bearer Token**

Payload to register vehicle

SL	Parameter Name	Data Type	Parameter Type
01	vehicleRegistrationNumber	String	Required
02	companyOid	Integer	Required
03	mobileNumber	String	Required
04	walletNumber	String	Required
05	description	String	Optional
06	currentBalance	String	Optional
07	dueBalance	String	Optional

***N.B:**

- Any "rfid" or "vehicleRegistrationNumber" is required for a single request.
- "walletNumber" is a mobile banking number or Core banking account number.
- "status" is the account status of walletNumber at the bank side.

Sample Request 1:

```
{  
  "vehicleRegistrationNumber": "DHAKA METRO-GA-37-1933",  
}
```

```
"companyOid": 2,  
"mobileNumber": "01813523401",  
"walletNumber": "01813523401",  
"description": "Requesting for vehicle info form UCB PLC",  
"currentBalance": "12345",  
"dueBalance": "12345"  
}
```

Sample response 1:

Response status: 200 - OK

```
{  
  "vehicleRegistrationNumber": "DHAKA METRO-GA-37-1933",  
  "chassisNo": "42****D0001",  
  "brtaClass": "MOTOR CAR (LARGE)",  
  "rhdClass": "MOTOR CAR (LARGE)",  
  "vehicleCC": "1500",  
  "VehicleColour": "BLUE"  
}
```

Unregister Vehicle:

API URL - {baseUrl}/api/v2/wallet/unregister-vehicle

HTTP REQUEST METHOD - PUT

APPLICATION CONTENT TYPE - application/json

AUTHORIZATION TYPE - Bearer Token

SL	Parameter Name	Data Type	Parameter Type
01	vehicleRegistrationNumber	String	Required
02	companyOid	Integer	Required
04	walletNumber	String	Required
05	status	Integer (0/1)	Required

NB: Status must be between 0 and 1. Status 1 = active and 0 = inactive;

Sample Request 1: For inactive(0) status:

```
{
  "vehicleRegistrationNumber": "DHAKA METRO-GA-26-6824",
  "walletNumber": "01763732127",
  "companyOid": 4,
  "status": 0
}
```

Sample response 1:

Response status: 200 - OK

```
{
  "message": "Wallet status updated successfully.",
  "httpStatus": "OK",
  "httpCode": 200,
  "body": {
    "vehicleRegistrationNumber": "DHAKA METRO-GA-26-6824",
    "companyName": "Agrani Bank PLC",
    "type": "BANK",
    "status": 0
  }
}
```

```
}
```

Sample response 2: If no wallet exist for the provided Vehicle Registration Number

Response status: 404 - NOT FOUND

```
{
  "status": "404 NOT_FOUND",
  "message": "Please provide the correct Vehicle Registration Number.",
  "reason": "No wallet records exist with the specified Vehicle Registration Number."
}
```

Sample response 3: When you want to activate(1) and already have an active wallet for the provided Vehicle Registration Number.

Response status: 409 - CONFLICT

```
{
  "message": "An active wallet already exists for the vehicle registration number. Please
inactivate it before proceeding.",
  "httpStatus": "CONFLICT",
  "httpCode": 409,
  "body": {
    "vehicleRegistrationNumber": "DHAKA METRO-GA-26-6824",
    "companyName": "Agrani Bank PLC",
    "type": "BANK",
    "status": 1
  }
}
```

Possible HTTP status:

200 - OK (The request succeeded.)

404 - Not Found (The server cannot find the requested resource.)

400 - Bad Request (The request cannot be fulfilled due to bad syntax.)

409 - Conflict (If the data already exists by the provided field).

429 - Too Many Requests (The user has sent too many requests in a given amount of time. Intended for use with rate limiting schemes. Proposed in an Internet-Draft.)

502 - Bad Gateway (Invalid IP-Address.)