Excel functions

(i) **isblank( )** → Returns true if specified cell reference or data is blank otherwise returns false.

Syntax :- = isblank(cell_reference)

e.g.

	A
1.	Anil
2.	

= isblank(A1) Result: false

= isblank(A2) Result: true

(ii) **if( )** → It returns the value depending upon the result of specified condition.

Syntax :- =if(condition, value1, value2)

Note :-
- if condition is true, value1 will be returned.
- if condition is false, value2 will be returned.

e.g.

	A
1.	90
2.	40

=if (A1 >20, "Hello", "world") Result :- Hello

= if (A2 <30, "Java", "Python") Result :- Python

for any task, approach would like this:-

=if (isblank(cell_reference), " ", another_task_or_formula)

Sumif( ) :- It is used to return sum of numeric values which are satisfying the given condition.

Syntax:-

=Sumif (range_of_data_for_condition, Condition, range_of data_to_be_added)

e.g.

	A	B	C
1	Region	Product	Sales
2	North	Pencil	300
3	East	Pen	200
4	South	Pencil	300
5	North	Pen	400

find total sales of Pencil

=Sumif(B2:B5, "Pencil", C2:C5)

∴ Result:- 600

Sumifs():- To calculate sum of numeric values which are satisfying all the specified conditions.

Syntax:-

=Sumifs(range_of_data_to_be_added, range_of_data_for_condition1, condition1, range_of_data_for_condition2, condition2, range_of_data_for_condition3, condition3, ...)

	A	B	C	D
1.	Region	Product	Quantity	Sales (in Rs.)
2	North	Pen	20	1000
3.	South	Pencil	40	500
4.	North	Pen	60	300
5.	East	Pencil	20	400
6	South	Pen	30	500

Question:- find total quantity of Pencil sold in North Region.

=Sumifs(C2:C6, B2:B6, "Pencil", A2:A6, "North")

∴ Result :- 0

Question:- find total quantity of Pen sold.

= Sumif(B2:B6, "Pen", C2:C6)

∴ Result : 110

Question :- find the total sales of Pen in North Region.

=Sumifs(D2:D6, B2:B6, "Pen", A2:A6, "North")

∴ Result :- 1300

Countif() :- to count the values satisfying given condition.

Syntax :-

=Countif(range_of_data_for_condition, condition)

	A
1.	20
2.	50
3.	30
4.	40
5.	90

No. greater than 40 :-

=Countif(A1:A5, ">40")

∴ Result : 2

Countifs() :- to count values satisfying all the conditions.

Syntax:-

= Countifs (range_of_data_for_condition1, condition1, range_of_data_for_condition2, condition2, ...)