



আন্তর্জাতিক ইসলামী বিশ্ববিদ্যালয় চট্টগ্রাম
الجامعة الإسلامية العالمية شيتاغونغ
International Islamic University Chittagong

Department of Computer Science &Engineering(CSE)

LAB - 7

Name : Shah Ibne Fahad
Student ID : C193048
Semester : 7th
Section : 7BM
Email : c193048@ugrad.iiuc.ac.bd
Contact : 01860793742
Course Code : CSE-4742
Course Title : Computer Graphics Lab

Name of the course Teacher :

Mahadi Hassan

Associate Professor

Dept of Computer Science and Engineering,IIUC

1. Rotate a point about origin.

```
#include<bits/stdc++.h>
```

```
#include <graphics.h>
```

```
using namespace std;
```

```
#define pi acos(-1.0)
```

```
int main()
```

```
{
```

```
    int gd = DETECT, gm;
```

```
    initgraph(&gd, &gm, "");
```

```
    line(250,100,250,300);
```

```
    line(250,300,450,300);
```

```
    int x=50,y=100,h=250,k=300;
```

```
    double thita =60;
```

```
    thita = (thita*pi)/180;
```

```
    int x_prime = (x*cos(thita)) - (y*sin(thita));
```

```
    int y_prime = (x*sin(thita)) + (y*(cos(thita)));
```

```
circle(h+x,k-y,5);  
circle(h+x_prime,k-y_prime,5);  
  
getch();  
closegraph();  
return 0;  
}
```

2. Rotate a point about another point.

```
#include <graphics.h>
```

```
#include <stdlib.h>
```

```
#include <math.h>
```

```
#define PI 3.14159265
```

```
void rotate_point(int x1, int y1, int x2, int y2, int *new_x, int *new_y,  
float angle)
```

```
{
```

```
    // Convert angle to radians
```

```
    angle = angle * PI / 180.0;
```

```
    // Translate point (x2, y2) to origin
```

```
    int x = x1 - x2;
```

```
int y = y1 - y2;
```

```
// Rotate point around origin
```

```
int new_x_temp = x * cos(angle) - y * sin(angle);
```

```
int new_y_temp = x * sin(angle) + y * cos(angle);
```

```
// Translate point back to original position
```

```
*new_x = new_x_temp + x2;
```

```
*new_y = new_y_temp + y2;
```

```
}
```

```
int main()
```

```
{
```

```
int gd = DETECT, gm;
```

```
initgraph(&gd, &gm, "");
```

```
// Original point
```

```
int x1 = 100, y1 = 100;
```

```
circle(x1, y1, 3);
```

```
// Point to rotate around
```

```
int x2 = 200, y2 = 200;
```

```

circle(x2, y2, 3);

// Angle of rotation in degrees
float angle = 45;

// Rotate point
int new_x, new_y;
rotate_point(x1, y1, x2, y2, &new_x, &new_y, angle);

// Display rotated point
circle(new_x, new_y, 3);

getch();
closegraph();

return 0;
}

```

3. Rotate a line about a point.

```

#include <graphics.h>
#include <stdlib.h>
#include <math.h>

```

```
#define PI 3.14159265
```

```
void rotate_line(int x1, int y1, int x2, int y2, int x, int y, float angle, int  
*new_x1, int *new_y1, int *new_x2, int *new_y2)
```

```
{
```

```
    // Convert angle to radians
```

```
    angle = angle * PI / 180.0;
```

```
    // Translate points (x1, y1) and (x2, y2) to origin
```

```
    int a1 = x1 - x;
```

```
    int b1 = y1 - y;
```

```
    int a2 = x2 - x;
```

```
    int b2 = y2 - y;
```

```
    // Rotate points around origin
```

```
    int new_a1 = a1 * cos(angle) - b1 * sin(angle);
```

```
    int new_b1 = a1 * sin(angle) + b1 * cos(angle);
```

```
    int new_a2 = a2 * cos(angle) - b2 * sin(angle);
```

```
    int new_b2 = a2 * sin(angle) + b2 * cos(angle);
```

```
    // Translate points back to original position
```

```
*new_x1 = new_a1 + x;  
*new_y1 = new_b1 + y;  
*new_x2 = new_a2 + x;  
*new_y2 = new_b2 + y;  
}
```

```
int main()  
{  
    int gd = DETECT, gm;  
    initgraph(&gd, &gm, "");  
  
    // Original line  
    int x1 = 100, y1 = 100, x2 = 200, y2 = 200;  
    line(x1, y1, x2, y2);  
  
    // Point to rotate around  
    int x = 200, y = 200;  
    circle(x, y, 5);  
  
    // Angle of rotation in degrees  
    float angle = 45;
```

```

// Rotate line
int new_x1, new_y1, new_x2, new_y2;
rotate_line(x1, y1, x2, y2, x, y, angle, &new_x1, &new_y1, &new_x2,
&new_y2);

// Display rotated line
line(new_x1, new_y1, new_x2, new_y2);

getch();
closegraph();

return 0;
}

```

4. Rotate a triangle about a point

```

#include <graphics.h>
#include <stdlib.h>
#include <math.h>

#define PI 3.14159265

void rotate_triangle(int x1, int y1, int x2, int y2, int x3, int y3, int x, int y,
float angle,

```



```
        int *new_x1, int *new_y1, int *new_x2, int *new_y2, int
        *new_x3, int *new_y3)
{
    // Convert angle to radians
    angle = angle * PI / 180.0;

    // Translate points (x1, y1), (x2, y2) and (x3, y3) to origin
    int a1 = x1 - x;
    int b1 = y1 - y;
    int a2 = x2 - x;
    int b2 = y2 - y;
    int a3 = x3 - x;
    int b3 = y3 - y;

    // Rotate points around origin
    int new_a1 = a1 * cos(angle) - b1 * sin(angle);
    int new_b1 = a1 * sin(angle) + b1 * cos(angle);
    int new_a2 = a2 * cos(angle) - b2 * sin(angle);
    int new_b2 = a2 * sin(angle) + b2 * cos(angle);
    int new_a3 = a3 * cos(angle) - b3 * sin(angle);
    int new_b3 = a3 * sin(angle) + b3 * cos(angle);
```

```

// Translate points back to original position
*new_x1 = new_a1 + x;
*new_y1 = new_b1 + y;
*new_x2 = new_a2 + x;
*new_y2 = new_b2 + y;
*new_x3 = new_a3 + x;
*new_y3 = new_b3 + y;
}

int main()
{
    int gd = DETECT, gm;
    initgraph(&gd, &gm, "");

    // Original triangle
    int x1 = 100, y1 = 100, x2 = 200, y2 = 200, x3 = 150, y3 = 50;
    line(x1, y1, x2, y2);
    line(x2, y2, x3, y3);
    line(x3, y3, x1, y1);

    // Point to rotate around
    int x = 200, y = 200;

```

```
circle(x, y, 3);

// Angle of rotation in degrees
float angle = 45;

// Rotate triangle
int new_x1, new_y1, new_x2, new_y2, new_x3, new_y3;
rotate_triangle(x1, y1, x2, y2, x3, y3, x, y, angle, &new_x1, &new_y1,
&new_x2, &new_y2, &new_x3, &new_y3);

// Display rotated triangle
line(new_x1, new_y1, new_x2, new_y2);
line(new_x2, new_y2, new_x3, new_y3);
line(new_x3, new_y3, new_x1, new_y1);

getch();
closegraph();

return 0;
}
```