

Installation Options









CX7

7 inch Countertop/Under-Cabinet Touchpanel

From the kitchen countertop to the conference room, the versatile CX7 is perfect wherever "always on", intuitive control is required. The 7" LCD touchpanel has adjustable tilt, allowing the display to be angled straight up to nearly flat. The CX7 can even be mounted inverted under a cabinet. Additional features include wired and wireless Ethernet for two-way control, digital video (motion JPEG) and web browsing, while analog audio/video inputs and stereo speakers provide video viewing from sources such as satellite TV or security cameras.

Key Features

- 800x480 WVGA LCD with integrated multi-touch capacitive touchscreen.
- Composite, S-video and component input for viewing video at 480i, 576i, 480p or 576p.
- Analog audio input and stereo speakers.
- Integrated 10/100 Base-T and 802.11 Wireless Ethernet.
- Built-in RS-232 port for one-way control without a separate control processor.
- Built-in high output IR port for direct control of devices through an IR connecting block.
- Powered using power supply or PoE (Power over Ethernet)
- Optional modules/processors provide advanced two-way control of electronics such as media servers, lighting, security and more!
- USB and Ethernet Programming.
- Adjustable tilt display (from 10°-90°) or CX7 can be mounted inverted under a cabinet.



Specifications

Power	+9VDC to +16VDC, 1A max
Power Management	Adjustable backlight brightness/proximity sensor
Touchscreen Display	High-brightness color TFT LCD
	WVGA (800x480 pixels) with 65K colors
	Integrated high-resolution capacitive touchscreen
Display Size	7.0 in (177mm) diagonal
Display Backlight	Dual CCFL, 300nit
Infrared Output	Through control port, 200mA output
Ethernet Port	10/100 Base-T with Power-over-Ethernet
Wireless Ethernet	
Operating Temperature	+32°F to +122°F (0°C to +50°C)
Operating Humidity	5% to 95% Non-condensing
Total System Memory	256M Bytes Flash (non-volatile) memory
Device Capability	Total number of devices is limited only by memory
Macro Capability	Unlimited steps in a single macro
	Total number of macros is limited only by memory
	Macro capability on every button
Communications	USB programming port
Video Input	
	NTSC/PAL/SECAM
Enclosure	High-impact molded ABS plastic
Mounting	Tabletop, or screws through mounting bracket (Included)
Dimensions (LxWxH)	7.5" (190mm) x 7.3" (185mm) x 6.25"(159mm)
Weight	
Warranty	One Year (Parts & Labor)
* 4 !! 0	



Remote Technologies Incorporated

5775 12th Avenue East, Suite 180, Shakopee, MN 55379 PH: (952) 253-3100 • Website: www.rticorp.com

RTI User Interfaces

RTiPanel	Mobile Software Interface (App)
Virtual Panel	PC Software Interface (App)
SURFIR	Companion Remote Control
T1-B+	Remote Control
T2i	Remote Control
T2x	Remote Control
T3x	Remote Control

RKM-1+ In-Wall Audio Distribution Keypad RK1+ 2-4-8 Button In-Wall Keypad

KX2 2.8 inch In-Wall Touchpanel Keypad KX3 3.5 inch In-Wall Touchpanel Keypad KX7 7 inch In-Wall Touchpanel

CX7 Countertop/Under-Cabinet Touchpanel



vIRsa





RTI Control Accessories

,,,,	Control Acceptance
RP-4	RF Control Processor
XP-3	Advanced Control Processor
XP-6	Advanced Control Processor
XP-8s	Advanced Control Processor
RM433	433MHz RF Antenna
ZM24	2.4GHz Zigbee Transceiver
CB-8	Touchpanel Connecting Block
CM-232	RS-232 Communication Module
CPB-1	Control Port Connecting Block
ECB-5	IR Connecting Block
ESC-2	Ethernet to Serial Converter
IPE-4	IR Port Expander
PCM-4	Port Control Module
RCM-4	Relay Control Module
Mouse	IR Emitter



RTI Audio Distribution

AD-4x Distributed Audio System
AD-8x Distributed Audio System
CP-450 4 Channel Amplifier
CP-1650 16 Channel Amplifier

