

Additional Bezel Options



Black Bezel

Brushed Aluminum Bezel



KX7

7 inch In-Wall Touchpanel

The extraordinary KX7 is packed full of features for complete control of entertainment, environment and security systems in any residential or commercial installation. The wall-mounted touchpanel has a slim profile, framing a vivid 7" LCD that can be custom tailored for intuitive control, while the multi-touch capacitive touchscreen allows screen swiping for page navigation. The built-in RS-232 and infrared communication allow for direct control of electronics without a control processor. In addition, video inputs make it possible to view analog video at up to 576p, while an Ethernet connection enables even more functionality, such as viewing IP security cameras, surfing the web and advanced two-way control. The integrated camera, microphone and speakers enable the convenience of intercom support directly on the KX7.*

Key Features

- Beautiful 7" 800x480 WVGA LCD with integrated multi-touch capacitive touch screen that allows screen swiping for page navigation.
- Composite, S-Video or Component video inputs allow viewing analog video at 480i/576i/480p/576p resolution.
- Integrated 10/100 Base-T (with PoE) and 802.11 wireless Ethernet.
- Built-in high output IR port for direct control of devices.
- Built-in RS-232 port for one-way control without a separate control processor.
- Built-in camera, microphone and speakers enable intercom capability (future support)*.
- Powered using power supply, CB8 connecting block or PoE (Power over Ethernet).
- Optional modules/processors provide additional control capabilities including two-way communication via RS-232/IP, sensing, IR and relay control.
- USB and Ethernet Programming.
- Stylish low-profile faceplate available in white, black or brushed aluminum (ships with white).
- Integrated mounting wings for easy retrofit installations (metal back box also available separately).



Specifications

| Power | +9VDC to +16VDC, 1A max |
|------------------------------------|--|
| Power Management | Adjustable backlight brightness/proximity sensor |
| Touchscreen Display | High-brightness color TFT LCD |
| | WVGA (800x480 pixels) with 65K colors |
| ll | ntegrated high-resolution projected capacitive touchscreen |
| Display Size | 7.0 in (177mm) diagonal |
| Display Backlight | LED Backlit, 310nit |
| Infrared Output | Through control port, 200mA output |
| | Drives up to 1000 ft (300 m) of wire |
| Serial Port | RJ-45, RS-232 communcation (one-way) |
| Ethernet Port | RJ-45, 10/100 Base-T with Power-over-Ethernet |
| Wireless Ethernet | 802.11b/g |
| Camera | Color CMOS VGA (640x480) |
| Microphone | Silicon MEMS |
| Speakers | Two (2), Stereo 2 Watt, 8 Ohm |
| Communications | USB programming port |
| Video Input | Three, BNC Connectors |
| | Composite, S-Video or Component Analog Video |
| | NTSC/PAL/SECAM |
| Total System Memory | 128M Bytes Flash (non-volatile) memory |
| | Total number of devices is limited only by memory |
| Macro Capability | Unlimited steps in a single macro |
| | Total number of macros is limited only by memory |
| | Macro capability on every button |
| | +32°F to +122°F (0°C to +50°C) |
| Operating Humidity | 5% to 95% Non-condensing |
| | High-impact molded ABS plastic |
| | High-impact molded ABS plastic |
| • | Integrated mounting wings, or screws through front plate |
| , , | 7.7 in (195mm) x 5.6 in (143mm) |
| · | H) 8.5 in (217mm) x 5.9 in (151mm) |
| · | 1.4 in (36mm), with video connector 2.1 in(53mm) |
| • | 1.4 lbs (634g) |
| • | One Year (Parts & Labor) |
| *Intercom support will be added | in a future firmware update. |
| All Specifications subject to char | nge without notice. |



Remote Technologies Incorporated

5775 12th Avenue East, Suite 180, Shakopee, MN 55379 PH: (952) 253-3100 • Website: www.rticorp.com

RTI User Interfaces

| RTiPanel | Mobile Software Interface (App) |
|---------------|------------------------------------|
| Virtual Panel | PC Software Interface (App) |
| SURFIR | Companion Remote Control |
| T1-B+ | Remote Control |
| T2i | Remote Control |
| T2x | Remote Control |
| T3x | Remote Control |
| RKM-1+ | In-Wall Audio Distribution Keypad |
| RK1+ | 2-4-8 Button In-Wall Keypad |
| KX2 | 2.8 inch In-Wall Touchpanel Keypad |
| KX3 | 3.5 inch In-Wall Touchpanel Keypad |
| KX7 | 7 inch In-Wall Touchpanel |



CX7



Countertop/Under-Cabinet Touchpanel



RTI Control Accessories

| RP-4 | RF Control Processor |
|-------------|--------------------------------------|
| XP-3 | Advanced Control Processor |
| XP-6 | Advanced Control Processor |
| XP-8s | Advanced Control Processor |
| RM433 | 433MHz RF Antenna |
| ZM24 | 2.4GHz Zigbee Transceiver |
| CB-8 | Touchpanel Connecting Block |
| CM-232 | RS-232 Communication Module |
| CPB-1 | Control Port Connecting Block |
| ECB-5 | IR Connecting Block |
| ESC-2 | Ethernet to Serial Converter |
| IPE-4 | IR Port Expander |
| PCM-4 | Port Control Module |
| RCM-4 | Relay Control Module |
| vIRsa Mouse | IR Emitter |



RTI Audio Distribution

| AD-4x | Distributed Audio System |
|---------|--------------------------|
| AD-8x | Distributed Audio System |
| CP-450 | 4 Channel Amplifier |
| CP-1650 | 16 Channel Amplifier |

