WalkSafe: A Real-Time Navigation Assistant for Blind and Low-Vision Pedestrians

SE-801 Software Project Lab 3

Submitted by
Shah Alam Abir
Roll: 1439
Institute of Information Technology,
University of Dhaka

Supervised by
Dr. Md. Nurul Ahad Tawhid
Associate Professor
Institute of Information Technology,
University of Dhaka



Institute of Information Technology
Date: August 02, 2026

Letter of Transmittal

August 01, 2026
BSSE 4th Year Exam Committee
Institute of Information Technology,
University of Dhaka

Subject: Technical Report Submission on WalkSafe: A Real-Time Navigation Assistant for Blind and Low-Vision Pedestrians.

Dear Sir,

I am submitting the midterm technical report for my Software Project Lab 3, WalkSafe: A Real-Time Navigation Assistant for Blind and Low-Vision Pedestrians. This report covers the project's technical details, including the requirements, system and data models, architecture, and preliminary test plan, along with the progress made on the working prototype so far.

Because the system is intended to be used by blind pedestrians while walking, I have also included a short analysis of the risks it can contribute to and the requirements that address them. While I have tried to do my best, I welcome your feedback for improvement.

Thank you for your consideration.

Sincerely,

Shah Alam Abir
BSSE-1439
Institute of Information Technology,
University of Dhaka

02.08.2026

—----------

Supervisor's Signature

Acknowledgement

I would like to express my sincere gratitude to the Institute of Information Technology, University of Dhaka, for the opportunity to work on the WalkSafe project. A special thanks to my supervisor, **Dr. Md. Nurul Ahad Tawhid**, Associate Professor at the Institute of Information Technology, whose guidance and encouragement were invaluable throughout the project. His feedback shaped the direction of the work and kept it focused on what the system actually needs to get right.

This project builds directly on models released by the open-source research community, and it would not have been feasible within a single lab course without the published work behind DepthPro, YOLO, ByteTrack, and RAFT. I also appreciate the feedback of my classmates during design discussions, which helped refine several decisions in this report.

Finally, I would like to acknowledge in advance the orientation-and-mobility professionals and blind participants whose review the later stages of this project depend on. A tool meant for blind travellers cannot be judged without them, and their involvement is planned into the validation stages described in this report.

Abstract

Blind and low-vision pedestrians rely on two tools for independent travel. A white cane finds the ground and obstacles within about one step, and GPS applications give route-level direction over tens of metres. Neither serves the space roughly one to eight metres ahead, which is where a pedestrian decides to slow down, move aside, or wait for someone to pass. A cyclist approaching from the side or a scooter parked across the footpath falls outside both: the cane reaches it too late, and the map does not know it exists.

WalkSafe is a real-time navigation assistant that fills this gap using a smartphone camera. It combines three pretrained vision models, DepthPro for depth in metres, YOLO with ByteTrack for detecting and following people, cyclists and vehicles, and RAFT for image motion, with deterministic rules that reduce the scene to one spoken instruction from a fixed nine-command vocabulary. Every decision is recorded with the values behind it, and no images are stored at any point.

The central finding of the work is that guidance of this kind cannot come from one place. A round trip to a shared Colab GPU takes about a second, which is acceptable for deciding which way to walk and useless for saying stop. WalkSafe therefore splits the work by urgency: a cheap check on the phone measures how fast the image is expanding and can warn of an imminent collision within 250 milliseconds, while the server performs the fuller analysis on a more generous budget. A warning from the phone always overrides the server, so the fast path can only ever make the system more cautious.

This report presents the requirements, the scenario, data and design models, the architecture, an AI engineering design, a preliminary test plan, and the risks the system can contribute to along with the requirements that address them. A working prototype of the perception pipeline, decision engine, logging, and analytics dashboard has been built, and the remaining work is scheduled in the timeline.

Timeline

WalkSafe: A Real-Time Navigation Assistant for Blind and Low-Vision Pedestrians.....1
Letter of Transmittal.....2
Acknowledgement.....3
Abstract.....4
1. Project Overview.....9
1.1 Project Title.....9
1.2 Problem Statement.....9
1.3 Objectives.....9
1.4 Scope.....9
1.5 Deliverables.....10
2. Requirements Analysis.....11
2.1 Functional Requirements.....11
Capture and Perception.....11
Interpretation.....12
Navigation Decision.....12
Guidance Delivery.....12
Safety and Failure Handling.....13
Setup, Session, and Accessibility.....13
Logging and Review.....13
2.2 Non-Functional Requirements.....14
Performance.....14
Safety.....14
Reliability.....15
Accessibility and Usability.....15
Resources and Maintainability.....15
2.3 Stakeholders.....15
2.4 Command Vocabulary.....16
3. Scenario-Based Modeling.....17
3.1 Use Case Diagram.....17
3.1.1 Level 0.....17
3.1.2 Level 1.....18
3.1.3 Level 1.1.....20
3.1.4 Level 1.2.....21
3.1.5 Level 1.3.....22
3.1.6 Level 1.4.....22

3.2 Activity Diagram....23
4. Data and Information Modeling....26
5. Software Design....30
5.1 Component Diagram....30
5.2 Component Responsibilities....31
6. Software Architecture....32
6.1 Architectural Overview....32
6.2 Requirement Traceability Matrix....33
7. AI Engineering Design....37
7.1 AI Pipeline....37
7.2 Model Selection....37
8. Preliminary Test Plan....38
8.1 Testing Objectives....38
8.2 Features to be Tested....39
8.3 Validation with Users....41
9. Timeline....42

Figures

#	Title
1	Use Case Diagram — Level 0
2	Use Case Diagram — Level 1
3	Level 1.1 (Setup and Session Management System)
4	Level 1.2 (Scene Analysis and Decision System)
5	Level 1.3 (Guidance Delivery System)
6	Level 1.4 (Logging and Review System)
7	Activity Diagram — Per-Frame Guidance Loop
8	Activity Diagram — Session Start and Calibration
9	Activity Diagram — Degradation Handling
10	ER Diagram
11	Component Diagram
12	Deployment Architecture
13	AI Pipeline
14	Gantt Chart

1. Project Overview

1.1 Project Title

WalkSafe — A Real-Time Navigation Assistant for Blind and Low-Vision Pedestrians

1.2 Problem Statement

Blind pedestrians rely on two tools for independent travel. A white cane finds the ground and obstacles within about one step. GPS applications give route-level directions like which street, which turn, etc. But say nothing about what is physically in the way.

This leaves the space from roughly one to eight metres ahead unserved. A cyclist approaching from the side, a parked scooter across the footpath, a crowd closing the path that the cane reaches too late, and the map does not know they exist. This is the range in which a pedestrian needs to make anticipatory decisions like slow down, move left, wait for someone to pass.

A smartphone camera can capture the information needed to fill this gap, and current vision models can process it. The difficulty is not perception but delivery: guidance must arrive fast enough to act on, must stay quiet when nothing needs saying, and must clearly announce when it cannot be trusted. A system that gives good advice most of the time and says nothing when it fails is worse than no system, because the user learns to rely on it.

1.3 Objectives

1. Detect obstacles and moving agents in the one-to-eight-metre range ahead using a smartphone camera.
2. Estimate distance, approach speed, and time-to-collision for each detected agent.
3. Identify traversable openings ahead and measure their width in metres.
4. Produce one navigation command per decision cycle from a fixed nine-command vocabulary.
5. Deliver imminent-obstacle warnings and routing guidance.
6. Announce every degradation and failure audibly instead of falling silent.
7. Make the application fully operable without sight.
8. Log every decision with its inputs for later evaluation, storing no images.

1.4 Scope

In scope

- Smartphone client application plus a remote GPU inference service.

- Depth estimation, agent detection and tracking, and optical flow based motion estimation.
- Per-agent distance, time-to-collision, and risk level.
- Traversable corridor detection with width measured in metres.
- Nine-command navigation vocabulary delivered as speech, earcon, and haptic pulse.
- On-device imminent-obstacle detection that works without a network and overrides remote guidance.
- Audible degradation reporting for connectivity loss, poor visibility, camera occlusion, low battery, and thermal throttling.
- Guided non-visual calibration for camera field of view, mounting geometry, shoulder width, and left/right polarity.
- Screen-reader-compatible operation with the screen off.
- Session logging of derived metrics and an analytics view over them.

Out of scope

- Route planning, destination navigation, and map integration.
- Reading text or signs; recognising specific people.
- Interpreting traffic signals or deciding when to cross a road.
- Reliable detection of kerbs, stairs, and drop-offs. Monocular depth is unreliable at downward steps, so this is declared a limitation rather than attempted.
- Indoor mapping.
- Replacing a white cane, guide dog, or orientation-and-mobility training.

Positioning. WalkSafe is a supplementary aid. All requirements assume the user is also using a cane or guide dog. It is not designed or tested for use as the only aid.

1.5 Deliverables

#	Deliverable	Contents	Status
D1	**Working prototype**	Depth, object detection, and motion models running together on a Colab GPU; rule-based decision engine; browser interface	Complete
D2	**Logging and dashboard**	SQLite record of every decision and the values behind it; dashboard showing command, risk, and speed summaries	In Progress
D3	**Smartphone application**	The app the user runs. Captures video, checks for close obstacles on the phone itself, gets guidance from the	In Progress

#	Deliverable	Contents	Status
		server, and speaks it. Includes first-time setup and works with a screen reader	
D4	**Test suite and test clips**	Automated tests for the safety requirements, plus recorded clips with known distances and directions to test against	Planned
D5	**Final report and demonstration**	Final report and a working demonstration	Planned

Device scope. The smartphone is the only device, and its camera is the only sensor. Commands are heard through the phone speaker or earphones plugged into it. The heavy models run on a Colab GPU, which is remote compute rather than something the user carries. Earphones are supported but not required, since a blind traveller needs to hear their surroundings (NFR-20).

2. Requirements Analysis

2.1 Functional Requirements

Each requirement below maps to a risk in the Appendix, which records what can go wrong if it is not met.

Capture and Perception

ID	Requirement
FR-1	Capture video from the rear camera, tagging every frame with the time it was taken, and reject frames too dark, bright, or blurred to use.
FR-2	Estimate the distance to obstacles and to the ground ahead.
FR-3	Detect and track people, cyclists, and vehicles across frames.

Interpretation

ID	Requirement
FR-4	Classify each tracked agent's motion: approaching, receding, crossing, or static.
FR-5	Estimate each agent's distance, approach speed, and time to collision, using measured frame times rather than an assumed frame rate.
FR-6	Assign each agent a risk level of critical, high, moderate, or low.

Navigation Decision

ID	Requirement
FR-7	Find openings ahead wide enough to walk through, and measure their width in metres.
FR-8	Compare each opening against the user's shoulder width plus a clearance margin, and report when no safe opening exists.
FR-9	Produce exactly one command per cycle from the nine commands, applying rules in a fixed order that puts hazard avoidance before route choice, with a cautious default when no rule matches.
FR-10	Restrict output to the cautious commands when confidence in what the camera is showing is low.
FR-11	Record with each command the rule and the values that produced it.

Guidance Delivery

ID	Requirement
FR-12	Speak each command and play a distinct sound for it, reinforcing urgent commands with a vibration.
FR-13	Speak only when the situation changes, and stay silent otherwise.
FR-14	Interrupt speech in progress immediately for a `stop`.
FR-15	Let the user mute guidance and adjust verbosity and speech rate during a session.

Safety and Failure Handling

ID	Requirement
FR-16	Never let guidance from the server override or delay a `stop` produced on the phone.
FR-17	Discard guidance that has become too old instead of speaking it late.
FR-18	Announce every loss of capability with its cause, and repeat the announcement while capability is reduced.
FR-19	Announce that guidance has stopped on any fault. Never fail silently.
FR-20	Warn before low battery or overheating ends the session.

Setup, Session, and Accessibility

ID	Requirement
FR-21	Start and end a session with a single action that does not require sight.
FR-22	Find the server automatically. Never ask the user to read or enter a link.
FR-23	Guide the user through setup by voice: camera field of view, mounting position, a depth check against a known distance, and a left/right test that blocks use if it fails.

Logging and Review

ID	Requirement
FR-24	Record every decision with the values behind it, and store no images at any point.
FR-25	Write logs without delaying guidance.
FR-26	Show command, risk, and speed summaries, guidance delay against target, and time spent in each reduced state.

2.2 Non-Functional Requirements

Performance

ID	Requirement
NFR-1	Warnings produced on the phone reach the user within 250 ms.
NFR-2	Guidance from the server reaches the user within 1.2 s. Anything older than 2 s is discarded.
NFR-3	The on-phone obstacle check runs at 10 frames per second or better.
NFR-4	The server produces at least 2 decisions per second on a Colab T4 GPU.

Safety

ID	Requirement
NFR-5	Every failure leaves the system more cautious, never less.
NFR-6	Left and right are never reversed.
NFR-7	No fault is signalled by silence alone.
NFR-8	Every requirement whose failure appears in the Appendix has an automated test.

Capability is reduced in defined steps, each more cautious than the last:

Level	Condition	Behaviour
L0	Everything working	Full command vocabulary
L1	Poor visibility — glare, rain, blur	Cautious commands only; announce reduced confidence
L2	Server unreachable	Obstacle warnings only; announce loss of route guidance
L3	On-phone check unavailable	Announce that guidance has stopped; issue none

Level	Condition	Behaviour
L4	Battery exhausted or user ends session	Announce shutdown with reason

Reliability

ID	Requirement
NFR-9	A two-hour session runs without crash or unannounced loss of capability.
NFR-10	Losing the server reduces capability; it never ends the session.

Accessibility and Usability

ID	Requirement
NFR-11	All functionality is reachable without sight.
NFR-12	Earphones are supported but never required, since the user needs to hear their surroundings.
NFR-13	At most 15 spoken messages per minute.

Resources and Maintainability

ID	Requirement
NFR-14	Battery use stays at or below 25% of a 4000 mAh battery per hour.
NFR-15	Mobile data stays at or below 250 MB per hour.
NFR-16	All tunable thresholds live in one configuration file, and perception models can be replaced without changing the decision rules.

2.3 Stakeholders

Stakeholder	Interest	Influence on requirements
Blind or low-vision pedestrian	Primary user. Wants timely, brief, trustworthy guidance and no added risk.	All accessibility, latency, and safety requirements

Stakeholder	Interest	Influence on requirements
Orientation-and-mobility instructor	Uses the system as a training aid; reviews sessions with clients.	Diagnostic view, session review, command vocabulary, safety review sign-off
Researcher / developer	Collects data, evaluates decision quality, tunes thresholds.	Logging, analytics, session review
Bystanders	Appear in camera images without consenting. Not users, but hold privacy interests.	No image retention, minimum sufficient resolution, disclosure
Project supervisor	Assesses scope, method, and rigour.	Documentation, traceability, test plan
Platform providers (Google, Apple, Colab, Kaggle)	Set capability limits and usage terms.	Deployment constraints, session limits, quota handling

2.4 Command Vocabulary

The decision engine outputs one of these nine commands, listed from most to least cautious. The order determines how commands are downgraded when confidence is low.

#	Command	Meaning
1	`stop`	Stop moving forward now
2	`yield`	Wait for an agent to pass
3	`slow_down`	Reduce pace
4	`walk_forward_slow`	Continue ahead with caution
5	`step_left`	Move left, keeping heading
6	`step_right`	Move right, keeping heading
7	`turn_left`	Change heading left
8	`turn_right`	Change heading right
9	`walk_forward`	Continue ahead, path clear

3. Scenario-Based Modeling


Scenario-based modeling is a method used in software development and design to create models that illustrate how a system behaves or responds to different real-world situations. These scenarios are based on user interactions, events, or conditions, and they help developers visualise how the software will function in various contexts. By working through these scenarios, developers can identify potential issues, make informed design choices, and check that the software meets user needs in the situations it will actually meet.

3.1 Use Case Diagram

A use case diagram is a visual tool in software engineering that shows how a system interacts with external entities, called actors, to accomplish specific tasks or goals. It shows the connections between use cases, which represent system functions, and actors, which represent external users or systems. Use case diagrams are drawn during requirements gathering, once system functions and user interactions have been identified.

3.1.1 Level 0

Figure 1: Level 0 (WalkSafe)




Use Case Name: WalkSafe System

Use Case ID: 0
Primary Actors: Pedestrian, O&M Instructor, Researcher
Secondary Actors: Phone Camera, Speech Engine, Colab GPU Platform, Session Database
Goal in Context: The diagram above shows the complete system overview for WalkSafe, a tool that gives blind and low-vision pedestrians spoken guidance about obstacles and openings one to eight metres ahead while they walk.

Description: This is the high-level, or level 0, view of the WalkSafe system. The pedestrian is the main primary actor. The O&M instructor and researcher are also primary actors, but use only the setup and review sides. The secondary actors are the phone camera, which supplies frames, the speech engine, which speaks the commands, the Colab GPU platform, which provides the compute the heavy models run on, and the session database, which stores what the app decided so it can be reviewed afterwards.

3.1.2 Level 1

Figure 2: Level 1 (Modules of WalkSafe)



Use Case Name: Modules of WalkSafe
Use Case ID: 1
Primary Actors: Pedestrian, O&M Instructor, Researcher
Secondary Actors: Phone Camera, Speech Engine, Colab GPU Platform, Session Database
Goal in Context: The diagram above shows the modules of WalkSafe. It consists of 4 modules, which are described below and elaborated in the following levels.

Description:

1. Setup and Session Management

- **Functionality:** Runs the spoken setup, starts and ends sessions, finds the server, and announces how much capability the system currently has.
- **Purpose:** Gets the app ready for this user and this phone, and keeps the user told about what it can currently do.
- **Key Role:** Acts as the starting point for all other operations. Nothing else runs until setup has passed.

2. Scene Analysis and Decision

- **Functionality:** Captures frames, checks on the phone whether something is closing in, analyses the scene on the server, and applies fixed rules to settle on one command, letting a phone warning override the server.
- **Purpose:** Turns camera frames into a single instruction.
- **Key Dependencies:** Depends on the phone camera for frames and on the Colab GPU platform for the depth, detection, and motion models.
- **Output:** One command per cycle, with the rule and values that produced it.

3. Guidance Delivery

- **Functionality:** Speaks the chosen command with its own short sound and a vibration for urgent ones, and controls when to speak so the app stays quiet unless something has changed.
- **Purpose:** Gets the instruction to the user in time, without talking so much that the user stops listening.
- **Key Dependencies:** Depends on the speech engine.
- **Key Role:** This is the only module the pedestrian directly experiences.


4. Logging and Review

- **Functionality:** Records every decision with the values behind it, and shows summaries and drill-down on a dashboard.

- **Purpose:** Makes it possible to check afterwards why the app said what it said, and to find where the thresholds are wrong.
- **Output:** Session summaries and a record of what was decided on each walk.

3.1.3 Level 1.1

Figure 3: Level 1.1 (Setup and Session Management System)



Use Case Name: Setup and Session Management System
Use Case ID: 2
Primary Actors: Pedestrian, O&M Instructor
Secondary Actors: Phone Camera, Colab GPU Platform
Goal in Context: Configures the app for one user and one phone, then runs sessions and keeps the user told about what the app can currently do.


Description:

1. **Onboarding:** states that WalkSafe does not replace a cane or guide dog and takes the user's acknowledgement, then asks consent to send camera images to the server, offering a phone-only mode if the user declines. It then calibrates the app to this phone and this user: reads the camera field of view, checks the app's depth estimate against a known distance, runs a left/right test in which the user steps left and the app confirms it saw a left step, and records the user's shoulder width. Onboarding is rejected if the depth check or the direction test fails, because both would otherwise produce wrong guidance the user has no way to detect. An O&M instructor may assist, but the whole procedure is spoken and can be completed without sighted help.
2. **Session Control:** starts and ends a session with one action that needs no sight, and finds the current server from a fixed address so the user never handles a link.

3. **Capability Announcer:** says out loud whenever the app loses or regains capability, with the reason, and repeats it while capability is reduced. It also warns before low battery or overheating ends the session.

3.1.4 Level 1.2

Figure 4: Level 1.2 (Scene Analysis and Decision System)



Use Case Name: Scene Analysis and Decision System
Use Case ID: 3
Primary Actors: Pedestrian
Secondary Actors: Phone Camera, Colab GPU Platform
Goal in Context: Turns camera frames into one command, using a fast check on the phone and a fuller analysis on the server.


Description:

1. **Frame Capture:** captures frames from the rear camera, records the time each was taken, and discards frames too dark, bright, or blurred to trust.
2. **Phone Collision Check:** measures how fast the image is spreading outward. Things that get closer get bigger, so rapid expansion means something is closing in. This runs on the phone with no model and no network, which is what makes it fast enough to warn in time.
3. **Scene Analysis:** on the server, estimates depth in metres, detects and tracks people, cyclists and vehicles, and works out each one's approach speed, time to collision, and risk level, along with walkable openings and the user's walking speed.
4. **Command Selection:** applies the rules in a fixed order that puts hazard avoidance before route choice and picks one command from the nine in section 2.4. A `stop` from the phone collision check overrides whatever the server chose, and a command that has

become too old is discarded rather than passed on. Records the rule and values behind the command it issues.

3.1.5 Level 1.3

Figure 5: Level 1.3 (Guidance Delivery System)




Use Case Name: Guidance Delivery System
Use Case ID: 4
Primary Actors: Pedestrian
Secondary Actors: Speech Engine
Goal in Context: Gets one clear instruction to the user in time, without talking so much that the user stops listening.

Description:

1. **Speech and Sound:** plays the command's own short sound, then speaks it, and adds a vibration for urgent commands so they get through in noisy places. Speaks at the verbosity and speech rate the user has chosen, both adjustable during a session without sight.
2. **Speaking Rules:** decides when to speak at all. A command that has not changed is not repeated, so silence is the normal state. Speech is capped at fifteen messages a minute, `step_left` and `step_right` cannot alternate faster than once every two seconds, an urgent command interrupts whatever is being said, and the user can mute guidance entirely at any time.

3.1.6 Level 1.4

Figure 6: Level 1.4 (Logging and Review System)



Use Case Name: Logging and Review System
Use Case ID: 5
Primary Actors: Pedestrian, Researcher, O&M Instructor
Secondary Actors: Session Database
Goal in Context: Keeps a record of what the app decided and why, so its behaviour can be checked after a walk.

Description:

1. **Decision Logger:** records every decision with the values behind it, storing no images. It runs during the pedestrian's walk and writes in the background, so guidance is never delayed.
2. **Session Dashboard:** shows command, risk, and speed summaries, guidance delay against target, time spent at each reduced level, and drill-down into any single command.

3.2 Activity Diagram

An activity diagram shows the order in which a system's steps happen, including the points where it chooses between alternatives. The three diagrams below cover the parts of WalkSafe where the ordering matters most: how a session begins, the loop that runs on every frame, and what happens when the app loses capability part-way through a walk.

Figure 7: Activity Diagram (Setup and Session Start)




Figure 8: Activity Diagram (Guidance Loop)

This runs once per frame. The phone check and the server work at the same time and meet at the arbitration step. The double-bordered box is where this loop hands over to the capability check in Figure 9: an unusable frame, a phone check that has stopped running, or a server that does not answer all become inputs to that flow.





Figure 9: Activity Diagram (Capability Change and Recovery)


This runs alongside the guidance loop for the whole session. Its inputs come from the double-bordered box in Figure 8, plus the battery and temperature readings. Every step down is announced with its reason, and the announcement repeats while capability stays reduced, so silence is never mistaken for everything being fine.



4. Data and Information Modeling

WalkSafe keeps a small relational store that records what the app measured and what it decided, never what it saw. No images are kept at any point, so a walk leaves behind numbers rather than footage of the street: enough to reconstruct why any command was given, and nothing that could identify a passer-by.

Figure 10: ER Diagram



The schemas derived from the ER diagram are as follows.

Schema	**Attribute**	**Type**
user	user_id	VARCHAR(64) PK
	phone_model	VARCHAR(128)
	verbosity	VARCHAR(16)
	speech_rate	FLOAT
	consent_send_images	BOOLEAN
	camera_fov_deg	FLOAT
	mount_height_m	FLOAT
	mount_pitch_deg	FLOAT


Schema	Attribute	Type
	clearance_margin_m	FLOAT
	depth_scale	FLOAT
	depth_check_passed	BOOLEAN
	direction_test_passed	BOOLEAN
	created_at	TIMESTAMP
session	session_id	VARCHAR(64) PK
	user_id	VARCHAR(64) FK
	started_at	TIMESTAMP
	ended_at	TIMESTAMP
	end_reason	VARCHAR(32)
	total_decisions	INTEGER
decision	session_id	VARCHAR(64) PK, FK
	sequence	INTEGER PK
	captured_at	TIMESTAMP
	spoken_at	TIMESTAMP
	delay_ms	INTEGER
	source	VARCHAR(8)
	command	VARCHAR(24)
	detail	TEXT
	reason	TEXT
	confidence	FLOAT
	level	VARCHAR(4)
	spoken	BOOLEAN

Schema	Attribute	Type
	user_speed_ms	FLOAT
agent	session_id	VARCHAR(64) FK
	sequence	INTEGER FK
	track_id	INTEGER
	type	VARCHAR(32)
	dist_m	FLOAT
	approach_speed_ms	FLOAT
	ttc_s	FLOAT
	risk	VARCHAR(16)
	motion	VARCHAR(24)
opening	session_id	VARCHAR(64) FK
	sequence	INTEGER FK
	direction	VARCHAR(8)
	width_m	FLOAT
	dist_m	FLOAT
	chosen	BOOLEAN
event	session_id	VARCHAR(64) FK
	occurred_at	TIMESTAMP
	type	VARCHAR(32)
	cause	VARCHAR(64)
	from_level	VARCHAR(4)
	to_level	VARCHAR(4)

5. Software Design

5.1 Component Diagram

Figure 11: Component Diagram



5.2 Component Responsibilities

Component	Does	Talks to
Camera Capture	Captures frames, notes the time of each, discards frames too dark, bright, or blurred	Expansion Check, server
Expansion Check	Measures how fast the image is spreading outward; asserts a stop when something is closing in. Runs on the phone with no network	Guidance Control
Depth Estimation	Produces a depth map for the frame	Interpretation
Agent Tracking	Detects people, cyclists, and vehicles and follows them across frames	Interpretation
Flow Estimation	Estimates image motion, used for the user's walking speed	Interpretation
Interpretation	Works out each agent's distance, approach speed, time to collision and risk, finds walkable openings, and estimates walking speed	Decision Rules
Decision Rules	Applies the rules in fixed order and returns one command with the reason for it	Guidance Control, Log Writer
Guidance Control	Lets a phone stop override the server, drops guidance that is too old, suppresses repeats, then plays the sound, speaks, and vibrates	Session Control, Log Writer

Component	Does	Talks to
Session Control	Starts and ends sessions, tracks the capability level, watches battery and temperature, and announces every change	Server Lookup, Log Writer
Setup	Runs the spoken setup: field of view, depth check, shoulder width, direction test	Camera Capture, Interpretation, Guidance Control
Server Lookup	A fixed address the phone asks for the current server, so the user never handles a link	Session Control
Log Writer / Session Store	Writes decisions and events in the background so guidance is never delayed	Dashboard
Dashboard	Shows session summaries and allows drill-down into any command	Session Store

6. Software Architecture

6.1 Architectural Overview


The system runs in two places: the phone and a Colab GPU server. What goes where is decided by how fast the answer is needed, not by how hard it is to compute.

A round trip to a shared Colab GPU takes about a second. At walking pace that is well over a metre of travel, which is fine for "step right" and useless for "stop". So the split is:

- **On the phone.** One cheap question: is something closing in? It compares consecutive frames and measures how fast the image is expanding. No model, no network, and fast enough to answer within 250 ms.
- **On the server.** Everything that needs real understanding of the scene: depth, agents, risk, openings, and the choice of command.

When the two disagree, the phone wins. A stop from the phone is never overridden or delayed by the server (FR-16). The reason for the asymmetry is that a wrong stop from the phone costs the user a needless pause, while a wrong "walk forward" from the server that the phone was not allowed to veto costs a collision.

Figure 12: Where Things Run



The server address changes every time the Colab session restarts, and a blind user cannot be asked to read a new link each day. A small always-on lookup service solves this: the notebook tells it where it is on startup, and the phone always asks the same fixed address (FR-22).

Free Colab sessions also end after a few hours and may not get a GPU at all. This is why losing the server has to be normal rather than exceptional: capability drops to collision warnings on the phone, the user is told, and the app reconnects on its own when a server comes back (NFR-10).

6.2 Requirement Traceability Matrix

Requirement	Component	Use Case	Test
FR-1 Capture and reject bad frames	Camera Capture	UC-3	T2

Requirement	Component	Use Case	Test
FR-2 Distance to obstacles and ground	Depth Estimation	UC-3	T2
FR-3 Detect and track agents	Agent Tracking	UC-3	T3
FR-4 Classify agent motion	Interpretation	UC-3	T3
FR-5 Approach speed and time to collision	Interpretation	UC-3	T4
FR-6 Assign risk level	Interpretation	UC-3	T3
FR-7 Find and measure openings	Interpretation	UC-3	T5
FR-8 Compare against shoulder width	Interpretation, Setup	UC-1	T5
FR-9 One command by fixed rules	Decision Rules	UC-3	T6
FR-10 Cautious commands when unsure	Decision Rules	UC-3	T6
FR-11 Record the rule and values	Decision Rules	UC-5	T13
FR-12 Speak, sound, vibrate	Guidance Control	UC-3	T9
FR-13 Silent when nothing changes	Guidance Control	UC-3	T9
FR-14 Interrupt speech for a stop	Guidance Control	UC-3	T9

Requirement	Component	Use Case	Test
FR-15 Mute and adjust during a session	Guidance Control	UC-2	T12
FR-16 Phone stop overrides the server	Guidance Control	UC-3	T7
FR-17 Discard guidance that is too old	Guidance Control	UC-3	T8
FR-18 Announce loss of capability	Session Control	UC-4	T10
FR-19 Announce faults, never fail silently	Session Control	UC-4	T10
FR-20 Warn on low battery or overheating	Session Control	UC-4	T10
FR-21 One-action session start and end	Session Control	UC-2	T12
FR-22 Find the server automatically	Session Control, Server Lookup	UC-2	T11
FR-23 Spoken setup with direction test	Setup	UC-1	T1
FR-24 Record decisions, store no images	Log Writer, Session Store	UC-5	T13
FR-25 Logging never delays guidance	Log Writer	UC-3	T13
FR-26 Session summaries	Dashboard	UC-5	T13


Requirement	Component	Use Case	Test
NFR-1 Phone warnings within 250 ms	Expansion Check, Guidance Control	UC-3	T7
NFR-2 Server guidance within 1.2 s	Guidance Control	UC-3	T8
NFR-3 Phone check at 10 frames per second	Expansion Check	UC-3	T7
NFR-4 Two server decisions per second	Server pipeline	UC-3	T2
NFR-5 Failures leave the system cautious	Session Control	UC-4	T10
NFR-6 Left and right never reversed	Setup, Interpretation	UC-1	T1
NFR-7 No fault signalled by silence	Session Control	UC-4	T10
NFR-8 Every safety requirement tested	All	—	T1 to T14
NFR-9 Two-hour session without crash	Phone App	UC-2	T14
NFR-10 Losing the server never ends it	Session Control	UC-2	T11
NFR-11 Usable without sight	Phone App	UC-1, UC-2	T12
NFR-12 Earphones optional	Guidance Control	UC-3	T12
NFR-13 At most 15 messages a minute	Guidance Control	UC-3	T9
NFR-14 Battery within budget	Phone App	UC-2	T14

Requirement	Component	Use Case	Test
NFR-15 Data within budget	Camera Capture	UC-3	T14
NFR-16 One config file, swappable models	All	—	T6

7. AI Engineering Design

7.1 AI Pipeline

Figure 13: AI Pipeline



The split is deliberate: **the models measure, the rules decide.** Every AI component produces a number — depth in metres, boxes with identities, a motion field. Everything after that is ordinary code. That is what makes it possible to say afterwards exactly why a command was issued, which FR-11 requires.

7.2 Model Selection

Nothing is trained or fine-tuned. All models are pretrained and used as they are.

Where	Model	Why this one	Also considered
Server, depth	**DepthPro**	Gives depth in metres from one	MiDaS and Depth Anything give relative

Where	Model	Why this one	Also considered
		image, so distances need no separate scaling step. Sharp edges matter for narrow things like poles	depth, needing an extra scaling step
Server, detection	**YOLOv8n + ByteTrack**	Small enough to leave GPU time for depth and flow. ByteTrack keeps the same identity across frames, which time to collision depends on	Larger YOLO models are more accurate but push past the 1.2 s budget
Server, motion	**RAFT-Small**	Reasonable accuracy for the cost; used for the user's walking speed in the session summaries	Farnebäck is cheaper but too noisy

8. Preliminary Test Plan

The plan has an unusual balance. For most software, testing checks that features work. Here a good part of it checks that **failures** behave correctly: that a lost server announces itself, that old guidance is dropped instead of spoken late, that a stop from the phone cannot be overruled.

8.1 Testing Objectives

1. Check each functional requirement in section 2.1 and each non-functional requirement in section 2.2.
2. Check that depth estimates match known distances, and that setup rejects a phone whose depth is badly wrong.
3. Check that agents keep the same identity across frames, including after being briefly hidden.
4. Check that speeds and times do not change when the frame rate changes.
5. Check that openings are judged in metres and that "no opening" actually gets reported.
6. Check that exactly one command comes out per cycle, that every rule can fire, and that unmatched states fall back to a cautious command.

7. Check that left and right are never reversed, on every phone used.
8. Check that phone warnings arrive within 250 ms and server guidance within 1.2 s, and that nothing older than 2 s is spoken.
9. Check that a stop from the phone always wins, whatever the server says and whenever it arrives.
10. Check that the app is silent when nothing changes and never exceeds 15 messages a minute.
11. Check that every fault and capability change is announced, and that nothing fails silently.
12. Check that losing the server reduces capability but never ends the session, and that recovery is automatic.
13. Check that everything is usable with a screen reader and without sight.
14. Check that no images are stored anywhere and that consent comes before any image is sent.
15. Check that logging never delays guidance and that sessions are closed even after a crash.
16. Check battery and data use over a continuous two-hour session.

8.2 Features to be Tested

#	**Feature**	**What we do**	**What should happen**
T1	Setup and direction test	Run setup on each phone, then repeat with a build whose left and right are deliberately swapped	Normal build passes; swapped build fails the direction test and is blocked from use
T2	Depth accuracy	Obstacles at measured 1, 2, 3, 5, and 8 m, plus glass and a blank wall	Estimates within the error band; confidence drops on difficult surfaces instead of staying high
T3	Detection and tracking	Recorded people and cyclists approaching, crossing, passing, and briefly hidden	Agents found, identity kept, motion and risk classified correctly
T4	Frame rate independence	Same recorded clip at 1.5, 5, and 15 frames per second	Speeds and times to collision agree across all three

#	Feature	What we do	What should happen
T5	Openings	Blank wall, blocked path, narrow gap, clear path; vary the shoulder width setting	"No opening" reported for wall and blocked path; widths match a tape measure; result changes with shoulder width
T6	Decision rules	Fixture scenes covering every rule, including states that match none	One command per cycle; every rule fires; unmatched states give a cautious command
T7	Phone stop wins	Assert a phone stop while the server sends `walk_forward` at full confidence, arriving before, during, and after	Stop is spoken every time; the server command is never spoken or blended
T8	Old guidance	Add network delay past 2 s; send commands out of order	Old commands discarded, not spoken late; out-of-order commands ignored
T9	Guidance delivery	Hold a static scene for a minute, then a fast-changing one with a stop during speech; play music in another app	Nothing repeated during the static scene; under 15 messages a minute; stop interrupts, sound first; music does not silence guidance
T10	Capability changes	Cause each in turn: server unreachable, camera covered, poor light, low	Correct level each time, announced with its cause, repeated

#	Feature	What we do	What should happen
		battery, overheating, speech engine failure	while reduced, and never silent
T11	Server loss and recovery	Kill the server mid-session, then bring it back	Session continues on the phone with an announcement; reconnects and announces full guidance when it returns
T12	Accessibility	Do every task with a screen reader only, one-handed, while holding a cane	Everything completes without sight; no link ever needs typing
T13	Logging and privacy	Run a session, then search phone storage, server files, and logs; export and delete data	No images anywhere; decisions and events all present; guidance not delayed; export and delete work without sight
T14	Two hours continuous	Full session on the target phone	No crash, no unannounced capability loss, battery and data within budget

8.3 Validation with Users

Testing shows the app matches this document. Showing that the document is right needs the people it is for.

Stage	What happens
1	An orientation-and-mobility instructor reviews the nine commands, the wording, and the announcements

Stage	What happens
2	Closed course with obstacles at known positions: sighted testers first, then blind participants with an instructor present
3	Supervised walks on familiar routes, participants using their usual cane or guide dog
4	Unfamiliar routes and poor conditions, which is the only way to see whether users start over-trusting the app

Stages 2 to 4 need ethics approval and an instructor present, so they are scheduled after the deadline in section 9.

---

9. Timeline

The first weeks went on studying the problem and choosing models, followed by the proposal presentation at the end of May. The prototype was built through June and the first half of July, and this report was written in the second half of July.

The remaining time is for development, testing, and writing up. Development in August covers both halves of the work still outstanding: correcting the parts of the prototype that behave incorrectly, and building the pieces that do not exist yet, which are the on-phone collision check, guidance delivery, the capability levels, and the setup flow.

Figure 14: Gantt Chart

