

# Contents

1	README	2
2	FCFS.jpg	6
3	Makefile	7
4	MapReduceFramework.cpp	9
5	Priority.jpg	17
6	RR.jpg	18
7	SRTF.jpg	19
8	Search.cpp	20
9	error handle.h	25
10	my pthread.h	26

# 1 README

```
1  ransha
2  Ran Shaham (203781000)
3  EX: 3
4
5  FILES:
6  README          -- This file
7  MapReduceFramework.cpp  -- My implementation of the uthreads library.
8  Search.cpp       -- The test (Task 1) for the library.
9  Makefile         -- Creates the library and 'Search' when called with
10                     no arguments
11  my_pthread.h     -- Wrapper for some of the pthread functions to handle
12                     unsuccessful pthread calls
13  error_handle.h   -- A header that includes the function that handles
14                     errors in this exercise
15  RR.jpg           -- Gantt chart for question 6 - Round Robin
16  FCFS.jpg         -- " - First Come First Serve
17  SRTF.jpg         -- " - Shortest Remaining Time First
18  Priority.jpg      -- " - Priority Scheduling
19
20
21  REMARKS:
22  Framework Design:
23  Most of the design was driven directly from the exercise description, except
24  for the following:
25  * The ExecMap output data structures are vectors, which allow the shuffle to
26    read from them while the map writes (push_back) to them.
27  * Synchronization between the map and the shuffle is done by signaling the
28    shuffle thread when a new chunk is written.
29  * The shuffle keeps a vector of indices. Each entry specifies the last index
30    in each ExecMap vector that has been written, and DOES NOT pop items from
31    the map's vector. After reading, it updates the index for that container.
32
33  Search.cpp Design:
34  First I'll describe the k1-k3,v1-v3 types I chose-
35  * The <k1,v1> pairs are the directory names and the substring to search
36    respectively. This way, on each call to the Map function, the given directory
37    is opened (it is written in the forums that we can assume that each folder
38    will appear only once in the arguments), iterated over and searched for file
39    names that contain the substring.
40  * The k2 is the filename that contains the substring. That is, a class that
41    has a string member that holds the filename. The v2's only purpose is to
42    free allocated k2 pointers. It takes a k2* as an argument and when destructed
43    it also deletes the k2 that it holds. The idea is that every v2 created has
44    its own k2, and the shuffle can "ignore" (merge) several <k2,v2> pairs to:
45    <k2, list<v2>> pairs - i.e. no v2 is ever ignored. Therefore when the v2s
46    are destroyed, all their k2s can be safely destroyed, and that happens
47    implicitly when calling to "delete v2" (destructor). This way all of the
48    <k2,v2> allocated memory is freed.
49  * k3 is the same as k2 (filename), and v3 is simply the number of times the
50    file name that is held in k3 appeared in the input directories. For example,
51    if the directory structre is this:
52
53    root    -> dir1    -> a, b, c, .vimrc
54            -> dir2    -> d, a, e
55            -> dir3    -> Makefile, README, test.o, a
56            -> dir4    -> .ssh, .config, Games
57
58    then calling "Search a dir1 dir2 dir3" will yield [after reduce] the <k3,v3>
59    entry: <"a",3> (among the other entries - <"e",1>, <"b",1> etc.).
```

60 Next, the Map/Reduce operations:

61 \* Map - Gets a <dirname, strToFind> pair. It checks whether the 'dirname' is a  
62 valid directory (and if it exists) - if not it returns. Otherwise, it opens  
63 the directory and for each entry (file/link/dir) checks if the 'strToFind'  
64 is a substring of that entry's name. If so, it creates the <filename, v2>  
65 pair using (using the 'new' operator) and sends it to Emit2.

66 \* Reduce - Gets a <filename, list<v2>> pair. It copies the filename to the  
67 k3 entry, and sets the value of v3 (filename count) to the size of the list  
68 of v2s. This works because the shuffle merges all files with the same name  
69 while keeping the v2s in a list for that filename, so the list size is  
70 exactly the number of occurrences of the filename.

71 Then, it iterates over the input list and delete the v2\* values (and k2,  
72 implicitly), since they are no longer needed for the framework.

73 Having said that, the Search procedure is as follows:

74 1. Prepare the input - convert the input string arguments to the  
75 string to search and the directory names, and create a list of  
76 <k1\*, v1\*> pairs.

77 2. Run the framework and get the output <filename,count> list.

78 3. For each list entry of <file\_i, count\_i>, print file\_i count\_i  
79 times.

80 4. Iterate over the input and output lists and delete allocated memory

81 ANSWERS:

82 Q1:

83 The program will work with multiple processes (instead of threads).

84 Each process

85 \* The process using select is the Shuffle, since it waits for data to be  
86 written

87 Q2:

88 Since the user's computer can run 8 threads concurrently - 1 on each core,  
89 multiThreadLevel should be at least 7 which will yield 8 threads running at  
90 the same time: 7 ExecMap threads + 1 shuffle thread.

91 Since the computer doesn't support hyper-threading, any additional thread will  
92 wait till a thread that was created earlier will finish running, therefore it  
93 is redundant. E.g., say multiThreadLevel is 10, then 8 ExecMap threads are  
94 created and being run and the remaining 2 WAIT until 2 of the earlier ones  
95 finish running. When they do, by definition there is no more mapping to be  
96 done so they are immediately terminated. Then, after the mapping is finished  
97 can a shuffle be created and only start shuffling.

98 On the other hand, less than 7 won't utilize all system resources - after  
99 creating 4 (for example) ExecMap threads the main thread then creates one  
100 shuffle thread and waits for them to finish. So there will be 5 working thread  
101 untill the shuffle is done and 2 cores will remain unused this entire time  
102 (lower CPU utilization).

103 In conclusion, I'd suggest to set multiThreadLevel to 7.

104 Q3:

105 a. Nira's solution - Single thread

106 \* Does not utilize multi-cores since only one thread of execution is running.

107 \* No scheduler is needed since no concurrency is happening, the program flow  
108 is serial.

109 \* No communication is needed since there's a single thread and process.

110 \* When waiting for I/O operations or other time consuming actions, the program  
111 does not progress

112 \* The overall speed is probably slower than the other methods, since the  
113 process can spend a lot of time waiting (for disk access when writing the  
114 log, for example) and cannot do anything in this time.

115 b. Moti - POSIX's library

116 \* Utilizes multi-cores since the OS is aware of kernel-level threads and can  
117 run a thread for each core or processor concurrently.

118 \* The library manages its own scheduling methods so besides block / signal  
119 there is no much scheduling that can be done.

120 \* Communication time is relatively fast since the threads share heap and static  
121 data segments, and can read from them concurrently. Writing requires locking  
122 shared resources, but it is still better than multi-process communication.

128 \* When one thread is blocked, another can proceed, although when accessing disk  
129 no concurrency can occur (that is, two threads cannot access the disk in the  
130 same time).

131 \* The overall speed depends on whether the machine running the framework has  
132 multiple cores or not. If not, there is no advantage for this method over  
133 user-level threads, and the overhead of context switching, thread creation  
134 and termination is bigger than in user-level threads.  
135 If the machine has multiple cores or processes, this method allows more than  
136 one thread running in the same time, thus is probably faster than the other  
137 methods.

138

139 c. Danny - User-level threads

140 \* Since the OS is not aware of the multiple threads running, it does not  
141 run threads on multiple cores concurrently, so this method does not utilize  
142 multiple cores.

143 \* This is THE method for creating scheduler based on internal data - the user  
144 can do whatever he/she wants, and has access to all data in the program, so  
145 this method is very flexible in terms of scheduling.

146 \* Communication time is similar to kernel-level threads. If no built-in OS  
147 mutex types are used (which guarantee atomic operations) synchronization can  
148 be more tricky than in kernel-level.

149 \* The OS is not aware of the fact multiple threads are running, so when the  
150 process makes a system call, the OS is likely to block it, therefore not  
151 allowing other user-level threads to run in the meantime. If the OS does  
152 not block the entire process, then the program can progress on another  
153 thread while another one waits.

154 \* This is likely to be a fast implementation on single core machines, since  
155 context switches and thread actions require mainly function calls, and not  
156 system calls, therefore overhead time is reduced. On multiple cores, no  
157 concurrency is involved so this method is likely to be slower than methods  
158 that enable concurrency (multi-process or kernel-level threads).

159

160 d. Galit - Multi-processes

161 \* This method utilizes multi-cores since modern OSs tend to do so with  
162 multiple processes.

163 \* The scheduling is almost entirely up to the OS to decide - there are some  
164 hints that can affect the scheduler (nice values, for example) but are based  
165 on general process role, and not fine-grained internal data.

166 \* Communication is trickier than in other methods - the processes need pipes  
167 or files to communicate and handling files require sys-calls, which are slow  
168 as we measured in EX1.

169 \* Each process is more or less independent, so while one is blocked another can  
170 proceed (if it should, logically).

171 \* In my opinion (i.e - based on my knowledge so far, not experience) this  
172 method will be slower than the others on single core machines, and perhaps  
173 a bit faster on multi-core than the single-thread or user-level threads  
174 methods, but slower than the kernel-level threads.

175

176 Q4:

177 Processes:

178 a. Stack is not shared, each process gets its own stack.  
179 b. Same for the heap.  
180 c. Same for global variables.

181 When using fork() sys call, the above data segments are copied to the child  
182 process, not shared.

183

184 Kernel-level threads:

185 a. Each thread gets its own stack  
186 b. Threads share heap data, since they reside in the same process  
187 c. Same as heap, the process' static data segment is the same for all threads

188

189 User-level threads:


190 Exactly the same as kernel-level threads.  
191 A stack can't be shared between threads since they run different functions and  
192 execute a different set of commands (perhaps), so each thread should have its  
193 own stack for local variables and addresses.  
194 The heap and static data segments are shared, since the threads are run in a  
195 one process.

```

196
197 Q5:
198 A deadlock is a situation in which two or more concurrent running threads of
199 execution (processes/ threads) try to access some shared resources; each of
200 them blocks another and is blocked by another, thus neither of them
201 progresses with their execution.
202 For example, threads A,B both need resources x,y to perform an operation.
203 Consider the following scenerio: A runs, reserves x; then, a context switch
204 occurs and B reserves y. If it tries to reserve x it will be blocked. If
205 A tries to reserve y it will also be blocked. Therefore they both block each
206 other and neither progresses.
207
208 A livelock is also a situation in which two or more running threads don't
209 proceed with their execution. In this case, all threads are taking active
210 actions in order to let the other threads finish their work, and then proceed.
211 If each thread lets the other threads proceed and no thread actually proceeds,
212 a livelock occurs.
213 For example, say threads A,B need resources x,y as before. Again, A reserves x
214 and B reserves y. Now B tries to reserve x and fails so it lets go of y and
215 waits 1 second. Before it does, A gets the control and tries to access y,
216 which is still in B's control, so it lets go of x and waits for 1 second.
217 Then, they try again using the same method. This creates the above scenerio,
218 where 2 threads aren't progressing but both are taking active actions to
219 prevent locks.
220
221 Q6:
222 # NAME      | Avg. wait time (format: (P1:a+b+... + P2:c+d+... + ...) / 5 = result
223 =====
224 1. RR       | (1+2+3+2 + 1 + 2 + 2+3+2 + 3) / 5 = 4.2
225 =====
226 2. FCFS     | (0 + (10-1) + (11-3) + (13-7) + (25-8)) / 5 = 8
227 =====
228 3. SRTF     | (1+2+1 + 0 + 0 + 7 + 0) / 5 = 2.2
229 =====
230 4. PRIO     | (0 + (10-1) + (23-3) + (11-7) + (25-8)) / 5 = 10
231 =====
232 # NAME      | Turnaround time
233 =====
234 1. RR       | (18 + (3-1) + (7-3) + (26-7) + (12-8)) / 5 = 9.4
235 =====
236 2. FCFS     | (10 + (11-1) + (13-3) + (25-7) + (26-8)) / 5 = 13.2
237 =====
238 3. SRTF     | (14 + (2-1) + (5-3) + (26-7) + (9-8)) / 5 = 7.4
239 =====
240 4. PRIO     | (10 + (11-1) + (25-3) + (23-7) + (26-8)) / 5 = 15.2
241
242 * (All time calculations are ignoring context switching)

```

## 2 FCFS.jpg



## 3 Makefile

```
1  CFLAGS=-std=c++11 -Wall -Wextra -g -pthread $(INCS)
2
3  # cpp to object files rule
4  %.o: %.cpp
5      $(CXX) $(CFLAGS) -c $<
6
7  # Library Stuff
8  INCS=-I.
9  LOADLIBES=-L.
10
11  LIBSRC=MapReduceFramework.cpp
12  LIBH=MapReduceFramework.h
13  LIBOBJ=MapReduceFramework.o
14  ARFLAGS=rvs
15  RANLIB=ranlib
16
17  LIBTARGET=MapReduceFramework.a
18
19  # test rules
20  TEST_SRC=Search.cpp
21  TEST_FILE=Search
22  VALGRIND_FLAGS = --leak-check=full --show-possibly-lost=yes \
23      --show-reachable=yes --undef-value-errors=yes
24
25  $(TEST_FILE): $(TEST_SRC) $(LIBTARGET)
26      $(CXX) $(CFLAGS) $(LOADLIBES) $^ -o $@
27
28  ValgrindTest: $(TEST_OBJ)
29      valgrind $(VALGRIND_FLAGS) ./$<
30
31
32  # library rules
33  $(LIBTARGET): $(LIBOBJ)
34      $(AR) $(ARFLAGS) $@ $^
35      $(RANLIB) $@
36
37  $(LIBOBJ): $(LIBSRC)
38      $(CXX) $(CFLAGS) -c $< -o $(LIBOBJ)
39
40  # cleaning and such
41  RM=rm -fv
42  LOG_FILE=.MapReduceFramework.log
43  clean:
44      $(RM) $(TEST_FILE) $(LIBTARGET) *.o $(LOG_FILE)
45
46  depend:
47      makedepend -- $(CFLAGS) -- $(SRC) $(LIBSRC)
48
49  # tar rule
50  TAR=tar
51  TARFLAGS=-cvf
52  TARNAME=ex3.tar
53  EXTRA_HEADERS=my_pthread.h error_handle.h
54  GANTT_PICS=RR.jpg FCFS.jpg SRTF.jpg Priority.jpg
55  TARSRC=$(LIBSRC) $(TEST_SRC) Makefile README $(EXTRA_HEADERS) $(GANTT_PICS)
56
57  tar:
58      $(TAR) $(TARFLAGS) $(TARNAME) $(TARSRC)
59
```

```
60 all: $(TEST_FILE)
61
62 .PHONY: all clean tar ValgrindTest
```



## 4 MapReduceFramework.cpp

```
1  /* == Includes == */
2  #include "MapReduceFramework.h"
3
4  #include "my_pthread.h"          /* includes pthread.h + error handling */
5  #include <fstream>
6  #include <vector>
7  #include <queue>
8  #include <map>
9
10 #include <cmath>                  /* for fmin */
11 #include <sys/time.h>             /* gettimeofday */
12 #include <ctime>                  /* for strftime */
13 #include <chrono>                 /* time measurements */
14 #include <algorithm>              /* for std::move */
15
16 /* To reduce line-length and increase readability */
17 using std::vector;
18 using std::queue;
19 using std::map;
20 using std::multimap;
21 using std::list;
22 using std::pair;
23
24 /* == Some constants == */
25 #define CHUNK_SIZE 10
26 #define USEC_TO_NSEC(x) ((x) * 1000)
27 #define NANO_IN_SEC 1000000000
28 #define TIME_TO_WAIT 1000000
29
30 #define TIME_FORMAT "[%d.%m.%Y %T]"
31
32 #define LOG_FILENAME ".MapReduceFramework.log"
33 #define LOG_OPEN_MODE std::ofstream::out | std::ofstream::app
34
35 #define THREAD_EXECMAP "ExecMap"
36 #define THREAD_SHUFFLE "Shuffle"
37 #define THREAD_EXECREDUCE "ExecReduce"
38
39 #define MSG_FRAMEWORK_START(t) "runMapReduceFramework started with " << t \
40     << " threads"
41 #define MSG_FRAMEWORK_END "runMapReduceFramework finished"
42 #define MSG_THREAD_CREATED(th) "Thread " th " created "
43 #define MSG_THREAD_TERMINATED(th) "Thread " th " terminated "
44 #define MSG_MAP_SHUFFLE_TIME(t) "Map and Shuffle took " << t << " ns"
45 #define MSG_REDUCE_TIME(t) "Reduce took " << t << " ns"
46
47 /* Struct for the map procedure. nextToRead is the only variable that *
48  * will be mutated, as specified in the instructions. */
49 typedef struct MapData
50 {
51     MapReduceBase &mapReduce;
52     vector<IN_ITEM> &itemsList;
53     size_t numOfItems;
54     size_t nextToRead;
55     std::ofstream &logofs;
56 } MapData;
57
58 /* Same for reduce, the items list is static and therefore not in here. */
59 typedef struct ReduceData
```

```

60 {
61     MapReduceBase &mapReduce;
62     size_t threadNum;
63     size_t numOfItems;
64     size_t nextToRead;
65     std::ofstream &logofs;
66 } ReduceData;
67
68 /* Comparator to sort keys by values, instead of addresses */
69 template<class T> struct ptr_less
70 {
71     bool operator()(T* lhs, T* rhs)
72     {
73         return *lhs < *rhs;
74     }
75 };
76
77 /* Threads variables */
78 vector<pthread_t> threadList; /* A list of existing ExecMap/Reduce threads */
79 pthread_t shuffleThread; /* The shuffle thread */
80
81 /* ExecMap variables */
82 typedef vector<pair<k2Base*, v2Base*>> K2_V2_LIST;
83 /* a list of pairs in which the first element is the pthread_t (id) and *
84  * the second is that thread's list (pointer) of the map-function-outputs */
85 vector<pair<pthread_t, K2_V2_LIST*>> mapResultLists;
86
87 /* Shuffle Variables */
88 /* An array of indices that specify till what index in the map-lists *
89  * the shuffle thread has already read */
90 vector<size_t> shuffleCurrIndex;
91 /* Note that the map compares keys using ptr_less defined above */
92 map<k2Base*, V2_LIST*, ptr_less<k2Base*>> shuffleOut;
93
94 /* Reduce Variables */
95 vector<pair<k2Base*, V2_LIST*>> reduceIn;
96 typedef queue<pair<k3Base*, v3Base*>> K3_V3_LIST;
97 /* Same as before, but for the reduce-function-outputs */
98 vector<pair<pthread_t, K3_V3_LIST*>> reduceResultLists;
99 multimap<k3Base*, v3Base*, ptr_less<k3Base*>> finalOutputMap;
100
101 /* Mutexes */
102 pthread_mutex_t mutex_map_read; /* protect input list */
103 pthread_mutex_t mutex_em_map; /* barrier to init maps */
104 pthread_mutex_t mutex_more_to_shuffle; /* condition of shuffle loop */
105 pthread_mutex_t mutex_reduce_read; /* protect reduce input */
106 pthread_mutex_t mutex_log_write; /* protect writing to log */
107 /* Condition Variables */
108 pthread_cond_t cv_more_to_shuffle;
109 bool more_to_shuffle;
110
111
112 /**
113  * Gets the current time as a string in the exercise format. i.e
114  * "[DD.MM.YYYY HH:MM:SS]"
115  */
116 string getTimeStr()
117 {
118     size_t MAX_CHARS = 64;
119     time_t rawtime;
120     struct tm * timeinfo;
121
122     time(&rawtime);
123     timeinfo = localtime(&rawtime);
124     char buff[MAX_CHARS];
125
126     strftime(buff, MAX_CHARS, TIME_FORMAT, timeinfo);
127     return buff;

```

```

128 }
129
130
131 /**
132  * Initializes all mutexes, cv and relevant static variables for the library.
133  */
134 void init(int multiThreadLevel)
135 {
136     // Pthread types
137     my_pthread_mutex_init(&mutex_map_read, nullptr);
138     my_pthread_mutex_init(&mutex_em_map, nullptr);
139     my_pthread_mutex_init(&mutex_more_to_shuffle, nullptr);
140     my_pthread_cond_init(&cv_more_to_shuffle, nullptr);
141     my_pthread_mutex_init(&mutex_reduce_read, nullptr);
142     my_pthread_mutex_init(&mutex_log_write, nullptr);
143     // Variables and data structures
144     more_to_shuffle = true;
145     threadList.resize(multiThreadLevel);
146     mapResultLists.resize(multiThreadLevel);
147     shuffleCurrIndex.resize(multiThreadLevel);
148     reduceResultLists.resize(multiThreadLevel);
149 }
150
151 /**
152  * Destroys mutexes, cv and clear the static data structures in use.
153  */
154 void cleanup()
155 {
156     // Pthread types
157     my_pthread_mutex_destroy(&mutex_map_read);
158     my_pthread_mutex_destroy(&mutex_em_map);
159     my_pthread_mutex_destroy(&mutex_more_to_shuffle);
160     my_pthread_cond_destroy(&cv_more_to_shuffle);
161     my_pthread_mutex_destroy(&mutex_reduce_read);
162     my_pthread_mutex_destroy(&mutex_log_write);
163     // heap-allocated data delete
164     for (size_t i = 0; i < mapResultLists.size(); ++i)
165     {
166         delete mapResultLists[i].second;
167         delete reduceResultLists[i].second;
168         mapResultLists[i].second = nullptr;
169         reduceResultLists[i].second = nullptr;
170     }
171     for (auto it = reduceIn.begin(); it != reduceIn.end(); ++it)
172     {
173         delete it->second;
174         it->second = nullptr;
175     }
176     // Variable & data structures reset
177     shuffleThread = 0;
178     threadList.clear();
179     mapResultLists.clear();
180     reduceResultLists.clear();
181     shuffleCurrIndex.clear();
182     shuffleOut.clear();
183     reduceIn.clear();
184     finalOutputMap.clear();
185 }
186
187 /**
188  * The ExecMap procedure: Reads data from the input <k1,v1> list and uses
189  * the user provided Map function to create a list of <k2,v2> values (for
190  * each thread running this function).
191  * Takes a MapData struct pointer as an argument.
192  */
193 void* ExecMap(void *arg)
194 {
195     /* A barrier, opens when all ExecMap data structures are */

```

```

196     * initialized */
197     my_pthread_mutex_lock(&mutex_em_map);
198     my_pthread_mutex_unlock(&mutex_em_map);
199     MapData* mapdata = (MapData*) arg;
200     size_t myItems; // The start index for this thread's data
201     // While there's more data to read, read a chunk and map.
202     while ((myItems = mapdata->nextToRead) < mapdata->numOfItems)
203     {
204         // Lock the index counter
205         my_pthread_mutex_lock(&mutex_map_read);
206         // Reserve items to map and get the start index of them.
207         myItems = (mapdata->nextToRead += CHUNK_SIZE) - CHUNK_SIZE;
208         // Unlock
209         my_pthread_mutex_unlock(&mutex_map_read);
210         // Map this thread's data
211         int end = fmin(myItems + CHUNK_SIZE, mapdata->numOfItems);
212         for (int i=myItems; i < end; ++i)
213         {
214             mapdata->mapReduce.Map(mapdata->itemsList.at(i).first,
215                                   mapdata->itemsList.at(i).second);
216         }
217         // Notify the shuffle thread
218         my_pthread_cond_signal(&cv_more_to_shuffle);
219     }
220     my_pthread_mutex_lock(&mutex_log_write);
221     mapdata->logofs << MSG_THREAD_TERMINATED(THREAD_EXECMAP)
222         << getTimeStr() << endl;
223     my_pthread_mutex_unlock(&mutex_log_write);
224     return nullptr;
225 }
226
227
228 /**
229  * The Shuffle procedure: Merge <k2,v2> pairs from the ExecMap containers
230  * to <k2, queue<v2>> containers.
231  */
232 void* Shuffle(void *)
233 {
234     struct timespec timeToWake;
235     struct timeval timeNow;
236     pair<k2Base*, v2Base*> currPair;
237     k2Base* currKey;
238     v2Base* currVal;
239     auto foundList = shuffleOut.end();
240     V2_LIST* newList = nullptr;
241     K2_V2_LIST* currList = nullptr;
242     size_t currIdx = 0;
243
244     my_pthread_mutex_lock(&mutex_more_to_shuffle);
245     while (more_to_shuffle)
246     {
247         if (gettimeofday(&timeNow, nullptr) < 0)
248         {
249             handleError("gettimeofday");
250         }
251         timeToWake.tv_sec = timeNow.tv_sec +
252             (USEC_TO_NSEC(timeNow.tv_usec) + TIME_TO_WAIT) /
253             NANO_IN_SEC;
254         timeToWake.tv_nsec = fmod(USEC_TO_NSEC(timeNow.tv_usec) +
255                                 TIME_TO_WAIT, NANO_IN_SEC);
256         // Wait for data (or time passing)
257         my_pthread_cond_timedwait(&cv_more_to_shuffle,
258                                 &mutex_more_to_shuffle, &timeToWake);
259         // Check every ExecMap container for items to shuffle
260         for (size_t i = 0; i < mapResultLists.size(); ++i)
261         {
262             currList = mapResultLists[i].second;
263             // Read all unread data and shuffle it.

```

```

264         for (currIdx = shuffleCurrIndex[i];
265             currList != nullptr && currIdx < currList->size();
266             ++currIdx)
267         {
268             currPair = currList->at(currIdx);
269             currKey = currPair.first;
270             currVal = currPair.second;
271             foundList = shuffleOut.find(currKey);
272             // If no k2 entry exists, create it.
273             if (foundList == shuffleOut.end())
274             {
275                 newList = new(std::nothrow) V2_LIST;
276                 // If new operator has failed
277                 if (newList == nullptr)
278                 {
279                     handleError("new operator");
280                 }
281                 newList->push_back(currVal);
282                 shuffleOut.insert(std::make_pair(
283                     currKey,
284                     newList));
285                 newList = nullptr;
286             }
287             else
288             {
289                 foundList->second->push_back(currVal);
290             }
291         }
292         // 'Mark' all read data as read
293         shuffleCurrIndex[i] = currIdx;
294     }
295 }
296 my_pthread_mutex_unlock(&mutex_more_to_shuffle);
297 return nullptr;
298 }
299
300
301 /**
302  * The Reduce procedure: Read input from a data structure and run the reduce
303  * function on it to produce the output data
304  */
305 void* ExecReduce(void *arg)
306 {
307     ReduceData* reducedata = (ReduceData*) arg;
308     // Create this thread's data structure (list of k3,v3)
309     size_t threadNum = reducedata->threadNum;
310     pthread_t tid = pthread_self();
311     if (!pthread_equal(reduceResultLists[threadNum].first, tid))
312     {
313         reduceResultLists[threadNum] = std::make_pair(
314             tid, new(std::nothrow) K3_V3_LIST);
315         if (reduceResultLists[threadNum].second == nullptr)
316         {
317             handleError("new operator");
318         }
319     }
320     size_t myItems; // The start index for this thread's data
321     // While there's more data to read, read a chunk
322     while ((myItems = reducedata->nextToRead) < reducedata->numOfItems)
323     {
324         // Lock the index counter
325         my_pthread_mutex_lock(&mutex_reduce_read);
326         // Reserve items to map and get the start index of them.
327         myItems = (reducedata->nextToRead += CHUNK_SIZE) - CHUNK_SIZE;
328         // Unlock
329         my_pthread_mutex_unlock(&mutex_reduce_read);
330         int end = fmin(myItems + CHUNK_SIZE, reducedata->numOfItems);
331         for (int i = myItems; i < end; ++i)

```

```

332         {
333             reducedata->mapReduce.Reduce( reduceIn.at(i).first,
334                                           *reduceIn.at(i).second);
335         }
336     }
337     my_pthread_mutex_lock(&mutex_log_write);
338     reducedata->logofs << MSG_THREAD_TERMINATED(THREAD_EXECREDUCE)
339     << getTimeStr() << endl;
340     my_pthread_mutex_unlock(&mutex_log_write);
341     return nullptr;
342 }
343
344
345 /**
346  * Transforms the many reduce-thread-data-structures to one big map.
347  * Same as shuffle, but for reduce.
348  */
349 void finalize_output()
350 {
351     pair<k3Base*, v3Base*> currPair;
352     for (size_t i = 0; i < reduceResultLists.size(); ++i)
353     {
354         while( reduceResultLists[i].second != nullptr &&
355                !reduceResultLists[i].second->empty() )
356         {
357             currPair = reduceResultLists[i].second->front();
358             reduceResultLists[i].second->pop();
359             finalOutputMap.insert(currPair);
360         }
361     }
362 }
363
364
365 /**
366  * The main framework function.
367  */
368 OUT_ITEMS_LIST runMapReduceFramework(MapReduceBase &mapReduce,
369                                     IN_ITEMS_LIST &itemsList, int multiThreadLevel)
370 {
371     // open the log file, write and start measuring time
372     std::ofstream ofs(LOG_FILENAME, LOG_OPEN_MODE);
373     ofs << MSG_FRAMEWORK_START(multiThreadLevel) << endl;
374     std::chrono::high_resolution_clock::time_point t1 =
375         std::chrono::high_resolution_clock::now();
376
377     // Initialize mutexes, cvs, datastructures...
378     init(multiThreadLevel);
379     // Turn the in_items_list into a vector for random access
380     vector<IN_ITEM> itemsVector( std::begin(itemsList),
381                                 std::end(itemsList) );
382
383     MapData mapdata = { .mapReduce = mapReduce, .itemsList = itemsVector,
384                        .numOfItems = itemsVector.size(),
385                        .nextToRead = 0, .logofs = ofs};
386
387     // Create the ExecMap threads!
388     my_pthread_mutex_lock(&mutex_em_map); // Barrier to prevent sigsegu
389     for (int i = 0; i < multiThreadLevel; ++i)
390     {
391         my_pthread_mutex_lock(&mutex_log_write);
392         ofs << MSG_THREAD_CREATED(THREAD_EXECMAP) << getTimeStr()
393         << endl;
394         my_pthread_mutex_unlock(&mutex_log_write);
395         my_pthread_create(&threadList[i], nullptr, &ExecMap, &mapdata);
396     }
397     // Initialize all threads' maps
398     for (int i = 0; i < multiThreadLevel; ++i)
399     {

```

```

400     mapResultLists[i] = std::make_pair(threadList[i],
401         new(std::nothrow) K2_V2_LIST);
402     if (mapResultLists[i].second == nullptr)
403     {
404         handleError("new operator");
405     }
406 }
407 my_pthread_mutex_unlock(&mutex_em_map); // Remove the barrier
408
409 // Create the shuffle thread
410 my_pthread_mutex_lock(&mutex_log_write);
411 ofs << MSG_THREAD_CREATED(THREAD_SHUFFLE) << getTimeStr() << endl;
412 my_pthread_mutex_unlock(&mutex_log_write);
413 my_pthread_create(&shuffleThread, nullptr, &Shuffle, nullptr);
414
415 // Wait for the ExecMaps to finish
416 for (int i = 0; i < multiThreadLevel; ++i)
417 {
418     my_pthread_join(threadList[i], nullptr);
419 }
420 // Wait for the shuffle to finish
421 my_pthread_mutex_lock(&mutex_more_to_shuffle);
422 more_to_shuffle = false;
423 my_pthread_mutex_unlock(&mutex_more_to_shuffle);
424 my_pthread_cond_signal(&cv_more_to_shuffle);
425 my_pthread_join(shuffleThread, nullptr);
426
427 // Stop time measuring
428 std::chrono::high_resolution_clock::time_point t2 =
429     std::chrono::high_resolution_clock::now();
430 auto mapShuffleDuration = std::chrono::duration_cast
431     <std::chrono::nanoseconds>(t2 - t1).count();
432 ofs << MSG_THREAD_TERMINATED(THREAD_SHUFFLE) << getTimeStr() << endl;
433
434 // Transform the shuffle output map to a vector.
435 reduceIn.resize(shuffleOut.size());
436 std::move(shuffleOut.begin(), shuffleOut.end(), reduceIn.begin());
437 // Initialize the reducedata struct
438 ReduceData reducedata = {.mapReduce = mapReduce, .threadNum = 0,
439     .numOfItems = reduceIn.size(), .nextToRead = 0, .logofs = ofs};
440
441 // Measure reduce time
442 t1 = std::chrono::high_resolution_clock::now();
443 // Reduce!
444 for (int i = 0; i < multiThreadLevel; ++i)
445 {
446     my_pthread_mutex_lock(&mutex_log_write);
447     ofs << MSG_THREAD_CREATED(THREAD_EXECREDUCE) << getTimeStr()
448         << endl;
449     my_pthread_mutex_unlock(&mutex_log_write);
450     reducedata.threadNum = i;
451     my_pthread_create(&threadList[i], nullptr,
452         &ExecReduce, &reducedata);
453 }
454 // Wait for reduce to finish
455 for (int i = 0; i < multiThreadLevel; ++i)
456 {
457     my_pthread_join(threadList[i], nullptr);
458 }
459 // "Shuffle" reduce's output!
460 finalize_output();
461 // Convert to output type and return.
462 OUT_ITEMS_LIST finalOutput(finalOutputMap.size());
463 std::move(finalOutputMap.begin(), finalOutputMap.end(),
464     finalOutput.begin());
465 // Clean up
466 cleanup();
467

```


```

468     // Stop measuring time, write to log and return
469     t2 = std::chrono::high_resolution_clock::now();
470     auto reduceDuration = std::chrono::duration_cast
471         <std::chrono::nanoseconds>(t2 - t1).count();
472     ofs << MSG_MAP_SHUFFLE_TIME(mapShuffleDuration) << endl;
473     ofs << MSG_REDUCE_TIME(reduceDuration) << endl;
474     ofs << MSG_FRAMEWORK_END << endl;
475     return finalOutput;
476 }
477
478
479 /**
480  * Add <k2*,v2*> to the map-threads data structures
481  */
482 void Emit2(k2Base *key, v2Base *val)
483 {
484     // Figure out which thread is handling this function
485     pthread_t currThread;
486     currThread = pthread_self();
487     size_t end = mapResultLists.size();
488     // Add the given key,val pair to the correct list:
489     for (size_t i = 0; i < end; ++i)
490     {
491         if (pthread_equal(mapResultLists[i].first, currThread))
492         {
493             mapResultLists[i].second->push_back(
494                 std::make_pair(key, val) );
495             return;
496         }
497     }
498 }
499
500 /**
501  * Add <k3*,v3*> to the reduce-threads data structures
502  */
503 void Emit3(k3Base *key, v3Base *val)
504 {
505     pthread_t currThread;
506     currThread = pthread_self();
507     size_t end = reduceResultLists.size();
508     for (size_t i = 0; i < end; ++i)
509     {
510         if (pthread_equal(reduceResultLists[i].first, currThread))
511         {
512             reduceResultLists[i].second->push(
513                 std::make_pair(key, val));
514             return;
515         }
516     }
517 }


```




## 5 Priority.jpg



## 6 RR.jpg



## 7 SRTF.jpg



## 8 Search.cpp

```
1  #include "MapReduceClient.h"
2  #include "MapReduceFramework.h"
3
4  #include <cerrno>
5  #include <string>
6  #include <vector>
7  #include <iostream>
8  #include <dirent.h>
9  #include <cstring>
10
11 #define ARG_STR_TO_FIND 1
12 #define ARG_DIR_START 2
13
14 #define EXIT_SUCC 0
15 #define EXIT_FAIL 1
16 #define THREAD_LEVEL 5
17 #define CURR_DIR "."
18 #define PARENT_DIR ".."
19
20 using std::string;
21
22 // Constants:
23 const int MIN_ARGS = 2;
24 const string USAGE_ERROR_MESSAGE = "Usage: <substring to search> "
25     "<folders, separated by spaces>";
26
27
28 /**
29  * Handle errors as required
30  */
31 static void handleError(const string funcName)
32 {
33     std::cerr << "MapReduceFramework Failure: " << funcName << " failed."
34         << std::endl;
35     exit(EXIT_FAIL);
36 }
37
38 /**
39  * The directory name key (k1Derived)
40  */
41 class DirNameKey : public k1Base
42 {
43 public:
44     DirNameKey(const string d) : dirName(d) {}
45
46     virtual ~DirNameKey() {}
47
48     virtual bool operator<(const k1Base &other) const override
49     {
50         const DirNameKey &dirother =
51             dynamic_cast<const DirNameKey&> (other);
52         return dirName < dirother.dirName;
53     }
54
55     const string getDirName() const
56     {
57         return dirName;
58     }
59 private:
```

```

60     const string dirName;
61 };
62
63 /**
64  * The string to search in the file names
65  */
66 class StringToFind : public v1Base
67 {
68 public:
69     StringToFind(const string toFind) : str(toFind) {}
70
71     string getStr() const
72     {
73         return str;
74     }
75 private:
76     const string str;
77 };
78
79
80 /**
81  * The k2 class (k2Derived) - the filename (inside the input directories)
82  */
83 class FileNameKey1 : public k2Base
84 {
85 public:
86     FileNameKey1(const string f) : fileName(f) {}
87
88     virtual ~FileNameKey1(){}
89
90     virtual bool operator<(const k2Base &other) const override
91     {
92         const FileNameKey1 &fileOther =
93             dynamic_cast<const FileNameKey1&>(other);
94         return fileName < fileOther.fileName;
95     }
96
97     const string getFileName() const
98     {
99         return fileName;
100     }
101
102 private:
103     const string fileName;
104 };
105
106
107 /**
108  * The v2 class (v2Derived) - holds a pointer to the k2 for later
109  * deletion
110  */
111 class v2Deriv : public v2Base
112 {
113 public:
114     v2Deriv(FileNameKey1 *k2p) : k2Pointer(k2p) {}
115
116     virtual ~v2Deriv()
117     {
118         delete k2Pointer;
119         k2Pointer = nullptr;
120     }
121 private:
122     FileNameKey1 *k2Pointer;
123 };
124
125
126
127 /**

```

```

128  * The k3 class (k3Derived) - the filename (inside the input directories)
129  * This is the same as k2
130  */
131  class FileNameKey2 : public k3Base
132  {
133  public:
134      FileNameKey2(const string f) : fileName(f) {}
135
136      virtual ~FileNameKey2(){}
137
138      virtual bool operator<(const k3Base &other) const override
139      {
140          const FileNameKey2 &fileOther =
141              dynamic_cast<const FileNameKey2&>(other);
142          return fileName < fileOther.fileName;
143      }
144
145      const string getFileName() const
146      {
147          return fileName;
148      }
149
150  private:
151      const string fileName;
152  };
153
154  /**
155   * The v3 class (v3Derived) - Holds the number of times the k3 filename
156   * appeared (in total)
157   */
158  class FileCountValue : public v3Base
159  {
160  public:
161
162      FileCountValue(int count) : myCount(count) {}
163
164      virtual ~FileCountValue() {}
165
166      int getCount() const
167      {
168          return myCount;
169      }
170
171  private:
172      const int myCount;
173  };
174
175  /**
176   * The map and reduce functions implementation
177   */
178  class MyMapReduce : public MapReduceBase {
179  public:
180
181      virtual void Map(const k1Base *const key, const v1Base *const val)
182          const override
183      {
184          // Downcast to k1*
185          const DirNameKey* const pdirkey = (const DirNameKey* const)key;
186          const StringToFind* const ptoFind =
187              (const StringToFind* const)val;
188
189          // Open the directory and iterate over files in it
190          string dirName = pdirkey->getDirName();
191
192          DIR *pdir = opendir(dirName.c_str());
193          if (pdir == nullptr)
194          {
195              // Skip this file if it is not a directory.

```

```

196         if (errno == ENOTDIR || errno == ENOENT)
197         {
198             return;
199         }
200         handleError("opendir");
201     }
202     struct dirent *pent = nullptr;
203     string currFile;
204     while ( (pent = readdir(pdir)) )
205     {
206         currFile = pent->d_name;
207         // Ignore '.' and '..' folders
208         if (currFile.compare(CURR_DIR) == 0 ||
209             currFile.compare(PARENT_DIR) == 0 ||
210             // or if searched string was not found.
211             currFile.find(ptoFind->getStr()) == string::npos)
212         {
213             continue;
214         }
215         FileNameKey1* pKey =
216             new(std::nothrow) FileNameKey1(pent->d_name);
217         v2Deriv* pVal = new(std::nothrow) v2Deriv(pKey);
218         if (pKey == nullptr || pVal == nullptr)
219         {
220             handleError("new");
221         }
222         Emit2(pKey, pVal);
223     }
224     if (closedir(pdir) < 0)
225     {
226         handleError("closedir");
227     }
228 }
229
230
231 virtual void Reduce(const k2Base *const key, const V2_LIST &vals)
232     const override
233 {
234     const FileNameKey1* const pfileName =
235         (const FileNameKey1* const)key;
236
237     FileNameKey2 *pKey =
238         new(std::nothrow) FileNameKey2(pfileName->getFileName());
239     FileCountValue *pVal =
240         new(std::nothrow) FileCountValue(vals.size());
241     if (pKey == nullptr || pVal == nullptr)
242     {
243         handleError("new");
244     }
245     Emit3(pKey, pVal);
246     // Delete the k2,v2 pairs
247     v2Deriv* currV2Item;
248     for (auto it = vals.begin(); it != vals.end(); ++it)
249     {
250         currV2Item = dynamic_cast<v2Deriv*>(*it);
251         delete currV2Item;
252         currV2Item = nullptr;
253     }
254 }
255 };
256
257
258 /**
259  * Delete allocated <k1,v1> <k3,v3> pairs from input/output lists
260  */
261 void cleanup(IN_ITEMS_LIST& inItems, OUT_ITEMS_LIST& outItems)
262 {
263     for (auto it = inItems.begin(); it != inItems.end(); ++it)

```

```

264     {
265         delete it->first;
266         delete it->second;
267     }
268     for (auto it = outItems.begin(); it != outItems.end(); ++it)
269     {
270         delete it->first;
271         delete it->second;
272     }
273 }
274
275 /**
276  * Runs the framework and prints the results
277  */
278 void runMapReduce(int numOfDirs, string strToFind,
279                  std::vector<string>& dirName)
280 {
281     // Prepare the input
282     IN_ITEMS_LIST inItems;
283     MyMapReduce mapReduce;
284     std::pair<k1Base*, v1Base*> currPair;
285     for (int i = 0; i < numOfDirs; ++i)
286     {
287         currPair = std::make_pair(new DirNameKey(dirName[i]),
288                                 new StringToFind(strToFind));
289         inItems.push_back(currPair);
290     }
291
292     // Run MapReduce
293     OUT_ITEMS_LIST outItems =
294         runMapReduceFramework(mapReduce, inItems, THREAD_LEVEL);
295
296     // Print the [sorted] output
297     for (auto it = outItems.begin(); it != outItems.end(); ++it)
298     {
299         FileNameKey2* filename =
300             dynamic_cast<FileNameKey2*>(it->first);
301         FileCountValue* count =
302             dynamic_cast<FileCountValue*>(it->second);
303
304         // For each occurrence of the filename, print it.
305         for (int i = 0; i < count->getCount(); ++i)
306         {
307             std::cout << filename->getFileName() << std::endl;
308         }
309     }
310     cleanup(inItems, outItems);
311 }
312
313 int main(int argc, char* argv[])
314 {
315     if (argc >= MIN_ARGS)
316     {
317         string strToFind = argv[ARG_STR_TO_FIND];
318         std::vector<string> dirNames(argv + ARG_DIR_START, argv + argc);
319         // Minus 2 for this file name (Search.cpp) and the str to find
320         runMapReduce(argc - 2, strToFind, dirNames);
321     }
322     else
323     {
324         std::cerr << USAGE_ERROR_MESSAGE << std::endl;
325         std::exit(EXIT_FAIL);
326     }
327     return EXIT_SUCC;
328 }

```



## 9 error handle.h

```
1  #ifndef _ERROR_HANDLE_H
2  #define _ERROR_HANDLE_H
3
4  #include <iostream>
5  #include <string>
6
7  #define EXIT_ERROR 1
8
9  using std::string;
10 using std::cerr;
11 using std::endl;
12
13 /**
14  * Handles an error with a function named <funcName> as specified in the
15  * exercise instructions.
16  */
17 void handleError(const string funcName)
18 {
19     cerr << "MapReduceFramework Failure: " << funcName << " failed."
20         << endl;
21     exit(EXIT_ERROR);
22 }
23
24 #endif
```

# 10 my pthread.h

```
1  /**
2   * This header is a wrapper for some of the pthread library functions
3   * which adds error handling, as specified in the exercise instructions.
4   * All functions don't return any value (void functions) and upon errors they
5   * print the default error message and exit the process.
6   */
7  #ifndef _MY_PTHREAD_H
8  #define _MY_PTHREAD_H
9
10 #include <pthread.h>
11 #include "error_handle.h"
12
13 #define PTHREAD_SUCCESS 0
14
15 void my_pthread_create(pthread_t *thread, const pthread_attr_t *attr,
16     void *(*start_routine) (void *), void *arg)
17 {
18     int ret_code = PTHREAD_SUCCESS;
19     ret_code = pthread_create(thread, attr, start_routine, arg);
20     if (ret_code != PTHREAD_SUCCESS)
21     {
22         handleError("pthread_create");
23     }
24 }
25
26 void my_pthread_join(pthread_t thread, void **retval)
27 {
28     int ret_code = PTHREAD_SUCCESS;
29     ret_code = pthread_join(thread, retval);
30     if (ret_code != PTHREAD_SUCCESS)
31     {
32         handleError("pthread_join");
33     }
34 }
35
36 void my_pthread_mutex_init(pthread_mutex_t *mutex,
37     const pthread_mutexattr_t *attr)
38 {
39     int ret_code = PTHREAD_SUCCESS;
40     ret_code = pthread_mutex_init(mutex, attr);
41     if (ret_code != PTHREAD_SUCCESS)
42     {
43         handleError("pthread_mutex_init");
44     }
45 }
46
47 void my_pthread_mutex_destroy(pthread_mutex_t *mutex)
48 {
49     int ret_code = PTHREAD_SUCCESS;
50     ret_code = pthread_mutex_destroy(mutex);
51     if (ret_code != PTHREAD_SUCCESS)
52     {
53         handleError("pthread_mutex_destroy");
54     }
55 }
56
57 void my_pthread_mutex_lock(pthread_mutex_t *mutex)
58 {
59     int ret_code = PTHREAD_SUCCESS;
```

```

60     ret_code = pthread_mutex_lock(mutex);
61     if (ret_code != PTHREAD_SUCCESS)
62     {
63         handleError("pthread_mutex_lock");
64     }
65 }
66
67 void my_pthread_mutex_unlock(pthread_mutex_t *mutex)
68 {
69     int ret_code = PTHREAD_SUCCESS;
70     ret_code = pthread_mutex_unlock(mutex);
71     if (ret_code != PTHREAD_SUCCESS)
72     {
73         handleError("pthread_mutex_unlock");
74     }
75 }
76
77 void my_pthread_cond_init(pthread_cond_t *cond,
78     const pthread_condattr_t *attr)
79 {
80     int ret_code = PTHREAD_SUCCESS;
81     ret_code = pthread_cond_init(cond, attr);
82     if (ret_code != PTHREAD_SUCCESS)
83     {
84         handleError("pthread_cond_init");
85     }
86 }
87
88 void my_pthread_cond_destroy(pthread_cond_t *cond)
89 {
90     int ret_code = PTHREAD_SUCCESS;
91     ret_code = pthread_cond_destroy(cond);
92     if (ret_code != PTHREAD_SUCCESS)
93     {
94         handleError("pthread_cond_destroy");
95     }
96 }
97
98 void my_pthread_cond_signal(pthread_cond_t *cond)
99 {
100     int ret_code = PTHREAD_SUCCESS;
101     ret_code = pthread_cond_signal(cond);
102     if (ret_code != PTHREAD_SUCCESS)
103     {
104         handleError("pthread_cond_signal");
105     }
106 }
107
108 void my_pthread_cond_wait(pthread_cond_t *cond, pthread_mutex_t *mutex)
109 {
110     int ret_code = PTHREAD_SUCCESS;
111     ret_code = pthread_cond_wait(cond, mutex);
112     if (ret_code != PTHREAD_SUCCESS)
113     {
114         handleError("pthread_cond_wait");
115     }
116 }
117
118
119 void my_pthread_cond_timedwait(pthread_cond_t *cond,
120     pthread_mutex_t *mutex, const struct timespec *abstime)
121 {
122     /* int ret_code = PTHREAD_SUCCESS;
123     ret_code = */pthread_cond_timedwait(cond, mutex, abstime);
124     /* if (ret_code != PTHREAD_SUCCESS)
125     {
126         handleError("pthread_cond_timedwait");
127     } */

```

```
128  
129  }  
130  
131  #endif
```