Mock Test based on C++

This test contains 20 questions based on C++ programming. Each question carries 2 marks.

Duration: 50 Minutes

choudharyfaizan15@gmail.com Switch account

Draft saved

* Required

Email *

choudharyfaizan15@gmail.com

Write Your Name and Roll Number *

Faizan Choudhary 20BCS021

What will be the output of the following C++ code?

```
#include <iostream>
using namespace std;
void square (int *x, int *y)
{
      *x = (*x) * - - (*y);
}
int main ( )
{
      int number = 30;
      square(&number, &number);
      cout << number;
      return 0;
}
```

- ○ Error
- ◉ 870
- ○ 30
- ○ Segmentation Fault

Clear selection

What will be the output of the following C++ program?

```
#include <iostream>
using namespace std;
class A{
public:
      A(){
            cout<<"Constructor called\n";
        }
      ~A(){
            cout<<"Destructor called\n";
         }
};
int main(int argc, char const *argv[])
{
      A *a = new A[5];
      delete[] a;
      return 0;
}
```

- (●) “Constructor called” five times and then “Destructor called” five times
- ( ) “Constructor called” five times and then “Destructor called” once
- ( ) Segmentation fault
- ( ) Error

Clear selection

What will be the output of the following C++ program?

```
class base
{
public:
      base()
      {
         cout<<"BCon";
      }
      ~base()
      {
         cout<<"BDest ";
      }
};
class derived: public base
{
public:
      derived()
      {    cout<<"DCon ";
      }
      ~derived()
      {    cout<<"DDest ";
      }
};

int main()
{
derived object;
return 0;
}
```

- ○ Dcon DDest
- ○ Dcon DDest BCon BDest
- ◉ BCon DCon DDest BDest
- ○ BCon DCon BDes DDest

Clear selection

What will be the output of the following C++ program?

```
#include<iostream.h>
void Execute(int &x, int y = 200)
{
 int TEMP = x + y;
 x+= TEMP;
 if(y!=200)
    cout<<TEMP<<x<<y"--";
}

int main()
{
 int A=50, B=20;
 cout<<A<<B<<"--";
 Execute(A,B);
 cout<<A<<B<<"--";
 return 0;
}
```

- ○ 5020--5020--
- ○ 5020--70120200--5020
- ◉ 5020--7012020--12020--
- ○ 5020--7050200--5020--
- ○ Option 5

Clear selection

Can we typecast void * into int *?

- ○ Yes
- ○ Depends on Compiler
- ◉ No
- ○ Undefined

Clear selection

What will be the output of the following C++ program?

```
#include<iostream>
using namespace std;

int main()
{

cout<<-1-1-1;

return 0;
}
```

- ○ 3
- ○ Compiler Error
- ◉ -3
- ○ 0

Clear selection

What is the output of the program?

```
#include <iostream>
using namespace std;

class X
{
public: X()
      { cout<<"X"; }
      ~X()
      { cout<<"~X"; }
};

class Y : public X
{
public: Y()
      { cout<<"Y"; }
      ~Y()
      { cout<<"~Y"; }
};

int main()
{
   Y obj;
   return 0;
}
```

- ○ XY~X~Y
- ◉ XY~Y~X
- ○ X~X~YY
- ○ X~XY~Y

Clear selection

What is size of void in C++?

- 0
- Undefined
- 4 Bytes
- 2 Bytes

Clear selection

What should be printed on screen?

```
int main()
{
int x = 5;

if(x++ == 5)
cout<<"Five"<<endl;
else
if(++x == 6)
cout<<"Six"<<endl;

return 0;
}
```

- None of these
- Six
- Five
- FiveSix

Clear selection

What should be output of below program
if use enter a = 5?

```
int main()
{
   int a;
   cin>>a; // user can enter any value

      if (++a*5 <= 25)
      {
         cout<<"Hello";
      }
      else
      {
         cout<<"Bye";
      }

}
```

- ○ Hello
- ◉ Bye
- ○ Undefined
- ○ Compilation Error

Clear selection

Find the output of below program.

```
int main()
{
for(int i=1;i<=2;i++)
{
for(int j=i;j<=2;j++)
cout<<i<<@;
}
}
```

- (●) 1@1@2@
- ( ) 1@2@1@
- ( ) 1@2@
- ( ) 1@2@2@

Clear selection

Find output of below program

```
int main()
{
int c1,c2;
int a = -8;
int b = 3;
c1 = --a + b;
c2 = a-- + b;
cout<<"c1="<<c1<<", "<<"c2="<<c2<<endl;

return 0;
}
```

- (●) c1=-6,c2=-6
- ( ) c1=-7,c2=-4
- ( ) c1=-4,c1=b-3
- ( ) c1=-7,c2=-3

Clear selection

Which Exception is thrown when new fails to allocate memory?

- ( ) std::runtime_error
- ( ) std::exception
- ( ) std::out_of_range
- (●) std::bad_alloc

Clear selection

What would happen in case one uses a void in the passing of an argument?

- ○ It may not or may depend on a declared return type of any function. The return type of the function is different from the passed arguments
- ○ It would return some value to the caller
- ◉ It would not return any value to the caller
- ○ It would return any value

Clear selection

Which of the following statements is correct about the formal parameters in C++?

- ○ Variables other than passed parameters in a function
- ○ Parameters with which functions are called
- ◉ Parameters which are used in the definition of the function
- ○ Variables that are never used in the function

Clear selection

```
#include<iostream>
using namespace std;

class A {
 public:
   A(int ii = 0) : i(ii) {}
   void show() { cout << "i = " << i << endl;}
 private:
   int i;
};

class B {
 public:
   B(int xx) : x(xx) {}
   operator A() const { return A(x); }
 private:
   int x;
};

void g(A a)
{  a.show(); }

int main() {
  B b(10);
  g(b);
  g(20);
  getchar();
  return 0;
}
```

- ○ 10
- ○ 1
- ○ 20
- ○ 0

```
#include<iostream>
using namespace std;

class base {
   int arr[10];
};

class b1: public base { };

class b2: public base { };

class derived: public b1, public b2 {};

int main(void)
{
  cout<<sizeof(derived);
  getchar();
  return 0;
}
```

- (●) 80
- ( ) 50
- ( ) 40
- ( ) 60

Clear selection

```
#include<iostream>

using namespace std;
class P {
public:
  void print()
  { cout <<" Inside P::"; }
};

class Q : public P {
public:
  void print()
  { cout <<" Inside Q"; }
};

class R: public Q {
};

int main(void)
{
  R r;

  r.print();
  return 0;
}
```

- (●) Inside Q
- ( ) None of the Above
- ( ) Inside P
- ( ) Error

Clear selection

```
#include<iostream>
using namespace std;
int &fun() {
  static int a = 10;
  return a;
}

int main() {
  int &y = fun();
  y = y +30;
  cout<<fun();
  return 0;
}
```

- ○ 0
- ○ 40
- ◉ 30
- ○ Error

Clear selection

```
#include<iostream>
using namespace std;

class Point
{
private:
   int x;
   int y;
public:
   Point(const Point&p) { x = p.x; y = p.y; }
   void setX(int i) {x = i;}
   void setY(int j) {y = j;}
   int getX() {return x;}
   int getY() {return y;}
   void print() { cout << "x = " << getX() << ", y = " << getY(); }
};


int main()
{
   Point p1;
   p1.setX(10);
   p1.setY(20);
   Point p2 = p1;
   p2.print();
   return 0;
}
```

- ○ 20
- ◉ Compilation error
- ○ 10
- ○ None of the above

Clear selection

Submit Clear form

Never submit passwords through Google Forms.

This content is neither created nor endorsed by Google. Report Abuse - Terms of Service - Privacy Policy

Google Forms