

NAME

nfservctl – syscall interface to kernel nfs daemon

LIBRARY

Standard C library (*libc*, *-lc*)

SYNOPSIS

```
#include <linux/nfsd/syscall.h>
```

```
long nfservctl(int cmd, struct nfsctl_arg *argp,
               union nfsctl_res *resp);
```

DESCRIPTION

Note: Since Linux 3.1, this system call no longer exists. It has been replaced by a set of files in the *nfsd* filesystem; see [nfsd\(7\)](#).

```
/*
 * These are the commands understood by nfsctl().
 */
#define NFSCTL_SVC          0 /* This is a server process. */
#define NFSCTL_ADDCLIENT   1 /* Add an NFS client. */
#define NFSCTL_DELCLIENT   2 /* Remove an NFS client. */
#define NFSCTL_EXPORT       3 /* Export a filesystem. */
#define NFSCTL_UNEXPORT     4 /* Unexport a filesystem. */
#define NFSCTL_UGIDUPDATE   5 /* Update a client's UID/GID map
                               (only in Linux 2.4.x and earlier). */
#define NFSCTL_GETFH        6 /* Get a file handle (used by mountd(8))
                               (only in Linux 2.4.x and earlier). */

struct nfsctl_arg {
    int                ca_version; /* safeguard */
    union {
        struct nfsctl_svc    u_svc;
        struct nfsctl_client u_client;
        struct nfsctl_export u_export;
        struct nfsctl_uidmap u_umap;
        struct nfsctl_fhparm u_getfh;
        unsigned int         u_debug;
    } u;
};

union nfsctl_res {
    struct knfs_fh    cr_getfh;
    unsigned int      cr_debug;
};
```

RETURN VALUE

On success, zero is returned. On error, *-1* is returned, and *errno* is set to indicate the error.

STANDARDS

Linux.

HISTORY

Removed in Linux 3.1. Removed in glibc 2.28.

SEE ALSO

[nfsd\(7\)](#)