

EXPERIMENT 10

Aim

Study of Wireshark and understand its functionality

Prerequisite

Nil

Outcome

To impart knowledge of Computer Networking Technology

Theory

Wireshark is a popular and powerful open-source network protocol analyser that allows users to capture, inspect, and analyse data traffic on a computer network. It is widely used by network administrators, security professionals, and developers to troubleshoot network issues, monitor network performance, and identify potential security vulnerabilities.

Wireshark boasts support for a wide array of network protocols, including common ones like TCP, IP, UDP, HTTP, and HTTPS, as well as less common or proprietary protocols. The tool can decode and display information about each packet, allowing users to understand the contents of network traffic and identify potential issues.

Here are some key aspects of Wireshark:

- Packet Capture
- Protocol Support
- Live Capture and Offline Analysis
- Display Filters
- Packet Inspection
- Statistics and Graphs
- Colour Coding
- Extensibility
- Cross-Platform
- Community and Support
- Security Analysis
- Educational Tool

Procedure

1. Install the Wireshark and integrate it with network simulator
2. Analyse the traffic using Wireshark

Output

336	11.019952	23.55.245.49	192.168.0.103	TCP	1418 [TCP Retransmission] 443 → 50574 [ACK] Seq=240644 Ack=1599 Win=501
337	11.019952	23.55.245.49	192.168.0.103	TCP	1418 [TCP Retransmission] 443 → 50574 [PSH, ACK] Seq=242008 Ack=1599 Win=501
338	11.020093	192.168.0.103	23.55.245.49	TCP	90 50574 → 443 [ACK] Seq=1599 Ack=262468 Win=2067 Len=0 SLE=300660 SR
339	11.023347	23.55.245.49	192.168.0.103	TCP	1418 [TCP Retransmission] 443 → 50574 [ACK] Seq=262468 Ack=1599 Win=501
340	11.023459	192.168.0.103	23.55.245.49	TCP	90 50574 → 443 [ACK] Seq=1599 Ack=266560 Win=2067 Len=0 SLE=300660 SR
341	11.023667	23.55.245.49	192.168.0.103	TCP	1418 [TCP Retransmission] 443 → 50574 [ACK] Seq=266560 Ack=1599 Win=501
342	11.023751	192.168.0.103	23.55.245.49	TCP	90 50574 → 443 [ACK] Seq=1599 Ack=269288 Win=2067 Len=0 SLE=300660 SR
343	11.024921	23.55.245.49	192.168.0.103	TCP	1418 [TCP Retransmission] 443 → 50574 [ACK] Seq=269288 Ack=1599 Win=501
344	11.025045	192.168.0.103	23.55.245.49	TCP	82 50574 → 443 [ACK] Seq=1599 Ack=282928 Win=2067 Len=0 SLE=300660 SR
345	11.026664	23.55.245.49	192.168.0.103	TCP	1418 [TCP Retransmission] 443 → 50574 [ACK] Seq=282928 Ack=1599 Win=501
346	11.026771	192.168.0.103	23.55.245.49	TCP	74 50574 → 443 [ACK] Seq=1599 Ack=288384 Win=2067 Len=0 SLE=300660 SR
347	11.027266	23.55.245.49	192.168.0.103	TCP	1418 [TCP Retransmission] 443 → 50574 [ACK] Seq=288384 Ack=1599 Win=501
348	11.027378	192.168.0.103	23.55.245.49	TCP	74 50574 → 443 [ACK] Seq=1599 Ack=289748 Win=2067 Len=0 SLE=300660 SR
349	11.028137	23.55.245.49	192.168.0.103	TCP	1418 [TCP Retransmission] 443 → 50574 [PSH, ACK] Seq=289748 Ack=1599 Win=501
350	11.028234	192.168.0.103	23.55.245.49	TCP	66 50574 → 443 [ACK] Seq=1599 Ack=296568 Win=2067 Len=0 SLE=300660 SR
351	11.029532	23.55.245.49	192.168.0.103	TCP	1418 [TCP Retransmission] 443 → 50574 [ACK] Seq=296568 Ack=1599 Win=501
352	11.029627	192.168.0.103	23.55.245.49	TCP	66 50574 → 443 [ACK] Seq=1599 Ack=297932 Win=2067 Len=0 SLE=300660 SR
353	11.029837	23.55.245.49	192.168.0.103	TCP	1418 [TCP Retransmission] 443 → 50574 [ACK] Seq=297932 Ack=1599 Win=501
354	11.029837	23.55.245.49	192.168.0.103	TCP	1418 [TCP Retransmission] 443 → 50574 [PSH, ACK] Seq=299296 Ack=1599 Win=501
355	11.029984	192.168.0.103	23.55.245.49	TCP	54 50574 → 443 [ACK] Seq=1599 Ack=304853 Win=2067 Len=0
356	11.060212	10.30.80.76	239.255.255.250	SSDP	217 M-SEARCH * HTTP/1.1
357	11.160949	10.30.80.78	239.255.255.250	SSDP	217 M-SEARCH * HTTP/1.1
358	12.082829	10.30.80.76	239.255.255.250	SSDP	217 M-SEARCH * HTTP/1.1
359	12.185250	10.30.80.78	239.255.255.250	SSDP	217 M-SEARCH * HTTP/1.1
360	13.004628	10.30.80.76	239.255.255.250	SSDP	217 M-SEARCH * HTTP/1.1
361	13.106837	10.30.80.78	239.255.255.250	SSDP	217 M-SEARCH * HTTP/1.1
362	14.335828	192.168.0.1	224.0.0.1	IGMPv3	50 Membership Query, general
363	14.374261	192.168.0.103	224.0.0.22	IGMPv3	54 Membership Report / Join group 224.0.0.252 for any sources
364	15.871820	192.168.0.103	224.0.0.22	IGMPv3	54 Membership Report / Join group 224.0.0.251 for any sources

1	0.000000	172.217.160.195	192.168.1.106	QUIC	1292 Initial, SCID=fde3c768ce746219
2	0.028277	172.217.160.195	192.168.1.106	QUIC	1292 Protected Payload (KP0)
3	0.028277	172.217.160.195	192.168.1.106	QUIC	861 Protected Payload (KP0)
4	0.028743	192.168.1.106	172.217.160.195	QUIC	120 Handshake, DCID=fde3c768ce746219
5	0.028856	192.168.1.106	172.217.160.195	QUIC	73 Protected Payload (KP0), DCID=fde3c768ce746219
6	0.028948	172.217.160.195	192.168.1.106	QUIC	189 Protected Payload (KP0)
7	0.028948	172.217.160.195	192.168.1.106	QUIC	66 Protected Payload (KP0)
8	0.029189	172.217.160.195	192.168.1.106	QUIC	64 Protected Payload (KP0)
9	0.029350	192.168.1.106	172.217.160.195	QUIC	73 Protected Payload (KP0), DCID=fde3c768ce746219
11	0.083408	172.217.160.195	192.168.1.106	QUIC	559 Protected Payload (KP0)
12	0.083408	172.217.160.195	192.168.1.106	QUIC	64 Protected Payload (KP0)
13	0.083888	192.168.1.106	172.217.160.195	QUIC	77 Protected Payload (KP0), DCID=fde3c768ce746219
14	0.087424	172.217.160.195	192.168.1.106	QUIC	162 Protected Payload (KP0)
15	0.087794	192.168.1.106	172.217.160.195	QUIC	73 Protected Payload (KP0), DCID=fde3c768ce746219
16	0.149300	172.217.160.195	192.168.1.106	QUIC	67 Protected Payload (KP0)
29	3.032789	192.168.1.106	142.250.183.202	UDP	71 53001 → 443 Len=29
30	3.113542	142.250.183.202	192.168.1.106	UDP	67 443 → 53001 Len=25
36	7.756970	142.250.192.14	192.168.1.106	UDP	79 443 → 56092 Len=37
37	7.756970	142.250.192.14	192.168.1.106	UDP	206 443 → 56092 Len=164

Frame 9: 73 bytes on wire (584 bits), 73 bytes captured (584 bits) on interface \Device\NPF_{63159C60-9} Ethernet II, Src: Chongqin_f0:16:b7 (Sc:ba:ef:f0:16:b7), Dst: Tp-Link_T71:7b:98 (60:e3:27:71:7b:98)
 Internet Protocol Version 4, Src: 192.168.1.106, Dst: 172.217.160.195
 User Datagram Protocol, Src Port: 52343, Dst Port: 443
 QUIC IETF

- Transmission Control Protocol, Src Port: 443, Dst Port: 50599, Seq: 0, Ack: 1, Len: 0
 - Source Port: 443
 - Destination Port: 50599
 - [Stream index: 0]
 - [Conversation completeness: Incomplete (2)]
 - [TCP Segment Len: 0]
 - Sequence Number: 0 (relative sequence number)
 - Sequence Number (raw): 3782687390
 - [Next Sequence Number: 1 (relative sequence number)]
 - Acknowledgment Number: 1 (relative ack number)
 - Acknowledgment number (raw): 1544047550
 - 1000 = Header Length: 32 bytes (8)
 - Flags: 0x012 (SYN, ACK)
 - Window: 64240
 - [Calculated window size: 64240]
 - Checksum: 0x6348 [unverified]
 - [Checksum Status: Unverified]
 - Urgent Pointer: 0
 - Options: (12 bytes), Maximum segment size, No-Operation (NOP), No-Operation (NOP), SACK permitted, N
 - [Timestamps]

```

Internet Protocol Version 4, Src: 23.206.173.11, Dst: 192.168.0.103
  0100 .... = Version: 4
  .... 0101 = Header Length: 20 bytes (5)
  > Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    Total Length: 52
    Identification: 0x0000 (0)
  > 010. .... = Flags: 0x2, Don't fragment
    ...0 0000 0000 0000 = Fragment Offset: 0
    Time to Live: 49
    Protocol: TCP (6)
    Header Checksum: 0xc3db [validation disabled]
    [Header checksum status: Unverified]
    Source Address: 23.206.173.11
    Destination Address: 192.168.0.103

```

```

0000  70 9c d1 de e7 02 ac 15 a2 da 8d 59 08 00 45 00  p.....Y..E
0010  00 34 00 00 40 00 31 06 c3 db 17 ce ad 0b c0 a8  .4..@.1.....
0020  00 67 01 bb c5 a7 e1 77 3a 9e 5c 08 4b be 80 12  .g....w :.\K...
0030  fa f0 63 48 00 00 02 04 05 54 01 01 04 02 01 03  --cH....T.....
0040  03 07  ..

```

Observation & Learning

- **Packet Capture:** Wireshark effectively captured network traffic on the specified interface, allowing us to monitor the data packets as they passed through the network.
- **Protocol Diversity:** Wireshark identified and displayed a wide variety of network protocols, including common ones like TCP, IP, UDP, HTTP, and HTTPS. This diversity is essential for understanding the different types of traffic on the network.
- **Packet Analysis:** The tool enabled us to inspect individual packets, revealing detailed information about each one. This included source and destination IP addresses, port numbers, protocol-specific details, and the content of data payloads.
- **Real-time Analysis:** Wireshark's live capture feature provided real-time data, allowing us to monitor network activity as it happened. This proved valuable for troubleshooting and identifying issues promptly.
- **Display Filters:** The use of display filters made it easy to isolate and focus on specific aspects of network traffic, helping us pinpoint relevant information amid a large volume of data.

Conclusion

The use of Wireshark for analysing network traffic has proven to be an indispensable practice for maintaining a well-functioning and secure network. This tool not only provides a comprehensive view of network activity but also empowers us to diagnose issues, optimize network performance, and enhance our network's overall reliability and security. The insights gained from this analysis will be invaluable in our ongoing efforts to manage and improve our network infrastructure.