Practical 3



3.1.1. Numpy Array Operations

Write a Python program to create a NumPy array based on user input and display the following:

- The created NumPy array.
- The number of dimensions of the array using `ndim`
- The shape of the array using `shape`
- The total number of elements in the array using `size`

Assume all input elements are valid integers.

Input Format:

- The first line contains two space-separated integers, r and c, representing the number of rows and the number of columns.
- The next r lines contain c space-separated integers representing the elements of the array, entered row by row.

Output Format:

- The created NumPy array (printed as a 2D array).
- An integer representing the number of dimensions of the array.
- A tuple representing the shape of the array.
- An integer representing the total number of elements in the array.

Note: Use `reshape()` function to reshape the input array with the specified number of rows and columns.

Sample Test Cases

```python
import numpy as np

r, c = map(int, input().split())

# If rows and columns are 0
if r == 0 and c == 0:
    arr = np.array([]).reshape(0, 0)
else:
    elements = []

    # Read elements row by row
    for _ in range(r):
        row = list(map(int, input().split()))
        elements.extend(row)

    # Convert to NumPy array and reshape
    arr = np.array(elements).reshape(r, c)

# Output
print(arr)
print(arr.ndim)
print(arr.shape)
print(arr.size)
```



3.2.1. Numpy: Matrix Operations

The given code takes two 3×3 matrices, **matrix_a**, and **matrix_b**, as input from the user and converts them into NumPy arrays.

Task:

You are required to compute and display the results of the following matrix operations:

1. **Addition** (matrix_a + matrix_b)
2. **Subtraction** (matrix_a − matrix_b)
3. **Element-wise Multiplication** (matrix_a * matrix_b)
4. **Matrix Multiplication** (matrix_a · matrix_b)
5. **Transpose of Matrix A**

Input Format:

- The user will input 3 rows for **matrix_a**, each containing 3 integers separated by spaces.
- Similarly, the user will input 3 rows for **matrix_b**, each containing 3 integers separated by spaces.

Output Format:

The program should display the results of the operations in the following order:

1. The result of Addition.
2. The result of Subtraction.
3. The result of Element-wise Multiplication.
4. The result of Matrix Multiplication.
5. The Transpose of Matrix A.

Sample Test Cases

```python
import numpy as np

# Input matrices
print("Enter Matrix A:")
matrix_a = np.array([list(map(int, input().split())) for i in range(3)])

print("Enter Matrix B:")
matrix_b = np.array([list(map(int, input().split())) for i in range(3)])


# Addition
print("Addition (A + B):")
print(matrix_a + matrix_b)
# Subtraction
print("Subtraction (A - B):")
print(matrix_a - matrix_b)
# Multiplication (element-wise)
print("Element-wise Multiplication (A * B):")
print(matrix_a * matrix_b)
# Matrix multiplication (dot product)
print("A dot B:")
print(np.dot(matrix_a, matrix_b))

# Transpose
print("Transpose of A:")
print(matrix_a.T)
```



3.2.2. Numpy: Horizontal and Vertical Stacking of Arrays

You are given two arrays `arr1` and `arr2`. You need to perform horizontal and vertical stacking operations on them using NumPy.

- **Horizontal Stacking**: Stack the two matrices horizontally (side by side).
- **Vertical Stacking**: Stack the two matrices vertically (one below the other).

Input Format:

- The program should first prompt the user to input two 3x3 arrays.
- Each array consists of 3 rows, and each row contains 3 space-separated integers.
- The user will input the two arrays row by row.

Output Format:

- The program should display the result of the Horizontal Stack (side-by-side stacking) of the two arrays.
- The program should then display the result of the Vertical Stack (one below the other) of the two arrays.

Sample Test Cases

```python
import numpy as np

# Input matrices
print("Enter Array1:")
arr1 = np.array([list(map(int, input().split())) for i in range(3)])

print("Enter Array2:")
arr2 = np.array([list(map(int, input().split())) for i in range(3)])

# Perform horizontal stacking (hstack)
print("Horizontal Stack:")

print(np.hstack((arr1, arr2)))


# Perform vertical stacking (vstack)
print("Vertical Stack:")

print(np.vstack((arr1, arr2)))
```


CODETANTRA
Home
Learn Anywhere
202501120022@mitaoe.ac.in
Support
Logout
3.2.3. Numpy: Custom Sequence Generation
01:52
Write a Python program that takes the following inputs from the user:
• Start value: The starting point of the sequence.
• Stop value: The sequence should end before this value.
• Step value: The increment between each number in the sequence.
The program should then generate a sequence using numpy based on these inputs and print the generated sequence.
Input Format:
• The user will input three integer values: start, stop, and step, each on a new line.
Output Format:
• The program should print the generated sequence based on the input values.
Sample Test Cases
customS...
Submit
Explorer
Debugger
import numpy as np
# Take user input for the start, stop, and step of the sequence
start = int(input())
stop = int(input())
step = int(input())
# Generate the sequence using np.arange()
seq=np.arange(start, stop, step)
#Print the generated sequence
print(seq)
Terminal
Test cases
‹ Prev
Reset
Submit
Next ›


CODETANTRA
Home
Learn Anywhere
202501120022@mitaoe.ac.in
Support
Logout
3.2.4. Numpy: Arithmetic and Statistical Operations, Mathematical Operations, Bitwise Operators
02:24
You are given two arrays A and B. Your task is to complete the function array_operations, which will convert these lists into NumPy arrays and perform the following operations:
1. Arithmetic Operations:
• Compute the element-wise sum, difference, and product of the two arrays.
2. Statistical Operations:
• Calculate the mean, median, and standard deviation of array A.
3. Bitwise Operations:
• Perform bitwise AND, bitwise OR, and bitwise XOR on the arrays (ex. A_1 OR B_1).
Input Format:
• The first line contains space-separated integers representing the elements of array A.
• The second line contains space-separated integers representing the elements of array B.
Output Format:
• For each operation (arithmetic, statistical, and bitwise), print the results in the specified format as shown in sample test cases.
Sample Test Cases
different...
Submit
Explorer
Debugger
import numpy as np
def array_operations(A, B):
# Convert A and B to NumPy arrays
A = np.array(A)
B = np.array(B)
# Arithmetic Operations
sum_result = A + B
diff_result = A - B
prod_result = A * B
# Statistical Operations
mean_A = np.mean(A)
median_A = np.median(A)
std_dev_A = np.std(A)
# Bitwise Operations
and_result =A & B
or_result = A | B
xor_result =A ^ B
# Output results with one space between each element
print("Element-wise Sum:", ' '.join(map(str, sum_result)))
print("Element-wise Difference:", ' '.join(map(str, diff_result)))
print("Element-wise Product:", ' '.join(map(str, prod_result)))
print(f"Mean of A: {mean_A}")
print(f"Median of A: {median_A}")
print(f"Standard Deviation of A: {std_dev_A}")
print("Bitwise AND:", ' '.join(map(str, and_result)))
Terminal
Test cases
‹ Prev
Reset
Submit
Next ›


CODETANTRA
Home
Learn Anywhere
202501120022@mitaoe.ac.in
Support
Logout
3.2.5. Numpy: Copying and Viewing Arrays
02:03
The given code takes a list of integers as input and converts it into a NumPy array. Your task is to complete the code by:
• Creating a view of the original_array and assigning it to view_array.
• Creating a copy of the original_array and assigning it to copy_array.
After completing these steps, observe how modifying the view affects the original_array, while modifying the copy does not.
Input Format:
• A single line of space-separated integers.
Output Format:
• After modifying the view:
Original array after modifying view: <original_array>
View array: <view_array>
• After modifying the copy:
Original array after modifying copy: <original_array>
Copy array: <copy_array>
Sample Test Cases
copyAnd...
Submit
Explorer
Debugger
import numpy as np
inputlist = list(map(int,input().split(" ")))
# Original array
original_array = np.array(inputlist)
# Create a view
view_array = original_array.view()
# Create a copy
copy_array = original_array.copy()
# Modify the view
view_array[0] = 99
print("Original array after modifying view:", original_array)
print("View array:", view_array)
# Modify the copy
copy_array[1] = 88
print("Original array after modifying copy:", original_array)
print("Copy array:", copy_array)
Terminal
Test cases
‹ Prev
Reset
Submit
Next ›


CODETANTRA
Home
Learn Anywhere
202501120022@mitaoe.ac.in
Support
Logout
3.2.6. Numpy: Searching, Sorting, Counting, Broadcasting
The given code in the editor takes a single array, array1, as space-separated integers as input from the user.
Additionally, it takes the following inputs:
• search_value: The value to search for in the array.
• count_value: The value to count its occurrences in the array.
• broadcast_value: The value to add for broadcasting across the array.
You need to complete the code to perform the following operations:
1. Searching: Find the indices where search_value appears in array1 and print these indices.
2. Counting: Count how many times count_value appears in array1 and print the count.
3. Broadcasting: Add broadcast_value to each element of array1 using broadcasting, and print the resulting array.
4. Sorting: Sort array1 in ascending order and print the sorted array.
Input Format:
1. A single line containing space-separated integers representing array1.
2. An integer search_value represents the value to search for in the array.
3. An integer count_value represents the value to count in the array.
4. An integer broadcast_value represents the value to add to each element of the array.
Output Format:
1. The indices where search_value occurs in array1.
2. The count of occurrences of count_value in array1.
3. The array after adding the broadcast_value to each element.
4. The sorted array.
Sample Test Cases
arrayOpe...
Submit
Explorer
Debugger
import numpy as np
# Input array from the user
array1 = np.array(list(map(int, input().split())))
# Searching
search_value = int(input("Value to search: "))
count_value = int(input("Value to count: "))
broadcast_value = int(input("Value to add: "))
# Find indices where value matches in array1
print(np.where(array1==search_value)[0])
# Count occurrences in array1
print(np.count_nonzero(array1==count_value))
# Broadcasting addition
print(array1+broadcast_value)
# Sort the first array
print(np.sort(array1))
Terminal
Test cases
‹ Prev
Reset
Submit
Next ›


CODETANTRA
Home
Learn Anywhere
202501120022@mitaoe.ac.in
Support
Logout
3.2.7. Student Data Analysis and Operations
Write a Python program that takes the file name of a CSV file containing student details, including roll numbers and their marks in three subjects as input, reads the data, and performs the following operations:
• Print all student details: Display the complete details of all students, including roll numbers and marks for all subjects.
• Find total students: Determine the total number of students in the dataset.
• Print all student roll numbers: Extract and print the roll numbers of all students.
• Print Subject 1 marks: Extract and print the marks of all students in Subject 1.
• Find minimum marks in Subject 2: Identify the lowest marks in Subject 2.
• Find maximum marks in Subject 3: Identify the highest marks in Subject 3.
• Print all subject marks: Display the marks of all students for each subject.
• Find total marks of students: Compute the total marks for each student across all subjects.
• Find the average marks of each student: Compute the average marks for each student.
• Find average marks of each subject: Compute the average marks for all students in each subject.
• Find average marks of Subject 1 and Subject 2: Compute the average marks for Subject 1 and Subject 2.
• Find average marks of Subject 1 and Subject 3: Compute the average marks for Subject 1 and Subject 3.
• Find the roll number of the student with maximum marks in Subject 3: Identify the student with the highest marks in Subject 3 and print their roll number.
• Find the roll number of the student with minimum marks in Subject 2: Identify the student with the lowest marks in Subject 2 and print their roll number.
• Find the roll number of students who scored 24 marks in Subject 2: Identify students who obtained exactly 24 marks in Subject 2 and print their roll numbers.
• Find the count of students who got less than 40 marks in Subject 1: Count the number of students who scored less than 40 marks in Subject 1.
• Find the count of students who got more than 90 marks in Subject 2: Count the number of students who scored more than 90 marks in Subject 2.
• Find the count of students who scored >=90 in each subject: Count the number of students who scored 90 or more marks in each subject.
• Find the count of subjects in which each student scored >=90: Determine how many subjects each student scored 90 or more marks in.
• Print Subject 1 marks in ascending order: Sort and print the marks of students in Subject 1 in ascending order.
• Print students who scored between 50 and 90 in Subject 1: Display students who scored marks between 50 and 90 in Subject 1.
• Find index positions of students who scored 79 in Subject 1: Identify the index positions of students who scored exactly 79 marks in Subject 1.
Operatio...
Submit
Explorer
Debugger
import numpy as np
a = np.loadtxt("Sample.csv", delimiter=',', skiprows=1)
# 1. Print all student details
print("All student Details:\n", a)
# 2. print total students
r,c = a.shape
print("Total Students:", r)
# 3. Print all student Roll numbers
print("All Student Roll Nos",a[:,0])
# 4. Print subject 1 marks
print("Subject 1 Marks",a[:,1])
# 5. print minimum marks of Subject 2
print("Min marks in Subject 2",np.min(a[:,2]))
# 6. print maximum marks of Subject 3
print("Max marks in Subject 3",np.max(a[:,3]))
# 7. Print All subject marks
print("All subject marks:", a[:,1:])
# 8. print Total marks of students
print("Total Marks",np.sum(a[:,1:], axis=1))
# 9. print average marks of each student
avg=np.mean(a[:,1:], axis=1)
print(np.round(avg,1))
Terminal
Test cases
‹ Prev
Reset
Submit
Next ›