



Artificial intelligence


Rajorshi Bhattacharya, Lecturer
(CSE), EU

<https://youtu.be/hEZjPZ-Ze0A>

BAYESIAN BELIEF NETWORKS – EXAMPLE – 1

- You have a new burglar alarm installed at home.
- It is fairly reliable at detecting burglary, but also sometimes responds to minor earthquakes.
- You have two neighbors, John and Merry , who promised to call you at work when they hear the alarm.
- John always calls when he hears the alarm, but sometimes confuses telephone ringing with the alarm and calls too.
- Merry likes loud music and sometimes misses the alarm.
- Given the evidence of who has or has not called, we would like to estimate the probability of a burglary.

BAYESIAN BELIEF NETWORKS – EXAMPLE – 1




BAYESIAN BELIEF NETWORKS – EXAMPLE – 1

1. What is the probability that the alarm has sounded but neither a burglary nor an earthquake has occurred, and both John and Merry call?

BAYESIAN BELIEF NETWORKS – EXAMPLE – 1

1. What is the probability that the alarm has sounded but neither a burglary nor an earthquake has occurred, and both John and Merry call?




Solution:

$$\begin{aligned} P(j \wedge m \wedge a \wedge \neg b \wedge \neg e) &= P(j \mid a) P(m \mid a) P(a \mid \neg b, \neg e) P(\neg b) P(\neg e) \\ &= 0.90 \times 0.70 \times 0.001 \times 0.999 \times 0.998 \\ &= 0.00062 \end{aligned}$$

BAYESIAN BELIEF NETWORKS – EXAMPLE – 1


2. What is the probability that John call?



BAYESIAN BELIEF NETWORKS – EXAMPLE – 1

2. What is the probability that John call?

Solution:



$$P(j) = P(j | a) P(a) + P(j | \neg a) P(\neg a)$$

$$= P(j|a)\{P(a|b,e)*P(b,e)+P(a|\neg b,e)*P(\neg b,e)+P(a|b,\neg e)*P(b,\neg e)+P(a|\neg b,\neg e)*P(\neg b,\neg e)\}$$

$$+ P(j|\neg a)\{P(\neg a|b,e)*P(b,e)+P(\neg a|\neg b,e)*P(\neg b,e)+P(\neg a|b,\neg e)*P(b,\neg e)+P(\neg a|\neg b,\neg e)*$$

$$P(\neg b, \neg e)\}$$

$$= 0.90 * 0.00252 + 0.05 * 0.9974 = 0.0521$$

