Led distance detector with ultrasonic sensor

Joydeep Das gupta
Electrical department
University of engineering and technology)
Chittagong,Bangladesh
u2302056@student.cuet.ac.bd

MD Tahmid Al Mashrafi
Electrical department
University of engineering and technology)
Chittagong,Bangladesh
u2302036@student.cuet.ac.bd

MD.Shadath Hussain
Electrical and Electronic Engineering
Chittagong University of Engineering and Technology,Bangladesh
u2302017@student.cuet.ac.bd

Abstract—This experiment presents the design and implementation of an LED-based distance detector using an ultrasonic sensor and a 555 timer IC. The system operates by transmitting ultrasonic waves and receiving the reflected signal from nearby objects. The time delay between transmission and reception is processed to activate visual and audible indicators. A buzzer and LED provide output indication when an object is detected within a predefined range. The circuit utilizes a lithium battery for portability, polarized capacitors for signal stabilization, and resistors of 1 k and 470 for current limiting. The proposed design is simple, low-cost, and suitable for educational and basic sensing applications.

IndexTerms—

I. INTRODUCTION

Distance measurement and object detection are fundamental requirements in many electronic and industrial applications, including obstacle detection, automation, security systems, and robotics. Among various sensing techniques, ultrasonic sensing is widely used due to its reliability, low cost, and ability to operate independently of lighting conditions. Ultrasonic sensors function by transmitting high-frequency sound waves and measuring the time taken for the reflected waves to return after striking an object. This time delay is directly related to the distance between the sensor and the object.

This experiment focuses on the design of an LED distance detector using an ultrasonic sensor integrated with a 555 timer IC. The 555 timer is a versatile integrated circuit commonly used for timing, pulse generation, and signal conditioning applications. In this design, the 555 timer assists in processing the received ultrasonic signal and triggering output indicators. The use of discrete components such as resistors, capacitors, LEDs, and a buzzer ensures simplicity and ease of implementation, making the circuit suitable for beginner-level electronics laboratories.

The ultrasonic sensor used in this experiment consists of a transmitter and a receiver. The transmitter emits ultrasonic sound waves, typically at a frequency of around 40 kHz. When these waves encounter an object, they are reflected back toward the receiver. The receiver detects the echoed signal, and the sensor produces an output corresponding to the presence of the object. This output signal is then applied to the control circuitry, which activates the LED and buzzer to indicate detection.

A lithium battery is used as the power source to ensure portability and stable operation. Polarized capacitors are incorporated into the circuit to filter noise, stabilize voltage fluctuations, and improve the reliability of the output signal. Current-limiting resistors of 1 k and 470 are used to protect the LED and other components from excessive current. The buzzer provides an audible alert, while the LED offers a clear visual indication of object detection.

The primary objective of this experiment is to demonstrate the practical working principle of ultrasonic distance detection and its integration with basic electronic components. The system is designed to be low-power, cost-effective, and easy to assemble. This makes it an ideal platform for understanding ultrasonic sensing, timer IC operation, and basic signal indica- tion techniques. The experiment also serves as a foundation for more advanced applications such as proximity sensors, smart alert systems, and embedded distance measurement modules.

II. LITERATUREREVIEW

Ultrasonic sensing has been extensively studied and implemented in distance measurement and object detection systems due to its accuracy and simplicity. Ultrasonic sensors operate on the principle of sound wave reflection, where high-frequency acoustic waves are transmitted and reflected by nearby objects. The time-of-flight of the reflected wave is measured to determine the distance. This method has been widely adopted in applications such as parking assistance systems, industrial automation, and robotic navigation.

Previous studies have shown that ultrasonic sensors are particularly effective in environments where optical sensors may fail due to poor lighting, dust, or smoke. Unlike infrared sensors, ultrasonic sensors are less affected by ambient light

conditions, making them suitable for both indoor and outdoor applications. Researchers have demonstrated that ultrasonic distance measurement provides acceptable accuracy for short- and medium-range detection tasks, especially in low-cost systems.

The 555 timer IC has been a popular choice in sensor-based electronic circuits for several decades. Its flexibility allows it to be configured in astable, monostable, or bistable modes, enabling pulse generation and signal processing. In ultrasonic detection systems, the 555 timer is often used to generate trigger pulses, shape received signals, or control output indicators. Studies indicate that combining ultrasonic sensors with timer ICs results in stable and reliable detection performance while minimizing circuit complexity.

Several experimental designs incorporate LEDs and buzzers as output indicators to provide immediate feedback to users. Visual indicators such as LEDs are effective for short-range detection, while audible indicators such as buzzers enhance system usability in environments where visual monitoring is difficult. Research has also emphasized the importance of current-limiting resistors and proper biasing to ensure long-term reliability of these output components.

The use of polarized capacitors in ultrasonic detection circuits has been highlighted in earlier works for their role in filtering noise and stabilizing supply voltages. Voltage fluctuations and signal noise can significantly affect sensor performance, leading to false triggering or unstable output. Capacitors help smooth the power supply and maintain consistent operation, particularly when battery-powered sources such as lithium batteries are used.

Recent educational and hobbyist projects focus on low-cost, modular designs that can be easily assembled and modified. Such designs emphasize the use of commonly available components to enhance learning outcomes and practical understanding. Compared to advanced microcontroller-based systems, discrete-component ultrasonic detectors offer a clear demonstration of fundamental electronic principles without requiring programming knowledge.


In summary, existing literature supports the effectiveness of ultrasonic sensors combined with simple timing and indication circuits. The approach adopted in this experiment aligns with established research trends by providing a reliable, economical, and educationally valuable solution for distance detection and object sensing application

III. METHODOLOGY

A. A.Required Equipment


1)ultrasonic sensor 2)555 timer ic 3)LED 4)Buzzer 5)Resistor(1k,470ohm) 6)polarized capacitor(50V,1000microF) 7)3.5V lithuim battery

B. Circuit Diagram



graphics ,

C. PCB design




graphics

D. Circuit operation

The LED distance detector circuit operates on the principle of ultrasonic wave transmission and echo reception. The system is powered by a lithium battery, which provides a stable DC supply to the ultrasonic sensor, 555 timer IC, and output components. Polarized capacitors are connected across the supply terminals to reduce noise and stabilize voltage fluctuations during operation. The ultrasonic sensor consists of a transmitter and a receiver unit. When the circuit is energized, the transmitter emits ultrasonic sound waves at a high frequency, typically around 40 kHz. These sound waves propagate through air and reflect back when they encounter an obstacle or object within the sensing range. The reflected ultrasonic waves are captured by the receiver section of the sensor,

which converts the acoustic signal into an electrical output. The received signal is fed into the 555 timer IC, which is configured to process the detection signal and generate a corresponding output pulse. The timer IC plays a critical role in signal conditioning by ensuring that only valid detection signals trigger the output stage. When an object is detected within the predefined distance range, the output of the 555 timer transitions to a high state. This high output activates the LED and buzzer connected to the output stage. A 470 resistor is used in series with the LED to limit the forward current and protect it from damage, while a 1 k resistor ensures proper biasing and current control within the circuit. The LED provides a visual indication of object detection, whereas the buzzer generates an audible alert, enhancing user awareness. In the absence of any object, no reflected ultrasonic signal is received, and the output of the 555 timer remains in a low state. As a result, both the LED and buzzer remain inactive. The circuit thus provides re- liable distance-based detection with simple components, low power consumption, and stable operation, making it suitable for educational and basic sensing applications.

E. Hardware Implementation



graphics

F. Cost analysis

The total expenditure for the development of the experi- ment is summarized in table 1.The components were sourced locally,and the budget was optimized.

G. Figures and Tables

TABLEI

DETAILS OF PURCHASED INSTRUMENTS

Items	QTY	Unit cost	total (BDT)
3.7 v battery	1	95	95
Ne 555 timer ic	1	35	35
HC SR04 ultrasonic sensor	1	100	100
RGB	1	20	20
Buzzer	1	18	18
Capacitor	1	12	12
Resistor	2	2	2
Jumper wire	10	10	10
PCB Board	1	45	45

A. A.result

This section operate when an object is close with sensor then the buzzer is on and when the object is far then the buzzer is off. Here ic produce the ulterasonic sound wave and transfer it to the transmitter of sensor.The detector is used for distance detection.

B. B.Application

Obstacle Detection Systems The LED distance detector can be used to detect obstacles in front of a moving object. The visual LED indication and audible buzzer alert help prevent collisions in basic robotic platforms and automated vehicles. 2. Parking Assistance Systems Ultrasonic distance detectors are commonly used in vehicle parking systems to indicate the proximity of nearby objects. The LED and buzzer provide immediate feedback when the vehicle approaches an obstacle

C. C.limitation

Limited Detection Range The detection range of the system is limited by the power of the ultrasonic transmitter and the sensitivity of the receiver. Objects beyond a certain distance cannot be reliably detected. 2. Accuracy Affected by Surface Properties The performance of the ultrasonic sensor depends on the shape, size, and material of the target object. Soft, angled, or irregular surfaces may absorb or deflect sound waves, resulting in weak or missed echoes.

ACKNOWLEDGMENT

The success of this project required continuous support . We are truly grateful who helped us in our work .We like to thank our respective teacher for their valuable suggestion

REFERENCES

in this project we take help from some content or resources. We research about different method to achieve the goal . Here are those link from which we take necessary information :

1)https://www.instructables.com/Distance-Sensor-with-LEDs-and-buzzer/?utm_source=chatgpt.com

2)https://learn.voltaat.com/tutorials/arduino-distance-detector-with-a-buzzer-and-leds-2?utm_source=chatgpt.com

3)https://docs.cirkitdesigner.com/project/published/3738c09d-f600-4486-bede-a2891568f230/arduino-uno-ultrasonic-distance-sensor-with-buzzer-and-led-indicator?utm_source=chatgpt.com

4)https://solderingmind.com/ultrasonic-sensor-with-555-timer-ic-circuit/?utm_source=chatgpt.com