FABRIQ FABRICATION VERIFICATION DOCUMENT


Banu Hashim Die Numbers & Authentic Catalogue Verification

Verified against Official Banu Hashim Ready Catalogue with Real Cropped Drawings & CAD Die Vectors


Target AI: Claude Code & Codex
Catalogue Source: BANUHASHIM READY.pdf
Total Sections: 8 Categories (Verified)
Timestamp: 12/11/2026

1. EURO TRACK (BH-6001 & BH-6000 / BH-6400)

Die BH-6001 (3-Track) & BH-6000 (2-Track) / BH-6400 (Euro 31mm)



Catalogue Scan



CAD 99.3×35mm

Euro Track 3-Track Outer Frame with Leg (Banu Hashim Domal/Euro)

(Euro Track Chaukhat (3-Track & 2-Track Outer Frame))

Exact Size:	BH-6001: 99.30 × 35.00 mm (BH-6000: 64.30 × 45.00 mm | BH-6400: 85.00 × 33.10 mm)	**Weight / 12':**	BH-6001: 5.700 – 6.200 kg / 12' | BH-6000: 3.700 – 4.100 kg / 12'
Catalogue:	Banu Hashim Ready Catalogue Page 42 (Printed 39) & Page 56		


FABRICATION CONDITION (Kahan aur Kyon Lagta Hai):

Euro track sliding window ke charo taraf outer frame (top head, bottom sill aur vertical sides) par lagta hai. BH-6001 me 3 track legs aur 3 separate sliding channels hote hain. Iske runner channel par snap clip (BH-2559) fit hoti hai jispar palla smooth slide karta hai.

- Banu Hashim verified Die BH-6001: 99.30mm width, 35.00mm height, 1.12mm wall gauge
- Sibling 2-Track Die BH-6000: 64.30mm width, 45.00mm height, 1.06mm wall gauge
- Carries 3 glass shutters (GGG) or 2 glass + 1 mosquito wire mesh shutter (GGJ)

2. SLIM INTERLOCK (SINGLE GLASS)

Die BH-6408 (Banu Hashim) / Ample 41289 (Sleek 40) / 992328 (Sleek 37)



Catalogue Scan



CAD 38.1×20.2mm

Slim Interlock Stile for Single Glass (SGU 5mm - 8mm)

(Slim Interlock Chhota Wala (Single Glass))

Exact Size:	38.10 × 20.20 mm (Visible sightline: 20.20 mm!)	**Weight / 12':**	2.500 kg per 12ft bar (Gauge: 1.25 mm)
Catalogue:	Banu Hashim Ready Catalogue Page 61 (Printed 58)		


FABRICATION CONDITION (Kahan aur Kyon Lagta Hai):

Single Glass (5mm, 6mm, 8mm Toughened Glass) wale palla ke center meeting stile me lagta hai. Bahar se room me sirf 20mm ki ultra-patli patti dikhti hai. Dono palla band hone par hooks aapas me airtight interlocking banate hain.


- Ultra-minimalist 20.2mm visible profile face for 90%+ clear panoramic glass view
- Single glass rebate with EPDM U-rubber / wedge gasket locking pocket
- Double wool-pile mohair groove for 100% dust, acoustic, and wind barrier

3. SLIM INTERLOCK (DOUBLE GLASS DGU)

Die BH-6410 (Banu Hashim 31mm DGU) / Die BH-6507 (Gulf 35mm DGU)



Catalogue Scan



CAD 38.1×20.2mm

Slim Interlock Stile for Double Glass (DGU 20mm / 24mm)

(Slim Interlock Chhota Wala (Double Glass DGU))


Exact Size:	38.10 × 24.00 mm (BH-6410) / 47.20 × 27.50 mm (BH-6507)	Weight / 12':	2.100 kg per 12ft bar (BH-6410) / 2.600 kg per 12ft bar (BH-6507)
Catalogue:	Banu Hashim Ready Catalogue Page 62 (Printed 59)		

FABRICATION CONDITION (Kahan aur Kyon Lagta Hai):
DGU Double Glazed Unit (20mm ya 24mm soundproof/acoustic double glass) wale palla me center meeting stile par lagta hai. Isme wider 24mm glass pocket hota hai jisme outer glass, warm spacer bar aur inner glass rubber seal ke saath baithte hain.


- Deep 24.0mm pocket for 20mm/24mm insulated double glass units (DGU)
- High thermal insulation & acoustic rating (up to 35 dB noise reduction)
- Retains ultra-slim sightline while accommodating heavy double glazing

4. SLIM INTERLOCK BADA VALA (SINGLE GLASS)

Die BH-6409 (Banu Hashim 31mm) / Die BH-6508 (Gulf 35mm) / Ample 914806



Catalogue Scan



CAD 80.1×20.2mm

Heavy Structural Reinforcement Spine for Single Glass

(Slim Interlock Bada Wala (Single Glass Heavy Wind Spine))


Exact Size:	80.10 × 20.20 mm (BH-6409) / 96.00 × 27.00 mm (BH-6508)	Weight / 12':	4.500 kg per 12ft bar (Gauge: 1.50 mm)
Catalogue:	Banu Hashim Ready Catalogue Page 62 (Printed 59) & Page 64		

FABRICATION CONDITION (Kahan aur Kyon Lagta Hai):
Single glass wale palla me interlock ke piche screw se attach hota hai. Jab window 7ft se 10ft unchi ho ya high-rise building (10th floor+) me ho, to yeh 80.1mm ki massive aluminium fin palla ko hawa ke dabav se lachakne (bend) se 100% rok leti hai.


- Massive 80.1mm deep aerodynamic structural fin (Moment of Inertia Ixx > 18 cm4)
- Direct dovetail screw mounting on BH-6408 slim interlock
- Tested for high wind pressures and coastal cyclonic gusts without vibration

5. SLIM INTERLOCK BADA VALA (DOUBLE GLASS DGU)

Die BH-6411 (Banu Hashim 31mm DGU) / Die BH-6509 (Gulf 35mm DGU)



Catalogue Scan



CAD 80.1×20.2mm

Heavy Structural Reinforcement Spine for Double Glass (DGU)

(Slim Interlock Bada Wala (Double Glass DGU Heavy Wind Spine))


Exact Size:	80.10 × 24.00 mm (BH-6411) / 96.00 × 27.00 mm (BH-6509)	Weight / 12':	4.200 kg per 12ft bar (BH-6411) / 5.250 kg per 12ft bar (BH-6509)
Catalogue:	Banu Hashim Ready Catalogue Page 62 (Printed 59)		

FABRICATION CONDITION (Kahan aur Kyon Lagta Hai):
Heavy DGU Double Glass wale oversized balcony shutters (8ft to 11ft height) ke meeting stiles par lagta hai. Double glass ke 100kg+ bhari vajan aur high-altitude wind suction dono ko withstand karta hai.


- Heavy 80.1mm depth with 24mm wide DGU glass rebate integration
- Heavy 1.70mm wall thickness for industrial structural rigidity
- Zero deflection under 1500 Pascal cyclonic wind tunnel pressure

6. EURO TRACK KI CLIP / TRACK RAIL (BH-2559)

Die BH-2559 (Banu Hashim) / Die BH-6513 (SS Patri) / Die BH-6512



Catalogue Scan



CAD 11×13.47mm

Euro Track Rail Snap Clip / Track Runner (Banu Hashim)

(Euro Track Ki Clip / Runner Rail Patri Clip)


Exact Size:	11.00 × 13.47 mm (BH-2559) | Thickness: 0.90 mm	Weight / 12':	0.480 – 0.550 kg per 12ft bar (Die BH-2559)
Catalogue:	Banu Hashim Ready Catalogue Page 41 (Printed 38)		

FABRICATION CONDITION (Kahan aur Kyon Lagta Hai):
Euro track ke runner fin channel par press karke 'tak' se snap fit hoti hai. Iske rounded runner top par shutter ke roller wheels daudte hain. Is clip ki wajah se main outer frame ka track kabhi ghisata nahi hai aur palla smooth chalta hai.


- Banu Hashim verified Die BH-2559: 11.00mm width, 13.47mm height, 0.90mm gauge
- Snap-fit dovetail locking teeth that grip the track fin securely without screws
- Prevents aluminium-on-aluminium friction and roller wheel grinding

7. GULF SERIES NICHE KI TRACK

Die BH-6501 (2-Track Bottom Sill) / Die BH-6503 (3-Track Bottom Sill)



Catalogue Scan



CAD 95×31.2mm

Gulf 35mm Bottom Sill Track (Horizontal Floor Sill)

(Gulf 35 Niche Ka Bottom Track (Floor Sill))


Exact Size:	95.00 × 31.20 mm (BH-6501 2T) / 145.60 × 31.20 mm (BH-6503 3T)	Weight / 12':	5.300 kg / 12' (BH-6501 2T) / 7.600 kg / 12' (BH-6503 3T)
Catalogue:	Banu Hashim Ready Catalogue Page 64 (Printed 61) & Page 65		

FABRICATION CONDITION (Kahan aur Kyon Lagta Hai):
Gulf series me window ke niche floor/sill par horizontally lagta hai. Isme internal water drainage slope channels, weeping slots aur stainless steel round runner rail (BH-6513 SS patri) fit hoti hai jahan heavy rollers smooth slide karte hain.


- Heavy 1.40mm bottom slab carrying massive glass weight (5.30 kg/12ft)
- Internal water drainage slope channels preventing rain water back-flow into the room
- Houses stainless steel cylindrical track patri (BH-6513) for zero aluminium track wear

8. GULF SERIES SIDO KI TRACK

Die BH-6500 (2-Track Vertical Jamb) / Die BH-6502 (3-Track Vertical Jamb)



Catalogue Scan



CAD 100×32.8mm

Gulf 35mm Vertical Side Jamb (Wall Frame)

(Gulf 35 Sido Ka Khada Track (Vertical Jamb))

Exact Size:	100.00 × 32.80 mm (BH-6500 2T) / 150.00 × 32.80 mm (BH-6502 3T)	Weight / 12':	3.550 kg / 12' (BH-6500 2T) / 4.900 kg / 12' (BH-6502 3T)
Catalogue:	Banu Hashim Ready Catalogue Page 64 (Printed 61) & Page 65		

FABRICATION CONDITION (Kahan aur Kyon Lagta Hai):
Deewar ke dono vertical khade sides (left aur right jambs) par 90° lagta hai. Gulf system me vertical khada jamb aur niche ka bottom track alag section hote hain — vertical jamb bottom sill par 90° butt joint se baith kar heavy stainless steel screws se tight hota hai.

- Deep 100.0mm frame depth accommodating heavy 35mm sliding shutters
- 90° butt screw-port bosses engineered for high-strength mechanical assembly
- Integrated interlock locking pocket and wall anchor grooves