TECHNICAL FABRICATION MANUAL & SECTION MASTER

FabriQ Systems Handbook

Aluminium Architectural Window, Door & Partition Profiles A to Z

Standard Edition
Catalogues: OMEO · Banu Hashim · Ample · Altech
Scale: Real 1:1 Vector CAD & Cropped Dies

INDEX OF SYSTEMS COVERED IN THIS MANUAL


01. Normal Sliding 18 mm (Bombay)
02. Normal Sliding 25 mm (1"×2")
03. Domal 27 mm Euro Groove
04. Domal 35 mm Heavy Architectural
05. Ample 29 mm Sleek Series
06. Banu Hashim 31 mm Slim
07. Banu Hashim 35 mm Gulf Series
08. Casement Window Z-Section 40 mm
09. Heavy Casement Z-Section 55 mm
10. Partition 2.5" × 1.5" Commercial
11. Aluminium Doors (Flush/Glazed)

01 Normal Sliding 18 mm (Bombay Series)

Standard 3/4" × 1.5" Residential Sliding Window · Sliding Window

Bharat me sabse zyada chalne wali economical sliding window system. Balconies, kitchen, bedrooms aur residential flats me 4ft se 5ft tak ki window ke liye standard choice hai.

Glass Compatibility:	**4 mm to 6 mm Single Float Glass**	Corner Joints:	**Outer Frame 90° Butt Joint · Shutter 90°**
Track Options:	**2-Track (2 Glass) & 3-Track (2 Glass + 1 Jali)**	Standard Length:	**16 ft / 18 ft commercial bars**



62 × 32 mm


2-Track Top/Side Outer Frame

FRAME

2-Track Upar aur Khada Side Frame

Die Code: OMEO #1000 **Standard Size:** 62 × 32 mm **Bar Length:** 16 / 18 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
2-Track sliding window me deewar ke upar (head) aur dono vertical sides (jambs) par lagta hai. Palla iske channels me guide hota hai.



62 × 32 mm


2-Track Bottom Sill (Track)

FRAME

2-Track Niche Ka Bottom Track

Die Code: OMEO #1011 **Standard Size:** 62 × 32 mm **Bar Length:** 16 / 18 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Window ke niche floor/sill par fix hota hai. Iske do raised track guides par bearing/roller palla slide karta hai. Water drainage slots isme bante hain.



92 × 32 mm


3-Track Top/Side Outer Frame

FRAME

3-Track Upar aur Khada Side Frame

Die Code: OMEO #1001 **Standard Size:** 92 × 32 mm **Bar Length:** 16 / 18 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
3-Track sliding window me (2 Glass Palla + 1 Mosquito Mesh Jali ya 3 Glass) ke liye head aur vertical jambs me lagta hai.



92 × 32 mm


3-Track Bottom Track

FRAME

3-Track Niche Ka Bottom Track

Die Code: OMEO #1012 **Standard Size:** 92 × 32 mm **Bar Length:** 16 / 18 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
3-Track window ke bottom sill par lagta hai. Isme 3 independent channels hote hain jisme teen alag-alag palla chalte hain.



40 × 18 mm


Handle Stile (Lock Side)

SHUTTER

Handle Pipe / Palla Ka Lock Side

Die Code: OMEO #1041 **Standard Size:** 40 × 18 mm **Bar Length:** 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Shutter ke outer vertical side me lagta hai. Isme haath se pakadne ka groove hota hai aur flush lock ya star lock fit hota hai.



40 × 18 mm


Interlock Stile (Meeting)

INTERLOCK

Interlock Pipe / Beech Ka Palla

Die Code: OMEO #1046 **Standard Size:** 40 × 18 mm **Bar Length:** 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Jab do palla band hote hain to unke beech me meeting point par lagta hai. Dono palla ke hook aapas me fas kar hawa, dhool aur paani ko rokte hain.



40 × 18 mm

Bottom Bearing & Top Rail

RAIL

Bearing Pipe / Wheel Rail

Die Code: OMEO #1051 **Standard Size:** 40 × 18 mm **Bar Length:** 16 ft


📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Palla ke horizontal top aur bottom me lagta hai. Niche wale bearing pipe ke andar roller/bearing wheels fit hote hain jo track par chalte hain.

02 Normal Sliding 25 mm (Bombay Heavy 1″ × 2″)

Heavy-Duty 1″ × 2″ Bombay Profile for High Heights · Sliding Window

Jab window ki height 5ft se zyada ho (up to 7ft), tab 18mm ke bajaye 25mm (1″×2″) ka heavy Bombay section lagaya jata hai taaki palla hawa me lachke nahi.

Glass Compatibility:	**5 mm to 8 mm Toughened Glass**	Corner Joints:	**90° Butt Screwed Joints**
Profile Size:	**1″ × 2″ (50 × 25 mm) Shutters**	Application:	**Medium to High Wind Zones, Living Rooms**



50 × 25 mm


25 mm 2-Track Top/Side Frame

FRAME

25mm Bhari 2-Track Frame

Die Code: BOMBAY-25 **Standard Size:** 50 × 25 mm **Bar Length:** 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
25mm sliding window me 2-track outer frame ke liye head aur vertical sides me lagta hai.



50 × 25 mm


25 mm 2-Track Bottom Track

FRAME

25mm Bhari Niche Ka Track

Die Code: BOMBAY-25-BOT **Standard Size:** 50 × 25 mm **Bar Length:** 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Heavy 25mm palla chalane ke liye bottom sill par lagta hai.



50 × 25 mm


25 mm Handle Stile (1″ × 2″)

SHUTTER

1″ × 2″ Handle Pipe (Lock Side)

Die Code: BH-25-HND **Standard Size:** 50 × 25 mm **Bar Length:** 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
25mm palla ke lock side vertical stiles me lagta hai. 6ft se 7ft height ke palla ko solid rigidity deta hai.



50 × 25 mm


25 mm Interlock Stile

INTERLOCK

1" × 2" Beech Ka Interlock

Die Code: BH-25-INT **Standard Size:** 50 × 25 mm **Bar Length:** 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
25mm sliding me dono palla ke meeting point par solid airtight seal banane ke liye lagta hai.



50 × 25 mm

25 mm Bearing Bottom / Top Rail

RAIL

1" × 2" Bearing Wheel Rail

Die Code: BH-25-BRG **Standard Size:** 50 × 25 mm **Bar Length:** 16 ft


📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Palla ke horizontal top aur bottom me lagta hai. Isme heavy 25mm nylon/brass rollers fit hote hain.

03 Domal 27 mm Series (Euro Groove 27 × 65 mm)

European Architectural Sliding System with 45° Mitre Cleat · Domal Type Sliding

High-end residential villas aur premium apartments ki sabse popular system. Isme palla chaaron taraf ek hi profile se 45° mitre cut par corner cleat se banta hai.

Glass Compatibility:	**5 mm, 8 mm, 12 mm Single & DGU**	Corner Joints:	**45° Mitre Cut with Aluminium Corner Cleats**
Weathersealing:	**EPDM Wedge Gaskets + Wool Pile Mohair**	Aesthetics:	**Rounded Soft-Edge European Finish**



80 × 45 mm


Domal 2-Track Outer Frame

FRAME

Domal 2-Track Outer Frame

Die Code: DOMAL-2T-80 **Standard Size:** 80 × 45 mm **Bar Length:** 16 / 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
2-Track Domal window me chaaron taraf 45° mitre cut par banta hai. Deewar par corner cleats se tight fit hota hai.



115 × 45 mm


Domal 3-Track Outer Frame

FRAME

Domal 3-Track Outer Frame

Die Code: DOMAL-3T-115 **Standard Size:** 115 × 45 mm **Bar Length:** 16 / 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
3-Track Domal window (2 Glass + 1 Jali) me chaaron taraf lagta hai.



65 × 27 mm


Domal Glass Shutter (27 × 65 mm)

SHUTTER

Domal Palla Section (4 Sides)

Die Code: DOMAL-SH-65 **Standard Size:** 65 × 27 mm **Bar Length:** 16 / 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Domal palla me top, bottom, left, right chaaron taraf yahi ek section lagta hai 45° cut ke saath. Isme Euro groove aur glass rebate hota hai.



55 × 27 mm


Domal Mosquito Mesh Shutter

SHUTTER

Domal Jali Palla Section

Die Code: DOMAL-JALI-55 **Standard Size:** 55 × 27 mm **Bar Length:** 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
3-Track Domal window ke 3rd track par machhardani palla banane ke liye lagta hai. SS wire mesh spline se lock hota hai.



39 × 28 mm

Domal Interlock Guide / Patti

INTERLOCK

Domal Interlock Patti

Die Code: DOMAL-INT-39 **Standard Size:** 39 × 28 mm **Bar Length:** 16 ft


📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Domal shutter ke vertical stile par screw se fix hoti hai. Do palla band hone par yahi patti aapas me fas kar airtight locking karti hai.

04 Domal 35 mm Heavy Architectural Series

Heavy DGU Insulated Double Glass Sliding System (35 × 75 mm) · Heavy Domal

Badi heights (8ft to 10ft) aur heavy DGU (Double Glazed Unit 20mm/24mm) soundproof aur thermal insulation glass ke liye heavy architectural system.

Glass Compatibility:	**18 mm to 24 mm DGU Double Glass**	Max Shutter Weight:	**150 kg per shutter with tandem rollers**
Corners:	**45° Mitre Cut with Heavy Mechanical Cleats**	Performance:	**Acoustic Noise Reduction + Cyclonic Wind Resistance**



95 × 50 mm


Domal 35 2-Track Outer Frame

FRAME

Domal 35 Heavy Outer Frame

Die Code: D35-FR-95 **Standard Size:** 95 × 50 mm **Bar Length:** 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Heavy 35mm series me deewar ke perimeter par lagta hai.



75 × 35 mm


Domal 35 Heavy Shutter Profile

SHUTTER

Domal 35 DGU Heavy Palla (35×75 mm)

Die Code: D35-SH-75 **Standard Size:** 75 × 35 mm **Bar Length:** 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
DGU Double Glass (20mm se 24mm) aur heavy shutter sizes (up to 10ft) ke liye chaaron taraf 45° mitre cut par lagta hai.



45 × 35 mm

Domal 35 Heavy Interlock Guide

INTERLOCK

Domal 35 Interlock Guide Patti

Die Code: D35-INT-45 **Standard Size:** 45 × 35 mm **Bar Length:** 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
35mm palla ke meeting stile par lagti hai. Double wool pile mohair ke saath air infiltration rokti hai.

05 Ample 29 mm Sleek Series

Ultra-Slim Sightline Minimalist Sliding Window · Sleek / Slim Sliding

Minimalist architecture ke liye sabse pasandida sleek system. Beech me sirf 37mm ya 40mm ka patla interlock dikhta hai, jisse bahar ka view 90% se zyada clear rehta hai.

Sightline:	**37 mm / 40 mm Ultra-Slim Interlock**	Glass Compatibility:	**6 mm to 12 mm Toughened Glass**
Reinforcement:	**Heavy T-Spine for High-Rise Wind Loads**	Locking:	**Multi-Point Concealed Flush Lock**

85.8 × 47.7 mm

85.8 × 47.7 mm

Ample 29 2-Track Sleek Frame

FRAME

Ample 29 Sleek Outer Frame

Die Code: Die #41011 **Standard Size:** 85.8 × 47.7 mm **Bar Length:** 16 / 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Sleek sliding window ke perimeter me outer frame banane ke liye lagta hai.

64.4 × 50.2 mm

64.4 × 50.2 mm

Ample 29 Shutter Rail (Top & Bottom)

RAIL

Ample 29 Top/Bottom Horizontal Rail

Die Code: Die #41010 **Standard Size:** 64.4 × 50.2 mm **Bar Length:** 16 / 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Shutter ke top aur bottom me lagta hai. Niche wale me heavy-duty concealed tandem rollers fit hote hain.

65 × 29 mm

65 × 29 mm

Ample 29 Handle Stile

SHUTTER

Ample 29 Lock Side Handle Pipe

Die Code: Die #41055 **Standard Size:** 65 × 29 mm **Bar Length:** 16 / 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Shutter ke wall side vertical stiles me lagta hai jisme integrated recessed handle aur multi-point lock lagta hai.

40 × 29 mm

40 × 29 mm

Ample 29 Slim Interlock 40 mm

INTERLOCK

Ample 29 Slim Interlock (40mm)

Die Code: Die #41289 **Standard Size:** 40 × 29 mm **Bar Length:** 16 / 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Shutter ke center meeting stile me lagta hai jab client ko ultra-slim 40mm ka beech ka danda chahiye ho.

37 × 29 mm

37 × 29 mm

Ample 29 Slim Interlock 37 mm

INTERLOCK

Ample 29 Extra Slim Interlock (37mm)

Die Code: Die #992328 **Standard Size:** 37 × 29 mm **Bar Length:** 16 / 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Sabse patli 37mm sightline ke liye. Maximum glass area aur unhindered view deta hai.

50.6 × 45 mm

50.6 × 45 mm

Ample 29 Heavy T-Spine Reinforcement

SPINE

T-Spine Structural Reinforcement

Die Code: Die #914806 **Standard Size:** 50.6 × 45 mm **Bar Length:** 16 ft


📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
High-rise buildings (10th floor+) ya heavy wind zones me shutter ko hawa ke dabav se bend hone se bachane ke liye interlock ke piche screw se attach hota hai.

06 Banu Hashim 31 mm Slim Series

Heavy Coastal, Cyclonic & DGU Double Glass Slim System · Slim / Architectural Sliding

High-end engineered slim sliding system. Isme single glass (SGU) aur double glass (DGU) dono ke dedicated profiles hain, aur 20mm ultra-slim sightline milti hai.

Interlock Sightline:	**20.3 mm Ultra-Slim Profile**	Glass Options:	**SGU (6mm-8mm) & DGU (20mm-24mm)**
Track Rail:	**Integrated Stainless Steel Runner Patri**	Wind Rating:	**Tested for Cyclonic Wind Pressure with Spine**



85 × 33.1 mm


BH 31 mm 2-Track Outer Frame

FRAME

BH 31mm 2-Track Outer Frame

Die Code: BH-6400 **Standard Size:** 85 × 33.1 mm **Bar Length:** 16 / 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
31mm slim series ka perimeter frame. Isme stainless steel runner patri integrate hoti hai.



65.9 × 29 mm


BH 31 Shutter Rail (Single Glass)

RAIL

BH 31 Single Glass Shutter Rail

Die Code: BH-6404 **Standard Size:** 65.9 × 29 mm **Bar Length:** 16 / 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Single glass (5mm/6mm/8mm) shutter ke top aur bottom rails ke liye use hota hai.



65.9 × 32 mm


BH 31 Shutter Rail (Double Glass DGU)

RAIL

BH 31 Double Glass (DGU) Rail

Die Code: BH-6405 **Standard Size:** 65.9 × 32 mm **Bar Length:** 16 / 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Jab double glazed unit (DGU 20mm acoustic/thermal glass) lagana ho to is wide glass rebate wale rail ko use kiya jata hai.



59 × 31.4 mm


BH 31 Handle Stile (Single Glass)

SHUTTER

BH 31 Single Glass Handle Pipe

Die Code: BH-6406 **Standard Size:** 59 × 31.4 mm **Bar Length:** 16 / 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Single glass shutter me lock vertical side par lagta hai.



59 × 33.5 mm


BH 31 Handle Stile (Double Glass DGU)

SHUTTER

BH 31 Double Glass Handle Pipe

Die Code: BH-6407 **Standard Size:** 59 × 33.5 mm **Bar Length:** 16 / 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Double glass DGU shutter me lock side vertical par lagta hai.



20.3 × 50.7 mm


BH 31 Slim Interlock (SGU)

INTERLOCK

BH 31 Ultra-Slim Interlock (20mm)

Die Code: BH-6408 **Standard Size:** 20.3 × 50.7 mm **Bar Length:** 16 / 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Bahar se sirf 20mm ki ultra-minimalist patti dikhti hai. Maximum transparency aur wide panorama view deta hai.



45 × 20 mm

BH 31 Heavy Reinforcement Spine

SPINE

BH 31 Wind Load Structural Spine

Die Code: BH-6409 **Standard Size:** 45 × 20 mm **Bar Length:** 16 ft


📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
High wind pressure aur cyclonic weather zones me shutter ko rigid rakhne ke liye interlock par piche se lagta hai.

07 Banu Hashim 35 mm Gulf Series

Heavy Screwed Frame with Sub-Sill & Water Drainage · Gulf Heavy Sliding

Middle-East / Gulf standards par designed heavy series. Isme bottom track me dedicated water drain slope hoti hai aur vertical jambs bottom sill par 90° screwed hote hain.

Frame Assembly:	**90° Screwed Butt Joints (Separate Vertical & Sill)**	Water Resistance:	**Stepped Internal Weep Drainage Channels**
Track Rail:	**Heavy Stainless Steel Round Bead Rail**	Glass Options:	**Up to 28 mm Heavy DGU Units**



95 × 31.2 mm


BH 35 mm 2-Track Vertical Side Jamb

FRAME

Gulf 2-Track Khada Side Jamb

Die Code: BH-6500 **Standard Size:** 95 × 31.2 mm **Bar Length:** 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Gulf series me vertical sides ke khade frames alag section hote hain jo bottom sill par 90° butt joint se screw hote hain.



95 × 31.2 mm


BH 35 mm 2-Track Bottom Sill Track

FRAME

Gulf 2-Track Niche Ka Bottom Track

Die Code: BH-6501 **Standard Size:** 95 × 31.2 mm **Bar Length:** 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Niche floor/sill par lagta hai. Isme drainage channels aur drain caps ke liye special slope hoti hai.



58 × 31.7 mm


BH 35 Shutter Rail

RAIL

BH 35 Shutter Top/Bottom Rail

Die Code: BH-6504 **Standard Size:** 58 × 31.7 mm **Bar Length:** 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Top aur bottom me shutter structure banane ke liye lagta hai.



58.9 × 35.2 mm


BH 35 Handle Stile

SHUTTER

BH 35 Handle Pipe (Lock Side)

Die Code: BH-6510 **Standard Size:** 58.9 × 35.2 mm **Bar Length:** 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Lock side palla vertical stile.



24 × 62 mm


BH 35 Slim Interlock

INTERLOCK

BH 35 Slim Interlock Stile

Die Code: BH-6506 **Standard Size:** 24 × 62 mm **Bar Length:** 19 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
35mm Gulf series me slim meeting interlock.



50 × 35 mm

BH 35 Heavy Cyclonic Spine

SPINE

Gulf 35 Cyclonic Structural Spine

Die Code: BH-6508 **Standard Size:** 50 × 35 mm **Bar Length:** 16 ft


📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Coastal areas aur cyclone zones me heavy wind pressure jhelne ke liye structural back-spine.

08 Casement Window / Z-Section 40 mm

Openable Hinged / Friction Stay Window System · Casement Window

Khulne wali (openable/hinged) window system jo friction stays ya hinges par khulti hai. 100% airtight aur watertight sealing deti hai.

Hardware:	**SS 304 Friction Stays + Cockspur / Espag Handles**	Sealing:	**Dual EPDM Hollow Gaskets on Z-Rebates**
Opening Styles:	**Side Hung (Door style) & Top Hung (Ventilator)**	Air Permeability:	**Class 4 (Zero Draft Air-Tight Sealing)**



40 × 40 mm


Z Outer Frame 40 × 40 mm

FRAME

Z-Section Outer Frame (Chaukhat)

Die Code: OMEO #2001 **Standard Size:** 40 × 40 mm **Bar Length:** 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Openable window me deewar ke chaaron taraf outer frame banta hai 45° mitre cut par.



40 × 40 mm


Z-Pipe (Openable Sash) 40 × 40 mm

SHUTTER

Z-Pipe Khulne Wala Palla

Die Code: OMEO #2002 **Standard Size:** 40 × 40 mm **Bar Length:** 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Khulne wale palla (shutter) ke chaaron taraf lagta hai. Iske Z-flange par EPDM rubber gasket lagti hai jo outer frame par tight seal karti hai.



40 × 55 mm


Z Center Mullion / Transom 40 × 55 mm

DIVIDER

Z-Section Center Divider / Mullion

Die Code: OMEO #2003 **Standard Size:** 40 × 55 mm **Bar Length:** 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Jab ek hi window me do khulne wale palle ya ek khulne wala aur ek fixed glass ho, to beech ke vertical ya horizontal divider me lagta hai.



18 × 12 mm

Z Glazing Clip

CLIP

Z-Section Glass Clip Patti

Die Code: OMEO #2004 **Standard Size:** 18 × 12 mm **Bar Length:** 16 ft


📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Glass ko palla ya fixed frame ke andar press karke hold karne ke liye snap hota hai.

09 Heavy Casement / Z-Section 55 mm

Heavy Architectural Openable & Fixed Glass Combination · Casement Window

Badi heights (6ft+) aur heavy DGU double glass ke liye heavy casement window series. Bade spans me mullion ko heavy strength milti hai.

Glass Options:	**Up to 24 mm DGU Double Glazing**	Hardware:	**Heavy Duty 24" Friction Stays + Multi-point Espagnolette**
Mullion Depth:	**70 mm Heavy Structural Divider**		



40 × 55 mm


Z Outer Frame 40 × 55 mm

FRAME

Heavy Z Outer Frame

Die Code: OMEO #2005 **Standard Size:** 40 × 55 mm **Bar Length:** 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Badi openable windows (5ft+ height) aur heavy double glass ke liye perimeter me lagta hai.



40 × 55 mm


Z-Pipe Sash 40 × 55 mm

SHUTTER

Heavy Z-Pipe Palla

Die Code: OMEO #2006 **Standard Size:** 40 × 55 mm **Bar Length:** 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Heavy openable shutter me chaaron taraf 45° mitre joint par corner cleat ke saath lagta hai.



40 × 70 mm

Z Center Mullion 40 × 70 mm

DIVIDER

Heavy 70mm Center Column Mullion

Die Code: OMEO #2007 **Standard Size:** 40 × 70 mm **Bar Length:** 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Badi window partitions me center column/divider jahan heavy wind load resistance chahiye.


10 Aluminium Partition Series (2.5″ × 1.5″ & 2″ × 1″)

Commercial Office Cabins, Showroom Dividers & Full-Height Partitions · Partition System

Commercial offices, clinics, hospitals aur banks me cabins aur room dividers banane ke liye sabse versatile system.

Infill Materials: **5mm/8mm/12mm Glass, Prelam Board, ACP Sheet** Joints: **90° Screwed Joints with Internal Corner Brackets**

Assembly: **Floor Channel, Ceiling Channel & Vertical Studs**



63.5 × 38.1 mm


Partition Outer Frame 2.5″ × 1.5″

FRAME

Partition Outer Frame (Chaukhat)

Die Code: OMEO #3001 **Standard Size:** 63.5 × 38.1 mm **Bar Length:** 12 / 14 / 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Office aur cabin partitions me floor, ceiling aur wall ke perimeter me lagta hai. Isme ek taraf glass clip channel hota hai.



63.5 × 38.1 mm


Partition Divider / Middle Mullion

DIVIDER

Partition Center Divider (H-Section)

Die Code: OMEO #3002 **Standard Size:** 63.5 × 38.1 mm **Bar Length:** 12 / 14 / 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Partition ke beech ke vertical aur horizontal joints me lagta hai. Iske dono taraf glass clip lagte hain taaki dono side glass fit ho sake.



18 × 14 mm

Snap-On Glazing Clip

CLIP

Glass Glazing Clip / Patti

Die Code: OMEO #3003 **Standard Size:** 18 × 14 mm **Bar Length:** 12 / 16 ft


📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Glass ko partition frame ke andar press karke lock karne ke liye use hota hai.

11 Aluminium Doors Series (Flush, Glazed & Pattam)

Commercial & Residential Entrance, Cabin & Bathroom Doors · Door System

Aluminium doors durable, rust-proof aur termite-proof hote hain. Office entrance, bathroom, balcony aur shopfront doors ke liye use hote hain.

Hinges & Hardware:	**Floor Spring / Pivot Hinge / Butt Hinges & Mortise Lock**	Styles:	**Full Glass, Half Glass + Half Board, Full ACP Flush Door**
Kick Plate:	**Heavy 100mm / 150mm Bottom Protection Rail**		



63.5 × 38.1 mm


Door Frame with Rebate (Pattam)

FRAME

Door Chaukhat / Pattam Frame

Die Code: DOOR-FR-63 **Standard Size:** 63.5 × 38.1 mm **Bar Length:** 14 / 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Door ke chaaron taraf deewar me lagta hai. Iske andar integrated stop rebate hota hai jahan darwaza aakar band hota hai.



75 × 44.5 mm


Door Palla 75 mm (3" × 1.75")

SHUTTER

Heavy Door Palla 75mm

Die Code: DOOR-SH-75 **Standard Size:** 75 × 44.5 mm **Bar Length:** 14 / 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Commercial aur residential doors me vertical lock stile, hinge stile aur top horizontal rail banane ke liye standard heavy section.



60 × 44.5 mm


Door Palla 60 mm

SHUTTER

Door Palla 60mm (Medium Duty)

Die Code: DOOR-SH-60 **Standard Size:** 60 × 44.5 mm **Bar Length:** 14 / 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Medium size room doors aur bathroom doors ke liye vertical stiles aur top rail me use hota hai.



50 × 44.5 mm


Door Palla 50 mm (2" × 1.75")

SHUTTER

Door Palla 50mm (Light Duty)

Die Code: DOOR-SH-50 **Standard Size:** 50 × 44.5 mm **Bar Length:** 14 / 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Light interior doors aur duct doors ke liye.



75 × 44.5 mm

Door Center Rail / Divider (75 mm)

DIVIDER

Door Beech Ka Center Rail

Die Code: DOOR-DIV-75 **Standard Size:** 75 × 44.5 mm **Bar Length:** 14 / 16 ft

📌 **Kahan aur Kab Lagta Hai (Fabrication Rule):**
Half panel and half glass doors me beech me lagta hai — niche aluminium sheet/ACP sheet aur upar glass ko divide karta hai.