

Edge / Boundary Detection

Computer Vision

Szeliski 4.2


Edge detection

- **Goal:** Identify sudden changes (discontinuities) in an image
 - Intuitively, most semantic and shape information from the image can be encoded in the edges
 - More compact than pixels




Why do we care about edges?

- Extract information, recognize objects
- Recover geometry and viewpoint



Origin of Edges




- Edges are caused by a variety of factors

Closeup of edges



Closeup of edges



Closeup of edges




Closeup of edges



Characterizing edges

- An edge is a place of rapid change in the image intensity function



Derivatives with convolution

For 2D function $f(x,y)$, the partial derivative is:

$$\frac{\partial f(x, y)}{\partial x} = \lim_{\varepsilon \rightarrow 0} \frac{f(x + \varepsilon, y) - f(x, y)}{\varepsilon}$$

For discrete data, we can approximate using finite differences:


$$\frac{\partial f(x, y)}{\partial x} \approx \frac{f(x + 1, y) - f(x, y)}{1}$$

To implement above as convolution, what would be the associated filter?

Partial derivatives of an image




$$\frac{\partial f(x, y)}{\partial x}$$



-1	1
----	---

$$\frac{\partial f(x, y)}{\partial y}$$



-1	or	1
1		-1

Which shows changes with respect to x?

Finite difference filters

- Other approximations of derivative filters exist:


Prewitt: $M_x = \begin{bmatrix} -1 & 0 & 1 \\ -1 & 0 & 1 \\ -1 & 0 & 1 \end{bmatrix} ; M_y = \begin{bmatrix} 1 & 1 & 1 \\ 0 & 0 & 0 \\ -1 & -1 & -1 \end{bmatrix}$

Sobel: $M_x = \begin{bmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{bmatrix} ; M_y = \begin{bmatrix} 1 & 2 & 1 \\ 0 & 0 & 0 \\ -1 & -2 & -1 \end{bmatrix}$

Roberts: $M_x = \begin{bmatrix} 0 & 1 \\ -1 & 0 \end{bmatrix} ; M_y = \begin{bmatrix} 1 & 0 \\ 0 & -1 \end{bmatrix}$

Image gradient

- The gradient of an image: $\nabla f = \left[\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y} \right]$

-  $\nabla f = \left[\frac{\partial f}{\partial x}, 0 \right]$ $\nabla f = \left[0, \frac{\partial f}{\partial y} \right]$ $\nabla f = \left[\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y} \right]$

The gradient points in the direction of most rapid increase in intensity



- How does this direction relate to the direction of the edge?

The gradient direction is given by $\theta = \tan^{-1} \left(\frac{\partial f}{\partial y} / \frac{\partial f}{\partial x} \right)$



The *edge strength* is given by the gradient magnitude

$$\|\nabla f\| = \sqrt{\left(\frac{\partial f}{\partial x}\right)^2 + \left(\frac{\partial f}{\partial y}\right)^2}$$

Intensity profile





With a little Gaussian noise



Source: D. Hoiem

Effects of noise

- Consider a single row or column of the image
 - Plotting intensity as a function of position gives a signal




Where is the edge?

Effects of noise

- Difference filters respond strongly to noise
 - Image noise results in pixels that look very different from their neighbors
 - Generally, the larger the noise the stronger the response
- What can we do about it?


Solution: smooth first




- To find edges, look for peaks in $\frac{d}{dx}(f * g)$

Derivative theorem of convolution


- Differentiation is convolution, and convolution is associative:
$$\frac{d}{dx}(f * g) = f * \frac{d}{dx}g$$
- This saves us one operation:




Derivative of Gaussian filter



$$* [1 \ -1] =$$



Tradeoff between smoothing and localization



1 pixel

3 pixels

7 pixels

- Smoothed derivative removes noise, but blurs edge. Also finds edges at different “scales”.

Designing an edge detector

- Criteria for a good edge detector:
 - **Good detection:** the optimal detector should find all real edges, ignoring noise or other artifacts
 - **Good localization**
 - the edges detected must be as close as possible to the true edges
 - the detector must return one point only for each true edge point
- Cues of edge detection
 - Differences in color, intensity, or texture across the boundary
 - Continuity and closure
 - High-level knowledge

Canny edge detector

- This is probably the most widely used edge detector in computer vision
- Theoretical model: step-edges corrupted by additive Gaussian noise
- Canny has shown that the first derivative of the Gaussian closely approximates the operator that optimizes the product of *signal-to-noise ratio* and localization


J. Canny, [**A Computational Approach To Edge Detection**](#), IEEE Trans. Pattern Analysis and Machine Intelligence, 8:679-714, 1986.

Example





original image (Lena)


Derivative of Gaussian filter



x-direction



y-direction




Compute Gradients



X-Derivative of Gaussian



Y-Derivative of Gaussian



Gradient Magnitude


Get Orientation at Each Pixel

- Threshold at minimum level
- Get orientation




$$\text{theta} = \text{atan2}(\text{gy}, \text{gx})$$

Non-maximum suppression for each orientation






At q , we have a maximum if the value is larger than those at both p and r . Interpolate to get these values.



Sidebar: Interpolation options

- ‘nearest’
 - Copy value from nearest known
 - Very fast but creates blocky edges
- ‘bilinear’
 - Weighted average from four nearest known pixels
 - Fast and reasonable results
- ‘bicubic’ (default)
 - Non-linear smoothing over larger area (4x4)
 - Slower, visually appealing, may create negative pixel values



Before Non-max Suppression



After non-max suppression




Hysteresis thresholding

- Threshold at low/high levels to get weak/strong edge pixels
- Do connected components, starting from strong edge pixels



Hysteresis thresholding

- Check that maximum value of gradient value is sufficiently large
 - drop-outs? use **hysteresis**
 - use a high threshold to start edge curves and a low threshold to continue them.



Final Canny Edges



Canny edge detector

1. Filter image with x, y derivatives of Gaussian
2. Find magnitude and orientation of gradient
3. Non-maximum suppression:
 - Thin multi-pixel wide “ridges” down to single pixel width
4. Thresholding and linking (hysteresis):
 - Define two thresholds: low and high
 - Use the high threshold to start edge curves and the low threshold to continue them

Effect of σ (Gaussian kernel spread/size)



original



Canny with $\sigma = 1$



Canny with $\sigma = 2$

The choice of σ depends on desired behavior


- large σ detects large scale edges
- small σ detects fine features

Where do humans see boundaries?



image



human segmentation




gradient magnitude



- Berkeley segmentation database:

<http://www.eecs.berkeley.edu/Research/Projects/CS/vision/grouping/segbench/>

pB boundary detector



pB Boundary Detector






Figure from Fowlkes


Brightness



Results




Results





Human (0.95)



Pb (0.63)



45 years of boundary detection

