

CSE 304

Design & Analysis of Algorithms

Greedy Algorithms (Part 2)

Greedy Algorithm

- Greedy algorithms make the choice that looks best at the moment.
- This **locally optimal** choice may lead to a globally optimal solution (i.e. an optimal solution to the entire problem).

When can we use Greedy algorithms?

We can use a greedy algorithm when the following are true:

- 1) **The greedy choice property:** A globally optimal solution can be arrived at by making a locally optimal (greedy) choice.
- 2) **The optimal substructure property:** The optimal solution contains within **its optimal solutions to subproblems**.

Designing Greedy Algorithms

1. Cast the optimization problem as one for which:
 - we make a choice and are left with only one subproblem to solve
2. Prove the **GREEDY CHOICE**
 - that there is always an optimal solution to the original problem that makes the greedy choice
3. Prove the **OPTIMAL SUBSTRUCTURE**:
 - the greedy choice + an optimal solution to the resulting subproblem leads to an optimal solution

Example: Making Change

- Instance: amount (in cents) to return to customer
- Problem: do this using fewest number of coins
- Example:
 - Assume that we have an unlimited number of coins of various denominations:
 - 1c (pennies), 5c (nickels), 10c (dimes), 25c (quarters), 1\$ (loonies)
 - Objective: Pay out a given sum \$5.64 with the smallest number of coins possible.

The Coin Changing Problem

- Assume that we have an unlimited number of coins of various denominations:
 - 1c (pennies), 5c (nickels), 10c (dimes), 25c (quarters), 1\$ (loonies)
- Objective: Pay out a given sum S with the smallest number of coins possible.
- The greedy coin changing algorithm:
 - This is a $\Theta(m)$ algorithm where m = number of denominations.

```
while  $S > 0$  do
   $c$  := value of the largest coin no larger than  $S$ ;
   $num$  :=  $S / c$ ;
  pay out  $num$  coins of value  $c$ ;
   $S$  :=  $S - num * c$ ;
```

Example: Making Change

- E.g.:

$$\begin{aligned} \$5.64 = & \quad \$2 + \$2 + \$1 + \\ & .25 + .25 + .10 + \\ & .01 + .01 + .01 + .01 \end{aligned}$$

Making Change – A big problem

- Example 2: Coins are valued \$.30, \$.20, \$.05, \$.01
 - Does not have greedy-choice property, since \$.40 is best made with two \$.20's, but the greedy solution will pick three coins (which ones?)

The Fractional Knapsack Problem

- **Given:** A set S of n items, with each item i having
 - b_i - a positive benefit
 - w_i - a positive weight
- **Goal:** Choose items with maximum total benefit but with weight at most W .
- If we are allowed to take fractional amounts, then this is the **fractional knapsack problem**.
 - In this case, we let x_i denote the amount we take of item i

- Objective: maximize






$$\sum_{i \in S} b_i (x_i / w_i)$$

- Constraint:

$$\sum_{i \in S} x_i \leq W, 0 \leq x_i \leq w_i$$

Example

- Given: A set S of n items, with each item i having
 - b_i - a positive benefit
 - w_i - a positive weight
- Goal: Choose items with maximum total benefit but with total weight at most W .

Items:					
Weight:	4 ml	8 ml	2 ml	6 ml	1 ml
Benefit:	\$12	\$32	\$40	\$30	\$50
Value: (\$ per ml)	3	4	20	5	50



“knapsack”

10 ml

Solution:
P

- 1 ml of 5
50\$
- 2 ml of 3
40\$
- 6 ml of 4
30\$
- 1 ml of 2
4\$

The Fractional Knapsack Algorithm

- Greedy choice: Keep taking item with highest **value** (benefit to weight ratio)

– Since
$$\sum_{i \in S} b_i (x_i / w_i) = \sum_{i \in S} (b_i / w_i) x_i$$

Algorithm *fractionalKnapsack*(S, W)

Input: set S of items w/ benefit b_i and weight w_i ; max. weight W

Output: amount x_i of each item i to maximize benefit w/ weight at most W

for *each item* i **in** S

$x_i \leftarrow 0$

$v_i \leftarrow b_i / w_i$ {value}

$w \leftarrow 0$ {total weight}

while $w < W$

remove item i *with highest* v_i

$x_i \leftarrow \min\{w_i, W - w\}$

$w \leftarrow w + \min\{w_i, W - w\}$

The Fractional Knapsack Algorithm

- Running time: Given a collection S of n items, such that each item i has a benefit b_i and weight w_i , we can construct a maximum-benefit subset of S , allowing for fractional amounts, that has a total weight W in $O(n \log n)$ time.
 - Use heap-based priority queue to store S
 - Removing the item with the highest value takes $O(\log n)$ time
 - In the worst case, need to remove all items

An Activity Selection Problem (Conference Scheduling Problem)

- **Input: A set of activities $S = \{a_1, \dots, a_n\}$**
- Each activity has start time and a finish time
 - $a_i = (s_i, f_i)$
- Two activities are compatible if and only if their interval does not overlap
- **Output: a maximum-size subset of mutually compatible activities**

The Activity Selection Problem

- Here are a set of start and finish times

i	1	2	3	4	5	6	7	8	9	10	11
s_i	1	3	0	5	3	5	6	8	8	2	12
f_i	4	5	6	7	8	9	10	11	12	13	14


- What is the maximum number of activities that can be completed?
 - $\{a_3, a_9, a_{11}\}$ can be completed
 - But so can $\{a_1, a_4, a_8, a_{11}\}$ which is a larger set
 - But it is not unique, consider $\{a_2, a_4, a_9, a_{11}\}$

The Activity Selection Problem

Input: list of time-intervals L

Output: a non-overlapping subset S of the intervals

Objective: maximize $|S|$




The Activity Selection Problem

Input: list of time-intervals L

Output: a non-overlapping subset S of the intervals

Objective: maximize $|S|$



The Activity Selection Problem


Algorithm 1:

1. sort the activities by the starting time
2. pick the first activity a
3. remove all activities conflicting with a
4. repeat

The Activity Selection Problem

Algorithm 1:


1. **sort** the activities by the **starting time**
2. pick the first activity “*a*”
3. remove all activities conflicting with “*a*”
4. repeat



The Activity Selection Problem

Algorithm 1:


1. **sort** the activities by the **starting time**
2. pick the first activity “*a*”
3. remove all activities conflicting with “*a*”
4. repeat



The Activity Selection Problem

Algorithm 2:


1. **sort** the activities **by length**
2. pick the **shortest activity** “***a***”
3. remove all activities conflicting with “***a***”
4. repeat



The Activity Selection Problem

Algorithm 2:


1. **sort** the activities **by length**
2. pick the **shortest activity** “***a***”
3. remove all activities conflicting with “***a***”
4. repeat



The Activity Selection Problem

Algorithm 2:


1. **sort** the activities **by length**
2. pick the **shortest activity** “**a**”
3. remove all activities conflicting with “**a**”
4. repeat



The Activity Selection Problem

Algorithm 3:


1. **sort** the activities by **ending time**
2. **pick** the activity which **ends first**
3. remove all activities conflicting with a
4. repeat



The Activity Selection Problem

Algorithm 3:


1. **sort** the activities by **ending time**
2. **pick** the activity which **ends first**
3. remove all activities conflicting with a
4. repeat



The Activity Selection Problem

Algorithm 3:


1. **sort** the activities by **ending time**
2. **pick** the activity which **ends first**
3. remove all activities conflicting with a
4. repeat



The Activity Selection Problem

Algorithm 3:

1. **sort** the activities by **ending time**
2. **pick** the activity which **ends first**
3. remove all activities conflicting with a
4. repeat



The Activity Selection Problem

Algorithm 3:

1. sort the activities by ending time
2. pick the activity a which ends first
3. remove all activities conflicting with a
4. repeat

Theorem:

Algorithm 3 gives an optimal solution to the activity selection problem.

Activity Selection Algorithm

Idea: At each step, select the activity with the smallest finish time that is compatible with the activities already chosen.

Greedy-Activity-Selector(s, f)

$n \leftarrow \text{length}[s]$

$A \leftarrow \{1\}$

{Automatically select first activity}

$j \leftarrow 1$

{Last activity selected so far}

for $i \leftarrow 2$ to n do

 if $s_i \geq f_j$ then

$A \leftarrow A \cup \{i\}$

{Add activity i to the set}

$j \leftarrow i$

{record last activity added}

return A

The Activity Selection Problem


- Here are a set of start and finish times


i	1	2	3	4	5	6	7	8	9	10	11
s_i	1	3	0	5	3	5	6	8	8	2	12
f_i	4	5	6	7	8	9	10	11	12	13	14


- What is the maximum number of activities that can be completed?
 - $\{a_3, a_9, a_{11}\}$ can be completed
 - But so can $\{a_1, a_4, a_8, a_{11}\}$ which is a larger set
 - But it is not unique, consider $\{a_2, a_4, a_9, a_{11}\}$


Interval Representation


i	1	2	3	4	5	6	7	8	9	10	11
s_i	1	3	0	5	3	5	6	8	8	2	12
f_i	4	5	6	7	8	9	10	11	12	13	14




















Why this Algorithm is Optimal?

- We will show that this algorithm uses the following properties
 - The problem has the optimal substructure property
 - The algorithm satisfies the greedy-choice property
- Thus, it is Optimal

Greedy-Choice Property

- Show there is an optimal solution that begins with a greedy choice (with activity 1, which has the earliest finish time)
- Suppose $A \subseteq S$ in an optimal solution
 - Order the activities in A by finish time. The first activity in A is k
 - If $k = 1$, the schedule A begins with a greedy choice
 - If $k \neq 1$, show that there is an optimal solution B to S that begins with the greedy choice, activity 1
 - Let $B = A - \{k\} \cup \{1\}$
 - $f_1 \leq f_k \rightarrow$ activities in B are disjoint (compatible)
 - B has the same number of activities as A
 - Thus, B is optimal

Optimal Substructures

- Once the greedy choice of activity 1 is made, the problem reduces to finding an optimal solution for the activity-selection problem over those activities in S that are compatible with activity 1
 - Optimal Substructure
 - If A is optimal to S , then $A' = A - \{1\}$ is optimal to $S' = \{i \in S: s_i \geq f_1\}$
 - Why?
 - If we could find a solution B' to S' with more activities than A' , adding activity 1 to B' would yield a solution B to S with more activities than A → contradicting the optimality of A
- After each greedy choice is made, we are left with an optimization problem of the same form as the original problem
 - By induction on the number of choices made, making the greedy choice at every step produces an optimal solution