

CS571
Mansi Shah
(19526)
Week 12

Simplifying API server communication with ambassador containers


Running the curl pod with an additional ambassador container

-The ambassador container, running the kubectl-proxy image

```
mansishah@macbookpro downward % vim curl-with-ambassador.yaml
mansishah@macbookpro downward % cat curl-with-ambassador.yaml
apiVersion: v1
kind: Pod
metadata:
  name: curl-with-ambassador
spec:
  containers:
  - name: main
    image: tutum/curl
    command: ["sleep", "9999999"]
  - name: ambassador
    image: luksa/kubectl-proxy:1.6.2
mansishah@macbookpro downward % kubectl create -f curl-with-ambassador.yaml
pod/curl-with-ambassador created
mansishah@macbookpro downward % kubectl get pod
```

NAME	READY	STATUS	RESTARTS	AGE
curl	1/1	Running	0	129m
curl-with-ambassador	2/2	Running	0	9s
downward	1/1	Running	0	6m1m
my-job-nglj9	0/1	Completed	0	4h42m

```
mansishah@macbookpro downward %
```



Talking to the API server through the ambassador:

-By default, kubectl proxy binds to port 8001, and because both containers in the pod share the same network interfaces.

```
mansishah@macbookpro downward % kubectl exec -it curl-with-ambassador -c main bash
root@curl-with-ambassador:/# curl localhost:8001
{
  "paths": [
    "/api",
    "/api/v1",
    "/apis",
    "/apis/",
    "/apis/admissionregistration.k8s.io",
    "/apis/admissionregistration.k8s.io/v1",
    "/apis/admissionregistration.k8s.io/v1beta1",
    "/apis/apiextensions.k8s.io",
    "/apis/apiextensions.k8s.io/v1",
    "/apis/apiextensions.k8s.io/v1beta1",
    "/apis/apiregistration.k8s.io",
    "/apis/apiregistration.k8s.io/v1",
    "/apis/apiregistration.k8s.io/v1beta1",
    "/apis/apps",
    "/apis/apps/v1",
    "/apis/authentication.k8s.io",
    "/apis/authentication.k8s.io/v1",
    "/apis/authentication.k8s.io/v1beta1",
    "/apis/authorization.k8s.io",
    "/apis/authorization.k8s.io/v1",
    "/apis/authorization.k8s.io/v1beta1",
    "/apis/autoscaling",
    "/apis/autoscaling/v1",
    "/apis/autoscaling/v2beta1",
    "/apis/autoscaling/v2beta2",
    "/apis/batch",
    "/apis/batch/v1",
    "/apis/batch/v1beta1",
    "/apis/certificates.k8s.io",
    "/apis/certificates.k8s.io/v1beta1",
    "/apis/coordination.k8s.io",
    "/apis/coordination.k8s.io/v1",
    "/apis/coordination.k8s.io/v1beta1",
    "/apis/discovery.k8s.io",
    "/apis/discovery.k8s.io/v1beta1",
    "/apis/events.k8s.io",
    "/apis/events.k8s.io/v1beta1",
    "/apis/extensions",
    "/apis/extensions/v1beta1",
    "/apis/networking.k8s.io",
    "/apis/networking.k8s.io/v1",
```

```
"/livez",
"/livez/autoregister-completion",
"/livez/etcd",
"/livez/log",
"/livez/ping",
"/livez/poststarthook/apiservice-openapi-controller",
"/livez/poststarthook/apiservice-registration-controller",
"/livez/poststarthook/apiservice-status-available-controller",
"/livez/poststarthook/bootstrap-controller",
"/livez/poststarthook/crd-informer-synced",
"/livez/poststarthook/generic-apiserver-start-informers",
"/livez/poststarthook/kube-apiserver-autoregistration",
"/livez/poststarthook/rbac/bootstrap-roles",
"/livez/poststarthook/scheduling/bootstrap-system-priority-classes",
"/livez/poststarthook/start-apiextensions-controllers",
"/livez/poststarthook/start-apiextensions-informers",
"/livez/poststarthook/start-cluster-authentication-info-controller",
"/livez/poststarthook/start-kube-aggregator-informers",
"/livez/poststarthook/start-kube-apiserver-admission-initializer",
"/logs",
"/metrics",
"/openapi/v2",
"/readyz",
"/readyz/autoregister-completion",
"/readyz/etcd",
"/readyz/log",
"/readyz/ping",
"/readyz/poststarthook/apiservice-openapi-controller",
"/readyz/poststarthook/apiservice-registration-controller",
"/readyz/poststarthook/apiservice-status-available-controller",
"/readyz/poststarthook/bootstrap-controller",
"/readyz/poststarthook/crd-informer-synced",
"/readyz/poststarthook/generic-apiserver-start-informers",
"/readyz/poststarthook/kube-apiserver-autoregistration",
"/readyz/poststarthook/rbac/bootstrap-roles",
"/readyz/poststarthook/scheduling/bootstrap-system-priority-classes",
"/readyz/poststarthook/start-apiextensions-controllers",
"/readyz/poststarthook/start-apiextensions-informers",
"/readyz/poststarthook/start-cluster-authentication-info-controller",
"/readyz/poststarthook/start-kube-aggregator-informers",
"/readyz/poststarthook/start-kube-apiserver-admission-initializer",
"/readyz/shutdown",
"/version"
```

```
] bot@curl:~$ curl -s -H 'Host: ambassador:/'
```