


Performance


Values are estimated and may vary. The [performance score is calculated](#) directly from these metrics. [See calculator.](#)

▲ 0–49 50–89 90–100



METRICS		Expand view
First Contentful Paint	0.9 s	Largest Contentful Paint
Total Blocking Time	0 ms	Cumulative Layout Shift
Speed Index		

1.0 s



Later this year, insights will replace performance audits. [Learn more and provide feedback here.](#)

[Go back to audits](#)

Show audits relevant to: [All](#) [FCP](#) [LCP](#) [TBT](#) [CLS](#)

## INSIGHTS

▲ Improve image delivery — Est savings of 416 KiB

Reducing the download time of images can improve the perceived load time of the page and LCP. [Learn more about optimizing image size](#) [FCP](#) [LCP](#)

URL	Resource Size	Est Savings
replit.dev <a href="#">1st Party</a>	1,040.8 KiB	416.5 KiB
/img/main2.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	171.0 KiB	137.0 KiB
This image file is larger than it needs to be (1176x1628) for its displayed dimensions (822x462). Use responsive images to reduce the image download size.		137.0 KiB
/img/fresno.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	186.9 KiB	71.5 KiB
Increasing the image compression factor could improve this image's download size.		71.5 KiB
/img/alamendsa1.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	242.1 KiB	71.3 KiB

URL	Resource Size	Est Savings
Increasing the image compression factor could improve this image's download size.		71.3 KiB
/img/sanjose1111.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	225.7 KiB	57.7 KiB
Increasing the image compression factor could improve this image's download size.		57.7 KiB
/img/santa-clara-county-neighborhood.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	89.3 KiB	37.2 KiB
Increasing the image compression factor could improve this image's download size.		37.2 KiB
/img/ventura-california-1-2.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	98.9 KiB	30.0 KiB
Increasing the image compression factor could improve this image's download size.		30.0 KiB
/img/favicon.ico (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	14.7 KiB	7.7 KiB
Using a modern image format (WebP, AVIF) or increasing the image compression could improve this image's download size.		7.7 KiB
/img/riverside.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	12.3 KiB	4.0 KiB
Increasing the image compression factor could improve this image's download size.		4.0 KiB
▲ Modern HTTP — Est savings of 120 ms ^		
HTTP/2 and HTTP/3 offer many benefits over HTTP/1.1, such as multiplexing. <a href="#">Learn more about using modern HTTP.</a> <span>FCP</span> <span>LCP</span>		
URL	Protocol	
replit.dev <span>1st Party</span>		
https://36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev	http/1.1	
/img/main2.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1	

URL	Protocol
/css/style.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/css/back-to.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/css/font-display-override.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/logo1.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/favicon.ico (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/css/header-fix.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/JS/header-fix.js (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/JS/accessible-nav.js (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/JS/back-to-top.js (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/JS/performance-optimization.js (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/video1.mp4 (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/LA.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/orange.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/san-francisco.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/san-diego.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/riverside.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/sanbardino12.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/ventura-california-1-2.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/sacramento12.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/santa-clara-county-neighborhood.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/alamendsa1.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/fresno.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1

URL	Protocol
/img/sanjose1111.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/site.webmanifest (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1

▲ Font display — Est savings of 320 ms

Consider setting [font-display](#) to swap or optional to ensure text is consistently visible. swap can be further optimized to mitigate layout shifts with [font metric overrides](#). FCP

URL	Est Savings
Cloudflare CDN <span>Cdn</span>	630 ms
...webfonts/fa-solid-900.woff2 (cdnjs.cloudflare.com)	320 ms
...webfonts/fa-brands-400.woff2 (cdnjs.cloudflare.com)	310 ms

▲ Network dependency tree

**Warnings:** More than 4 `preconnect` connections were found. These should be used sparingly and only to the most important origins.

[Avoid chaining critical requests](#) by reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. LCP

Maximum critical path latency: **1,014 ms**

*Initial Navigation*

https://36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev - **259 ms**, 23.93 KiB

...css/all.min.css (cdnjs.cloudflare.com) - **317 ms**, 18.75 KiB

...webfonts/fa-brands-400.woff2 (cdnjs.cloudflare.com) - **1,014 ms**, 115.05 KiB

...webfonts/fa-solid-900.woff2 (cdnjs.cloudflare.com) - **979 ms**, 153.64 KiB

/css/header-fix.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev) - **437 ms**, 4.27 KiB

/css/font-display-override.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev) - **367 ms**, 2.33 KiB

/css/back-to.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev) - **354 ms**, 2.48 KiB

/css/style.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev) - **339 ms**, 10.35 KiB

---

### Preconnected origins

[preconnect](#) hints help the browser establish a connection earlier in the page load, saving time when the first request for that origin is made. The following are the origins that the page preconnected to.

Origin	Source
https://fonts.googleapis.com/	link
https://fonts.gstatic.com/	link
https://stackpath.bootstrapcdn.com/	link
https://cdnjs.cloudflare.com/	link
https://www.google-analytics.com/	link
Unused preconnect. Only use `preconnect` for origins that the page is likely to request.	
https://www.googletagmanager.com/	link
Unused preconnect. Only use `preconnect` for origins that the page is likely to request.	

---

### Preconnect candidates

Add [preconnect](#) hints to your most important origins, but try to use no more than 4.

No additional origins are good candidates for preconnecting

Render blocking requests



Requests are blocking the page's initial render, which may delay LCP. [Deferring or inlining](#) can move these network requests out of the critical path. FCP LCP

URL	Transfer Size	Duration
replit.dev <span>1st Party</span>	15.2 KiB	580 ms
/css/font-display-override.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	2.3 KiB	210 ms
/css/back-to.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	2.5 KiB	210 ms
/css/style.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	10.4 KiB	170 ms

Layout shift culprits



Layout shifts occur when elements move absent any user interaction. [Investigate the causes of layout shifts](#), such as elements being added, removed, or their fonts changing as the page loads. CLS


Element	Layout shift score
Total	0.030
<div>div.container</div>	0.009
<div>...v20/UcC73FwrK....woff2 (fonts.gstatic.com)</div> <div>Web font</div> <div>section.hero-section</div>	0.008

Element		Layout shift score												
	div.container													
		0.007												
	div.container													
		0.006												
	div.company-main													
		0.000												
<div> <input type="radio"/> Optimize DOM size         <span>^</span> </div> <p>A large DOM can increase the duration of style calculations and layout reflows, impacting page responsiveness. A large DOM will also increase memory usage. <a href="#">Learn how to avoid an excessive DOM size.</a></p> <table> <tr> <th>Statistic</th><th>Element</th><th>Value</th></tr> <tr> <td>Total elements</td><td></td><td>675</td></tr> <tr> <td rowspan="2">Most children</td><td rowspan="2"></td><td rowspan="2">body#top.home-page</td></tr> <tr> </tr> <tr> <td>DOM depth</td><td>span</td><td>12</td></tr> </table>			Statistic	Element	Value	Total elements		675	Most children		body#top.home-page	DOM depth	span	12
Statistic	Element	Value												
Total elements		675												
Most children		body#top.home-page												
DOM depth	span	12												
<div> <input type="radio"/> LCP breakdown         <span>^</span> </div>														



Each [subpart has specific improvement strategies](#). Ideally, most of the LCP time should be spent on loading the resources, not within delays. LCP

Subpart	Duration
Time to first byte	90 ms
Resource load delay	160 ms
Resource load duration	260 ms
Element render delay	580 ms



3rd parties

3rd party code can significantly impact load performance. [Reduce and defer loading of 3rd party code](#) to prioritize your page's content.

3rd party	Transfer size	Main thread time
pphgdbglmicfdkhondlafkiomnelnk	0 KiB	121 ms
chrome-extension://pphgdbglmicfdkhondlafkiomnelnk/libs/processor.js	0 KiB	48 ms
chrome-extension://pphgdbglmicfdkhondlafkiomnelnk/ad-blocker/content.js	0 KiB	42 ms
chrome-extension://pphgdbglmicfdkhondlafkiomnelnk/content.js	0 KiB	26 ms
chrome-extension://pphgdbglmicfdkhondlafkiomnelnk/content/location/location.js	0 KiB	2 ms
chrome-extension://pphgdbglmicfdkhondlafkiomnelnk/libs/requests.js	0 KiB	2 ms

3rd party	Transfer size	Main thread time
chrome-extension://pphgdbglldmicfdkhondlafkiomnelnk/libs/extend-native-history-api.js	0 KiB	1 ms
chrome-extension://pphgdbglldmicfdkhondlafkiomnelnk/executors/traffic.js	0 KiB	0 ms
jQuery CDN <span>Cdn</span>	<b>55 KiB</b>	<b>23 ms</b>
/jquery-3.5.1.min.js (code.jquery.com)	30 KiB	13 ms
/jquery-3.5.1.slim.min.js (code.jquery.com)	24 KiB	10 ms
Bootstrap CDN <span>Cdn</span>	<b>49 KiB</b>	<b>8 ms</b>
...js/bootstrap.bundle.min.js (stackpath.bootstrapcdn.com)	24 KiB	8 ms
...css/bootstrap.min.css (stackpath.bootstrapcdn.com)	25 KiB	0 ms
JSDelivr CDN <span>Cdn</span>	<b>22 KiB</b>	<b>5 ms</b>
...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	22 KiB	5 ms
Google Fonts <span>Cdn</span>	<b>65 KiB</b>	<b>0 ms</b>
...v20/UcC73FwrK....woff2 (fonts.gstatic.com)	47 KiB	0 ms
...v12/UcCO3FwrK....woff2 (fonts.gstatic.com)	17 KiB	0 ms
/css2?family=Inter:wght@400;600;700&display=swap (fonts.googleapis.com)	1 KiB	0 ms
Cloudflare CDN <span>Cdn</span>	<b>306 KiB</b>	<b>0 ms</b>
...webfonts/fa-solid-900.woff2 (cdnjs.cloudflare.com)	154 KiB	0 ms
...webfonts/fa-brands-400.woff2 (cdnjs.cloudflare.com)	115 KiB	0 ms
...css/all.min.css (cdnjs.cloudflare.com)	19 KiB	0 ms
...css/all.min.css (cdnjs.cloudflare.com)	19 KiB	0 ms

These insights are also available in the Chrome DevTools Performance Panel - [record a trace](#) to view more detailed information.

## DIAGNOSTICS

▲ Use HTTP/2 — 26 requests not served via HTTP/2

HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. [Learn more about HTTP/2.](#) LCP

FCP

URL	Protocol
replit.dev <span>1st Party</span>	
https://36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev	http/1.1
/img/main2.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/css/style.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/css/back-to.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/css/font-display-override.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/logo1.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/favicon.ico (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/css/header-fix.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/JS/header-fix.js (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/JS/accessible-nav.js (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/JS/back-to-top.js (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1

URL	Protocol
/JS/performance-optimization.js (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/video1.mp4 (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/LA.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/orange.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/san-francisco.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/san-diego.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/riverside.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/sanbardino12.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/ventura-california-1-2.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/sacramento12.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/santa-clara-county-neighborhood.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/alamendsa1.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/fresno.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/img/sanjose1111.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1
/site.webmanifest (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	http/1.1

### ▲ Reduce unused CSS — Est savings of 50 KiB

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. [Learn how to reduce unused CSS.](#) FCP LCP

URL	Transfer Size	Est Savings
Cloudflare CDN <span>Cdn</span>	<b>28.8 KiB</b>	<b>28.3 KiB</b>
...css/all.min.css (cdnjs.cloudflare.com)	14.4 KiB	14.2 KiB
...css/all.min.css (cdnjs.cloudflare.com)	14.3 KiB	14.1 KiB
Bootstrap CDN <span>Cdn</span>	<b>23.1 KiB</b>	<b>22.1 KiB</b>
...css/bootstrap.min.css (stackpath.bootstrapcdn.com)	23.1 KiB	22.1 KiB

### Minify CSS — Est savings of 3 KiB

Minifying CSS files can reduce network payload sizes. [Learn how to minify CSS.](#) FCP LCP

URL	Transfer Size	Est Savings
replit.dev <span>1st Party</span>	<b>10.4 KiB</b>	<b>3.2 KiB</b>
/css/style.css (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	10.4 KiB	3.2 KiB

### Avoid serving legacy JavaScript to modern browsers — Est savings of 0 KiB

Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. Consider modifying your JavaScript build process to not transpile [Baseline](#) features, unless you know you must support legacy browsers. [Learn why most sites can deploy ES6+ code without transpiling.](#) FCP LCP

URL	Est Savings
JSDelivr CDN <span>Cdn</span>	<b>0.2 KiB</b>
...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	0.2 KiB
<div><div>bootstrap.bundle.min.js:6</div><div>@babel/plugin-transform-classes</div></div>	
Bootstrap CDN <span>Cdn</span>	<b>0.1 KiB</b>
...js/bootstrap.bundle.min.js (stackpath.bootstrapcdn.com)	0.1 KiB
<div><div>bootstrap.bundle.min.js:6</div><div>@babel/plugin-transform-classes</div></div>	
1ClickVPN Proxy for Chrome <span>Chrome Extension</span>	<b>0.0 KiB</b>
chrome-extension://pphgdbglldmicfdkhondlafkiomnelnk/ad-blocker/content.js	0.0 KiB
<div><div>content.js:1</div><div>@babel/plugin-transform-regenerator</div></div>	

Reduce unused JavaScript — Est savings of 100 KiB ^

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. [Learn how to reduce unused JavaScript.](#) FCP LCP

URL	Transfer Size	Est Savings
1ClickVPN Proxy for Chrome <span>Chrome Extension</span>	162.1 KiB	100.1 KiB
chrome-extension://pphgdbgldlmicfdkhondlafkiomnelnk/ad-blocker/content.js	79.6 KiB	66.6 KiB
chrome-extension://pphgdbgldlmicfdkhondlafkiomnelnk/libs/processor.js	82.5 KiB	33.5 KiB

Avoid enormous network payloads — Total size was 3,578 KiB ^

Large network payloads cost users real money and are highly correlated with long load times. [Learn how to reduce payload sizes.](#)

☒ Show 3rd-party resources (2)

URL	Transfer Size
replit.dev <span>1st Party</span>	2,715.5 KiB
/img/video1.mp4 (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	1,426.8 KiB
/img/sanbardino12.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	244.1 KiB
/img/alamendsa1.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	244.0 KiB
/img/sanjose1111.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	227.6 KiB
/img/fresno.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	188.8 KiB
/img/main2.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	172.9 KiB
/img/sacraamento12.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	110.3 KiB

URL	Transfer Size
/img/ventura-california-1-2.webp (36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev)	100.8 KiB
Cloudflare CDN <span>Cdn</span>	<b>268.7 KiB</b>
...webfonts/fa-solid-900.woff2 (cdnjs.cloudflare.com)	153.6 KiB
...webfonts/fa-brands-400.woff2 (cdnjs.cloudflare.com)	115.0 KiB

Avoid long main-thread tasks — 2 long tasks found

^

Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. [Learn how to avoid long main-thread tasks](#) TBT

URL	Start Time	Duration
replit.dev <span>1st Party</span>		<b>147 ms</b>
https://36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev	454 ms	92 ms
https://36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev	347 ms	55 ms

More information about the performance of your application. These numbers don't [directly affect](#) the Performance score.

## PASSED AUDITS (17)

Hide

Use efficient cache lifetimes	^
A long cache lifetime can speed up repeat visits to your page. <a href="#">Learn more.</a> <span>FCP</span> <span>LCP</span>	



### Document request latency



Your first network request is the most important. Reduce its latency by avoiding redirects, ensuring a fast server response, and enabling text compression. FCP LCP

Avoids redirects

Server responds quickly (observed 86 ms)

Applies text compression

### Duplicated JavaScript



Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity. FCP LCP

### Forced reflow



A forced reflow occurs when JavaScript queries geometric properties (such as `offsetWidth`) after styles have been invalidated by a change to the DOM state. This can result in poor performance. Learn more about [forced reflows](#) and possible mitigations.

### ☐ INP breakdown



Start investigating with the longest subpart. [Delays can be minimized](#). To reduce processing duration, [optimize the main-thread costs](#), often JS.

### LCP request discovery



Optimize LCP by making the LCP image [discoverable](#) from the HTML immediately, and [avoiding lazy-loading](#) LCP

`fetchpriority=high` applied

Request is discoverable in initial document

lazy load not applied



video#hero-video

## Legacy JavaScript



Polyfills and transforms enable older browsers to use new JavaScript features. However, many aren't necessary for modern browsers. Consider modifying your JavaScript build process to not transpile [Baseline](#) features, unless you know you must support older browsers. [Learn why most sites can deploy ES6+ code without transpiling](#) FCP LCP

## Optimize viewport for mobile



Tap interactions may be [delayed by up to 300 ms](#) if the viewport is not optimized for mobile.

meta

## Defer offscreen images



Consider lazy-loading offscreen and hidden images after all critical resources have finished loading to lower time to interactive. [Learn how to defer offscreen images](#). FCP LCP

## Minify JavaScript



Minifying JavaScript files can reduce payload sizes and script parse time. [Learn how to minify JavaScript](#). FCP LCP

## ☐ User Timing marks and measures



Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. [Learn more about User Timing marks](#).

JavaScript execution time — 0.1 s



Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to reduce Javascript execution time.](#) TBT

URL	Total CPU Time	Script Evaluation	Script Parse
replit.dev <span>1st Party</span>	<b>620 ms</b>	<b>71 ms</b>	<b>38 ms</b>
https://36a15763-daa0-4034-9c05-90a308805a6f-00-3in4w5ae5i40v.worf.replit.dev	620 ms	71 ms	38 ms
Unattributable	<b>214 ms</b>	<b>33 ms</b>	<b>0 ms</b>
Unattributable	214 ms	33 ms	0 ms

Minimizes main-thread work — 0.9 s



Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to minimize main-thread work](#) TBT

Category	Time Spent
Style & Layout	326 ms
Other	230 ms
Script Evaluation	172 ms
Rendering	93 ms

Category	Time Spent
Script Parsing & Compilation	51 ms
Parse HTML & CSS	41 ms
Garbage Collection	10 ms



  

<input type="radio"/> Lazy load third-party resources with facades	^
Some third-party embeds can be lazy loaded. Consider replacing them with a facade until they are required. <a href="#">Learn how to defer third-parties with a facade.</a> TBT	
Uses passive listeners to improve scrolling performance	^
Consider marking your touch and wheel event listeners as <code>passive</code> to improve your page's scroll performance. <a href="#">Learn more about adopting passive event listeners.</a>	
Avoids <code>document.write()</code>	^
For users on slow connections, external scripts dynamically injected via <code>document.write()</code> can delay page load by tens of seconds. <a href="#">Learn how to avoid document.write().</a>	
Page didn't prevent back/forward cache restoration	^
Many navigations are performed by going back to a previous page, or forwards again. The back/forward cache (bfcache) can speed up these return navigations. <a href="#">Learn more about the bfcache</a>	

# Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so [manual testing](#) is also encouraged.

## ARIA

 **[aria-\*] attributes do not match their roles** 

Each ARIA role supports a specific subset of aria-\* attributes. Mismatching these invalidates the aria-\* attributes. [Learn how to match ARIA attributes to their roles.](#)

Failing Elements

div#headingOne.faq-header.d-flex.align-items-center

div#headingTwo.faq-header.d-flex.align-items-center



div#headingThree.faq-header.d-flex.align-items-center

div#headingFour.faq-header.d-flex.align-items-center

div#headingFive.faq-header.d-flex.align-items-center

These are opportunities to improve the usage of ARIA in your application which may enhance the experience for users of assistive technology, like a screen reader.

## CONTRAST

 **Background and foreground colors do not have a sufficient contrast ratio.** 

Low-contrast text is difficult or impossible for many users to read. [Learn how to provide sufficient color contrast.](#)

## Failing Elements

span

a.quote-button

span.author-location

div.premium-feature

span

div.premium-card

span

div.premium-card

span

div.premium-card

span

div.premium-card

a.premium-button

h3.faq-category-title

div.faq-category

h3.faq-category-title

div.faq-category



h3.faq-category-title

div.faq-category

Failing Elements
h3.faq-category-title
div.faq-category
h3.faq-category-title
div.faq-category
a.btn.btn-primary.faq-btn
a.btn.btn-outline-primary.faq-btn
div.faq-cta.text-center
a
footer.footer
a
footer.footer

These are opportunities to improve the legibility of your content.

## NAVIGATION

 <b>Heading elements are not in a sequentially-descending order</b> 		
<p>Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. <a href="#">Learn more about heading order.</a></p>		
<table> <tr> <th>Failing Elements</th></tr> <tr> <td>h4</td></tr> </table>	Failing Elements	h4
Failing Elements		
h4		

Failing Elements
h5.footer-title

These are opportunities to improve keyboard navigation in your application.

## AUDIO AND VIDEO

☐
<video> elements contain a <track> element with [kind="captions"]

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. [Learn more about video captions.](#)

Failing Elements
<div> <div></div> <div>video#hero-video</div> </div>

These are opportunities to provide alternative content for audio and video. This may improve the experience for users with hearing or vision impairments.

## ADDITIONAL ITEMS TO MANUALLY CHECK (10)

Hide

☐
Interactive controls are keyboard focusable

Custom interactive controls are keyboard focusable and display a focus indicator. [Learn how to make custom controls focusable.](#)

☐
Interactive elements indicate their purpose and state



Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. <a href="#">Learn how to decorate interactive elements with affordance hints.</a>	
<input type="radio"/> The page has a logical tab order	^
Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. <a href="#">Learn more about logical tab ordering.</a>	
<input type="radio"/> Visual order on the page follows DOM order	^
DOM order matches the visual order, improving navigation for assistive technology. <a href="#">Learn more about DOM and visual ordering.</a>	
<input type="radio"/> User focus is not accidentally trapped in a region	^
A user can tab into and out of any control or region without accidentally trapping their focus. <a href="#">Learn how to avoid focus traps.</a>	
<input type="radio"/> The user's focus is directed to new content added to the page	^
If new content, such as a dialog, is added to the page, the user's focus is directed to it. <a href="#">Learn how to direct focus to new content.</a>	
<input type="radio"/> HTML5 landmark elements are used to improve navigation	^
Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. <a href="#">Learn more about landmark elements.</a>	
<input type="radio"/> Offscreen content is hidden from assistive technology	^
Offscreen content is hidden with display: none or aria-hidden=true. <a href="#">Learn how to properly hide offscreen content.</a>	
<input type="radio"/> Custom controls have associated labels	^

Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. <a href="#">Learn more about custom controls and labels.</a>	
<input type="radio"/> Custom controls have ARIA roles	^
Custom interactive controls have appropriate ARIA roles. <a href="#">Learn how to add roles to custom controls.</a>	

These items address areas which an automated testing tool cannot cover. Learn more in our guide on [conducting an accessibility review](#).

## PASSED AUDITS (20)

Hide

<code>[aria-hidden="true"]</code> is not present on the document <code>&lt;body&gt;</code>	^
Assistive technologies, like screen readers, work inconsistently when <code>aria-hidden="true"</code> is set on the document <code>&lt;body&gt;</code> . <a href="#">Learn how aria-hidden affects the document body.</a>	
<code>[role]</code> s have all required <code>[aria-*)</code> attributes	^
Some ARIA roles have required attributes that describe the state of the element to screen readers. <a href="#">Learn more about roles and required attributes.</a>	
<code>[aria-*)</code> attributes have valid values	^
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. <a href="#">Learn more about valid values for ARIA attributes.</a>	
<code>[aria-*)</code> attributes are valid and not misspelled	^
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. <a href="#">Learn more about valid ARIA attributes.</a>	

Buttons have an accessible name	^
When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. <a href="#">Learn how to make buttons more accessible.</a>	
Image elements have <code>[alt]</code> attributes	^
Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. <a href="#">Learn more about the alt attribute.</a>	
<code>[user-scalable="no"]</code> is not used in the <code>&lt;meta name="viewport"&gt;</code> element and the <code>[maximum-scale]</code> attribute is not less than 5.	^
Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. <a href="#">Learn more about the viewport meta tag.</a>	
ARIA attributes are used as specified for the element's role	^
Some ARIA attributes are only allowed on an element under certain conditions. <a href="#">Learn more about conditional ARIA attributes.</a>	
Elements use only permitted ARIA attributes	^
Using ARIA attributes in roles where they are prohibited can mean that important information is not communicated to users of assistive technologies. <a href="#">Learn more about prohibited ARIA roles.</a>	
<code>[role]</code> values are valid	^
ARIA roles must have valid values in order to perform their intended accessibility functions. <a href="#">Learn more about valid ARIA roles.</a>	
Document has a <code>&lt;title&gt;</code> element	^

<p>The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. <a href="#">Learn more about document titles.</a></p>	
<p><code>&lt;html&gt;</code> element has a <code>[lang]</code> attribute</p>	^
<p>If a page doesn't specify a <code>lang</code> attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. <a href="#">Learn more about the <code>lang</code> attribute.</a></p>	
<p><code>&lt;html&gt;</code> element has a valid value for its <code>[lang]</code> attribute</p>	^
<p>Specifying a valid <a href="#">BCP 47 language</a> helps screen readers announce text properly. <a href="#">Learn how to use the <code>lang</code> attribute.</a></p>	
<p>Links have a discernible name</p>	^
<p>Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. <a href="#">Learn how to make links accessible.</a></p>	
<p>Lists contain only <code>&lt;li&gt;</code> elements and script supporting elements (<code>&lt;script&gt;</code> and <code>&lt;template&gt;</code>).</p>	^
<p>Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. <a href="#">Learn more about proper list structure.</a></p>	
<p>List items (<code>&lt;li&gt;</code>) are contained within <code>&lt;ul&gt;</code>, <code>&lt;ol&gt;</code> or <code>&lt;menu&gt;</code> parent elements</p>	^
<p>Screen readers require list items (<code>&lt;li&gt;</code>) to be contained within a parent <code>&lt;ul&gt;</code>, <code>&lt;ol&gt;</code> or <code>&lt;menu&gt;</code> to be announced properly. <a href="#">Learn more about proper list structure.</a></p>	
<p>Touch targets have sufficient size and spacing.</p>	^
<p>Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to activate the targets. <a href="#">Learn more about touch targets.</a></p>	

Uses ARIA roles only on compatible elements	^
Many HTML elements can only be assigned certain ARIA roles. Using ARIA roles where they are not allowed can interfere with the accessibility of the web page. <a href="#">Learn more about ARIA roles.</a>	
Deprecated ARIA roles were not used	^
Deprecated ARIA roles may not be processed correctly by assistive technology. <a href="#">Learn more about deprecated ARIA roles.</a>	
Image elements do not have <code>[alt]</code> attributes that are redundant text.	^
Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be read twice. <a href="#">Learn more about the alt attribute.</a>	

NOT APPLICABLE (33)

Hide

<input type="radio"/> <code>[accesskey]</code> values are unique	^
Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. <a href="#">Learn more about access keys.</a>	
<input type="radio"/> <code>button</code> , <code>link</code> , and <code>menuitem</code> elements have accessible names	^
When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <a href="#">Learn how to make command elements more accessible.</a>	
<input type="radio"/> Elements with <code>role="dialog"</code> or <code>role="alertdialog"</code> have accessible names.	^
ARIA dialog elements without accessible names may prevent screen readers users from discerning the purpose of these elements. <a href="#">Learn how to make ARIA dialog elements more accessible.</a>	

- `[aria-hidden="true"]` elements do not contain focusable descendents



Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. [Learn how aria-hidden affects focusable elements.](#)

- ARIA input fields have accessible names



When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about input field labels.](#)

- ARIA `meter` elements have accessible names



When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name meter elements.](#)

- ARIA `progressbar` elements have accessible names



When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to label progressbar elements.](#)

- Elements with an ARIA `[role]` that require children to contain a specific `[role]` have all required children.



Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more about roles and required children elements.](#)

- `[role]`s are contained by their required parent element



Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. [Learn more about ARIA roles and required parent element.](#)

- Elements with the `role=text` attribute do not have focusable descendents.



Adding <code>role=text</code> around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. <a href="#">Learn more about the <code>role=text</code> attribute.</a>	
<input type="radio"/> ARIA toggle fields have accessible names	^
When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <a href="#">Learn more about toggle fields.</a>	
<input type="radio"/> ARIA <code>tooltip</code> elements have accessible names	^
When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <a href="#">Learn how to name tooltip elements.</a>	
<input type="radio"/> ARIA <code>treeitem</code> elements have accessible names	^
When a <code>treeitem</code> element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <a href="#">Learn more about labeling treeitem elements.</a>	
<input type="radio"/> The page contains a heading, skip link, or landmark region	^
Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. <a href="#">Learn more about bypass blocks.</a>	
<input type="radio"/> <code>&lt;d1&gt;</code> 's contain only properly-ordered <code>&lt;dt&gt;</code> and <code>&lt;dd&gt;</code> groups, <code>&lt;script&gt;</code> , <code>&lt;template&gt;</code> or <code>&lt;div&gt;</code> elements.	^
When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. <a href="#">Learn how to structure definition lists correctly.</a>	
<input type="radio"/> Definition list items are wrapped in <code>&lt;d1&gt;</code> elements	^
Definition list items ( <code>&lt;dt&gt;</code> and <code>&lt;dd&gt;</code> ) must be wrapped in a parent <code>&lt;d1&gt;</code> element to ensure that screen readers can properly announce them. <a href="#">Learn how to structure definition lists correctly.</a>	

○ ARIA IDs are unique ^

The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. [Learn how to fix duplicate ARIA IDs.](#)

○ No form fields have multiple labels ^

Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. [Learn how to use form labels.](#)

○ `<frame>` or `<iframe>` elements have a title ^

Screen reader users rely on frame titles to describe the contents of frames. [Learn more about frame titles.](#)

○ `<html>` element has an `[xml:lang]` attribute with the same base language as the `[lang]` attribute. ^

If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. [Learn more about the lang attribute.](#)

○ Input buttons have discernible text. ^

Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. [Learn more about input buttons.](#)

○ `<input type="image">` elements have `[alt]` text ^

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn about input image alt text.](#)

○ Form elements have associated labels ^

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. [Learn more about form element labels.](#)



<input type="radio"/> Links are distinguishable without relying on color.	^
Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. <a href="#">Learn how to make links distinguishable.</a>	
<input type="radio"/> The document does not use <code>&lt;meta http-equiv="refresh"&gt;</code>	^
Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. <a href="#">Learn more about the refresh meta tag.</a>	
<input type="radio"/> <code>&lt;object&gt;</code> elements have alternate text	^
Screen readers cannot translate non-text content. Adding alternate text to <code>&lt;object&gt;</code> elements helps screen readers convey meaning to users. <a href="#">Learn more about alt text for object elements.</a>	
<input type="radio"/> Select elements have associated label elements.	^
Form elements without effective labels can create frustrating experiences for screen reader users. <a href="#">Learn more about the select element.</a>	
<input type="radio"/> Skip links are focusable.	^
Including a skip link can help users skip to the main content to save time. <a href="#">Learn more about skip links.</a>	
<input type="radio"/> No element has a <code>[tabindex]</code> value greater than 0	^
A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. <a href="#">Learn more about the tabindex attribute.</a>	
<input type="radio"/> Tables have different content in the summary attribute and <code>&lt;caption&gt;</code> .	^

The summary attribute should describe the table structure, while <caption> should have the onscreen title. Accurate table mark-up helps users of screen readers. <a href="#">Learn more about summary and caption.</a>	
<input type="radio"/> Cells in a <table> element that use the [headers] attribute refer to table cells within the same table.	^
Screen readers have features to make navigating tables easier. Ensuring <td> cells using the [headers] attribute only refer to other cells in the same table may improve the experience for screen reader users. <a href="#">Learn more about the headers attribute.</a>	
<input type="radio"/> <th> elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.	^
Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. <a href="#">Learn more about table headers.</a>	
<input type="radio"/> [lang] attributes have a valid value	^
Specifying a valid <a href="#">BCP 47 language</a> on elements helps ensure that text is pronounced correctly by a screen reader. <a href="#">Learn how to use the lang attribute.</a>	



## Best Practices

### TRUST AND SAFETY

<input type="radio"/> Ensure CSP is effective against XSS attacks	^
A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. <a href="#">Learn how to use a CSP to prevent XSS</a>	

Description	Directive	Severity
Host allowlists can frequently be bypassed. Consider using CSP nonces or hashes instead, along with "strict-dynamic" if necessary.	script-src	High
"unsafe-inline" allows the execution of unsafe in-page scripts and event handlers. Consider using CSP nonces or hashes to allow scripts individually.	script-src	High
"unsafe-inline" allows the execution of unsafe in-page scripts and event handlers. Consider using CSP nonces or hashes to allow scripts individually.	script-src-attr	High
'unsafe-hashes', while safer than 'unsafe-inline', allows the execution of unsafe in-page scripts and event handlers as long as their hashes appear in the CSP. Please refactor them to no longer use inline scripts if possible.	script-src-attr	High

Mitigate DOM-based XSS with Trusted Types

The require-trusted-types-for directive in the Content-Security-Policy (CSP) header instructs user agents to control the data passed to DOM XSS sink functions. [Learn more about mitigating DOM-based XSS with Trusted Types.](#)

Description	Severity
No 'Content-Security-Policy' header with Trusted Types directive found	High

## GENERAL

<div> Detected JavaScript libraries </div> <div> <p>All front-end JavaScript libraries detected on the page. <a href="#">Learn more about this JavaScript library detection diagnostic audit.</a></p> </div>
--

Name	Version
Bootstrap	4.5.2
jQuery	3.5.1

PASSED AUDITS (14)

Hide

Uses HTTPS	^
<p>All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding <a href="#">mixed content</a>, where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. <a href="#">Learn more about HTTPS</a>.</p>	
Avoids deprecated APIs	^
<p>Deprecated APIs will eventually be removed from the browser. <a href="#">Learn more about deprecated APIs</a>.</p>	
Avoids third-party cookies	^
<p>Third-party cookies may be blocked in some contexts. <a href="#">Learn more about preparing for third-party cookie restrictions</a>.</p>	
Allows users to paste into input fields	^
<p>Preventing input pasting is a bad practice for the UX, and weakens security by blocking password managers. <a href="#">Learn more about user-friendly input fields</a>.</p>	
Avoids requesting the geolocation permission on page load	^
<p>Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. <a href="#">Learn more about the geolocation permission</a>.</p>	

Avoids requesting the notification permission on page load	^
Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. <a href="#">Learn more about responsibly getting permission for notifications.</a>	
Displays images with correct aspect ratio	^
Image display dimensions should match natural aspect ratio. <a href="#">Learn more about image aspect ratio.</a>	
Serves images with appropriate resolution	^
Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. <a href="#">Learn how to provide responsive images.</a>	
Has a <code>&lt;meta name="viewport"&gt;</code> tag with <code>width</code> or <code>initial-scale</code>	^
A <code>&lt;meta name="viewport"&gt;</code> not only optimizes your app for mobile screen sizes, but also prevents <a href="#">a 300 millisecond delay to user input</a> . <a href="#">Learn more about using the viewport meta tag.</a>	
Page has the HTML doctype	^
Specifying a doctype prevents the browser from switching to quirks-mode. <a href="#">Learn more about the doctype declaration.</a>	
Properly defines charset	^
A character encoding declaration is required. It can be done with a <code>&lt;meta&gt;</code> tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. <a href="#">Learn more about declaring the character encoding.</a>	
No browser errors logged to the console	^
Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. <a href="#">Learn more about this errors in console diagnostic audit</a>	

No issues in the [Issues](#) panel in Chrome Devtools



Issues logged to the Issues panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

Page has valid source maps



Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more about source maps.](#)

URL	Map URL
Bootstrap CDN <span>Cdn</span>	
...js/bootstrap.bundle.min.js (stackpath.bootstrapcdn.com)	...js/bootstrap.bundle.min.js.map (stackpath.bootstrapcdn.com)
Error: Protocol error (Network.loadNetworkResource): Protocol error (Network.loadNetworkResource): CSP violation	
JSDelivr CDN <span>Cdn</span>	
...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	...js/bootstrap.bundle.min.js.map (cdn.jsdelivr.net)
Error: Protocol error (Network.loadNetworkResource): Protocol error (Network.loadNetworkResource): CSP violation	



<input type="radio"/> Redirects HTTP traffic to HTTPS	^
Make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. <a href="#">Learn more.</a>	
<input type="radio"/> Use a strong HSTS policy	^
Deployment of the HSTS header significantly reduces the risk of downgrading HTTP connections and eavesdropping attacks. A rollout in stages, starting with a low max-age is recommended. <a href="#">Learn more about using a strong HSTS policy.</a>	
<input type="radio"/> Ensure proper origin isolation with COOP	^
The Cross-Origin-Opener-Policy (COOP) can be used to isolate the top-level window from other documents such as pop-ups. <a href="#">Learn more about deploying the COOP header.</a>	
<input type="radio"/> Mitigate clickjacking with XFO or CSP	^
The X-Frame-Options (XFO) header or the frame-ancestors directive in the Content-Security-Policy (CSP) header control where a page can be embedded. These can mitigate clickjacking attacks by blocking some or all sites from embedding the page. <a href="#">Learn more about mitigating clickjacking.</a>	
<input type="radio"/> Document uses legible font sizes	^
Font sizes less than 12px are too small to be legible and require mobile visitors to “pinch to zoom” in order to read. Strive to have >60% of page text ≥ 12px. <a href="#">Learn more about legible font sizes.</a>	



SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on [Core Web Vitals](#). [Learn more about Google Search Essentials](#).

## CRAWLING AND INDEXING

 Page is blocked from indexing 

Search engines are unable to include your pages in search results if they don't have permission to crawl them. [Learn more about crawler directives](#).

Blocking Directive Source



X-Robots-Tag: none, noindex, noarchive, nofollow, nositelinkssearchbox, noimageindex

X-Robots-Tag: none, noindex, noarchive, nofollow, nositelinkssearchbox, noimageindex

To appear in search results, crawlers need access to your app.

## ADDITIONAL ITEMS TO MANUALLY CHECK (1)

Hide

 Structured data is valid 

Run the [Structured Data Testing Tool](#) and the [Structured Data Linter](#) to validate structured data. [Learn more about Structured Data](#).

Run these additional validators on your site to check additional SEO best practices.

## PASSED AUDITS (9)

Hide

Document has a `<title>` element 



The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. <a href="#">Learn more about document titles.</a>	
Document has a meta description	^
Meta descriptions may be included in search results to concisely summarize page content. <a href="#">Learn more about the meta description.</a>	
Page has successful HTTP status code	^
Pages with unsuccessful HTTP status codes may not be indexed properly. <a href="#">Learn more about HTTP status codes.</a>	
Links have descriptive text	^
Descriptive link text helps search engines understand your content. <a href="#">Learn how to make links more accessible.</a>	
Links are crawlable	^
Search engines may use href attributes on links to crawl websites. Ensure that the href attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. <a href="#">Learn how to make links crawlable</a>	
robots.txt is valid	^
If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. <a href="#">Learn more about robots.txt.</a>	
Image elements have <code>[alt]</code> attributes	^
Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. <a href="#">Learn more about the alt attribute.</a>	
Document has a valid <code>hreflang</code>	^

hreflang links tell search engines what version of a page they should list in search results for a given language or region.

[Learn more about hreflang.](#)

Document has a valid `rel=canonical`



Canonical links suggest which URL to show in search results. [Learn more about canonical links.](#)

Captured at Nov 2, 2025, 3:15

PM PST

Initial page load

Emulated Desktop with

Lighthouse 12.8.2

Custom throttling

Single page session

Using Chromium 141.0.0.0 with  
devtools

Generated by **Lighthouse** 12.8.2 | [File an issue](#)