



DC-1

Report generated by Tenable Nessus™

Mon, 18 May 2026 14:16:59 Bangladesh Standard Time

TABLE OF CONTENTS

Vulnerabilities by Host

- 192.168.3.140.....4

Compliance 'FAILED'

Compliance 'SKIPPED'

Compliance 'PASSED'

Compliance 'INFO', 'WARNING', 'ERROR'

Remediations

- Suggested Remediations.....78

Vulnerabilities by Host

192.168.3.140

2

CRITICAL

1

HIGH

5

MEDIUM

4

LOW

40

INFO

Scan Information

Start time: Mon May 18 14:00:45 2026

End time: Mon May 18 14:16:59 2026

Host Information

IP: 192.168.3.140

MAC Address: 00:0C:29:3A:EE:0E

OS: Linux Kernel 3.2 on Debian 7.0 (wheezy)

Vulnerabilities

201366 - Debian Linux SEoL (7.x)

Synopsis

An unsupported version of Debian Linux is installed on the remote host.

Description

According to its version, Debian Linux is 7.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

See Also

<https://www.debian.org/News/2016/20160425>

Solution

Upgrade to a version of Debian Linux that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2024/07/03, Modified: 2025/03/26

Plugin Output

tcp/22/ssh

```
OS : Debian Linux 7.0
Security End of Life : April 24, 2016
Time since Security End of Life (Est.) : >= 10 years
```

58987 - PHP Unsupported Version Detection

Synopsis

The remote host contains an unsupported version of a web application scripting language.

Description

According to its version, the installation of PHP on the remote host is no longer supported.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it is likely to contain security vulnerabilities.

See Also

<http://php.net/eol.php>

<https://wiki.php.net/rfc/releaseprocess>

Solution

Upgrade to a version of PHP that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

References

XREF IAVA:0001-A-0581

Plugin Information

Published: 2012/05/04, Modified: 2025/10/29

Plugin Output

tcp/80/www

```
Source          : X-Powered-By: PHP/5.4.45-0+deb7u14
Installed version : 5.4.45-0+deb7u14
```

End of support date : 2015/09/03
Announcement : <http://php.net/supported-versions.php>
Supported versions : 8.1.x / 8.2.x / 8.3.x / 8.4.x

78515 - Drupal Database Abstraction API SQLi

Synopsis

The remote web server is running a PHP application that is affected by a SQL injection vulnerability.

Description

The remote web server is running a version of Drupal that is affected by a SQL injection vulnerability due to a flaw in the Drupal database abstraction API, which allows a remote attacker to use specially crafted requests that can result in arbitrary SQL execution. This may lead to privilege escalation, arbitrary PHP execution, or remote code execution.

See Also

<https://www.drupal.org/SA-CORE-2014-005>

<https://www.drupal.org/project/drupal/releases/7.32>

Solution

Upgrade to version 7.32 or later.

Risk Factor

High

VPR Score

7.4

EPSS Score

0.9422

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.2 (CVSS2#E:F/RL:OF/RC:C)

References

BID	70595
CVE	CVE-2014-3704
XREF	EDB-ID:34984
XREF	EDB-ID:34992

XREF EDB-ID:34993
XREF EDB-ID:35150

Exploitable With

CANVAS (true) Core Impact (true) (true) Metasploit (true)

Plugin Information

Published: 2014/10/16, Modified: 2022/04/11

Plugin Output

tcp/80/www

Nessus was able to exploit the issue using the following request :

```
POST /?q=node&destination=node HTTP/1.1
Host: 192.168.3.140
Accept-Charset: iso-8859-1,utf-8;q=0.9,*;q=0.1
Accept-Language: en
Content-Type: application/x-www-form-urlencoded
Connection: Keep-Alive
Content-Length: 117
Pragma: no-cache
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
name[0];SELECT
+@@version;#]=0;&name[0]=nessus&pass=nessus&test2=test&form_build_id=&form_id=user_login_block&op=Log
+in
```

This produced the following truncated output (limited to 5 lines) :

```
----- snip -----
>Warning</em>: mb_strlen() expects parameter 1 to be string, array given in <em
class="placeholder">drupal_strlen()</em> (line <em class="placeholder">478</em> of <em
class="placeholder">/var/www/includes/unicode.inc</em>).</li>
<li><em class="placeholder">Warning</em>: addcslashes() expects parameter 1 to be string,
array given in <em class="placeholder">DatabaseConnection-&gt;escapeLike()</em> (line <em
class="placeholder">981</em> of <em class="placeholder">/var/www/includes/database/database.inc</
em>).</li>
<li>Sorry, unrecognized username or password. <a href="/user/password?name[0%3BSELECT
%20%40%40version%3B%23]=0%3B&name[0]=nessus">Have you forgotten your password?</a></li>
</ul>
</div>
[...]
```

----- snip -----

136929 - JQuery 1.2 < 3.5.0 Multiple XSS

Synopsis

The remote web server is affected by multiple cross site scripting vulnerability.

Description

According to the self-reported version in the script, the version of JQuery hosted on the remote web server is greater than or equal to 1.2 and prior to 3.5.0. It is, therefore, affected by multiple cross site scripting vulnerabilities.

Note, the vulnerabilities referenced in this plugin have no security impact on PAN-OS, and/or the scenarios required for successful exploitation do not exist on devices running a PAN-OS release.

See Also

<https://blog.jquery.com/2020/04/10/jquery-3-5-0-released/>

<https://security.paloaltonetworks.com/PAN-SA-2020-0007>

Solution

Upgrade to JQuery version 3.5.0 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

6.1 (CVSS:3.0/AV:N/AC:L/PR:N/UI:R/S:C/C:L/I:L/A:N)

CVSS v3.0 Temporal Score

5.7 (CVSS:3.0/E:F/RL:O/RC:C)

VPR Score

5.7

EPSS Score

0.439

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.6 (CVSS2#E:F/RL:OF/RC:C)

STIG Severity

II

References

CVE	CVE-2020-11022
CVE	CVE-2020-11023
XREF	IAVB:2020-B-0030
XREF	CEA-ID:CEA-2021-0004
XREF	CEA-ID:CEA-2021-0025
XREF	CISA-KNOWN-EXPLOITED:2025/02/13

Plugin Information

Published: 2020/05/28, Modified: 2025/01/24

Plugin Output

tcp/80/www

```
URL           : http://192.168.3.140/misc/jquery.js?v=1.4.4
Installed version : 1.4.4
Fixed version   : 3.5.0
```

142591 - PHP < 7.3.24 Multiple Vulnerabilities

Synopsis

The version of PHP running on the remote web server is affected by multiple vulnerabilities.

Description

According to its self-reported version number, the version of PHP running on the remote web server is prior to 7.3.24. It is, therefore affected by multiple vulnerabilities

See Also

<https://www.php.net/ChangeLog-7.php#7.3.24>

Solution

Upgrade to PHP version 7.3.24 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

STIG Severity

I

References

XREF IAVA:2020-A-0510-S

Plugin Information

Published: 2020/11/06, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
URL      : http://192.168.3.140/ (5.4.45-0+deb7u14 under X-Powered-By:
PHP/5.4.45-0+deb7u14)
Installed version : 5.4.45-0+deb7u14
Fixed version    : 7.3.24
```

152853 - PHP < 7.3.28 Email Header Injection

Synopsis

The version of PHP running on the remote web server is affected by an email header injection vulnerability.

Description

According to its self-reported version number, the version of PHP running on the remote web server is prior to 7.3.28.

It is, therefore affected by an email header injection vulnerability, due to a failure to properly handle CR-LF sequences in header fields. An unauthenticated, remote attacker can exploit this, by inserting line feed characters into email headers, to gain full control of email header content.

See Also

<https://www.php.net/ChangeLog-7.php#7.3.28>

Solution

Upgrade to PHP version 7.3.28 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

Plugin Information

Published: 2021/08/26, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
URL           : http://192.168.3.140/ (5.4.45-0+deb7u14 under X-Powered-By:
PHP/5.4.45-0+deb7u14)
Installed version : 5.4.45-0+deb7u14
Fixed version    : 7.3.28
```

90317 - SSH Weak Algorithms Supported

Synopsis

The remote SSH server is configured to allow weak encryption algorithms or no algorithm at all.

Description

Nessus has detected that the remote SSH server is configured to use the Arcfour stream cipher or no cipher at all. RFC 4253 advises against using Arcfour due to an issue with weak keys.

See Also

<https://tools.ietf.org/html/rfc4253#section-6.3>

Solution

Contact the vendor or consult product documentation to remove the weak ciphers.

Risk Factor

Medium

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2016/04/04, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

The following weak server-to-client encryption algorithms are supported :

aes128-ctr,aes192-ctr,aes256-ctr,arcfour256,arcfour128,aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,aes192-cbc,aes256-cbc,arcfour,rijndael-cbc@lysator.liu.se

The following weak client-to-server encryption algorithms are supported :

aes128-ctr,aes192-ctr,aes256-ctr,arcfour256,arcfour128,aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,aes192-cbc,aes256-cbc,arcfour,rijndael-cbc@lysator.liu.se

121479 - web.config File Information Disclosure

Synopsis

The remote web server hosts an application that is affected by an information disclosure vulnerability.

Description

An information disclosure vulnerability exists in the remote web server due to the disclosure of the web.config file. An unauthenticated, remote attacker can exploit this, via a simple GET request, to disclose potentially sensitive configuration information.

Solution

Ensure proper restrictions are in place, or remove the web.config file if the file is not required.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2019/01/30, Modified: 2020/04/27

Plugin Output

tcp/80/www

Nessus was able to exploit the issue using the following request :

```
GET /web.config HTTP/1.1
Host: 192.168.3.140
Accept-Charset: iso-8859-1,utf-8;q=0.9,*;q=0.1
Accept-Language: en
Connection: Keep-Alive
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Pragma: no-cache
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
```

This produced the following truncated output (limited to 5 lines) :

```
----- snip -----
<?xml version="1.0" encoding="UTF-8"?>
<configuration>
```



```
<system.webServer>
<!-- Don't show directory listings for URLs which map to a directory. -->
<directoryBrowse enabled="false" />
[...]

----- snip -----
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

VPR Score

2.2

EPSS Score

0.0037

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

The difference between the local and remote clocks is -21601 seconds.

70658 - SSH Server CBC Mode Ciphers Enabled

Synopsis

The SSH server is configured to use Cipher Block Chaining.

Description

The SSH server is configured to support Cipher Block Chaining (CBC) encryption. This may allow an attacker to recover the plaintext message from the ciphertext.

Note that this plugin only checks for the options of the SSH server and does not check for vulnerable software versions.

Solution

Contact the vendor or consult product documentation to disable CBC mode cipher encryption, and enable CTR or GCM cipher mode encryption.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N)

VPR Score

1.4

EPSS Score

0.0307

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	32319
CVE	CVE-2008-5161
XREF	CERT:958563
XREF	CWE:200

Plugin Information

Published: 2013/10/28, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
The following client-to-server Cipher Block Chaining (CBC) algorithms  
are supported :
```

```
    aes128-ctr,aes192-ctr,aes256-ctr,arcfour256,arcfour128,aes128-cbc,3des-cbc,blowfish-cbc,cast128-  
cbc,aes192-cbc,aes256-cbc,arcfour,rijndael-cbc@lysator.liu.se
```

```
The following server-to-client Cipher Block Chaining (CBC) algorithms  
are supported :
```

```
    aes128-ctr,aes192-ctr,aes256-ctr,arcfour256,arcfour128,aes128-cbc,3des-cbc,blowfish-cbc,cast128-  
cbc,aes192-cbc,aes256-cbc,arcfour,rijndael-cbc@lysator.liu.se
```

153953 - SSH Weak Key Exchange Algorithms Enabled

Synopsis

The remote SSH server is configured to allow weak key exchange algorithms.

Description

The remote SSH server is configured to allow key exchange algorithms which are considered weak.

This is based on the IETF draft document Key Exchange (KEX) Method Updates and Recommendations for Secure Shell (SSH) RFC9142. Section 4 lists guidance on key exchange algorithms that SHOULD NOT and MUST NOT be enabled. This includes:

diffie-hellman-group-exchange-sha1

diffie-hellman-group1-sha1

gss-gex-sha1-*

gss-group1-sha1-*

gss-group14-sha1-*

rsa1024-sha1

Note that this plugin only checks for the options of the SSH server, and it does not check for vulnerable software versions.

See Also

<https://datatracker.ietf.org/doc/html/rfc9142>

Solution

Contact the vendor or consult product documentation to disable the weak algorithms.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2021/10/13, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

The following weak key exchange algorithms are enabled :

ecdh-sha2-nistp256,ecdh-sha2-nistp384,ecdh-sha2-nistp521,diffie-hellman-group-exchange-sha256,diffie-hellman-group-exchange-sha1,diffie-hellman-group14-sha1,diffie-hellman-group1-sha1
ecdh-sha2-nistp256,ecdh-sha2-nistp384,ecdh-sha2-nistp521,diffie-hellman-group-exchange-sha256,diffie-hellman-group-exchange-sha1,diffie-hellman-group14-sha1,diffie-hellman-group1-sha1

71049 - SSH Weak MAC Algorithms Enabled

Synopsis

The remote SSH server is configured to allow MD5 and 96-bit MAC algorithms.

Description

The remote SSH server is configured to allow either MD5 or 96-bit MAC algorithms, both of which are considered weak.

Note that this plugin only checks for the options of the SSH server, and it does not check for vulnerable software versions.

Solution

Contact the vendor or consult product documentation to disable MD5 and 96-bit MAC algorithms.

Risk Factor

Low

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2013/11/22, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
The following client-to-server Message Authentication Code (MAC) algorithms
are supported :
```

```
  hmac-md5,hmac-sha1,umac-64@openssh.com,hmac-sha2-256,hmac-sha2-256-96,hmac-sha2-512,hmac-
sha2-512-96,hmac-ripemd160,hmac-ripemd160@openssh.com,hmac-sha1-96,hmac-md5-96
```

```
The following server-to-client Message Authentication Code (MAC) algorithms
are supported :
```

```
  hmac-md5,hmac-sha1,umac-64@openssh.com,hmac-sha2-256,hmac-sha2-256-96,hmac-sha2-512,hmac-
sha2-512-96,hmac-ripemd160,hmac-ripemd160@openssh.com,hmac-sha1-96,hmac-md5-96
```


18261 - Apache Banner Linux Distribution Disclosure

Synopsis

The name of the Linux distribution running on the remote host was found in the banner of the web server.

Description

Nessus was able to extract the banner of the Apache web server and determine which Linux distribution the remote host is running.

Solution

If you do not wish to display this information, edit 'httpd.conf' and set the directive 'ServerTokens Prod' and restart Apache.

Risk Factor

None

Plugin Information

Published: 2005/05/15, Modified: 2025/03/31

Plugin Output

tcp/0

```
The Linux distribution detected was :  
- Debian 7.0 (wheezy)  
- Debian unstable (sid)  
- Debian testing (wheezy)
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
URL      : http://192.168.3.140/
Version  : 2.2.22
Source   : Server: Apache/2.2.22 (Debian)
backported : 1
os       : Debian
```

39520 - Backported Security Patch Detection (SSH)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote SSH server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/22/ssh

```
Give Nessus credentials to perform local checks.
```

39521 - Backported Security Patch Detection (WWW)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
Give Nessus credentials to perform local checks.
```

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/01/05

Plugin Output

tcp/0

Following application CPE's matched on the remote system :

```
cpe:/a:apache:http_server:2.2.22 -> Apache Software Foundation Apache HTTP Server
cpe:/a:drupal:drupal:7 -> Drupal
cpe:/a:jquery:jquery:1.4.4 -> jQuery
cpe:/a:openbsd:openssh:6.0 -> OpenBSD OpenSSH
cpe:/a:openbsd:openssh:6.0p1 -> OpenBSD OpenSSH
cpe:/a:php:php:5.4.45 -> PHP PHP
cpe:/a:php:php:5.4.45-0%2bdeb7u14 -> PHP PHP
```

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

```
Remote device type : general-purpose  
Confidence level : 95
```

18638 - Drupal Software Detection

Synopsis

A content management system is running on the remote web server.

Description

Drupal, an open source content management system written in PHP, is running on the remote web server.

See Also

<https://www.drupal.org/>

Solution

Ensure that the use of this software aligns with your organization's security and acceptable use policies.

Risk Factor

None

References

XREF IAVT:0001-T-0586

Plugin Information

Published: 2005/07/07, Modified: 2023/05/24

Plugin Output

tcp/80/www

```
URL      : http://192.168.3.140/  
Version : 7
```

35716 - Ethernet Card Manufacturer Detection

Synopsis

The manufacturer can be identified from the Ethernet OUI.

Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

See Also

<https://standards.ieee.org/faqs/regauth.html>

<http://www.nessus.org/u?794673b4>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

Plugin Output

tcp/0

```
The following card manufacturers were identified :
```

```
00:0C:29:3A:EE:0E : VMware, Inc.
```


86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

```
The following is a consolidated list of detected MAC addresses:  
- 00:0C:29:3A:EE:0E
```

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>

<http://www.nessus.org/u?b019cbdb>

[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/80/www

Based on tests of each method :

- HTTP methods ACL BASELINE-CONTROL BCOPY BDELETE BMOVE BPROPFIND
BPROPPATCH CHECKIN CHECKOUT COPY DEBUG DELETE GET HEAD INDEX
LABEL LOCK MERGE MKACTION MKCOL MKWORKSPACE MOVE NOTIFY OPTIONS
ORDERPATCH PATCH POLL POST PROPFIND PROPPATCH PUT REPORT
RPC_IN_DATA RPC_OUT_DATA SEARCH SUBSCRIBE UNCHECKOUT UNLOCK
UNSUBSCRIBE UPDATE VERSION-CONTROL X-MS-ENUMATTS are allowed on :

/

- Invalid/unknown HTTP methods are allowed on :

/

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :  
Apache/2.2.22 (Debian)
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

Date: Mon, 18 May 2026 14:12:06 GMT

Server: Apache/2.2.22 (Debian)

X-Powered-By: PHP/5.4.45-0+deb7u14

Expires: Sun, 19 Nov 1978 05:00:00 GMT

Last-Modified: Mon, 18 May 2026 14:12:06 +0000

Cache-Control: no-cache, must-revalidate, post-check=0, pre-check=0

ETag: "1779113526"

Content-Language: en

X-Generator: Drupal 7 (http://drupal.org)

Vary: Accept-Encoding

Content-Length: 7606

Keep-Alive: timeout=5, max=98

Connection: Keep-Alive

Content-Type: text/html; charset=utf-8

Response Body :

```

<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML+RDFa 1.0//EN"
  "http://www.w3.org/MarkUp/DTD/xhtml-rdfa-1.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" version="XHTML+RDFa 1.0" dir="ltr"
  xmlns:content="http://purl.org/rss/1.0/modules/content/"
  xmlns:dc="http://purl.org/dc/terms/"
  xmlns:foaf="http://xmlns.com/foaf/0.1/"
  xmlns:og="http://ogp.me/ns#"
  xmlns:rdfs="http://www.w3.org/2000/01/rdf-schema#"
  xmlns:sioc="http://rdfs.org/sioc/ns#"
  xmlns:sioc="http://rdfs.org/sioc/types#"
  xmlns:skos="http://www.w3.org/2004/02/skos/core#"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema#">

<head profile="http://www.w3.org/1999/xhtml/vocab">
  <meta http-equiv="Content-Type" content="text/html; charset=utf-8" />
<link rel="shortcut icon" href="http://192.168.3.140/misc/favicon.ico" type="image/
vnd.microsoft.icon" />
<meta name="Generator" content="Drupal 7 (http://drupal.org)" />
  <title>Welcome to Drupal Site | Drupal Site</title>
  <style type="text/css" media="all">@import url("http://192.168.3.140/modules/system/
system.base.css?pn6csl");
@import url("http://192.168.3.140/modules/system/system.menus.css?pn6csl");
@import url("http://192.168.3.140/modules/system/system.messages.css?pn6csl");
@import url("http://192.168.3.140/modules/system/system.theme.css?pn6csl");</style>
<style type="text/css" media="al [...]
```

Synopsis

This plugin detects the protocols understood by the remote IP stack.

Description

This plugin detects the protocols understood by the remote IP stack.

See Also

<http://www.iana.org/assignments/protocol-numbers/protocol-numbers.xhtml>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/09/22, Modified: 2022/08/15

Plugin Output

tcp/0

```
The following IP protocols are accepted on this host:
1ICMP
2IGMP
6TCP
17UDP
103PIM
136UDPLite
```

106658 - JQuery Detection

Synopsis

The web server on the remote host uses JQuery.

Description

Nessus was able to detect JQuery on the remote host.

See Also

<https://jquery.com/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/02/07, Modified: 2024/02/08

Plugin Output

tcp/80/www

```
URL      : http://192.168.3.140/misc/jquery.js?v=1.4.4
Version  : 1.4.4
```


19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/03/04

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.8.4
Nessus build : 20028
Plugin feed version : 202605172244
Scanner edition used : Nessus
Scanner OS : WINDOWS
Scanner distribution : win-x86-64
Scan type : Normal
Scan name : DC-1
```

```
Scan policy used : Advanced Scan
Scanner IP : 192.168.3.1
Port scanner(s) : nessus_udp_scanner nessus_syn_scanner
Port range : 65535
Ping RTT : 1.934 ms
Thorough tests : yes
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 50
Max checks : 5
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/5/18 14:00 Bangladesh Standard Time (UTC +06:00)
Scan duration : 962 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no
```

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : Linux Kernel 3.2 on Debian 7.0 (wheezy)
Confidence level : 95
Method : SSH
Type : general-purpose
Fingerprint : SSH:SSH-2.0-OpenSSH_6.0p1 Debian-4+deb7u7

Remote operating system : Linux Kernel 3.2 on Debian 7.0 (wheezy)
Debian unstable (sid)
Debian testing (wheezy)
Confidence level : 45
Method : HTTP
Type : general-purpose
Fingerprint : unknown

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 3.2 on Debian 7.0 (wheezy)
Confidence level : 95
Method : SSH
```

```
The remote host is running Linux Kernel 3.2 on Debian 7.0 (wheezy)
```

117886 - OS Security Patch Assessment Not Available

Synopsis

OS Security Patch Assessment is not available.

Description

OS Security Patch Assessment is not available on the remote host.

This does not necessarily indicate a problem with the scan.

Credentials may not have been provided, OS security patch assessment may not be supported for the target, the target may not have been identified, or another issue may have occurred that prevented OS security patch assessment from being available. See plugin output for details.

This plugin reports non-failure information impacting the availability of OS Security Patch Assessment. Failure information is reported by plugin 21745 : 'OS Security Patch Assessment failed'. If a target host is not supported for OS Security Patch Assessment, plugin 110695 : 'OS Security Patch Assessment Checks Not Supported' will report concurrently with this plugin.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0515

Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

Plugin Output

tcp/0

The following issues were reported :

```
- Plugin      : no_local_checks_credentials.nasl
  Message     :
Credentials were not provided for detected SSH service.
```

181418 - OpenSSH Detection

Synopsis

An OpenSSH-based SSH server was detected on the remote host.

Description

An OpenSSH-based SSH server was detected on the remote host.

See Also

<https://www.openssh.com/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/09/14, Modified: 2026/05/05

Plugin Output

tcp/22/ssh

```
Service      : ssh
Version      : 6.0p1
Banner       : SSH-2.0-OpenSSH_6.0p1 Debian-4+deb7u7
backported   : 1
```

48243 - PHP Version Detection

Synopsis

It was possible to obtain the version number of the remote PHP installation.

Description

Nessus was able to determine the version of PHP available on the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0936

Plugin Information

Published: 2010/08/04, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
Nessus was able to identify the following PHP version information :
```

```
Version : 5.4.45-0+deb7u14  
Source  : X-Powered-By: PHP/5.4.45-0+deb7u14  
Backported : 0
```

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2026/05/12

Plugin Output

tcp/0

```
. You need to take the following action :  
[ JQuery 1.2 < 3.5.0 Multiple XSS (136929) ]  
+ Action to take : Upgrade to JQuery version 3.5.0 or later.
```


11111 - RPC Services Enumeration

Synopsis

An ONC RPC service is running on the remote host.

Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

Plugin Output

tcp/111/rpc-portmapper

```
The following RPC services are available on TCP port 111 :
```

- program: 100000 (portmapper), version: 4
- program: 100000 (portmapper), version: 3
- program: 100000 (portmapper), version: 2

11111 - RPC Services Enumeration

Synopsis

An ONC RPC service is running on the remote host.

Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

Plugin Output

udp/111/rpc-portmapper

```
The following RPC services are available on UDP port 111 :
```

- program: 100000 (portmapper), version: 4
- program: 100000 (portmapper), version: 3
- program: 100000 (portmapper), version: 2

11111 - RPC Services Enumeration

Synopsis

An ONC RPC service is running on the remote host.

Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

Plugin Output

udp/40227/rpc-status

```
The following RPC services are available on UDP port 40227 :  
- program: 100024 (status), version: 1
```

11111 - RPC Services Enumeration

Synopsis

An ONC RPC service is running on the remote host.

Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

Plugin Output

tcp/44812/rpc-status

```
The following RPC services are available on TCP port 44812 :  
- program: 100024 (status), version: 1
```

53335 - RPC portmapper (TCP)

Synopsis

An ONC RPC portmapper is running on the remote host.

Description

The RPC portmapper is running on this port.

The portmapper allows someone to get the port number of each RPC service running on the remote host by sending either multiple lookup requests or a DUMP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/04/08, Modified: 2011/08/29

Plugin Output

tcp/111/rpc-portmapper

10223 - RPC portmapper Service Detection

Synopsis

An ONC RPC portmapper is running on the remote host.

Description

The RPC portmapper is running on this port.

The portmapper allows someone to get the port number of each RPC service running on the remote host by sending either multiple lookup requests or a DUMP request.

Solution

n/a

Risk Factor

None

CVSS v3.0 Base Score

0.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:N)

CVSS v2.0 Base Score

0.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:N)

References

CVE CVE-1999-0632

Plugin Information

Published: 1999/08/19, Modified: 2019/10/04

Plugin Output

udp/111/rpc-portmapper

277650 - Remote Services Not Using Post-Quantum Ciphers

Synopsis

Reports remote services that do not offer post-quantum ciphers.

Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

See Also

<http://www.nessus.org/u?7a390f87>

<http://www.nessus.org/u?ad7d6b3b>

<http://www.nessus.org/u?1c0c61e0>

<http://www.nessus.org/u?5eec4b28>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/22/ssh

```
The target SSH server offers no post-quantum ciphers.
```

70657 - SSH Algorithms and Languages Supported

Synopsis

An SSH server is listening on this port.

Description

This script detects which algorithms and languages are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/28, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
Nessus negotiated the following encryption algorithm(s) with the server :
```

```
Client to Server: aes256-ctr
Server to Client: aes256-ctr
```

```
The server supports the following options for compression_algorithms_server_to_client :
```

```
none
zlib@openssh.com
```

```
The server supports the following options for mac_algorithms_client_to_server :
```

```
hmac-md5
hmac-md5-96
hmac-ripemd160
hmac-ripemd160@openssh.com
hmac-sha1
hmac-sha1-96
hmac-sha2-256
hmac-sha2-256-96
hmac-sha2-512
hmac-sha2-512-96
umac-64@openssh.com
```

```
The server supports the following options for server_host_key_algorithms :
```

```
ecdsa-sha2-nistp256
ssh-dss
ssh-rsa
```


The server supports the following options for encryption_algorithms_client_to_server :

```
3des-cbc
aes128-cbc
aes128-ctr
aes192-cbc
aes192-ctr
aes256-cbc
aes256-ctr
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

The server supports the following options for mac_algorithms_server_to_client :

```
hmac-md5
hmac-md5-96
hmac-ripemd160
hmac-ripemd160@openssh.com
hmac-sha1
hmac-sha1-96
hmac-sha2-256
hmac-sha2-256-96
hmac-sha2-512
hmac-sha2-512-96
umac-64@openssh.com
```

The server supports the following options for kex_algorithms :

```
diffie-hellman-group-exchange-sha1
diffie-hellman-group-exchange-sha256
diffie-hellman-group1-sha1
diffie-hellman-group14-sha1
ecdh-sha2-nistp256
ecdh-sha2-nistp384
ecdh-sha2-nistp521
```

The server supports the following options for compression_algorithms_client_to_server :

```
none
zlib@openssh.com
```

The server supports the following options for encryption_algorithms_server_to_client :

```
3des-cbc
aes128-cbc
aes128-ctr
aes192-cbc
aes192-ctr
aes256-cbc
aes256-ctr
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

149334 - SSH Password Authentication Accepted

Synopsis

The SSH server on the remote host accepts password authentication.

Description

The SSH server on the remote host accepts password authentication.

See Also

<https://tools.ietf.org/html/rfc4252#section-8>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/05/07, Modified: 2021/05/07

Plugin Output

tcp/22/ssh

10881 - SSH Protocol Versions Supported

Synopsis

A SSH server is running on the remote host.

Description

This plugin determines the versions of the SSH protocol supported by the remote SSH daemon.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/03/06, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
The remote SSH daemon supports the following versions of the  
SSH protocol :
```

- 1.99
- 2.0

153588 - SSH SHA-1 HMAC Algorithms Enabled

Synopsis

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Description

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Although NIST has formally deprecated use of SHA-1 for digital signatures, SHA-1 is still considered secure for HMAC as the security of HMAC does not rely on the underlying hash function being resistant to collisions.

Note that this plugin only checks for the options of the remote SSH server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/09/23, Modified: 2022/04/05

Plugin Output

tcp/22/ssh

```
The following client-to-server SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :
```

```
    hmac-md5,hmac-sha1,umac-64@openssh.com,hmac-sha2-256,hmac-sha2-256-96,hmac-sha2-512,hmac-sha2-512-96,hmac-ripemd160,hmac-ripemd160@openssh.com,hmac-sha1-96,hmac-md5-96
```

```
The following server-to-client SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :
```

```
    hmac-md5,hmac-sha1,umac-64@openssh.com,hmac-sha2-256,hmac-sha2-256-96,hmac-sha2-512,hmac-sha2-512-96,hmac-ripemd160,hmac-ripemd160@openssh.com,hmac-sha1-96,hmac-md5-96
```

10267 - SSH Server Type and Version Information

Synopsis

An SSH server is listening on this port.

Description

It is possible to obtain information about the remote SSH server by sending an empty authentication request.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0933

Plugin Information

Published: 1999/10/12, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

```
SSH version : SSH-2.0-OpenSSH_6.0p1 Debian-4+deb7u7
SSH supported authentication : publickey,password
```

Synopsis

This plugin performs service detection.

Description

This plugin is a complement of find_service1.nasl. It attempts to identify common services which might have been missed because of a network problem.

Solution

See below

Risk Factor

None

Plugin Information

Published: 2004/09/17, Modified: 2011/04/01

Plugin Output

tcp/80/www

```
A web server is running on this port
```

Synopsis

Reports remote services potentially vulnerable to Shor's Algorithm.

Description

This plugin reports network services that may be vulnerable now to a future attack by adversaries using a cryptographically relevant quantum computer (CRQC). Shor's is a theoretical algorithm that leverages the unique ability of quantum computation to do massively parallel calculations developed by Peter Shor in 1994.

This algorithm easily computes two classically difficult mathematical problems used in modern cryptography; discrete logarithms, and factoring numbers formed by multiplying large primes. Shor's reduces both of these problems from taking exponential time in chosen cases to being solvable in polynomial time.

Asymmetric encryption algorithms such as RSA, Diffie-Hellman and Elliptic Curve Diffie-Hellman are impacted by Shor's Algorithm. The most common uses of these algorithms are in symmetric key establishment and authentication. These uses render Shor's Algorithm particularly dangerous because it may give an adversary the ability to harvest network communications now, and in the future, when a CRQC becomes available, extract the symmetric key and decrypt the communication.

See Also

<http://www.nessus.org/u?54fba2c1>

Solution

Replace affected ciphers with algorithms chosen to resist CRQC attack.

Risk Factor

None


Plugin Information

Published: 2026/02/09, Modified: 2026/04/13

Plugin Output

tcp/0

```
The SSH service on port 22 offers these ciphers vulnerable to Shor's:
diffie-hellman-group-exchange-sha256
ecdh-sha2-nistp256
ecdh-sha2-nistp521
ecdh-sha2-nistp384
diffie-hellman-group-exchange-sha1
diffie-hellman-group1-sha1
diffie-hellman-group14-sha1
```



277652 - Target Cipher Inventory

Synopsis

Reports the ciphers and algorithms discovered during the scan.

Description

This plugin collects cryptographic ciphers and algorithms discovered during the scan as a machine parsable JSON file attachment.

See Also

<http://www.nessus.org/u?7a390f87>

<http://www.nessus.org/u?ad7d6b3b>

<http://www.nessus.org/u?1c0c61e0>

<http://www.nessus.org/u?5eec4b28>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2026/04/13

Plugin Output

tcp/0

```
[
  {
    "ports": [
      {
        "ciphers": [
          {
            "name": "diffie-hellman-group-exchange-sha256",
            "type": "key exchange"
          },
          {
            "name": "ecdh-sha2-nistp256",
            "type": "key exchange"
          },
          {
            "name": "ecdh-sha2-nistp521",
            "type": "key exchange"
          },
          {
            "name": "ecdh-sha2-nistp384",
```

```

    "type": "key exchange"
  },
  {
    "name": "diffie-hellman-group-exchange-sha1",
    "type": "key exchange"
  },
  {
    "name": "diffie-hellman-group1-sha1",
    "type": "key exchange"
  },
  {
    "name": "diffie-hellman-group14-sha1",
    "type": "key exchange"
  },
  {
    "name": "ssh-rsa",
    "type": "host auth"
  },
  {
    "name": "ecdsa-sha2-nistp256",
    "type": "host auth"
  },
  {
    "name": "ssh-dss",
    "type": "host auth"
  },
  {
    "name": "aes192-ctr",
    "type": "encryption"
  },
  {
    "name": "rijndael-cbc@lysator.liu.se",
    "type": "encryption"
  },
  {
    "name": "aes256-ctr",
    "type": "encryption"
  },
  {
    "name": "aes128-cbc",
    "type": "encryption"
  },
  {
    "name": "aes256-cbc",
    "type": "encryption"
  },
  {
    "name": "blowfish-cbc",
    "type": "encryption"
  },
  {
    "name": "cast128-cbc",
    "type": "encryption"
  },
  {
    "name": "arcfour128",
    "type": "encryption"
  },
  {
    "name": "aes192-cbc",
    "type": "encryption"
  },
  {
    "name": "aes128-ctr",
    "type": "encryption"
  },
  {
    [...]
  }

```

110723 - Target Credential Status by Authentication Protocol - No Credentials Provided

Synopsis

Nessus was able to find common ports used for local checks, however, no credentials were provided in the scan policy.

Description

Nessus was not able to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials. There may have been a protocol failure that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may be invalid. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.
- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0504

Plugin Information

Published: 2018/06/27, Modified: 2024/04/19

Plugin Output

tcp/0

```
SSH was detected on port 22 but no credentials were provided.  
SSH local checks were not enabled.
```


10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 192.168.3.1 to 192.168.3.140 :
192.168.3.1
192.168.3.140

Hop Count: 1
```

20094 - VMware Virtual Machine Detection

Synopsis

The remote host is a VMware virtual machine.

Description

According to the MAC address of its network adapter, the remote host is a VMware virtual machine.

Solution

Since it is physically accessible through the network, ensure that its configuration matches your organization's security policy.

Risk Factor

None

Plugin Information

Published: 2005/10/27, Modified: 2019/12/11

Plugin Output

tcp/0

```
The remote host is a VMware virtual machine.
```

Synopsis

The remote web server contains a 'robots.txt' file.

Description

The remote host contains a file named 'robots.txt' that is intended to prevent web 'robots' from visiting certain directories in a website for maintenance or indexing purposes. A malicious user may also be able to use the contents of this file to learn of sensitive documents or directories on the affected site and either retrieve them directly or target them for other attacks.

See Also

<http://www.robotstxt.org/orig.html>

Solution

Review the contents of the site's robots.txt file, use Robots META tags instead of entries in the robots.txt file, and/or adjust the web server's access controls to limit access to sensitive material.

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2026/03/10

Plugin Output

tcp/80/www

```
Contents of robots.txt :
```

```
#
# robots.txt
#
# This file is to prevent the crawling and indexing of certain parts
# of your site by web crawlers and spiders run by sites like Yahoo!
# and Google. By telling these "robots" where not to go on your site,
# you save bandwidth and server resources.
#
# This file will be ignored unless it is at the root of your host:
# Used:      http://example.com/robots.txt
# Ignored:   http://example.com/site/robots.txt
#
# For more information about the robots.txt standard, see:
# http://www.robotstxt.org/wc/robots.html
#
# For syntax checking, see:
# http://www.sxw.org.uk/computing/robots/check.html
```

```
User-agent: *
Crawl-delay: 10
# Directories
Disallow: /includes/
Disallow: /misc/
Disallow: /modules/
Disallow: /profiles/
Disallow: /scripts/
Disallow: /themes/
# Files
Disallow: /CHANGELOG.txt
Disallow: /cron.php
Disallow: /INSTALL.mysql.txt
Disallow: /INSTALL.pgsql.txt
Disallow: /INSTALL.sqlite.txt
Disallow: /install.php
Disallow: /INSTALL.txt
Disallow: /LICENSE.txt
Disallow: /MAINTAINERS.txt
Disallow: /update.php
Disallow: /UPGRADE.txt
Disallow: /xmlrpc.php
# Paths (clean URLs)
Disallow: /admin/
Disallow: /comment/reply/
Disallow: /filter/tips/
Disallow: /node/add/
Disallow: /search/
Disallow: /user/register/
Disallow: /user/password/
Disallow: /user/login/
Disallow: /user/logout/
# Paths (no clean URLs)
Disallow: /?q=admin/
Disallow: /?q=comment/reply/
Disallow: /?q=filter/tips/
Disallow: /?q=node/add/
Disallow: /?q=search/
Disallow: /?q=user/password/
Disallow: /?q=user/register/
Disallow: /?q=user/login/
Disallow: /?q=user/logout/
```


Compliance 'FAILED'

Compliance 'SKIPPED'

Compliance 'PASSED'

Compliance 'INFO', 'WARNING', 'ERROR'

Remediations

Suggested Remediations

For Trial Use Only