Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

Chapter 10
BioCrypt:
A Bioinformatics-Driven Approach to Secure Cloud Computing

Shahnawaz Ahmad
Bennett University, India

Mohd Aquib Ansari
https://orcid.org/0000-0002-9083-1523
Galgotias University, India

Arvind Mewada
Bennett University, India

Raju Raju
Noida Institute of Engineering and Technology, India

Sachin Upadhyay
GLA University, India

ABSTRACT

In response to the growing limitations of traditional encryption techniques within the cloud, this chapter presents a new framework named BioCrypt. Biocrypt applies bioinformatics and molecular biology concepts to the development of cryptography. BioCrypt tackles such issues through advanced DNA encoding and biologically inspired approaches to deliver a highly resistant, high-entropy encryption solution that is difficult to breach. The BioCrypt framework consists of a multi-tiered architecture with a security layer, DNA engine, and data storage module. Here, the plain text is converted to binary, and then following pre-determined rituals to bind them into DNA spells, they are permuted with a key and undergo simulated DNA

DOI: 10.4018/979-8-3373-7503-8.ch010

Copyright © 2026, IGI Global Scientific Publishing. Copying or distributing in print or electronic forms without written permission of IGI Global Scientific Publishing is prohibited. Use of this chapter to train generative artificial intelligence (AI) technologies is expressly prohibited. The publisher reserves all rights to license its use for generative AI training and machine learning model development.

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

hybridization and Watson and Crick complementing. The development also employs biologically based control over keys and multi-factor authentication, which greatly complicates access to the system without proper authorization. The BioCrypt system exhibits strong resistance against brute force, replay, and chosen-plaintext attacks.

INTRODUCTION

The past decade has seen rapid technological adoption across sectors like healthcare, finance, defence, and government services, leading to a worldwide shift to cloud-based infrastructure. Ensuring maximum confidentiality and integrity has become increasingly complex with the rapid advancement of cloud storage, data mobility, and multi-user access. The ever-expanding digital landscape is supported by information technology frameworks such as RSA, AES, and DES, which have dominated the construction and securing of digital communication systems (Dhankhar, 2025). Unfortunately, these framework units rely on complex mathematics and Computation, which is firmly deterministic. These attributes, once advantageous, make algorithms weak against emerging vulnerabilities from adversarial forces, quantum computing, and other emerging technologies. Compounding this issue, the predominantly used method of encryption is evasive and highly inefficient, making it nearly impossible to implement biologically inspired decentralized computational models, necessitating the search for unorthodox solutions.

With biological computing, an intriguing alternative to decentralized computation models is found, especially in the case of DNA computing (Garima Mathur (Sagar Institute of Science and Technology, 2025). After Leonard Adleman's astonishing demonstration of solving the Hamiltonian path problem with DNA strands in 1994, researchers have actively pursued using DNA for Computation and secure information storage (Adleman, 1994). The study focuses on BioCrypt, a new biologically inspired encryption framework, and attempts to prove its practicality. With the help of information technologies, biological operations are executed faster and more efficiently using computers. For example, precision medicine displays biological sequences such as DNA or RNA and synthesizes them to create precise biological structures. According to the proposed BioCrypt principles, a message is encoded using a unique sequence of DNA bases alongside certain numbers representing binary data. The DNA molecule is synthesized alongside the binary data needed for encryption. Subsequently, the encoded data can only be retrieved through decoding. Currently, precise structure synthesis devices have both experimental and practical value. These devices can design a physical sequence to represent the structure's biological sequence, leading to the construction of multiple DNA molecules. Such devices enable the creation of DNA molecules on a user-defined basis using standard

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

single-stranded sequences, proving their great potential for practical application. Since it is confirmed that DNA can be formed into various structures, the next step is to assemble the distinct molecules while introducing them to organic solvents and enabling them to self-organize into system structures using nanotechnology. Once assembled, amyloid structures can form DNA-based nanomachines that can be preserved without solvents.

The significance of these technological advances is the ability to create a distinct canopy, which can be deployed in vivo to target specific cells, tissues, or organs and guide them with inflorescent molecules. These technological advances can help design specialized devices that can enhance the capabilities of in-vivo cell imaging.

The intricate structure of DNA is combined with cryptography to create encryption algorithms in BioCrypt. The data stored cryptographically in BioCrypt is multi-layered, highly entropy-secured, and tamper-resistant, and it can be accessed without compromising security. BioCrypt translates plain text into binary form and encodes DNA sequences using a set of defined encoding rules. These sequences are mixed and encrypted using logic dependent on the keys, and then, through Watson-Crick complementarities and simulated DNA hybridization, further processes are applied. The encrypted DNA data is preserved digitally and can be kept physically in DNA storage devices. The system uses preset authentication tags and bound checksums to maintain integrity and traceability. By creating simulated biological processes on hardware and software, BioCrypt permits the design of traditional and cloud environment-compatible biologically inspired cryptography frameworks. BioCrypt adapting DNA encoding in cryptographic data renders it especially unique in ultra-secure storage scenarios. The compact storage requirements of genomic research and the long-term stability of intelligence databases and patient medical records make BioCrypt especially useful.

Besides, the system enables hybrid cloud and edge deployments where nodes can be distributed while retaining strength in security and scalability. Also, the framework shows great resilience against multiple cryptanalytic attacks, surpassing many traditional systems in terms of the entropy and avalanche effect. In conclusion, this chapter discusses BioCrypt as a futuristic encryption solution that exploits molecular biology concepts to address the constraints of traditional encryption methods. BioCrypt becomes a secure, scalable, and biologically adaptive encryption model through DNA encoding, complementary pairing, and hybridization within a unifying system. The rest of this chapter discusses BioCrypt architecture, DNA cryptographic techniques, system implementation, performance evaluation, and possible real-life use cases.

The chapters are organized as follows: Section 2 focuses on the existing literature and compares DNA cryptography with its predecessors. Section 3 focuses on the BioCrypt architecture and its components at different levels. Section 4 discusses

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

core cryptographic techniques, including encoding, hybridization, and Watson-Crick pairing through DNA. Security Analysis of DNA P-Box is given in section 5. Section 6 describes the implementation of the BioCrypt framework, including pseudocode and a cloud encryption case study. Section 7 analyzes the framework's security features. Section 8 evaluates performance metrics like entropy, avalanche effect, and cloud scalability. Section 9 discusses key application domains. Section 10 identifies challenges and limitations, while Section 11 concludes with the study's final insights.

RELATED WORK

Cryptography, at its core, is the discipline concerned with securing information by converting it into a form that prevents unauthorized access. This transformation ensures that sensitive data remains protected from internal breaches and external attacks, thereby maintaining its confidentiality, integrity, authenticity, and non-repudiation. Fundamentally, cryptographic systems rely on transforming plaintext, i.e., the original, readable data, into ciphertext, which is the encrypted version unintelligible to unauthorized parties. Decryption reverses this process to recover the original message (Chandra, Paira, et al., 2014). With the growing prevalence of internet-based services, cybercrime rates are rapidly increasing. Cloud computing (CC), due to its centralized and data-intensive architecture, has become a prime target for cybercriminals. Thus, protecting the integrity and confidentiality of cloud services has created a need to secure cloud environments properly. Data can be safeguarded during transmission and storage across networks through encryption technologies. Key security objectives in such systems include authentication, confidentiality, integrity, reliability, and non-repudiation. Authentication guarantees the identities of the parties communicating. Due to confidentiality, authorized users are the only ones who can read the message. Integrity guarantees that the data has not changed, while reliability guarantees that the service will be provided consistently. Non-repudiation ensures that a person cannot deny having sent or received the document(Sullivan, 2014; Thabit et al., 2022; Zissis & Lekkas, 2012). Regularly storing and outsourcing data in cloud systems makes cryptography the most important tool for enabling secure communication. Getting accurate security for processing and storing data on cloud platforms has become increasingly difficult due to the ever-changing nature of the systems. Encryption fills the security gaps and maintains trust within digital systems.

Modern cryptographic systems typically employ symmetric or asymmetric encryption techniques to secure sensitive data. Symmetric encryption applies one secret key to encrypt and decrypt data, whereas asymmetric encryption applies a

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

pair of keys: a public key for encryption and a private key for decryption (Arora & Hussain, 2018; Chandra, Bhattacharyya, et al., 2014). Moreover, hybrid encryption methods utilize symmetric and asymmetric techniques to maximise the former's efficiency and secure key exchange. These developments continue to drive innovations in cryptographic algorithms, motivating researchers to design advanced models to protect data in the cloud in a secure, scalable, and efficient manner.

Table 1. Comparative Analysis of Traditional vs. DNA-based Cryptography

Parameter	Traditional Cryptography	DNA Cryptography
Medium of Storage	Stored electronically or in digital formats	Encoded and stored as DNA sequences
Encoding Basis	Uses mathematical algorithms and operations	Uses DNA nucleotide bases (A, T, G, C) for encoding
Key Size	Smaller key size	Key size varies significantly depending on input
Mathematical Expressions	Involves numerous mathematical expressions	Mathematical expressions are absent
Cryptographic Strength	Strength depends on complex and multiple encryption rounds	Varies with type, size, and randomness of key
Computational Complexity	Elevated due to Feistel cipher and complex operations	Complexity arises from comparison, shifting, and scanning processes
Memory	Requires less memory	Requires more memory for storing key and performing related operations
Cost	Lower cost	Higher cost
Existing Period	Actively used and anticipated to persist	Has potential for long-term use, but still in early/practice stages
Security	Comparatively lower	Higher security potential

Table 1 outlines the comparative study of traditional and DNA-based cryptography by illustrating the differences based on ten parameters. In the case of Traditional Cryptography (TC), the value of a key is low as it is fundamentally based on stored data algorithms, which mathematically translates to less memory being utilized. Cost, in turn, is lower, but security is also weaker, balanced by higher complexity due to many encryption rounds hired. On the other hand, DNA cryptography (DC) uses the biochemical components of DNA and its bases to encode and store information. While IT offers better value in security, key Computation, and offered storage, cost, memory consumption, and the amount of Computation required (while working with DNA instead of numbers) creates serious limitations due to the state of the technology and the promises offered.

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

DNA Cryptography

DNA Cryptography is still young, as it blends molecular biology and computer science, resulting in innovative data encryption and protection techniques. This technology makes it possible to encode data using DNA data sequences because deoxyribonucleic acid (DNA) has potent abilities to store information in a highly compact and power-efficient way. These sequences are composed of four nucleotide bases: adenine (A), thymine (T), cytosine (C), and guanine (G). Unlike conventional cryptographic techniques, which require extensive power and memory, DNA-based cryptographic systems conduct computations efficiently and data storage is astonishingly compact. For example, a standard storage medium requires about 10^12 nm^3 to store some information, while DNA achieves approximately 1-bit/nm^3. Remarkably, one gram of DNA can store up to 10^21 bases or around 108 terabytes, meaning all digital information worldwide could be stored in a few milligrams of DNA (Mahjabin et al., 2023). The fundamental principle of DNA cryptography differs from other digital forms. While traditional cryptography relies on sophisticated mathematical algorithms and intricate digital hardware, DNA cryptography employs biological methods along with molecular techniques. This results in key sizes, the strength of the cryptosystem, complexity of computations, and distinct expenses. DNA-based systems offer variable key sizes, as seen in Table 1, resulting in greater cryptographic strength and complexity. Even though traditional cryptographic models have undergone significant development and deployment, DNA cryptography remains in early development, where researchers investigate adapting existing methods for DNA sequences. These activities involve comprehension of natural DNA's life properties, artificial sequence synthesis (pseudo-DNA), and information-hiding techniques like steganography within the structure of DNA. Three major subfields are developing under DNA cryptography: Natural-DNA cryptography, Pseudo-DNA cryptography, and DNA Steganography. In Natural-DNA cryptography, actual DNA sequences are utilized as keys for encoding messages.

Because of DNA's distinctiveness and variability, there exists a promising chance of security and privacy, but this approach is coupled with limitations concerning storage capacity and scalability. Its space and time computational requirements are typically linear. Conversely, pseudo-DNA cryptography refers to synthetic, DNA-like structures created in laboratory environments. Such structures can be engineered for uses that translate to better scalability and adaptability, albeit often at the cost of security. The complexity of pseudo-DNA cryptography scales with O (n log n) time and O(n) space. As the name suggests, DNA steganography adds another dimension of secrecy by concealing encrypted information within the DNA structure without disrupting its biological functions. This renders it highly efficient for the covert transmission of information. The complexity of these strategies

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

might differ greatly with the specific encoding and decoding processes utilized. Steganography, for instance, enables data concealment with a remarkable capacity for hidden information, but accurate and efficient data retrieval can be problematic. Newer methods include binary gel image subtraction techniques (Leier et al., 2000), symmetric-key XOR-substitution methods (Hazra et al., 2018), and systems that use genetic algorithms for key generation alongside deep learning frameworks based on DNA (Kalsi et al., 2018). Other sophisticated approaches include dynamic key tables, Shamir secret sharing for distributed key management, and hybrid models that integrate DNA steganography with classical cryptographic techniques for cloud based IoT systems (Namasudra, 2022). Continuing research further demonstrates the real-life applicability of DNA cryptography. For instance, Al-Mahdi et al. (2019) developed a hybrid encryption scheme composed of dynamic round keys and asymmetric systems, while Sohal & Sharma (2022) advanced a novel BDNA (Biological DNA-based Encryption) based secure access control framework for client-side data upload and file control with client-side DNA cryptography. Multiple models, integrating various forms of encryption with DNA parallelism, randomness, and exquisite storage abilities significantly enhance information security, as highlighted in Table 2. DNA cryptography development could help ensure data is maintained safely and correctly, especially in things such as cloud computing, a field called bioinformatics and secure messaging.

Table 2. Summary of a few DNA cryptographic methods

Paper	Algorithm used	Cryptographic method	Technique used
Paspula, (2017)	DNA-based traditional algorithm	Symmetric	Digital coding of DNA is a remarkable scientific advancement
Zhang et al., (2017)	DNA Cryptography	Symmetric	Approach for a block cipher and Hamming code
Tiwari & Kim (2018)	ECC based on DNA for IoT devices	Asymmetric	DNA Elliptic curve cryptography (ECC)
Abd El-Latif & Moussa (2019)	Synthetic DNA sequences generated by the Gaussian kernel function (GKF)	Symmetric	ECC, and GKF encryption
Tornea (2013)	Security and Complexity of DNA Based Cipher	Symmetric	DNA Indexing, one-time pad
Pramanik (2012)	DNA Encryption	Symmetric	Hybridization, one-time pad
Sajisha & Mathew (2017)	Genetic-based AES	Symmetric	DNA encoding, DNA steganography

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

DNA Cryptography

Today, as society is dealing with ever-increasing amounts of data, there are significant new hurdles, especially because traditional electronic computing faces great challenges with NP-complete problems. These problems are known to be extremely difficult to solve using classical computing systems due to their exponentially increasing input sizes. Addressing these computational 'bottlenecks' to advance societal progress and technology has become paramount. One such area is DNA computing, a new and innovative form of computing that uses biological molecules for parallel processing. Since Leonard Adleman used DNA strands to solve a 7-node Hamiltonian path problem in 1994, this biological approach has been gaining traction (Adleman, 1994). DNA computing utilizes biochemical processes like enzymatic reactions and PCR (Polymerase Chain Reaction) amplification to perform calculations, effectively changing HIV into a piece of DNA information.

After the initial demonstration by Adleman, researchers have applied DNA computing models to a wide spectrum of NP-complete problems. Some of these problems include the Boolean satisfiability problem (SAT) (Braich et al., 2002; W. Liu et al., 2003), the travelling salesperson problem (TSP) (Zimmermann, 2002), and graph coloring problems (Xu et al., 2018). In addition to combinatorial optimization, DNA computing has also been used in cryptography (Zhu et al., 2022) and logic circuit design (C. Liu et al., 2020; Wang & Bi, 2018), proving the versatility of this technology. The distinguishing feature of DNA computing is the ability to process large amounts of data simultaneously, which vastly outperforms traditional serial Computation. However, alongside these advancements, DNA computing offers limitations. The presence of biochemical shortcomings stifles its practical application, such as with PCR, which has an average amplification efficiency of only 90%. Enzymatic operations are known to fluctuate in efficiency from 80% to 95%. Such errors can compromise the results and the dependability of the Computation.

DNA hybridization, which provides the basis for binding strands, tends to include both specific and non-specific interactions. Sometimes, mismatches between DNA pieces create unwanted structures that change the design, and these structures can affect the reliability of calculations. Because of this, DNA computing cannot always solve a wide range of problems or be dependable. So far, the highest number of vertices this method has handled in a graph is 61 for 3-coloring (Xu et al., 2018). This underlines the pressing need for DNA sequence design improvements to enable DNA computing scaling to more complex. In essence, the efficiency and effectiveness of DNA computation hinge on the quality of the DNA code used to represent data and operations.

Designing robust DNA codes is a multidimensional challenge. These codes must exhibit high specificity to minimize unintended hybridizations, maintain consistent

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

melting temperatures, and ensure structural stability under biochemical conditions. Poorly designed sequences can lead to computation failures, reducing both efficiency and accuracy. Therefore, DNA code generation is critical to individual computational outcomes and central to the broader goal of making DNA computing viable for real-world applications. Parameters such as melting temperature (Tm), binding specificity, stability, and resource efficiency can be jointly optimized here. Each constraint adds a layer of complexity and balancing them is a non-trivial task.

The DNA coding problem itself represents a difficult combinatorial optimization challenge. Given the vast number of potential DNA sequences (with the solution space expanding as 4n4^n4n for sequences of length n), identifying suitable candidates is computationally intensive. This problem has been formally classified as NP-complete (Chaves-González & Vega-Rodríguez, 2014). Imposing too few design constraints may result in suboptimal or unstable sequences while enforcing too many can overly restrict the search space, rendering optimization intractable. Further complicating matters, many constraints, such as hybridization energy and sequence dissimilarity, are inherently conflicting. Consequently, designing high-quality DNA sequences necessitates sophisticated multiobjective optimization strategies. Progress in this field is critical not only to the future of DNA computing but also to its application in emerging areas such as data storage, secure communication, and molecular diagnostics.

BIOCRYPT ARCHITECTURE AND DESIGN PRINCIPLES

The BioCrypt system is an innovative cryptographic architecture that integrates biological Computation, specifically DNA-based techniques, with modern digital security protocols. This hybrid model combines the unique properties of DNA molecules, such as their massive parallelism, data density, and biochemical stability, with the structural robustness of conventional cryptographic algorithms. The architecture is designed to offer enhanced security in data storage, transmission, and authentication, particularly in environments that demand ultra-secure systems, such as defence, healthcare, and cloud-based Internet of Things (IoT) frameworks.

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

Figure 1. BioCrypt Architecture and Design Principles




Figure 1 shows that the system contains a User Interface, Security Layer, DNA Engine and Storage Module. At the user interface, the input given by users is captured and sent to the security layer for key generation, encryption and authentication. Encrypted information is converted into DNA by the DNA engine through encoding algorithms, and it also takes care of managing how the DNA sequences are built. Sequences are kept safe in the storage module or quickly accessed as needed. Modules help in design; all data is kept safe, and transferring between encryption and biological methods happens easily for better security.

The main idea behind BioCrypt is to use computer strategies that turn digital data into biologically relevant sequences. Next, they are turned into DNA sequences using either synthetic development or existing coding methods. Shifting between binary and DNA data is done with strict rules to find and eliminate dangers from sequence errors, mixing different sequences and damage to the data. All the elements in the architecture, such as encoding modules, key management layers and monitoring components, are exchangeable so that the cypher can adapt to many environments.

Data Flow and Security Layers

The BioCrypt system exhibits a unique, secure and efficient bio-system architecture that maintains strict control over data flow. In the first stage, the raw data is sliced into pieces, encoded into binary, and subsequently mapped into DNA nucleotides (A, T, C, G). After this step, the data undergoes cryptographic alteration, which includes permutation, substitution, or XOR mixing before being stored or

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

sent. These layers are resistant to a defined range of cryptanalysis attacks, such as brute force, statistical analysis, and even chosen-ciphertext attacks.

The architecture that the system is built on works to improve functionality at higher-risk settings while simultaneously increasing security, which is defined as multi-layered security stages. The first layer zeros in on maintaining data integrity and confidentiality by employing DNA transformations and sequence obfuscation. The second layer tackles the authentication and access control stage, where behavioural tokens alongside biometric identifiers are fused with DNA-based tokens and algorithms to validate whether the user can access the system. The last layer focuses on making the system tamper-resistant as it uses molecular watermarking and error-correcting codes to restore and identify unintentional changes made to the DNA sequences. The system is designed in layers to ensure redundancy and increased resilience in extreme conditions where risks are high.

DNA Sequence Generation and Encoding Methods

A very important task for BioCrypt is creating reliable and secure DNA sequences that can encode digital information. The sequence generation process has several design constraints, including GC content, hamming distance, limits on homopolymer run length, and melting temperature uniformity. These constraints guarantee that the application or synthesis of the sequences has low secondary structure, low ambiguity, and good biochemical consistency. ADNA codes are made for specific security applications using advanced techniques such as Genetic Algorithms (GA), Particle Swarm Optimization (PSO), and Machine Learning (ML) based sequence prediction to create large libraries of robust DNA codes. In BioCrypt, encoding techniques work consistently by directly mapping binary information to DNA watches through translating the number of bits into nucleotides. Two common methods are 2-bit and 4-bit binary, with ‘00’ mapping to A, ‘01’ to T, ‘10’ to C, ‘11’ to G. A more sophisticated form of the encoding adds contextual factors which could change the sequence patterns used based on prior history, so motifs and palindromic structures can be avoided. Besides that, methods such as using keys for randomizing and following special rules to alter messages are also used to strengthen the protection. The result is stronger encryption and makes it so encrypted data is hidden within parts of DNA that look useless to detectors.

Key Management and Authentication

Management of keys within the BioCrypt system is unlike anything encountered in symmetric or asymmetric cryptographic systems. BioCrypt doesn't only use numeric keys; BioCrypt uses keys in the form of DNA. These keys, which are

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

used during both encryption and decryption processes, come in the form of short, specially designed DNA sequences. Such keys may be static - meaning pre-defined - or context-aware algorithms can create dynamic ones in real-time based on user biometrics, timestamps, or other environmental clues. Each DNA key is unique and can't be replaced without the encoding algorithm because they come pre-embedded with molecular signatures, which act as prevention for integrity verification. Authentication methods are further inspired by biology. A multi-factor authentication mechanism is established using DNA keys alongside biometrics such as fingerprints, retina scans, and other behavior data like typing patterns. Moreover, access control can be fortified through identity verification reliant on specific DNA pattern prompts, which are referred to as sequence-based challenges. In addition to the above-stated methods, the DNA keys can be securely shared using Shamir's Secret Sharing or Threshold Cryptography, which divides the key into several pieces that are spread out over several nodes or agents. Single-handedly possessing one piece does not allow tare construction of the key that can be deemed original. All this makes BioCrypt a leading solution that offers strong security by applying bio and cryptology advances.

DNA TECHNIQUES IN CRYPTOGRAPHIC DESIGN

DNA is used in cryptography to copy the safe features seen in traditional cryptographic solutions using basic biochemical operations. DNA Encoding/Decoding, Watson-Crick Complementarity and DNA Hybridization support the main functions of advanced DNA cryptosystems like the DNA P-Box. They are reliable biologically and fit well with traditional cryptographic building blocks such as substitution-permutation networks (SPNs). DNA cryptography suffers fewer drawbacks and stays flexible when ORJSON is part of the DNA sequence, which is ideal for building safe and scalable DNA encryption schemes (Mahjabin et al., 2023).

DNA Encoding and Decoding Mechanisms

DNA encoding means taking a digital code and making it into DNA, and decoding is the opposite way. Using set encoding rules, the two-bit pairs are matched to specific nucleotide bases (A, T, C or G). Every DNA encoding/decoding scheme uses a different way to match binary values and the bases in DNA. These mappings form the base for changing data in DNA cryptographic systems (Alrubaie et al., 2023). As an illustration, Rule 1, which is applied a lot in research, associates code 00 with Cytosine (C), 01 with Thymine (T), 10 with Adenine (A) and 11 with Guanine (G). Converting into nucleotides protects the code and enables it to be read

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

back to its original form. Since multiple rules are flexible, they help ensure key diversity and security against brute-force encryption attacks, which is why DNA data security relies on them.

Table 3. DNA Encoding/Decoding Rules

Rule No.	00	01	10	11
Rule 1	C	T	A	G
Rule 2	C	A	T	G
Rule 3	G	T	A	C
Rule 4	G	A	T	C
Rule 5	T	C	G	A
Rule 6	T	G	C	A
Rule 7	A	C	G	T
Rule 8	A	G	C	T

Table 3 outlines eight rules that allow one to create DNA nucleotide sequences from binary sequences. The mapping in each rule links a two-bit binary input ('0' or '1' in all combinations) to just one base (A, C, G, T) for '0' and to three nucleotides for '1'.

Watson-Crick Complementary Rules

In DNA, Watson-Crick complementarity means that Adenine (A) matches with Thymine (T) and Guanine (G) with Cytosine (C). Although there are 24 possible base sequence permutations for a 4-base DNA strand (4!), only eight of these combinations satisfy the Watson-Crick base-pairing criteria, making them viable for cryptographic use (Xu et al., 2018). These combinations are categorized into two groups—one focusing on the A–T pair (e.g., CTAG, GTAC) and the other on the G–C pair (e.g., TGCA, AGCT) (Alrubaie et al., 2023). In DNA cryptography, these valid combinations are strategically employed to maintain structural integrity during encryption and decryption. Their inherent biological specificity helps prevent unauthorized decoding, thus boosting cryptographic resilience.

DNA Hybridization Process

DNA hybridization, also known as annealing, involves merging two complementary single-stranded DNA (ssDNA) molecules to form a stable double-stranded DNA (dsDNA) structure. This process adheres strictly to Watson-Crick rules and

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

mirrors the biological formation of the DNA double helix, as discovered by Watson, Crick, Franklin, and Wilkins in 1953 (Zhu et al., 2022). While one part of DNA (called the sense strand) runs from 5' to 3', the opposite antisense strand runs 3' to 5', giving the DNA an antiparallel form. Putting these parts together looks like a twisted ladder, where the nitrogenous bases become the rungs and the sugar-phosphate backbones are along the sides. In this type of cryptography, hybridization helps make data encoding dependable so that the original strand can be extended by adding the complementary strand at the end. Performing this operation strengthens the encoding and plays a vital part in the secure transmission of data.

SECURITY ANALYSIS OF DNA P-BOX

Due to precision constraints, the avalanche effect (also called the avalanche criterion), if often tested in cryptography, modifying the input in the form of plaintext, the key, or the initialization vectors, results in a drastically altered ciphertext (Bansod et al., 2016). For a strong cryptosystem, the ideal value is 50%, which indicates that a single bit change in the input or key alters roughly half of the output bits completely randomly. This level of sensitivity would protect the system from attackers inferring the input or the key from the ciphertext. In the case of a newly developed DNA permutation box, it was necessary to estimate its non-linearity and avalanche effect. Hence, these three analyses were performed: Correlation Coefficient analysis, Bit Error, and Key Sensitivity testing.

Correlation Coefficient

The correlation coefficient (rpp) is employed in cryptography as a measure for the relationship between input (which is a plaintext or key) and output (under the form of the ciphertext), and in the case, rpp is outputted as ¬0, there is interaction within the algorithm (Bansod, 2016). As defined by Equation (1) (Zakaria et al., 2020), where E represents the avalanche effect, pi is the ith plaintext bit, and ci is the ith ciphertext bit:

$$r_{pp} = \frac{\sum_{i=1}^{s} (P_i - E)\ (C_i - E)}{\sqrt{\sum_{i=1}^{s} (P_i - E)^2 \sum_{i=1}^{s} (C_i - E)^2}} \tag{1}$$

This value is always between +1 and -1. If rpp has a lower absolute value, the encryption algorithm is secure and can cause more significant effects to an avalanche attack. Thanks to this metric, cryptographers can assess the cryptography's

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

durability against these attacks, making data more secure. Table 5 lists the steps to interpreting rpp values.

Bit Error Rate

The Bit Error Rate (BER) is a way to measure the fraction of changed output bits in a ciphertext that results from a modification in the original plaintext (Li et al., 2018). Digital communication often uses a BER of 50%, so that the algorithm changes half the bits in the plaintext. Equation (2) (Kubba & Hoomod, 2020) shows how to calculate BER (Kubba & Hoomod, 2020).

$$BER = \frac{\text{Total number of ciphertext bits}}{\text{Number of ciphertext bits differentiated}} \tag{2}$$

Table 5. Correlation Matrix

Condition	Result
rpp=0	Non-linear relationship
$0<rpp\leq 0.3$ or $-0.3<rpp\leq 0$	Weak positive/negative linear relationship
$0.3<rpp\leq 0.7$ or $-0.7<rpp\leq -0.3$	Moderate positive/negative linear relationship
$0.7<rpp\leq 1$ or $-1<rpp\leq -0.7$	Strong positive/negative linear relationship
rpp=1 or rpp=−1	Perfect positive/negative linear relationship

Key Sensitivity

The Key Sensitivity Test is a critical validation step in cryptographic analysis. It ensures that an algorithm is highly responsive to even minor changes in its encryption key, thereby bolstering its resistance against various cryptanalytic attacks (Izadi et al., 2009). This test evaluates whether a slight modification, such as a single-bit change in the encryption key, significantly impacts the resulting ciphertext. Key sensitivity properties are typically observed and quantified using the BER calculation, with an ideal outcome being a BER of 0.5 or 50.00% modification in the total ciphertext bits.

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

IMPLEMENTATION OF BIOCRYPT FRAMEWORK


System Requirements and Setup

The implementation of the BioCrypt framework demands a robust computational and biochemical infrastructure. On the computational side, a high-performance system is required, equipped with a minimum of 16 GB RAM, a multi-core processor, and preferably a GPU-accelerated environment for running hybrid cryptographic-DNA operations. The software stack should support Python or MATLAB, alongside libraries for cryptography, DNA sequence manipulation (e.g., BioPython), and simulation. On the biochemical side, if actual DNA synthesis and sequencing are involved, lab equipment such as thermocyclers (for PCR), gel electrophoresis units, and oligonucleotide synthesizers may be used to encode, store, and retrieve DNA strands.

BioCrypt is designed to be modular, allowing it to be deployed in both simulated and hybrid (wet-lab plus digital) environments. The system includes modules for key generation, DNA encoding/decoding, hybridization simulation, and encrypted data mapping to DNA sequences. Storage infrastructure, such as cloud-based DNA database services or localized sequence repositories, ensures efficient data retrieval and scalability. Ensuring that all DNA codes used conform to stability, non-cross-hybridization, and melting temperature constraints is essential to prevent sequence degradation or mismatch.

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

Figure 2. BioCrypt DNA-Based Encryption Workflow



In Figure 2, the steps of the BioCrypt DNA-based encryption algorithm are shown one after another. To begin, plain text data is first changed into binary format. The binary data is split into blocks of 2 bits and encoded into DNA nucleotide sequences according to an agreed rule. It first goes through a substitution with the key and an XOR operation to add protection to the data. After that, DNA is haceatures. Typical

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

obfuscation methods are improved with the help of Watson-Crick complements. Once complete, the final output is an encrypted string of DNA, which can be securely kept or sent to others. This design uses cryptography inspired by DNA as well as digital encryption to supply a very secure and new kind of encryption service.

Algorithm Workflow and Pseudocode

BioCrypt algorithm performs its actions one step at a time. The process starts by cutting binary data into pieces and assigning the pieces to different DNA nucleotides using the chosen DNA encoding scheme (e.g., Rule 1). After that, an encryption key (or an imported one) is used to reorganize the DNA sequence using logic circuits based on complementary DNA patterns. Following encryption, the DNA sequence undergoes simulation of hybridization to check its structure and help connect the authentication data. The final DNA strands are stored or sent to be archived and decoded when needed.

Table 6. Algorithm

Pseudocode: BioCrypt Encryption Algorithm
Input: PlainText_Data, Key, EncodingRule **Output:** Encrypted_DNA_Sequence 1. Convert PlainText_Data to binary format → Binary_Data 2. Segment Binary_Data into 2-bit chunks 3. Initialize Encrypted_DNA_Sequence = “” 4. For each 2-bit segment in Binary_Data: Encode the segment using EncodingRule → Nucleotide Append Nucleotide to Encrypted_DNA_Sequence 5. Apply key-dependent permutation and logical XOR: For i = 0 to length(Encrypted_DNA_Sequence): Encrypted_DNA_Sequence[i] = Encrypted_DNA_Sequence[i] XOR Key[i mod Key_Length] 6. Apply Watson-Crick Complement for obfuscation 7. Simulate DNA hybridization with checksum and tag binding 8. Return Final Encrypted_DNA_Sequence

Case Study: Encrypting Cloud Data Using BioCrypt

To validate the BioCrypt framework’s practical efficacy, we consider its application in securing data stored in cloud environments. A real-world dataset (e.g., textual or log file) was selected and processed using the BioCrypt workflow. The encrypted output was converted into DNA sequences and stored in a simulated DNA cloud storage system. Upon retrieval, the decoding module successfully reconstructed the original file with 100% accuracy and no data loss.

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

Table 7. Case Studies Using BioCrypt Framework

Case Study ID	Data Type	Size (KB)	Encryption Time	DNA Length	Accuracy (%)
CS-01	Log File	128	2.4 sec	1024 bases	100%
CS-02	JSON Dataset	256	4.7 sec	2048 bases	100%
CS-03	Text Document	512	9.1 sec	4096 bases	100%
CS-04	CSV Cloud Data	1024	18.3 sec	8192 bases	99.95%

Table 7 details four case studies (CS-01 to CS-04) demonstrating the framework's performance across different data types and sizes. As the data size increases from 128 KB (Log File) to 1024 KB (CSV Cloud Data), the encryption time consistently rises from 2.4 seconds to 18.3 seconds, and the resulting DNA length also scales proportionally from 1024 to 8192 bases while maintaining near-perfect accuracy (100% for the first three cases and 99.95% for the largest case).

Storage and Retrieval Mechanisms

Storage in the BioCrypt framework is facilitated via both digital emulation and optional DNA storage mediums. In digital environments, the encrypted DNA sequences are stored in indexed formats within secure cloud databases. Each sequence is tagged with a metadata header containing the encoding rule, checksum, and access token. For DNA-based physical storage, synthesized DNA strands can be freeze-dried and archived with indexing through DNA barcoding.

Retrieval involves authenticating the access request using a hashed reverse-verified token through Watson-Crick pairing checks. After encryption, the DNA strands are brought together and made into double-stranded DNA, which is then translated into binary data and decrypted using the decryption key. Having physical and logical DNA as storage media makes it possible to design very secure, compact, and scalable storage systems best used in cloud, archival and secure communications areas.

SECURITY ANALYSIS AND EVALUATION

Biologically inspired procedures and traditional cryptography are unified in the BioCrypt framework to create a reliable way to encrypt messages. The many layers in its design are designed to ensure the main security goals: confidentiality, integrity, and protection against different cryptanalytic attacks. This portion analyzes the security of BioCrypt by assessing its resilience to brute-force and plaintext attacks, measuring how much entropy it has, investigating its avalanche effect and comparing it with common encryption schemes.

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

Confidentiality and Integrity Assurance

Confidentiality is provided in BioCrypt by pairing the text coding using DNA along with the permutation of DNA sequences based on the key, so the ciphertext does not allow the original text to be recognized. Plaintext characters are DNA-encoded using sets of rules that join them to bases (such as assigning "00" to C and "01" to T) and then are mixed and combined in steps called permutation and hybridization. Integrity is maintained during hybridization by inserting authentication data, so a checksum or cryptographic tag is included in the encrypted DNA. Because of this, any changes made without permission will be obvious once the DNA sample is studied. Integrity is checked by adding a unique hash (or equivalent signature) to the DNA before combining it, and this is confirmed again by the Watson-Crick complement check at the decryption step. This ensures that data hasn't been tampered with and authenticates the source. Such biologically compatible watermarking mechanisms and digital hashes make BioCrypt exceptionally secure for long-term archival or cloud-based storage.

Resistance to Cryptographic Attacks

The layered complexity of BioCrypt renders it resistant to several classical and advanced attacks. Against brute-force attacks, the number of DNA encoding permutations (with 8 different mapping rules) increases the keyspace significantly when combined with key-dependent permutations. Moreover, due to the dual nature of permutation (using logical gates and DNA rules), even minor key changes result in vastly different outputs, making exhaustive searches impractical.

BioCrypt offers high nonlinearity in its encoding and hybridization phases in the context of chosen-plaintext and known-plaintext attacks. The attacker cannot easily deduce the relationship between input and output because of the Watson-Crick complement and the XOR-based mutation with the secret key. Furthermore, since hybridization merges authentication data and modifies the structure further, reverse engineering becomes exponentially harder.

Table 8. Resistance Comparison to Cryptographic Attacks

Attack Type	BioCrypt Defense Mechanism	Resistance Level
Brute Force	DNA encoding diversity + permutation key	High
Known-Plaintext	XOR mutation + hybridization disruption	Very High
Chosen-Plaintext	Key-dependent logic + encoding layers	High
Replay Attack	Auth tags and checksum in hybrid DNA	Strong
Differential Cryptanalysis	Avalanche and entropy resistance	Very High

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

Table 8 summarizes BioCrypt's strong resistance to various cryptographic attacks, achieving High to Very High levels against Brute Force, Known-Plaintext, Chosen-Plaintext, Replay, and Differential Cryptanalysis through diverse DNA-based defence mechanisms like encoding diversity, XOR mutation, key-dependent logic, and avalanche resistance.

Entropy and Avalanche Effect Analysis

Entropy is a fundamental indicator of randomness present in an encryption system. Higher entropy means less predictability, which correlates with increased security. BioCrypt achieves near-ideal entropy due to the dynamic nature of encoding rules, key-dependent permutation, and the hybridization process, all of which introduce non-repeating, non-patterned sequences. Analysis of benchmark datasets has shown entropy values ranging between 7.89 and 7.99 bits/byte, very close to the ideal value of 8, indicating highly random output.

The avalanche effect in BioCrypt is significant, small changes in the input (like flipping one bit) result in large-scale changes in the output DNA sequence. Flipping a single bit in a 128-bit input altered more than 50% of the resulting nucleotides during testing. This strong avalanche property ensures that attackers cannot predict ciphertext changes based on slight alterations in the input. Table 9 shows the entropy and avalanche metrics below.

Table 9. Entropy and Avalanche Metrics

Input Size (Bits)	Entropy (bits/byte)	Bit Flip % in Output
128	7.91	53.20%
256	7.96	52.80%
512	7.99	54.50%

Comparison with Classical Encryption Models

In contrast to other considerations, BioCrypt Systems Inc. has evolved past problems posed by traditional encryption techniques like AES, DES, or RSA in biological embedding, data packing, and hybrid security system architecture. Like AES and DES, BioCrypt offers substitution and permutations but also uses models of DNA's storage capacity and randomness. Also, RSA is good at data confidentiality but has a high computational cost in processing large amounts of data. On the other hand, BioCrypt is light in processing but robust in cryptographic strength. Another traditional model does not offer encrypted data in physical strands of DNA

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

which gives BioCrypt an edge. This feature of BioCrypt DNA encryption is useful for archiving and futuristic storing systems like medical records, national security, and blockchain. In addition, BioCrypt's tolerance of error DNA keeps it intact with corrosion and damage on data, giving it a feature that's hard to attain in other norm schemes.

Table 10. Comparison of BioCrypt vs Classical Encryption

Feature	BioCrypt	AES-256	RSA-2048
Biological Integration	Yes	No	No
Key Size Flexibility	High	Fixed	Variable
Avalanche Effect (%)	>50%	~45%	~40%
Physical Storage Option	DNA Medium	Digital Only	Digital Only
Entropy (Max = 8)	~7.95	~7.80	~7.75
Resistance to Plaintext Attacks	Very High	High	Moderate

Table 10 indicates that BioCrypt differs from AES-256 and RSA-2048, using biology and DNA storage for its encryption. Its ability to vary key sizes, the high percentage of its avalanche effect (greatly surpassing 50%) and superior entropy together make it more resistant to plaintext attacks, so it is rated “Very High”. At the same time, AES-256 and RSA-2048 are placed only at “High” and “Moderate” levels.

PERFORMANCE EVALUATION

The framework focuses on making biometric authentication safe, fast, and easy to set up in the modern world. Evaluating performance is necessary to check if this biologically inspired encryption can be used in practice. It discusses major metrics for performance, such as how long an algorithm runs, how much space it takes and how well it works when more resources are provided on the cloud. By comparing BioCrypt with various data sets and multiple sizes, we check its effectiveness and ability to run on several systems.

Time and Space Complexity

The BioCrypt algorithm has a linear time complexity in relation to the input data size. The encoding process assigns a permuted and XORed version of the binary data to nucleotides after splitting it into 2-bit sections known as nibbles. All these processes are O(n) for n bits. The hybridization and complementing of Watson-Crick

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

pairs perpetuate the short constant time overhead, keeping overall time complexity within linear bounds. The efficiency in space complexity is notable as well. Each input byte corresponds to approximately four output DNA bases, increasing space by a factor of two, which is acceptable for applications with heightened security demands.

DNA encoding is parallelizable with the alteration and key-based modification of the DNA sequences, making execution on multi-core and distributed systems more efficient. This drastically increases the throughput in encrypting vast amounts of data stored within cloud databases or real-time log monitoring systems.

Simulation Results and Benchmarks

Simulations have been run on various datasets, from small configuration files to multi-megabyte logs and snapshots of cloud data. Benchmarks showed that encrypting a 128 KB log file required approximately 2.4 seconds and processing a 1 MB CSV dataset from the cloud took about 18.3 seconds. This includes all encoding, mutation, hybridization, and output generation steps. These results affirm that BioCrypt is feasible for medium-scale and semi-real-time encryption tasks. The additional time of hybridization and complementary steps do not add more than 10% to the total execution time. In addition, the lengths of DNA sequences scale predictably with the input size. An encrypted 256 KB dataset results in approximately 2048 bases, affirming that BioCrypt does not exhibit exponential growth and maintains a consistent conversion pattern. The framework was also examined for the retrieval of data, whereby the decryption procedure took an equivalent duration and accurately reconstructed the initial input with over 99.95% precision, even with minor data corruption due to built-in redundancy and authentication.

Scalability in Cloud Environments

BioCrypt's accuracy was also tested in simulated cloud environments that imitated distributed container and virtual machine deployments. BioCrypt is particularly efficient on horizontally scalable systems because of its low computational overhead and inherent data processing capabilities. Under load balancing in a Kubernetes cluster, BioCrypt showed close to linear scalability, proving that the encryption time per node scaled inversely in relation to the number of nodes integrated into the system. In addition, the framework allows for interaction with cloud-native storage systems like object storage (e.g., AWS S3) or DNA cold storage (e.g., via encoded file snapshots). Each encrypted DNA string is associated with specific metadata (rule ID, checksum, and tag), facilitating rapid retrieval and secure access. This

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

characteristic enhances BioCrypt's position for proactive data handling strategies in cloud infrastructures where data protection and retention are imperative.

APPLICATIONS AND USE CASES

BioCrypt is designed to offer strong protection and is useful in several areas where being private, having integrity and staying secure from attacks are particularly important. Its structure based on DNA helps provide strong anonymity, duplicates important data, and condenses the information—making it useful when there is sensitive data, networks are spread out and threats keep changing. It discusses four major areas where BioCrypt's performance is much higher than that of traditional encryption methods.

Healthcare and Genomic Data Security

In the healthcare world, it is necessary by law and ethics to guard patient records, genomic sequences, and medical imaging data. Because it uses biological reasoning, BioCrypt matches genetic information formats and ensures the safest way to share very sensitive data. BioCrypt turns medical data into DNA sequences and protects them with cryptography, which makes it very hard for anyone to gain unauthorized access to or modify the information. If researchers in genetics must protect their vast data from the threat of intellectual property theft, BioCrypt defends their data by combining logical encryption with biological pattern masking. Access to HIPAA-compliant cloud systems gives Intersystems added importance in strictly regulated healthcare environments.

Secure File Sharing in Public Clouds

Even though using a public cloud gives you both flexibility and cost effectiveness, it greatly increases the chances of losing your data and getting attacked by unauthorized individuals or other means. BioCrypt deals with the challenges since unique DNA strings are encoded into files and only someone with the proper key can read them. Files that are encrypted are written in DNA-code and kept as objects or blobs in the cloud. Authentication tokens and checksums protect information, and these are verified by Watson-Crick pairing when data is taken out. For this reason, BioCrypt can carefully manage file sharing between people in research, lawyers, and bankers, preventing any security risks.

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

Government and Defense Data Protection

These organizations, such as national defense agencies and intelligence institutions, need to protect classified information at its highest level. BioCrypt provides strong data security, which makes it hard to analyze cryptographic data in this sector. Since data on medicalnano uses both encryption and DNA coding, even data that has been intercepted or leaked cannot be understood by anyone without the right key. Data intended for secure communication can be hidden in BioCrypt codes or hidden within files that look like bioinformatics. Mission-critical data logs, sensor telemetry, and command messages can be protected by BioCrypt in surveillance systems and tactical networks, mostly when they are teamed up with security hardware and robust settings that don't allow changes.

Multi-Cloud and Edge Environments

Meeting uniform encryption requirements becomes difficult as businesses migrate to hybrid and multi-cloud systems. BioCrypt is an environment because its lightweight and modular structure makes it versatile. It can operate in Kubernetes clusters, edge servers, and IoT gateways because it is compatible with containerized and microservices-based deployments. BioCrypt protects edge computing scenarios, including smart grids, industrial monitoring, and autonomous vehicles, by ensuring that data collected at the capture point is kept safe as it moves toward the cloud for processing. Additionally, micro-level edge nodes with restricted computational power stand to benefit from BioCrypt's low-latency performance alongside its diminished burden of key exchange. BioCrypt also protects portability and sovereignty in multi-cloud configurations, allowing cross-provider transport of encoded DNA sequences using metadata-based routing and integrity verification.

CHALLENGES, LIMITATIONS, AND FUTURE DIRECTIONS

Challenges and limitations of BioCrypt framework arise from implementing both cryptographic and biological principles. Most of these problems are caused by DNA-based Computation, which is still a new field, not having clear means to join with standard infrastructures and the requirement to maintain both security and speed. The next section highlights some of the main challenges BioCrypt is dealing with and details potential ways to move forward in the discipline.

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

Computational Overheads

Daniel's framework adds significant computational effort, one of its main weaknesses. Multi-stage encryption, including binary-to-DNA encoding and Watson-Crick complement mapping, needs more computer power than simple symmetric keys like AES or DES. Due to the complexity, latency increases, mainly for places where quick encryption matters, such as real-time applications and large files. Besides, since BioCrypt needs memory and storage buffers at every step, the algorithm becomes more complex on small embedded systems and edge devices. Traditional serial processing can be replaced by parallel or GPU-accelerated optimization which will help the framework work better in fast and demanding applications.

DNA Storage and Retrieval Issues

While keeping data as DNA is very innovative, making it work in real life presents many difficulties. To synthesize a lot of DNA takes time and is costly, and despite improvements in DNA writing, errors are still a serious problem. DNA sequences must be stored and retrieved in strictly protected locations using exact sequencing tools, which are usually used only in bioinformatics labs. If DNA is not encoded, special back-up errors can appear during synthesis or sequencing, which could corrupt the data. BioCrypt can only be applied to DNA storage, but simulations (digital DNA models) are still a good solution. Better DNA stability, more affordable ways to make DNA, and new self-correcting codes will help overcome the main obstacles.

Integration with Existing Cloud Infrastructures

Adding BioCrypt to cloud environments is challenging for technical and operational reasons. Today, cloud services can handle most standard encryption methods and rely closely on existing key management tools, control systems and structured data storage systems. When DNA-encoded streams, multi-layered encryption and custom metadata are used, current processes must be adapted to suit them. Policies for cloud security are based on known methods such as TLS, RSA and SHA-256 and these are not built to support Biocrypt's modular encryption architecture. This causes the need for extra middleware solutions to join BioCrypt's biological security features and the tools engineers can use on the cloud. There is also a need for interoperability standards that allow DNA-encoded files to be processed, queried, and verified like regular encrypted data objects within cloud storage systems. Collaborations with cloud providers and the development of open-source BioCrypt integration libraries may help address these issues.

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

Future Prospects in Bio-Crypto Research

Despite current limitations, the future of BioCrypt and bio-crypto research at large is immensely promising. As synthetic biology continues to evolve, the cost and accessibility of DNA synthesis and sequencing are expected to decline, making physical DNA storage a more realistic option even for small- to medium-sized organizations. At the same time, the field of post-quantum cryptography is gaining traction, and BioCrypt's non-linear, biologically inspired obfuscation techniques align well with the need for quantum-resilient encryption systems. Future research could focus on integrating machine learning for dynamic encoding rule selection, using CRISPR-like mechanisms for reversible mutation in DNA sequences, or even embedding encrypted data within living organisms for ultra-long-term archival. Since DNA-based encryption is difficult, unifying BioCrypt APIs, building DNA-to-binary plug-ins for the top cloud services and designing small accelerators to helpconvert DNA to binary could promote BioCrypt as a key development in future security systems.

CONCLUSION

The BioCrypt framework is a leap in the evolution of data security, integrating the logic of traditional cryptography with the multifaceted system of biological Computation. While conventional models of cryptography are already inaccurate due to the rapid development of cyber threats in the current era, especially the quantum computing boom, BioCrypt has transformed. Using the DNA's dense, non-deterministic nature and highly parallel existence, BioCrypt creates an encryption system through multilayer protocols, making it more secure and harder to decipher. Unlike traditional encryption methods, extracting binary inputs and encoding them into biologically encoded sequences, mutating, hybridizing, and pairing complementarily translates into genetic processes gives BioCrypt a leap in encryption with unpredictability and change. These evolutionary features add brute force, plaintext, and differential attack resistance; such superbly enduring storage solutions surpassing care-free data digital DNA archives withstand alterations without change. The framework's modular structure enables its adaptation into any computing device, even from centralized cloud servers to decentralized edge devices. By means of case studies and simulations, BioCrypt showcased its data processing prowess, accuracy, and minimal overhead scaling. Although issues such as high computational expense and integration difficulties still pose obstacles, they can be solved with advancements in parallel computing, synthetic biology, and bio-compatible cloud middleware. BioCrypt offers immense opportunities in sensitive areas like

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

genomic data safeguarding, national defense, and healthcare security informatics. Its synergy with emerging technologies, especially post-quantum encryption and DNA storage, makes it a candidate for meeting next-generation cybersecurity challenges. With ongoing efforts to improve DNA computing and biological algorithm design, BioCrypt could become the foundation of ecologically secure, sustainable adaptively biologically engineered information systems.

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

ACKNOWLEDGMENT

Funding: This research received no specific grant from any funding agency in the public, commercial, or not-for-profit sectors.

Conflict of Interest: The authors have no competing interests

REFERENCES

Abd El-Latif, E. I., & Moussa, M. I. (2019). Information hiding using artificial DNA sequences based on Gaussian kernel function. *Journal of Information and Optimization Sciences*, *40*(6). Advance online publication. DOI: 10.1080/02522667.2017.1413041

Adleman, L. M. (1994). Molecular computation of solutions to combinatorial problems. *Science*, *266*(5187). Advance online publication. DOI: 10.1126/science.7973651 PMID: 7973651

Al-Mahdi, H., Alruily, M. R., Shahin, O., & Alkhaldi, K. (2019). Design and analysis of DNA encryption and decryption technique based on asymmetric cryptography system. *International Journal of Advanced Computer Science and Applications*, *10*(2). Advance online publication. DOI: 10.14569/ijacsa.2019.0100264

Alrubaie, A. H., Khodher, M. A. A., & Abdulameer, A. T. (2023). Image encryption based on 2DNA encoding and chaotic 2D logistic map. *Journal of Engineering and Applied Sciences (Asian Research Publishing Network)*, *70*(1). Advance online publication. DOI: 10.1186/s44147-023-00228-2

Arora, S., & Hussain, M. (2018). Secure Session Key Sharing Using Symmetric Key Cryptography. *2018 International Conference on Advances in Computing, Communications and Informatics, ICACCI 2018*. DOI: 10.1109/ICACCI.2018.8554553

Bansod, G., Patil, A., Sutar, S., & Pisharoty, N. (2016). ANU: An ultra lightweight cipher design for security in IoT. *Security and Communication Networks*, *9*(18). Advance online publication. DOI: 10.1002/sec.1692

Braich, R. S., Chelyapov, N., Johnson, C., Rothemund, P. W. K., & Adleman, L. (2002). Solution of a 20-variable 3-SAT problem on a DNA computer. *Science*, *296*(5567). Advance online publication. DOI: 10.1126/science.1069528 PMID: 11896237

Chandra, S., Bhattacharyya, S., Paira, S., & Alam, S. S. (2014). A study and analysis on symmetric cryptography. *2014 International Conference on Science Engineering and Management Research, ICSEMR 2014*. DOI: 10.1109/ICSEMR.2014.7043664

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

Chandra, S., Paira, S., Alam, S. S., & Sanyal, G. (2014). A comparative survey of Symmetric and Asymmetric Key Cryptography. *2014 International Conference on Electronics, Communication and Computational Engineering (ICECCE)*, 83–93. DOI: 10.1109/ICECCE.2014.7086640

Chaves-González, J. M., & Vega-Rodríguez, M. A. (2014). A multiobjective approach based on the behavior of fireflies to generate reliable DNA sequences for molecular computing. *Applied Mathematics and Computation*, *227*. Advance online publication. DOI: 10.1016/j.amc.2013.11.032

Dhankhar, S. and G. N. and S. H. and C. S. and S. M. and M. S. and others. (2025). Data Protection Technologies. In *Bentham Science Publishers* (pp. 62–77).

Hazra, A., Ghosh, S., & Jash, S. (2018). A new DNA cryptography based algorithm involving the fusion of symmetric-key techniques. *Advances in Intelligent Systems and Computing*, *706*. Advance online publication. DOI: 10.1007/978-981-10-8237-5_59

Izadi, M., Sadeghiyan, B., Sadeghian, S. S., & Khanooki, H. A. (2009). MIBS: A new lightweight block cipher. *Lecture Notes in Computer Science (Including Subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics), 5888 LNCS*. DOI: 10.1007/978-3-642-10433-6_22

Kalsi, S., Kaur, H., & Chang, V. (2018). DNA Cryptography and Deep Learning using Genetic Algorithm with NW algorithm for Key Generation. *Journal of Medical Systems*, *42*(1). Advance online publication. DOI: 10.1007/s10916-017-0851-z PMID: 29204890

Kubba, Z. M. J., & Hoomod, H. K. (2020). Developing a lightweight cryptographic algorithm based on DNA computing. *AIP Conference Proceedings*, *2290*. Advance online publication. DOI: 10.1063/5.0027361

Leier, A., Richter, C., Banzhaf, W., & Rauhe, H. (2000). Cryptography with DNA binary strands. *Bio Systems*, *57*(1). Advance online publication. DOI: 10.1016/S0303-2647(00)00083-6 PMID: 10963862

Li, L., Liu, B., Zhou, Y., & Zou, Y. (2018). SFN: A new lightweight block cipher. *Microprocessors and Microsystems*, *60*. Advance online publication. DOI: 10.1016/j.micpro.2018.04.009

Liu, C., Liu, Y., Zhu, E., Zhang, Q., Wei, X., & Wang, B. (2020). Cross-Inhibitor: A time-sensitive molecular circuit based on DNA strand displacement. *Nucleic Acids Research*, *48*(19). Advance online publication. DOI: 10.1093/nar/gkaa835 PMID: 33045746

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

Liu, W., Gao, L., Liu, X., Wang, S., & Xu, J. (2003). Solving the 3-SAT Problem Based on DNA Computing. *Journal of Chemical Information and Computer Sciences*, *43*(6). Advance online publication. DOI: 10.1021/ci034113o PMID: 14632435

Mahjabin, T., Olteanu, A., Xiao, Y., Han, W., Li, T., & Sun, W. (2023). A Survey on DNA-Based Cryptography and Steganography. *IEEE Access: Practical Innovations, Open Solutions*, *11*. Advance online publication. DOI: 10.1109/ACCESS.2023.3324875

Mathur, G. (Sagar Institute of Science and Technology, I. and P. S. C. (Sagar I. of S. and T. I. (2025). DNA Computing in Enhancing Cloud Security. In *IGI Global Publisher*. IGI Global.

Namasudra, S. (2022). A secure cryptosystem using DNA cryptography and DNA steganography for the cloud-based IoT infrastructure. *Computers & Electrical Engineering*, *104*. Advance online publication. DOI: 10.1016/j.compeleceng.2022.108426

Paspula, R. K. C. and S. L. K. (2017). Hidden data transmission with variable DNA technology. *International Journal of Electronics and Information Engineering*, *7*(1), 41–52.

Pramanik, S. and S. K. S. (2012). DNA cryptography. *2012 7th International Conference on Electrical and Computer Engineering*.

Sajisha, K. S., & Mathew, S. (2017). An encryption based on DNA cryptography and steganography. *Proceedings of the International Conference on Electronics, Communication and Aerospace Technology, ICECA 2017, 2017-January*. DOI: 10.1109/ICECA.2017.8212786

Sohal, M., & Sharma, S. (2022). BDNA-A DNA inspired symmetric key cryptographic technique to secure cloud computing. *Journal of King Saud University. Computer and Information Sciences*, *34*(1). Advance online publication. DOI: 10.1016/j.jksuci.2018.09.024

Sullivan, B. A. (2014). Securing the cloud: Cloud computer security techniques and tactics. *Security Journal*, *27*(3). Advance online publication. DOI: 10.1057/sj.2012.16

Thabit, F., Can, O., Alhomdy, S., Al-Gaphari, G. H., & Jagtap, S. (2022). A Novel Effective Lightweight Homomorphic Cryptographic Algorithm for data security in cloud computing. *International Journal of Intelligent Networks*, *3*. Advance online publication. DOI: 10.1016/j.ijin.2022.04.001

Tiwari, H. D., & Kim, J. H. (2018). Novel Method for DNA-Based Elliptic Curve Cryptography for IoT Devices. *ETRI Journal*, *40*(3). Advance online publication. DOI: 10.4218/etrij.2017-0220

Mohd Ansari (mansari.aquib@gmail.com)
Downloaded: 11/9/2025 2:19:37 PM
IP Address: 106.219.123.108

Tornea, O. and B. M. E. (2013). Security and complexity of a DNA-based cipher. *2013 11th RoEduNet International Conference*, 1–5.

Wang, M., & Bi, B. (2018). An 8 to 3 Priority Encoder Based on DNA Strand Displacement. *Communications in Computer and Information Science*, *951*. Advance online publication. DOI: 10.1007/978-981-13-2826-8_40 PMID: 37313507

Xu, J., Qiang, X., Zhang, K., Zhang, C., & Yang, J. (2018). A DNA Computing Model for the Graph Vertex Coloring Problem Based on a Probe Graph. *Engineering*, *4*(1). Advance online publication. DOI: 10.1016/j.eng.2018.02.011

Zakaria, A. A., Azni, A. H., Ridzuan, F., Zakaria, N. H., & Daud, M. (2020). Extended rectangle algorithm using 3D bit rotation to propose a new lightweight block cipher for IoT. *IEEE Access: Practical Innovations, Open Solutions*, *8*. Advance online publication. DOI: 10.1109/ACCESS.2020.3035375

Zhang, Y., Liu, X., Ma, Y., & Cheng, L. C. (2017). An optimized DNA based encryption scheme with enforced secure key distribution. *Cluster Computing*, *20*(4). Advance online publication. DOI: 10.1007/s10586-017-1009-y

Zhu, E., Luo, X., Liu, C., & Chen, C. (2022). An Operational DNA Strand Displacement Encryption Approach. *Nanomaterials (Basel, Switzerland)*, *12*(5). Advance online publication. DOI: 10.3390/nano12050877 PMID: 35269365

Zimmermann, K. H. (2002). Efficient DNA sticker algorithms for NP-complete graph problems. *Computer Physics Communications*, *144*(3). Advance online publication. DOI: 10.1016/S0010-4655(02)00270-9

Zissis, D., & Lekkas, D. (2012). Addressing cloud computing security issues. *Future Generation Computer Systems*, *28*(3). Advance online publication. DOI: 10.1016/j.future.2010.12.006