

2.2 Rated nominal feeder current based upon rated ambient temperature

Main Busbar Configuration	Circuit Breaker	Ventilation	Hz	25°C	30°C	35°C	40°C	45°C	50°C	55°C
80 X 10 X 1	3AH5272-1	Without	50	1065	953	867	800	745	698	658
100 X 10 X 1	3AH5272-2 / 3AH5273-2 / 3AH5274-2	Without	50	1400	1250	1138	1050	981	916	864
80 X 10 X 1	3AH5272-2 / 3AH5273-2 / 3AH5274-2	Natural	50	1665	1490	1356	1250	1163	1090	1030
80 X 10 X 2	3AH5283-4 / 3AH5283-6 / 3AH5284-6	Natural	50	2245	2120	1979	1850	1705	1554	1387
100 X 10 X 2	3AH5283-6 / 3AH5284-6	Forced Ventilation	50	3320	2980	2712	2500	2330	2180	2055
80 X 10 X 1	3AH5272-1	Without	60	1058	945	860	795	738	693	650
100 X 10 X 1	3AH5272-2 / 3AH5273-2 / 3AH5274-2	Without	60	1360	1205	1095	1000	930	860	815
80 X 10 X 1	3AH5272-2 / 3AH5273-2 / 3AH5274-2	Natural	60	1598	1430	1300	1200	1116	1047	988
80 X 10 X 2	3AH5283-4 / 3AH5283-6 / 3AH5284-6	Natural	60	2595	2320	2115	1950	1814	1700	1605
100 X 10 X 2	3AH5283-6 / 3AH5284-6	Forced Ventilation	60	3263	2919	2657	2450	2279	2138	2017

2.2.1 Panel dimensions

Panel type	Rated normal voltage	Rated normal current	Panel width	
	U _r [kV]	I _r [A]	800 mm	1000 mm
Withdrawable panel with circuit breaker truck, disconnecter truck	≤ 24 kV		≤1250 A	>1250 A
Bus-coupler panel	≤ 24 kV	---	≤1250 A	>1250 A
Metering panel / Riser panel / Busbar Termination panel / Busbar Esw & VT Panel	≤ 24 kV	---	✓	-
Load break switch panel	≤ 24 kV	630	500mm	-
Fused Load break switch panel	≤ 24 kV	200	500mm	-

Panel depth	1900 mm ¹⁵
Panel height	2250 mm

¹⁵ Without front doors and rear covers