

# Computer Networks and Distributed Systems

## Part 6 – Application Layer

Course 527 – Spring Term 2015-2016


**Emil C Lupu & Daniele Sgandurra**

[e.c.lupu@imperial.ac.uk](mailto:e.c.lupu@imperial.ac.uk), [d.sgandurra@imperial.ac.uk](mailto:d.sgandurra@imperial.ac.uk)

## Part 6 – Contents

### Application Layer

- Application level protocols
  - Domain name resolution (DNS)
  - Email (SMTP, POP, IMAP)
  - World Wide Web (HTTP)



1

## Client

Initiates connection

Often user-invoked app running on local machine

- e.g. web browser, email clients

Uses service/resource from server

Resource use usually temporary

## Server

Waits for connections

- Handles multiple clients

Special purpose app providing service/resource

- e.g. web server, chat server

Provides controlled access to resources/services

Often started at boot time

- e.g. “daemon” in UNIX; “service” under WIN

2

## Peer-to-Peer

Not all communication client/server based

### Peer-to-peer model

- Hosts operating together rather than one sided
- Offering of resources/service to one another
  - e.g. chat, file trading, Internet telephony

Often implemented as client/server on same host  
Centralised server may coordinate

3

# Application Layer Protocols

Clients, servers, peers need communication protocols

Web: HTTP  
Email protocols: SMTP, MIME, POP, IMAP  
File transfer: FTP  
Name resolution: DNS  
– Not user application but service

4

# Names vs IP Addresses

IP addrs good for identification of network interfaces, but:

- Addr **146.169.14.6** not very memorable
- Machines, services may move between networks

Use meaningful, user-friendly names in addition to IP addrs

- e.g. **columbia.doc.ic.ac.uk** instead of **146.169.7.41**

Names assigned independently of IP addresses

- Names fixed when IP addrs change for technical reasons

Alias names can identify services

- Independent of machine providing service
- e.g. **www.doc.ic.ac.uk** for **linnet.doc.ic.ac.uk**

5

# Mapping Names to IP Addrs

Need mapping between names and numbers

## Local file

- Large and hard to maintain
- Was used in early ARPANET

## Centralised server

- Clients query database to perform name resolution
- Bottleneck, single point of failure, admin hard

## Distributed look-up system

- Domain Name System (DNS)

6

# Domains Name System (DNS)

Internet is inter-network of autonomous networks

- Must avoid conflicts between names
- Must support independent administration of names

**DNS** names form hierarchies

- e.g. **columbia.doc.ic.ac.uk**

Requires uniqueness of complete name only

- Like postal address
- e.g. **fred.foo.com** different to **fred.bar.com**

7

# Names and Domains: Externally Managed

## Top-level structure conveys meaning

- .**uk** = United Kingdom
  - Country ID from global naming standard
- .**ac** = Academic network
  - Standard sub-domain within UK
- .**ic** = Imperial College
  - Name assigned by UK academic net administration
  - Owned by Imperial College

## Within each domain naming managed independently

- e.g. **co.uk** is independent of **co.fr**

8

# Top Level Domains (TLDs)

Domain	Specification	Example
<b>com</b>	Commercial	<b>ibm.com</b>
<b>net</b>	Network providers	<b>internic.net</b> , <b>demon.net</b>
<b>edu</b>	Educational institution	<b>mit.edu</b>
<b>gov</b>	Government organisation	<b>whitehouse.gov</b>
<b>mil</b>	US Military organisation	<b>navy.mil</b>
<b>org</b>	Other organisation	<b>linux.org</b> , <b>redcross.org</b>
<country code>	Domain administered by country (ISO 3166)	<b>fr</b> , <b>uk</b> , <b>zw</b>
2 <sup>nd</sup> level country domains	Sub-domains to TLD administered by organisation for that country	<b>ac.uk</b> , <b>co.uk</b>

9

# Name Assignment

## ICANN authorises registrars for .uk, .com, .org

- Non-profit corp. with various Internet responsibilities

## In UK, Nominet assigns names

- 2nd level names (co, ltd etc.) used by Nominet only
- TLD & 2nd level names not allowed as 3rd level names
  - **nhs.co.uk** not allowed as **nhs.uk** is 2nd level domain
  - **net.org.uk** not allowed as **.net** is TLD
- One character 3rd level names reserved
- **ac.uk**, **gov.uk**, **nhs.uk**, **police.uk**, **mod.uk** not controlled by Nominet

10

# UK 2<sup>nd</sup> Level Domains

<b>.co.uk</b>	Commercial enterprises
<b>.me.uk</b>	Personal domains
<b>.org.uk</b>	Non-commercial organisations
<b>.plc.uk</b> <b>.ltd.uk</b>	Registered company names only
<b>.net.uk</b>	Internet Service Providers
<b>.sch.uk</b>	Schools
<b>.ac.uk</b>	Academic Establishments
<b>.gov.uk</b>	Government Bodies
<b>.nhs.uk</b>	NHS Organisations
<b>.police.uk</b>	UK Police Forces
<b>.mod.uk</b>	Ministry of Defence

11

# Names and Domains: Internally Managed

Local domains follow organisational structure

- .doc = Dept. of Computing
  - Assigned by College admin
- .columbia = Machine in DoC
  - Assigned by Dept admin

Type of name may reflect type of machine, naming conventions.

- e.g. in DoC birds are servers, colours are printers

Names may reflect services machine provides

- e.g. **www**, **mail**

12

## Recursive DNS Lookups

If name cannot be resolved locally:

- Make new request to server up the hierarchy
- DNS server now becomes DNS client

When the top level is reached:

- Go down to required domain

Repeated until someone knows name,

- or decided that name not resolvable

DNS Servers are not required to support recursive queries.

14

# DNS Name Resolution

Host knows local DNS server to ask for names

- Local database of names maintained manually

**Authoritative results**

- Returned from name server managing that name

Local DNS servers do not move often

- May be hard-coded or given by DHCP
- DNS server known by its IP address
- Domain will typically have 2-3 DNS servers e.g., ns0, ns1 in doc.ic.ac.uk or ic.ac.uk.

13

## Example: Recursive DNS Lookup

vm-shell1.doc.ic.uk → www.csail.mit.edu

Vm-shell1.doc.ic.ac.uk → dns0.doc.ic.ac.uk

dns0.doc.ic.ac.uk queries ns.ic.ac.uk

ns.ic.ac.uk queries edu-server.net

edu-server.net queries mit.edu

mit.edu queries csail.mit.edu

```
vm-shell1-> dig www.csail.mit.edu
<<> DIG 9.9.5-ubuntu0.7-Ubuntu <<> www.csail.mit.edu
global options: <cmd>
Got answer:
--HEADER-- opcode: QUERY, status: NOERROR, id: 3127
flags: qr rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 4, ADDITIONAL: 5

OPT PSEUDOSECTION:
EDNS: version: 0, flags: udp: 4096
QUESTION SECTION:
www.csail.mit.edu.
IN
A

ANSWER SECTION:
www.csail.mit.edu. 1800 IN A 128.30.2.155

AUTHORITY SECTION:
csail.mit.edu. 413 IN NS auth-n2.csail.mit.edu.
csail.mit.edu. 413 IN NS auth-n1.csail.mit.edu.
csail.mit.edu. 413 IN NS auth-n0.csail.mit.edu.
csail.mit.edu. 413 IN NS auth-n3.csail.mit.edu.

ADDITIONAL SECTION:
auth-n3.csail.mit.edu. 413 IN A 128.52.32.80
auth-n0.csail.mit.edu. 413 IN A 128.30.2.123
auth-n1.csail.mit.edu. 413 IN A 18.24.0.120
auth-n2.csail.mit.edu. 413 IN A 128.52.32.80

Query time: 119 msec
SERVER: 155.188.142.8#53(155.188.142.8)
WHEN: Tue Feb 23 17:58:12 GMT 2016
MSG SIZE rcvd: 218
```

TLD servers replicated around the world

- Make queries faster that reach top of tree
- Load shared and gives redundancy

15

## Iterative (non-recursive) DNS Lookups

```

vm-shell:~ > dig +trace www.csail.mit.edu;
<<>> DiG 9.8.3-P1 <<>> +trace www.csail.mit.edu
;; global options: +cmd
.                339347    IN            NS            j.root-servers.net.
...
;; Received 228 bytes from 192.168.1.1#53(192.168.1.1) in 25 ms

edu.             172800    IN            NS            a.edu-servers.net.
...
;; Received 270 bytes from 199.7.83.42#53(199.7.83.42) in 112 ms

mit.edu.         172800    IN            NS            usw2.akam.net.
...
;; Received 414 bytes from 192.31.80.30#53(192.31.80.30) in 104 ms
csail.mit.edu.   1800     IN            NS            auth-ns2.csail.mit.edu.
...
;; Received 191 bytes from 193.108.91.37#53(193.108.91.37) in 11 ms
www.csail.mit.edu. 1800     IN            A            128.30.2.155
;; Received 51 bytes from 18.24.0.120#53(18.24.0.120) in 85 ms

```

## Types of DNS Records

A records:            name → IP address mapping

MX records: mail server address for domain

- Used when delivering email to, e.g., **@doc.ic.ac.uk**

NS records:            name server address for domain

CNAME records: alias names

- e.g. `www.doc.ic.ac.uk` alias for `linnet.doc.ic.ac.uk`

PTR records: name → IP addr (for reverse lookups)

- e.g. 146.169.7.41 → columbia.doc.ic.ac.uk

RRSIG records: DNSSEC Signature

## DNS Caching

Servers cache responses as names often needed again

- Exploits locality of reference
  - If I look at a web site, my colleagues may look too
  - If **ns.ic.ac.uk** resolves **www.doc.ic.ac.uk** once, likely to get more requests in future

Cached answers non-authoritative

- May be wrong, out-of-date

DNS entries give TTL based on volatility

- Caches expire records after their TTL has expired
- Stable names can safely be cached for much longer

## Example: DNS Host Lookup

```

[vm-shell:] => dig sharepoint.ic.ac.uk ANY

<<>> DiG 9.9.5-3ubuntu0.7-Ubuntu <<>> sharepoint.ic.ac.uk ANY
;; global options: +cmd
;; Got answer:
->>HEADER<<< opcode: QUERY, status: NOERROR, id: 28112
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 4, AUTHORITY: 4, ADDITIONAL: 9

;; OPT PSEUDOSECTION:
;; EDNS: version: 0, flags::, udp: 4096
;; QUESTION SECTION:
;sharepoint.ic.ac.uk.      IN      ANY

;; ANSWER SECTION:
sharepoint.ic.ac.uk.      300     IN      A        155.198.142.69
sharepoint.ic.ac.uk.      300     IN      RRSIG    A 5 4 300 20160320231006 2016021
9224826 47502 ic.ac.uk.  SK6pnqv/smM9tU2G808sHb0qXj789RBTQb4j75dqYRhCmLYTtCgCvXg
9N813QwQmR+XCojpcuRxBH0h/8nGfv60vFTWY15E8X4ZF7LliaoIcPI x77wLD27dHDKr45AERAKN
ZQlXyGU1ebG9KhJ2XBNOjMc+G2L43o3c xCW=
sharepoint.ic.ac.uk.      3600    IN      NSEC     shibboleth.ic.ac.uk. A RRSIG NX
C
sharepoint.ic.ac.uk.      3600    IN      RRSIG    FvBmaZJgtSPnufPmfvEq2wTh1qgDWE8Af15i
t0fV 12044621 47502 ic.ac.uk. Mltvg010f7L3CnwFInBmaZJgtSPnufPmfvEq2wTh1qgDWE8Af15i
t0fV 6yG1gn0NsMCiKJ09wzbX6G0ULK3Uec+vbN7K1/vRW5eWu/5hoc6BJY0 M4WtbktFtFEJ4JQNs

```

Answer of form:

```
<domain name> <TTL> <class> <type> <value>
```

TTL: Time to expiry if cached (in sec)

class: IN = Internet (almost always)

type: Type of record

## Example: DNS Domain Lookup

```
vm-shell1:~> dig google.com ANY

; <<> DiG 9.9.5-3ubuntu0.7-Ubuntu <<> google.com ANY
;; global options: +cmd
;; Got answer:
;; -->HEADER<< opcode: QUERY, status: NOERROR, id: 46860
;; flags: qr rd ra; QUERY: 1, ANSWER: 14, AUTHORITY: 4, ADDITIONAL: 5

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 4096
;; QUESTION SECTION:
;google.com.                IN      ANY

;; ANSWER SECTION:
google.com. 66400 IN TYPE257 \# 19 00056973737565737960616E74
65632E636F60
google.com. 60 IN SOA ns2.google.com. dns-admin.google
.com. 115345670 900 900 1800 60
google.com. 3600 IN TXT "v=spf1 include:_spf.google.com
~all"
google.com. 600 IN MX 50 alt4.aspmx.l.google.com.
google.com. 600 IN MX 20 alt1.aspmx.l.google.com.
google.com. 600 IN MX 30 alt2.aspmx.l.google.com.
google.com. 600 IN MX 40 alt3.aspmx.l.google.com.
google.com. 600 IN MX 10 aspmx.l.google.com.
google.com. 198 IN AAAA 2a00:1450:4009:80f::200e
google.com. 150 IN A 216.58.213.110
google.com. 87838 IN NS ns2.google.com.
google.com. 87838 IN NS ns1.google.com.
google.com. 87838 IN NS ns4.google.com.
google.com. 87838 IN NS ns3.google.com.

;; AUTHORITY SECTION:
google.com. 87838 IN NS ns1.google.com.
google.com. 87838 IN NS ns4.google.com.
google.com. 87838 IN NS ns2.google.com.
google.com. 87838 IN NS ns3.google.com.

;; ADDITIONAL SECTION:
ns2.google.com. 88517 IN A 216.239.34.10
ns3.google.com. 88517 IN A 216.239.36.10
ns1.google.com. 88517 IN A 216.239.32.10
ns4.google.com. 88517 IN A 216.239.38.10

;; Query time: 12 msec
;; SERVER: 155.190.142.8#53(155.190.142.8)
;; WHEN: Tue Feb 23 17:54:30 GMT 2016
;; MSG SIZE rcvd: 500
```

## Electronic Mail

Movement of structured text msg between systems

Email message fields:

To:, Cc:, Sender:, Reply-to:	Email addresses
From:	Who sent the message
Received:	List of mail servers that processed mail
Subject:	Summary of message
Message-Id:	Unique id for message
• Detect duplicate messages, responses	

Email address: <user name>@<mail domain name>

- e.g. ec11@doc.ic.ac.uk
- Mail server for domain found through DNS MX records

21

## Email Subsystems

Mail User Agents (MUA)

- e.g. Thunderbird, Outlook, mutt, ...
- Email client for composition, display, filing, ...

Message Transfer Agents (MTA)

- e.g. sendmail, exim, Exchange, ...
- Mail server that handles message transfer

Email often sent from MUA to **relay** (or **gateway**) MTA

- Usually in same organisation as sender
- Delivers to MTA in recipient's domain
  - Possibly via other relays
- Holds (spools) mail if destination unreachable
  - Supposed never to lose mail

22

## Simple Mail Transfer Protocol (SMTP)

Protocol used by MTAs (and MUAs)

- Delivers mail from one system to another

Two parties communicate using TCP and port 25

- Sender (client) & Receiver (server)

Three basic steps

1. Start session
2. Exchange data
3. Complete session

23

## SMTP: Protocol Steps

Open TCP connection to port 25

Server responds with 220 message

Client sends **HELO** command identifying its domain

Client sends 1+ mail messages

- First giving identity information (**MAIL-FROM**, **RCPT-TO**)
- Then sending **DATA** part
- Server responds to each message with 3-digit code

**QUIT** message tells server to close TCP connection

24

## SMTP: Basic Sender Commands

Command	Argument	Meaning
HELLO/HELO	Sender's domain	I'm in this domain (must be first command)
MAIL FROM:	User id	Identify sender
RCPT TO: (1 or more)	User id	Identify recipient(s) (first must follow MAIL (or other starting command))
DATA		Email data follows (must follow RCPT)
<CRLF>.<CRLF>		End of email text (line with just full-stop)
RESET/RSET		Abort current mail
VERIFY/VRFY	User id	Is user ID valid?
QUIT		Sender signing off (last command)

26

## Example: SMTP Session

Often direct connection  
hosts no longer allowed

```
220 finch.doc.ic.ac.uk ESMTP Exim 4.63 Wed, 03 Jan 2006
16:18:37 +0000
helo doc.ic.ac.uk
250 finch.doc.ic.ac.uk Hello columbia.doc.ic.ac.uk
[146.169.7.41]
mail from: prp@doc.ic.ac.uk
250 <prp@doc.ic.ac.uk> is syntactically correct
rcpt to: prp@doc.ic.ac.uk
250 <prp@doc.ic.ac.uk> is syntactically correct
data
354 Enter message, ending with "." on a line by itself
subject: test
1 2 3
.
250 OK id=16178a-0001cK-00
quit
221 finch.doc.ic.ac.uk closing connection
```

25

## SMTP: Basic Receiver Replies

Reply Code	Meaning
220	Service ready
221	OK, I too am closing connection
250	OK, requested mail action completed
354	Start sending me email text, end with <CRLF>.<CRLF>
500	Syntax error – command unrecognised
501	Syntax error in parameters or arguments
503	Bad sequence of commands
550	Requested action not taken: mailbox unavailable
552	Requested mail action aborted: exceeded storage allocation

27



## Example: Delivered Message

```
Return-path: <prp@doc.ic.ac.uk>
Envelope-to: prp@doc.ic.ac.uk
Delivery-date: Wed, 02 Jan 2006 11:42:00 +0000
Received: from [146.169.7.46] (helo=finch.doc.ic.ac.uk
  ident=exim) by falcon.doc.ic.ac.uk with esmtp (Exim
  3.13 #8) id 16178q-0004M7-00 for prp@doc.ic.ac.uk; Wed,
  02 Jan 2006 11:42:00 +0000
Received: from columbia.doc.ic.ac.uk ([146.169.7.41]
  helo=doc.ic.ac.uk) by finch.doc.ic.ac.uk with smtp
  (Exim 3.16 #7) id 16178a-0001cK-00 for
  prp@doc.ic.ac.uk; Wed, 02 Jan 2006 11:41:59 +0000
Subject: test
Message-ID: <E16178a-0001cK-00@finch.doc.ic.ac.uk>
From: prp@doc.ic.ac.uk
BCC:
Date: Wed, 02 Jan 2006 11:41:59 +0000
```

1 2 3

28

## Internet Message Access Protocol (IMAP)

POP only supports downloads of Inbox

IMAP handles multiple folders

- Possible to leave emails on mail server
- Useful when using multiple MUAs or machines

Other features

- Partial downloads of emails/attachments
- Offline mode when unconnected
- Server-side searches

But IMAP complex and adds server load

30

## Post Office Protocol (POP)

SMTP designed for permanently available hosts

- e.g. Internet mail servers
- SMTP delivers mail to mailbox at ISP
- Not usually used to deliver mail to user's desktop

Post Office Protocol allows user access to mailbox

- POP client (MUA) connects to mailbox (POP) server
- Connection to port 110 when “get mail” is requested
- POP authenticates user (with password)
- Mailbox downloaded for processing

29

## File Transfer Protocol (FTP)

Used to exchange files between hosts

- Optimised for efficient transfer of large files
- Separate control and data connections
  - Uses port 21 to initiate control connection
- Data can be
  - fetched by client (GET)
  - sent to server (PUT)

Typical FTP client exposes messages exchanged

- Some command capabilities but not designed to be terminal program

31



```

vm-shell1:~> sftp ec11@shell2.doc.ic.ac.uk
WARNING : Unauthorized access to this system is forbidden and will be
prosecuted by law. By accessing this system, you agree that your actions
may be monitored if unauthorized usage is suspected.

***DO NOT RUN RESOURCE-INTENSIVE PROCESSES ON THE SHELL SERVERS***
Connected to shell2.doc.ic.ac.uk.
[sftp> !ls
Desktop      IMAP_backup  Microsoft    Templates
desktop.ini  KDesktop    Pictures     testftp.txt
Documents    lib          Public       WINDOWS
GNUstep      Macromedia  public_html  WindowsDocuments
[sftp> get testftp.txt
Fetching /homes/ec11/testftp.txt to testftp.txt
/homes/ec11/testftp.txt      0%   0   0.0KB/s  ---:-- ETA
[sftp> put testftp.txt
Uploading testftp.txt to /homes/ec11/testftp.txt
testftp.txt                  100%  0   0.0KB/s   00:00
[sftp> bye
vm-shell1:~>

```

32

## World Wide Web (WWW)

Developed by Tim Berners-Lee (CERN in 1989)

Killer application for the Internet

- Supports transfer and display of documents
- Documents include multimedia content and hyperlinks
- Important lesson for HCI...

Client/server based

- Client (browser): Firefox, Explorer, Opera, lynx, ...
- Web servers: Apache, IIS, ...

34

## SMTP

vs.

## FTP

Information transfer from client to server

Single connection for control/data

Message transfer protocol

- Server file system invisible

ASCII/MIME encoded data

- Data typed with MIME

Multiple “hops” to perform end-to-end transaction

- Spooling when server unavailable

Information transfer in either direction

Separate control and data connections

File transfer protocol

- File system (partly) visible

ASCII/binary data

- Data un-typed

Direct client/server interaction

- Interactive protocol - fails if server unavailable

33

## Web Standards

World Wide Web Consortium (W3C) manages standards:

HyperText Transfer Protocol (**HTTP**)

- Used by browsers to get resources from servers

HyperText Mark-up Language (**HTML**)

- Encoding of data for web pages
- Supports text with images, formatting and hyperlinks

Uniform Resource Locator (**URL**)

- Used to identify links to resources on servers


Uniform Resource Identifier (**URI**)

- More general, newer version of URLs
- URIs can also be location independent (pure names)

35

# Uniform Resource Locators (URLs)

`http://www.doc.ic.ac.uk:80/~prp/v313.html`



URLs can indicate:

- other protocols, e.g. ftp, gopher, telnet, mail, news, file, ...
- other resource types, e.g. image, program, service ...

URLs encode location of resource

36

# Hypertext Transfer Protocol (HTTP)

HTTP server usually listens at TCP port 80

**Stateless, transaction-oriented** protocol

1. Client opens connection to server
2. Request sent from client to server
3. Server responds
4. Connection closed

37

# HTTP Request Message

Request format:

- Request line (method, identifier, version)
- Header (additional info)
- Body (data)

Retrieve web page from server:

```
GET /index.html HTTP/1.0
User-Agent: Mozilla/2.01 (X11; I; IRIX 5.2 IP7)
Accept: image/gif, image/x-bitmap, image/jpeg
/* a blank line */
```

38

# HTTP/1.0 Methods

HTTP 1.0 has **methods** rather than commands

**GET:** Client requests resource from server

- No permanent action on server is implied
- Most common method

**HEAD:** Requests only header of web page

- Useful when deciding if changed

**POST:** Append/send data to named resource

- Used to submit client data from web forms

Others often not implemented:

PUT, DELETE, LINK, UNLINK

39

## HTTP Reply Messages

### Reply format:

Status line (version, code, optional message)

Header (additional info)

Body (data, MIME compatible)

### Sample response:

```
HTTP/1.0 200 OK
MIME-Version: 1.0
Server: CERN/3.0
Date: Wednesday 10-Apr-96 03:59:47 GMT
Content-type: text/html
Content-length: 2168
Last-Modified: Friday 06-Oct-95 07:16:52 GMT
/* a blank line */

/* HTML text of the Web page */
```

40

## HTTP Reply Codes

200	OK
204	No response
301	Moved (permanently)
400	Bad request (e.g. syntax error)
401	Unauthorised
402	Payment required
404	Not found
503	Service unavailable
505	HTTP version unsupported

41

## Stateless and Non-Persistent

### HTTP protocol is stateless

- Server doesn't keep track of client requests
  - Simplifies server design
- But websites would like to keep track of customers

### HTTP/1.0 uses non-persistent connections

- New TCP connection opened for every request
  - Page with 10 images will open 11 TCP connections
- Adds server load and setup costs and delays
- TCP congestion control inefficient for short transfers

42

## Maintaining State: Cookies

### Websites want to identify users

- IP addrs not practical ids for users due to NAT, sharing

### Persistent information through **cookies**

- Allows server to maintain state between HTTP requests
- Sent by web server and stored by browser
  - Name/value pair with expiry time
  - Set-Cookie header in HTTP response
  - Javascript (setCookie/getCookie)

43

## Persistent Connections: HTTP/1.1

Deals with some of HTTP/1.0's performance issues

- **Persistent connections**
  - Client opens TCP connection
  - HTTP requests pipelined through this connection
  - Multiple requests with one TCP open/close overhead
- Other features:  
Better proxy handling; more methods; improved encoding and authentication

Now in widespread use

- Easy transition because backwards compatible

## Further Information On The Web

World Wide Web Consortium (W3C)

- [www.w3.org](http://www.w3.org) website
- Much information, tutorials, standards definitions for HTTP, HTML, XML, DOM, CSS, RDF etc.

Practical guides in the O'Reilly books