

Congratulations! You passed!

Grade received 100% To pass 80% or higher

Go to next item

Week 3 Quiz

Latest Submission Grade 100%

1. If X is the standard notation for the input to an RNN, what are the standard notations for the outputs?

1 / 1 point

- ☐ Y
- ☐ H
- ☒ Y(hat) and H
- ☐ H(hat) and Y

✓ Correct

2. What is a sequence to vector if an RNN has 30 cells numbered 0 to 29

1 / 1 point

- ☒ The Y(hat) for the last cell
- ☐ The average Y(hat) for all 30 cells
- ☐ The total Y(hat) for all cells
- ☐ The Y(hat) for the first cell

✓ Correct

3. What does a Lambda layer in a neural network do?

1 / 1 point

- ☐ Changes the shape of the input or output data
- ☐ There are no Lambda layers in a neural network
- ☐ Pauses training without a callback
- ☒ Allows you to execute arbitrary code while training

✓ Correct

4. What does the axis parameter of tf.expand_dims do?

1 / 1 point

- ☒ Defines the dimension index at which you will expand the shape of the tensor
- ☐ Defines the dimension index to remove when you expand the tensor
- ☐ Defines the axis around which to expand the dimensions
- ☐ Defines if the tensor is X or Y

✓ Correct

5. A new loss function was introduced in this module, named after a famous statistician. What is it called?

1 / 1 point

- ☒ Huber loss
- ☐ Hubble loss
- ☐ Hyatt loss
- ☐ Hawking loss

✓ Correct

6. What's the primary difference between a simple RNN and an LSTM

1 / 1 point

- ☐ LSTMs have multiple outputs, RNNs have a single one
- ☐ In addition to the H output, RNNs have a cell state that runs across all cells
- ☐ LSTMs have a single output, RNNs have multiple
- ☒ In addition to the H output, LSTMs have a cell state that runs across all cells

✔ Correct

7. If you want to clear out all temporary variables that tensorflow might have from previous sessions, what code do you run?

1 / 1 point

- ☐ tf.cache.backend.clear_session()
- ☒ tf.keras.backend.clear_session()
- ☐ tf.keras.clear_session
- ☐ tf.cache.clear_session()

✔ Correct

8. What happens if you define a neural network with these two layers?

1 / 1 point

tf.keras.layers.Bidirectional(tf.keras.layers.LSTM(32)),

tf.keras.layers.Bidirectional(tf.keras.layers.LSTM(32)),

tf.keras.layers.Dense(1),

- ☒ Your model will fail because you need return_sequences=True after the first LSTM layer
- ☐ Your model will fail because you need return_sequences=True after each LSTM layer
- ☐ Your model will fail because you have the same number of cells in each LSTM
- ☐ Your model will compile and run correctly

✔ Correct