

Name: Shah Vinit Vijay

Gene Expression Analysis of Alzheimer's Disease in Hippocampal Tissue Using Microarray Data and Python

Abstract:

Alzheimer's disease (AD) is a progressive neurodegenerative disorder characterized by memory loss and cognitive decline. The hippocampus is one of the earliest and most severely affected brain regions in Alzheimer's disease. This study aimed to analyze gene expression differences between Alzheimer's disease patients and healthy control individuals using publicly available microarray data obtained from the Gene Expression Omnibus (GEO) database (Dataset: GSE5281).

The dataset was processed using Python libraries including Pandas, NumPy, Matplotlib, and SciPy. Hippocampal samples were extracted from the complete dataset based on metadata information. Exploratory Data Analysis (EDA) was performed using histogram and boxplot visualizations after $\log_2$ transformation of expression values to normalize the data distribution. Differential gene expression analysis was carried out using Welch's t-test, and the results were visualized through a volcano plot to identify significantly altered genes.

This project demonstrates the application of computational biology and data science techniques in identifying potential molecular changes associated with Alzheimer's disease. The workflow provides a reproducible approach for analyzing gene expression datasets using Python.

Keywords: Alzheimer's disease, Bioinformatics, Gene Expression, Microarray, GEO, Python, Hippocampus, Differential Expression Analysis

1. Introduction

Alzheimer's disease (AD) is the most common cause of dementia worldwide and is characterized by progressive degeneration of neurons, leading to memory impairment and cognitive dysfunction. One of the earliest brain regions affected in Alzheimer's disease is the hippocampus, which plays a crucial role in learning and memory formation.

With the advancement of high-throughput technologies such as microarrays, researchers can simultaneously measure the expression levels of thousands of genes. Bioinformatics provides computational methods to analyze these large datasets and identify genes that may contribute to disease progression.

The Gene Expression Omnibus (GEO), maintained by the National Center for Biotechnology Information (NCBI), serves as a public repository containing thousands of gene expression datasets. In this project, the publicly available dataset GSE5281 was analyzed to investigate gene expression changes in hippocampal tissue from Alzheimer's disease patients and healthy controls.

2. Objectives

- To download and preprocess a publicly available Alzheimer's disease microarray dataset.
- To extract hippocampal samples from the complete dataset.
- To perform exploratory data analysis using Python.
- To identify differentially expressed genes between Alzheimer's disease and control samples.
- To visualize the results using histogram, boxplot, and volcano plot.
- To understand the application of bioinformatics in disease analysis.

3. Dataset Description

Dataset ID: GSE5281

Database: NCBI Gene Expression Omnibus (GEO)

Platform: Affymetrix Human Genome U133 Plus 2.0 Array (GPL570)

Brain Region Selected: Hippocampus


Total Samples in Original Dataset: 161

Samples Used in This Study: 23 Hippocampus samples

Number of Probes: 54,676

4. Methodology

METHODOLOGY



5. Software & Libraries

Software Used

- Python 3.x
- Google Colab
- Microsoft Excel
- Microsoft Word

Libraries Used


- Pandas
- NumPy
- Matplotlib
- SciPy
- Scikit-learn
- Seaborn

6. Results

6.1 Dataset Summary


- Total Probes: 54,676
- Total Hippocampus Samples: 23

6.2 Histogram




The histogram of $\log_2$ -transformed gene expression values demonstrates an approximately normal distribution after preprocessing. $\log_2$ transformation reduced the influence of extreme expression values and made the data suitable for downstream statistical analysis.

6.3 Boxplot




The boxplot shows that the overall distribution of gene expression values is similar across all hippocampal samples. No major outlier samples were observed, indicating good data quality for comparative analysis.

6.4 Volcano Plot




The volcano plot illustrates differentially expressed probes between Alzheimer's disease and control hippocampal samples. Probes with significant p-values and large $\log_2$ fold changes are located away from the center and above the significance threshold, indicating potential disease-associated genes.

6.5 PCA



Principal Component Analysis separated Alzheimer's disease and control samples into distinct clusters. This suggests that the overall gene expression profiles differ between the two groups. Principal Component Analysis (PCA) was performed to reduce the dimensionality of the gene expression data and visualize sample clustering. The PCA plot demonstrated a noticeable separation between Alzheimer's disease and control hippocampal samples, indicating distinct gene expression patterns between the two groups. Principal Component 1 (PC1) explained 18.49% of the total variance, while Principal Component 2 (PC2) explained 8.09% of the variance.

6.6 Heatmap



The heatmap of the top differentially expressed probes shows distinct expression patterns between Alzheimer's disease and control samples. These differences further support disease-associated alterations in gene expression.

7. Discussion

Gene expression analysis revealed several probes exhibiting significant differential expression between Alzheimer's disease and control hippocampal samples. Log₂ transformation improved data visualization by reducing the influence of extreme expression values. The volcano plot effectively highlighted genes with both statistically significant and biologically meaningful expression changes. These findings demonstrate the usefulness of bioinformatics approaches for studying molecular mechanisms underlying Alzheimer's disease.

8. Conclusion

This project successfully demonstrated the application of bioinformatics techniques for analyzing Alzheimer's disease microarray data. Publicly available GEO datasets were processed using Python to perform exploratory data analysis and differential expression analysis. The workflow included data preprocessing, sample extraction, statistical testing, and visualization of significant gene expression changes. Such computational approaches can assist researchers in identifying potential biomarkers and understanding disease mechanisms.

9. Future Scope

- Perform Gene Ontology (GO) enrichment analysis.
- Conduct KEGG pathway analysis.
- Validate significant genes using RNA-Seq datasets.
- Apply machine learning models for disease prediction.
- Compare Alzheimer's disease with other neurodegenerative disorders.

References

1. **Edgar R, Domrachev M, Lash AE.** *Gene Expression Omnibus: NCBI gene expression and hybridization array data repository.* Nucleic Acids Research. 2002.

2. **Liang WS, et al.** *Gene expression profiles in anatomically and functionally distinct regions of the normal aged human brain.* (GSE5281 dataset publication)
3. National Center for Biotechnology Information (NCBI). Gene Expression Omnibus (GEO).
4. Pandas Documentation
5. NumPy Documentation
6. SciPy Documentation