Task #1

```
#include <iostream>
using namespace std;
int main() {
int age;
double pay;
char section;
cin >> age >> pay >> section;
cout << "age << " " << pay << " " << section <
                                        endl
   "=="
   return 0;
}
```

Task #2

28/4 - 2	28/4 = 7 - 2 = 5
6 + 12 * 2 - 8	24 + 6 = 30 - 8 = 22
4 + 8 * 2	16 + 4 = 20
6 + 17 % 3 - 2	17 % 3 = 2 = 2 + 6 = 8 - 2 = 6
2 + 22 * (9 - 7)	22 * 2 = 44 + 2 = 46
(8 + 7) * 2	15 * 2 = 30
(16 + 7) * % 2 - 1	23 % 2 = 1 - 1 = 0
12 / (10 - 6)	12 / 4 = 3
(19 - 3) * (2 + 2) / 4	16 * (4/4) = 64/4 = 16

int ( ).

Task 3

Correct Answer is = B

units is promoted to float, mass remains a float, and the result of mass * units is a float.

Task # 4

int a, b = 2; float c = 4.2;
then a = b * c;
what value is stored in a?

1) b * c : b(int 2) is promoted to float 2.0, so product is the float 8.4.

2) a is an int and cannot store a fractional part. when a float is assigned to an int, the decimal part is cut off.
So Answer will be 8.

Home Task 2

#include

Task #5

```
#include <iostream>
using namespace std;
int main(){
int qty = 17, salesReps = 4;
double unitsEach;
unitsEach = static_cast<double>(qty)/
salesReps;
cout << unitsEach << endl;
return 0;
}
```

Task #6

```
#include <iostream>
#include <cstdlib>
#include <ctime>
#include <iomanip>
using namespace std;
int main(){
srand(time(0));
int num1 = rand()%900+100;
int num2 = rand()%900+100;
cout << setw(6) << num1 << endl;
cout << "+" << setw(4) << num2 << endl;
cout << "------" << endl;
cout << "press Enter when you are rea
to see the answer...";
```

```
cin.get();
cout << endl;
cout << setw(6) << num1 << endl;
cout << "+ " << setw(4) << num2 << endl;
cout << "------" << endl;
cout << setw(6) << num1+num2 << endl;
return 0;
}
```

Home Task 1 (i) Errors.

```
#include <iostream>
  void main() --> int main()

  cin >> number1;
  cin >> number2;
  Sum = number1 + number2;
  cout << " The sum ---- " << sum;
  return 0;
  cout << " The sum of the two number
       is " << sum << endl;
```

(ii)

- void main() --> int main()
- cin >> number1, number2 -> cin >> number
  >> number2;
- float < static_cast > (number1)
  static_cast < float > (number1)
- cout << quotient;
  return 0;

Home task 2

```
#include <iostream>
using namespace std;
int main() {
int v1 = 28, v2 = 32, v3 = 37, v4 = 24, v5 = 33;
int sum;
double average;
Sum = v1 + v2 + v3 + v4 + v5;
average = sum / 5.0;
cout << "Sum = " << sum << endl;
cout << "Average = " << average << endl;
return 0;
}
```

Lab 3 - Task #1

Code

(invalid)* new* new* new new

```
1  #include <iostream>
2  using namespace std;
3  int main()
4  {
5   int age;
6   double pay;
7   char section;
8   cin >> age >> pay >> section;
9   cout << age << " " << pay << " " << section
   << endl;
10  return 0;
11  }
```

Output

```
20 1500.75 C
20 1500.75 C
```

Sample run of the same code

Lab 3 - Task #5

Code

(invalid)* **new*** new* new new

```cpp
#include <iostream>
using namespace std;
int main()
{
 int qty = 17, salesReps = 4;
 double unitsEach;
 unitsEach = static_cast<double>(qty) /
salesReps;
 cout << unitsEach << endl;
 return 0;
 }
```

Output

```
4.25

[Program finished]
```

Lab 3 - Task #6

Code

(invalid)* **new*** new* new new

```cpp
#include <iostream>
#include <cstdlib>
#include <ctime>
#include <iomanip>
using namespace std;
int main()
{
 srand(time(0));
 int num1 = rand() % 900 + 100;
 int num2 = rand() % 900 + 100;
 cout << setw(6) << num1 << endl;
 cout << "+ " << setw(4) << num2 << endl;
 cout << "------" << endl;
 cout << "Press Enter when you are ready
to see the answer...";
 cin.get();
 cout << endl;
 cout << setw(6) << num1 << endl;
 cout << "+ " << setw(4) << num2 << endl;
 cout << "------" << endl;
 cout << setw(6) << num1 + num2 << endl;
 return 0;
 }
```

Output

```
   902
+  180
------
Press Enter when you are ready
to see the answer...
   902
+  180
------
  1082
```

Sample run (random numbers differ each run)

Lab 3 - Home Task #2

Code

(invalid)* **new*** new* new new

```cpp
#include <iostream>
using namespace std;
int main()
{
 int v1 = 28, v2 = 32, v3 = 37, v4 = 24, v5 = 33;
 int sum;
 double average;
 sum = v1 + v2 + v3 + v4 + v5;
 average = sum / 5.0;
 cout << "Sum = " << sum << endl;
 cout << "Average = " << average << endl;
 return 0;
 }
```

Output

