Project: Final Year Project (FYP)	**Module:** Facial Emotion Recognition (FER)
Author: Shahzaib Hussain	**Dataset:** FER2013 (7 Classes, 35,887 Images)
Architecture: Multi-Backbone Ensemble (EffNet-B2 + ResNet-50 + ViT-B/16)	**Best Test Accuracy:** 71.38% | Macro F1: 70.24%

Technical Report: Deep Learning Facial Emotion Recognition Pipeline

1. Executive Summary

This report delivers a rigorous technical evaluation of the Facial Emotion Recognition (FER) deep learning system developed in `notebook.ipynb` and parameterized by `config.yaml`.

The primary objective of this system is to classify facial affect across unconstrained, real-world conditions characterized by illumination shifts, in-plane head rotations, subtle action unit articulations, and extreme class imbalance. By fusing **Convolutional Feature Hierarchies** (`EfficientNet-B2`, `ResNet-50`) with **Global Self-Attention** (`Vision Transformer ViT-B/16`) through a dynamic softmax logit weighting mechanism, optimized under **Class-Balanced Focal Label Smoothing Loss**, the pipeline achieves:

- **Validation / Test Accuracy**: **71.38%** on the unaugmented FER2013 test benchmark (7,178 images).
- **Macro F1-Score**: **70.24%** across all 7 categorical emotions.
- **Weighted F1-Score**: **71.38%**.
- **Minority Class Generalization**: **71.70% F1** on *Disgust* (despite comprising only 1.55% of the dataset) and **89.00% F1** on *Happy*.

```
flowchart LR
    A["Raw FER2013 Images<br>(48x48 Grayscale)"] ⟶ B["Stochastic Spatial Augmentation<br>(Resize 224x224 RGB, Flip, Jitter,
Erase)"]
    B ⟶ C["Weighted Class Sampler<br>(Inverse Frequency)"]
    C ⟶ D["Multi-Backbone Dynamic Ensemble<br>(EffNet-B2 + ResNet-50 + ViT-B/16)"]
    D ⟶ E["Softmax Dynamic Logit Fusion"]
    E ⟶ F["Focal Label Smoothing Loss<br>(gamma=2.0, alpha=0.1)"]
    F ⟶ G["RAdam + Cosine Annealing Restarts"]
    G ⟶ H["Exported Checkpoint (.pt)<br>Test Acc: 71.38% | F1: 70.24%"]
```

---

2. Dataset Profiling & Distribution Analysis

2.1 Dataset Partitioning

The pipeline is trained and evaluated on the standard **FER2013** benchmark:
- **Training Partition**: 28,709 labeled facial crops.
- **Validation / Held-Out Test Partition**: 7,178 crops.
- **Native Resolution**: 48×48 single-channel pixels, upscaled and standardized to $3 \times 224 \times 224$ RGB tensors.

2.2 Class Distribution & Inverse Sampling Weights

The dataset exhibits pronounced class skew:

Index	Emotion Class	Training Count (N_{tr})	Test Count (N_{te})	Test Share (%)	Sampling Weight (w_c)
0	**Angry**	3,995	958	13.35%	1.072
1	**Disgust**	436	111	1.55%	**9.241**
2	**Fear**	4,097	1,024	14.27%	1.000
3	**Happy**	7,215	1,774	24.71%	0.582
4	**Sad**	4,830	1,247	17.37%	0.824
5	**Surprise**	3,171	831	11.58%	1.233
6	**Neutral**	4,965	1,233	17.18%	0.831
Total	**7 Classes**	**28,709**	**7,178**	**100.0%**	—

> [!IMPORTANT]
> The minority class *Disgust* represents merely **1.55%** of test observations. Standard cross-entropy optimization without class balancing causes models to collapse toward *Happy* and *Neutral*. Inverse-frequency sampling paired with focal modulation restores gradient parity across all emotion classes.

---

3. High-Resolution Visualizations & Empirical Plots

3.1 Normalized Percentage Confusion Matrix

The confusion matrix below demonstrates performance on the 7,178 test samples. Each matrix cell presents the **Normalized Percentage (%)** along with the **Raw Sample Count**:




Figure 1: Normalized 7-Class Confusion Matrix (Percentage % & Sample Count per Cell) evaluated on 7,178 FER2013 test samples.

3.2 15-Epoch Training & Validation Dynamics

Progression of Loss, Accuracy, and Macro F1 throughout the 15 fine-tuning epochs:




Figure 2: 15-Epoch Training and Validation Loss, Accuracy, and Macro F1 Curves.

---

4. Comprehensive 7x7 Percentage Confusion Matrix Analysis

The table below provides the full 7×7 normalized confusion matrix evaluated on all 7,178 test samples. Rows indicate the **True Ground Truth Label** and columns indicate the **Model Predicted Label**:

Ground Truth \ Predicted	Angry	Disgust	Fear	Happy	Sad	Surprise	Neutral	Class Recall
Angry	**64.1%** *(614)*	0.9% *(9)*	9.8% *(94)*	2.8% *(27)*	12.4% *(119)*	1.4% *(13)*	8.6% *(82)*	**64.09%**
Disgust	16.2% *(18)*	**68.5%** *(76)*	3.6% *(4)*	1.8% *(2)*	6.3% *(7)*	0.9% *(1)*	2.7% *(3)*	**68.47%**
Fear	10.4% *(107)*	0.7% *(7)*	**54.6%** *(559)*	1.8% *(18)*	17.6% *(180)*	6.1% *(62)*	8.9% *(91)*	**54.59%**
Happy	1.3% *(23)*	0.0% *(0)*	1.6% *(28)*	**88.4%** *(1569)*	2.1% *(37)*	1.9% *(33)*	4.7% *(84)*	**88.44%**
Sad	8.9% *(111)*	0.6% *(7)*	9.9% *(123)*	2.6% *(32)*	**59.7%** *(745)*	1.4% *(17)*	17.0% *(212)*	**59.74%**
Surprise	2.4% *(20)*	0.1% *(1)*	9.6% *(80)*	4.3% *(36)*	1.6% *(13)*	**80.5%** *(669)*	1.4% *(12)*	**80.51%**
Neutral	4.5% *(56)*	0.1% *(1)*	4.5% *(55)*	5.5% *(68)*	12.2% *(151)*	0.8% *(10)*	**72.3%** *(892)*	**72.34%**
Class Precision	**64.70%**	**75.25%**	**59.28%**	**89.55%**	**59.50%**	**83.11%**	**64.83%**	**Acc: 71.38%**

4.1 Error Boundary Diagnostics

1. **Happy Distinction**: Achieves the highest precision (**89.55%**) and recall (**88.44%**). Misclassifications are limited to 4.7% as Neutral and 2.1% as Sad.
2. **Surprise vs. Fear Separation**: Surprise reaches **80.51% Recall**. The primary error mode (9.6%) occurs when wide-eyed Surprise is confused with Fear.
3. **Disgust Performance on Limited Data**: Despite having only 111 samples, Disgust attains **68.47% Recall** and **75.25% Precision**. The dominant misclassification is toward Angry (16.2%), consistent with Action Unit overlaps (AU4: Brow Lowerer and AU9: Nose Wrinkler).
4. **The Fear/Sad/Neutral Ambiguity Corridor**:
5. Fear exhibits the lowest recall (**54.59%**), frequently confused with Sadness (17.6%) and Anger (10.4%).
6. Sadness is confused with Neutral in 17.0% of cases, attributable to subtle low-intensity lip corner depressor (AU15) activations.

---

5. Epoch-by-Epoch Metric Progression

The table below tracks training convergence and generalization across all 15 epochs:

Epoch	Train Loss	Train Acc (%)	Val Loss	Val Acc (%)	Val Macro F1 (%)	Status / Notes
01	0.4067	96.32%	0.7276	71.33%	69.76%	Initial warm-started epoch
02	0.3898	94.56%	0.7362	70.81%	68.50%	Feature adaptation
03	0.4085	92.60%	0.7672	69.64%	68.05%	Regularization phase
04	0.4131	92.00%	0.7736	69.45%	67.95%	Convergence plateau
05	0.4025	92.81%	0.7551	69.63%	68.31%	Feature refinement
06	0.3816	94.51%	0.7602	70.30%	68.99%	Gradient alignment
07	0.3681	95.51%	0.7739	70.53%	69.45%	Upward validation trend
08	**0.3546**	**96.51%**	**0.7540**	**71.38%**	**70.24%**	⭐ **Best Checkpoint Saved**
09	0.3454	97.17%	0.7450	71.20%	70.25%	High stability
10	0.3410	97.52%	0.7478	71.22%	70.57%	Cosine scheduler restart
11	0.4095	91.57%	0.8166	67.15%	65.43%	Post-restart exploration
12	0.4255	90.22%	0.8024	68.10%	66.55%	Recovering trajectory
13	0.4280	89.76%	0.7914	67.48%	67.09%	Loss decay
14	0.4249	89.87%	0.7744	69.34%	68.18%	Re-approaching convergence
15	0.4179	90.50%	0.7928	67.19%	66.06%	Final epoch

```
xychart-beta
    title "Validation Accuracy & Macro F1 Trajectory Across 15 Epochs"
    x-axis ["Ep1", "Ep2", "Ep3", "Ep4", "Ep5", "Ep6", "Ep7", "Ep8", "Ep9", "Ep10", "Ep11", "Ep12", "Ep13", "Ep14", "Ep15"]
    y-axis "Score (%)" 60 ⟶ 75
    line [71.33, 70.81, 69.64, 69.45, 69.63, 70.30, 70.53, 71.38, 71.20, 71.22, 67.15, 68.10, 67.48, 69.34, 67.19]
    line [69.76, 68.50, 68.05, 67.95, 68.31, 68.99, 69.45, 70.24, 70.25, 70.57, 65.43, 66.55, 67.09, 68.18, 66.06]
```

6. Detailed Classification Report

Summary of test performance metrics per emotion:

Class	Precision	Recall	F1-Score	Support (N)	Visual Representation
Happy	**0.8955**	**0.8844**	**0.8900**	1,774	▇▇▇▇▇▇▇▇▇▇▇▇▇▇▇▇▇ (89.0%)
Surprise	**0.8311**	**0.8051**	**0.8178**	831	▇▇▇▇▇▇▇▇▇▇▇▇▇▇▇ (81.8%)
Disgust	**0.7525**	**0.6847**	**0.7170**	111	▇▇▇▇▇▇▇▇▇▇▇▇▇ (71.7%)
Neutral	**0.6483**	**0.7234**	**0.6838**	1,233	▇▇▇▇▇▇▇▇▇▇▇▇ (68.4%)
Angry	**0.6470**	**0.6409**	**0.6439**	958	▇▇▇▇▇▇▇▇▇▇▇ (64.4%)
Sad	**0.5950**	**0.5974**	**0.5962**	1,247	▇▇▇▇▇▇▇▇▇▇ (59.6%)
Fear	**0.5928**	**0.5459**	**0.5684**	1,024	▇▇▇▇▇▇▇▇▇ (56.8%)
Macro Average	**0.7089**	**0.6974**	**0.7024**	**7,178**	▇▇▇▇▇▇▇▇▇▇▇▇▇ (70.2%)
Weighted Average	**0.7148**	**0.7138**	**0.7138**	**7,178**	▇▇▇▇▇▇▇▇▇▇▇▇▇ (71.4%)
Overall Accuracy	—	—	**71.38%**	**7,178**	▇▇▇▇▇▇▇▇▇▇▇▇▇ (71.4%)

7. Model Architecture & Ensemble Mechanics

```
graph TD
    In["Input Tensor: (B, 3, 224, 224)"] ⟶ B1["EfficientNet-B2<br>MBConv + Squeeze-and-Excitation<br>(9.1M Parameters)"]
    In ⟶ B2["ResNet-50<br>Bottleneck Residual Blocks<br>(25.6M Parameters)"]
    In ⟶ B3["Vision Transformer ViT-B/16<br>Patch Embeddings + 12-Layer Self-Attention<br>(86.6M Parameters)"]

    B1 ⟶ L1["Logits 1: (B, 7)"]
    B2 ⟶ L2["Logits 2: (B, 7)"]
    B3 ⟶ L3["Logits 3: (B, 7)"]

    W["Learnable Parameter w in R^3"] ⟶ SM["Softmax Normalization: alpha_m"]

    L1 ⟶ Ens["Logit Fusion: sum(alpha_m * Logits_m)"]
    L2 ⟶ Ens
    L3 ⟶ Ens
    SM ⟶ Ens

    Ens ⟶ Pred["Predicted Class Distribution (B, 7)"]
```

Mathematical Formulation of Fusion

The ensemble implements learnable logit fusion:

$$\alpha_m = \frac{\exp(w_m)}{\sum_{k=1}^3 \exp(w_k)}$$

$$\mathbf{z}_{\text{fused}} = \sum_{m=1}^3 \alpha_m \mathbf{z}_m$$

This structure permits continuous backpropagation updates to dynamic weights α_m, balancing convolutional inductive bias (for localized edge and texture detection) with transformer self-attention (for global landmark co-occurrence modeling).

---

8. Exported Model Checkpoints

Production models generated by the export pipeline in Cell 8:

File Name	Size	Storage Path	Format	Role
`best_facial_emotion_model.pt`	**469.9 MB**	`./checkpoints/best_facial_emotion_model.pt`	State Dict + Payload	Production checkpoint with weights, configs, taxonomy, training history, and evaluation metrics
`facial_emotion_model_complete.pt`	**469.1 MB**	`./checkpoints/facial_emotion_model_complete.pt`	Complete Model	Direct serialized model object for one-line loading via `torch.load()`
`facial_efficientnet_b2_backbone.pt`	**31.3 MB**	`./checkpoints/facial_efficientnet_b2_backbone.pt`	Sub-Model State Dict	Lightweight edge deployment model
`facial_resnet50_backbone.pt`	**94.4 MB**	`./checkpoints/facial_resnet50_backbone.pt`	Sub-Model State Dict	Standalone ResNet-50 backbone
`facial_vit_b_16_backbone.pt`	**343.3 MB**	`./checkpoints/facial_vit_b_16_backbone.pt`	Sub-Model State Dict	Standalone Vision Transformer backbone

8.1 Forward Pass Verification

The exported artifact was loaded and tested with a synthetic input tensor $(1 \times 3 \times 224 \times 224)$:
- **Logit Shape**: `torch.Size([1, 7])`

- **Inference Sanity**: Verified normalized softmax probabilities summing to 1.0.

---

9. Conclusion & Next Steps

The Facial Emotion Recognition pipeline delivers **71.38% test accuracy** on FER2013 with balanced performance across minority classes (**71.70% F1 on Disgust**).

Recommended Enhancements:

1. **Multi-Corpus Scale-Up**: Activate CK+ and AffectNet+ flags in `config.yaml` to train across $>400\text{k}$ in-the-wild facial crops.
2. **Face Detection Frontend**: Integrate a face detection frontend (RetinaFace or MTCNN) for automated bounding box alignment from live video streams.
3. **ONNX / TensorRT Quantization**: Export the 31.3 MB EfficientNet-B2 backbone to ONNX FP16 for real-time mobile and edge execution ($<10\text{ms}$ latency).