Supplementary replication notes

The main manuscript states the score limits, vocabulary grouping result and headline experiments. This supplement contains repair accounting, solver details and optional controls. Current results are mapped in the artifact's CLAIMS.md. Raw datasets follow their owners' distribution terms; aggregate confusion matrices and fold manifests accompany the code.

Historical protocols

The archived CICIDS2017 within-day protocol takes a last-30-percent row-order holdout separately within each day and label. It has no verified clock-time cutoff in the local MachineLearningCVE release. Its unweighted forest macro F1 is 0.78692. It is retained for archive verification and is not interpreted as future-traffic performance. The archive also contains shuffled UNSW-NB15 CV and deduplicated versions. Their test cohorts differ, preventing causal attribution by raw score subtraction.

Optional confidence rejection

The seed-42 forests for three deterministic UNSW pairs replace predictions with maximum class probability below 0.5 by rejection. This threshold was fixed without test tuning. In fine-grained scoring, rejection misses the true class without adding a false positive to a scored class. The ceiling remains 0.8. When the two withheld true labels merge to one unknown class and rejection predicts that class, nine labels are scored and the ceiling becomes one.

Table 1: Seed-42 rejection controls. The unknown column scores a different target.

Withheld labels	Closed set	Abstention	Unknown
Analysis + Backdoor	0.47067	0.45535	0.52624
Exploits + Generic	0.31378	0.32332	0.42663
Shellcode + Worms	0.40321	0.39132	0.43927

Rejection improves fine-grained macro F1 in one condition and lowers it in two. A deployable confidence rule can reject covered rows and accept unavailable rows, unlike a counterfactual that knows exactly which rows are unavailable.

Uncertainty targets

Five forest seeds describe variation in fitting on the same training and test partitions. Pair-grid summaries exhaust the 36 pairs of nine attack labels and describe that finite population. They share test rows and are not independent network samples. Gas and NSL row-bootstrap intervals use 500 multinomial resamples of fixed-prediction confusion counts, keeping the original scored label inventory. This resampling assumes exchangeable rows and does not correct within-batch temporal dependence. The intervals condition on the selected batches or partition and do not estimate uncertainty across independent networks. Very rare classes can be absent from a bootstrap draw and retain zero F1 under this fixed-inventory calculation.

Artifact boundaries

The count API accepts an optional allowed-output flag specifying the legal vocabulary, which may include labels absent from training. Threshold summaries are hard ceilings only when that output restriction is enforced. Train-only labels must be included for exact and union oracles. The Dockerfile is a build recipe, not a verified container image. Public hosting, a permanent DOI, an external anonymous mirror and independent reproduction require separate verification.

Exact vocabulary-oracle results

Vocabulary oracle

Correcting a wrong prediction on a row whose true label is legal cannot reduce macro F1: it adds a true positive to that class and removes a false positive from the old destination. After these repairs, let $U_f = \sum_{k \notin V_f} n_{fk}$ be the unavailable rows and a_{fk} their destination counts. They satisfy $a_{fk} \geq 0$, $a_{fk} = 0$ outside V_f, and $\sum_k a_{fk} = U_f$. With $a_k = \sum_f a_{fk}$, the maximum legal score is

$$O = \max_a \frac{1}{\mid S \mid} \sum_{k \in S} \frac{2m_k}{n_k + m_k + a_k}.$$

The oracle knows test truth and can choose destinations freely. It bounds a score; it does not estimate achievable deployment performance. The gap $O - F$ is the remaining score shortfall, not a causal estimate of model quality.

Theorem 1. Vertex allocation.

An optimum repairs all available rows and sends all unavailable rows in each fold to one legal destination. For $m_k > 0$, the second derivative of $2m_k/(n_k + m_k + a)$ is $4m_k/(n_k + m_k + a)^3 > 0$; a zero-$m_k$ term is constant. The objective is convex on a product of allocation simplexes. A maximum has a vertex representative, and each such vertex assigns an integer number of rows to one destination per fold.

Let $g_k(a) = 2m_k/(n_k + m_k) - 2m_k/(n_k + m_k + a)$ on S, and zero outside S. A fold can avoid any loss from C exactly when it permits a destination outside S or with $m_k = 0$. Consequently $O = C$ exactly when every unavailable fold has such a destination. For a single unavailable fold,

$$O = C - \min_{k \in V_f} g_k(U_f) / \mid S \mid .$$

This also applies to any number of unavailable folds with one common vocabulary after summing their row counts. For a general input, set $c_f = \min_{k \in V_f} g_k(U_f) / \mid S \mid$. Concavity, monotonicity and $g_k(0) = 0$ give

$$\max(0, C - \sum_f c_f) \leq O \leq C - \max_f c_f.$$

Sending each fold to its own minimum-loss destination proves the lower bound by subadditivity; any allocation incurs at least each individual minimum loss. These polynomial-time bounds remain available when exact search reaches its budget.

Complexity and repeated vocabularies

Theorem 2. General hardness.
Computing the exact oracle for arbitrary vocabularies is NP-hard. Reduce from Set Cover with K candidate sets. Give each set a destination label and one coverable anchor row. For each element create $L = 2K + 1$ rows of an unavailable label in a fold permitting exactly the sets containing that element. Assume each element belongs to a set. Theorem 1 assigns each element to one set. Occupied destinations form a cover. If their number is q, the unaveraged loss is $\sum_{a_k>0} a_k/(2 + a_k)$, and

$$q - 1 < qL/(L + 2) \le \sum_{a_k>0} a_k/(2 + a_k) < q.$$

The intervals are disjoint, so the exact optimum identifies the minimum cover size. The construction is polynomial. This is a worst-case result, not a claim about difficulty on a named benchmark.

Theorem 3. Parameterization by destination labels.
If no row is unavailable, $O = C = 1$. Otherwise, if the union of legal destinations in unavailable folds contains q labels, there is an exact algorithm using at most

$$\prod_{j=1}^{q} j^{\binom{q}{j}} \le q^{2^q-1}$$

candidate allocations and polynomial work per candidate. Group folds by identical vocabulary V and sum their unavailable counts. The Minkowski sum of their simplexes is the simplex with that summed mass. Convexity again gives an optimum placing the whole group at one destination. There are at most $2^q - 1$ nonempty vocabularies, proving the bound and fixed-parameter tractability in q. The candidate bounds for $q = 2, 3, 4$ are 2, 24 and 20,736. The growth is rapid; this result does not promise efficient exact search for large q.

Both enumeration and branch-and-bound implement grouping. Branch-and-bound uses the partial score before remaining false positives are charged as a completion upper bound, starts from a feasible greedy assignment and merges equivalent states. A node-budget exception certifies no optimum. Fixed uncovered-fold count instead gives an XP enumeration bound; it is a different parameterization. An independent pseudo-polynomial count-grid MILP and solver checks are in the supplement.

Other scoring conventions

If a scorer infers the union of true and predicted labels, let W be the activated outputs outside S. Its denominator is $\mid S \mid + \mid W \mid$, while those additional classes contribute zero. The coverage ceiling remains valid. Vertex allocation and vocabulary grouping still admit an optimum: fix the outside labels used by an optimum, maximize its convex numerator over those decisions, and take a vertex. Activating a subset of those outside labels can only improve the denominator.

If U_S bounds the oracle after restricting vocabularies to S, use zero when this restriction is infeasible. With outside outputs available, a valid bound is $\max\{U_S, C \mid S \mid /(\mid S \mid + 1)\}$. Otherwise

use U_S. The software offers exact support and union objectives. A weighted average of fold scores instead has ceiling $\sum_f \alpha_f C_f$ using each fold's scored inventory. For CICIDS2017 the equal-fold ceiling is 0.39000, distinct from pooled 0.06667.

Abstention scored as a miss without a false positive reaches C: repair available rows and abstain on the rest. A scored unknown class changes both the target and the allowed decisions and needs a new audit. Neither convention permits exact recognition of an unavailable fine-grained label.

Repair accounting

The seed-42 NSL forest destination-routing control illustrates a scoring-convention effect. Routing unavailable rows to the train-only label `spy` changes positive-test-support macro F1 from 0.25456 to 0.26914 and inferred-union macro F1 from 0.24804 to 0.25569; the true-positive count remains 16,287. The `spy` destination does not add a false positive to a positive-test-support class, while it is an extra zero-F1 class under inferred-union scoring. This counterfactual uses true availability and does not represent improved recognition or a deployable unknown-attack rule.

Let F be the observed full score. Let R repair all available rows while preserving the model's destinations for unavailable rows. Let Q remove false positives contributed by unavailable rows while preserving covered-row errors; unavailable rows still contribute misses for their true labels. With C the coverage ceiling and O the vocabulary oracle,

$$C - F = (C - O) + (O - R) + (R - F).$$

C-O is the unavoidable vocabulary loss. O-R is excess destination loss after available rows are made correct. R-F is the recoverable score from repairing those rows at the original unavailable destinations. We call C-R the combined destination penalty; it includes unavoidable and model-dependent parts. It is not all forced by the split. Repairing in the opposite order gives

$$C - F = (C - Q) + (Q - F).$$

In general Q-F differs from C-R. Both are exact accounting identities, not order-free causal attributions. The released three-part table retains its seed and withholding condition. Historical forced_assignment_gap fields mean C-R only. Covered-only macro F1 is a separate quantity: it removes unavailable rows and uses the covered subset's positive-support inventory. It is neither R nor Q.

MILP and numerical checks

Binary variables x(f,k) choose one destination per unavailable fold. Set a(k) equal to the sum of U(f)x(f,k). Binary variables z(k,t) select a total t from zero through the maximum possible false-positive count at k. Enforce one selected total and equality between that total and a(k). Minimize the sum of g(k,t)z(k,t)/|S|. This count-grid formulation is pseudo-polynomial in row totals and implemented for positive-support scoring. It is not a scalable claim for arbitrary large traffic datasets.

The grouped solver checks use synthetic shapes with 6, 30, 60 and 100 unavailable folds, six destination labels, three choices per fold, and counts from one to five. At 10,000 nodes, branch-

and-bound certifies the six-fold case and stops uncertified on the larger inputs. The independent MILP certifies the 30-fold value 0.67337 within solver tolerance. Ten-second runs on larger inputs retain feasible/dual bounds when available; a missing incumbent is not an optimum. Current statuses and runtimes are in results/solver_shapes_grouped.csv. Enumeration and branch scores use floating-point arithmetic; exhaustive checks compare at tolerance 1e-12. They do not supply arbitrary-precision certificates.

Digits fractional-coverage control

The supplementary digits control uses scikit-learn's 1,797 images, five stratified folds with shuffle seed 42 and a 100-tree forest. Digits zero and one are withheld from training in the first two folds while retaining every test row. Their covered fractions are 106/178 and 110/182. The other eight labels are fully covered. Coverage ceiling 0.94999 and exact oracle 0.92176 differ by 0.02824 when rounded from full precision; observed macro F1 is 0.89253. This is a constructed protocol check rather than a natural benchmark claim.

External source compatibility checks

The historical targeted audit is separate from the frozen candidate sample. Nuako's public project report [1] uses a capped CICIDS2017 Friday cohort with 5,688 benign and 30,704 unavailable attack rows. Its support-scored ceiling is 0.25. Reported macro F1 of 0.0435 cannot be assigned to that convention from the displayed counts and benign recall; a larger scored inventory is possible. This is unresolved scorer compatibility, not a verified score violation. Yang et al.'s day-holdout study [2] and Alnattaf and Mahmood's chronological study [3] use binary targets. Ahmed et al. [4] harmonize seven shared labels in cross-year evaluation, giving legal ceiling one. These verified 2026 publisher records are identified in audit/reference_verification.csv. Web project pages are labeled as technical reports, not peer-reviewed articles. A gas-protocol comparison with target calibration and the CICDDoS2019 schedule remain unresolved; neither is counted as a violation.

References

[1] F. A. Nuako, "Network intrusion detection and traffic analysis." Available: https://www.pcboss.me/projects/network-intrusion-detection/

[2] Y. Yang, J. Yuan, M. Gao, M. Chen, D. Gong, and L. Gao, "A leakage-aware evaluation of a multi-scale attention temporal convolutional network for binary network intrusion detection," *Mathematics*, vol. 14, no. 18, p. 3357, 2026, doi: 10.3390/math14183357.

[3] Y. Alnattaf and H. F. Mahmood, "A hybrid eBPF/ML intrusion detection system with two-model heterogeneous ensemble learning and real-time gateway-mode network blocking," *Journal of King Saud University Computer and Information Sciences*, 2026, doi: 10.1007/s44443-026-01098-3.

[4] W. Ahmed, M. A. Rahaman, P. Roy, and P. Alam, "The dashboard says perfect: A systematic audit of label-free model monitoring and test-time adaptation under temporal distribution shift in network intrusion detection," *Frontiers in Artificial Intelligence*, vol. 9, p. 1928858, 2026, doi: 10.3389/frai.2026.1928858.