Label Coverage Bounds Pooled Macro F1: A Reporting Diagnostic for Closed-Set IDS Benchmarks

Abstract We present a pre-fit audit of the label outputs a benchmark split permits. On the original-label NSL-KDD split, 17 of 38 test labels are unavailable to a training-restricted classifier, giving a macro-F1 ceiling of 0.55263. A corrected CICIDS2017 Friday holdout has five supported labels but only one available in training, giving a fine-label ceiling of 0.20. Binary detection scores vary across capped fitting settings, illustrating that the fine-label ceiling and attack detection answer different questions; these settings are not a model ranking. A benign-only UNSW-NB15 detector likewise has a binary ceiling of one and mean attack recall of 0.181. We re-score ten confusion matrices from one openly released study and find its reported score compatible with a ceiling of one. No incompatible published score is verified. These results motivate reporting legal outputs and scoring conventions but do not establish field-wide impact. Code, counts and split manifests accompany the paper.

Macro F1, label coverage, benchmark protocols, intrusion detection, reproducibility

Introduction

A low benchmark score can describe two different failures: a model misclassifies a label it can output, or the evaluation asks it to name a label outside its output vocabulary. These failures have different remedies. Better features or fitting might address the first. They cannot address the second without changing the model's permitted decisions.

NSL-KDD provides a natural example: 21 of the 38 fine-grained labels in its official test set occur in training. A classifier restricted to training labels therefore has a positive-test-support ceiling of 21/38 (0.55263). CICIDS2017 leave-one-day-out is more extreme: its 14 attack labels are each confined to one capture day, giving a 15-class ceiling of 1/15. The attack schedule is known; this paper records the scoring consequence under an explicit label inventory.

The coverage inequality follows directly from recall and precision; we do not present it as a new theory of F1. The contribution is an operational audit for pooled scoring when legal vocabularies differ across folds: it computes the fraction of each class's test rows that can be named, makes the chosen output inventory explicit, and distinguishes training-restricted models from global-head and open-set tasks. We add a paired label-resolution analysis on NSL-KDD, a benign-only anomaly baseline, and a map of the audit to published evaluation practice. The broader search has not established a published score that violates its legal-output ceiling, so impact on prior reported conclusions remains unproven. An optional vocabulary oracle accounts for false positives sent to legal destinations; its proofs and computational details are in the supplement.

The empirical examples illustrate how the same fixed predictions score under different label inventories. These are different tasks, so score differences are descriptive rather than evidence that one model is better. In a published NSL-KDD study, Ayantayo et al. describe 17 test-only fine-grained attack types, map the task to five broad categories, and also construct a test subset without those unseen subtypes [1]. Under that five-category output space, the five categories are available in training and the ceiling is one; the reported category task does not establish fine-grained attribution of unseen subtypes. This is a verified example of target resolution in published practice, not an incompatible score. Our broader frozen screen still establishes no published score conflict.

Related Work

Security evaluations can become misleading when the sampling protocol answers a different question from the intended deployment setting [2], [3]. Dataset surveys and CICIDS2017 audits document traffic-generation, feature and labeling limitations [4], [5], [6]. We condition on the released labels and a declared partition; the present analysis neither repairs those datasets nor removes their other biases.

Macro F1 itself requires an explicit definition. Averaging class F1 differs from taking the harmonic mean of macro precision and recall [7]. Pooling out-of-fold predictions also differs from averaging fold scores [8]. Work on classification metrics studies prevalence and prediction bias [9], [10], while confusion-matrix objectives can guide learning algorithms [11]. Our optimization uses the true test labels to bound a fixed evaluation cohort; it is not a learning procedure.

Label shift concerns changed class priors under assumptions on conditional feature distributions [12]. A missing legal output is a separate constraint: reweighting cannot create that output. Open-set recognition and selective prediction add unknown or reject decisions [13], [14], [15], [16]. Generalized zero-shot learning permits unseen outputs through side information and evaluates seen and unseen recognition separately [17]. These settings explain why absence from training alone is insufficient to establish zero recall. Temporal and spatial discipline, as in TESSERACT [18], remains necessary even when every legal label is covered.

A Score Limit from Legal Outputs

Let f index folds, T_f their training labels, and $V_f \neq \varnothing$ their legal output vocabularies. Assume a nonempty pooled test cohort. Every test row receives one label in V_f. We allow V_f to contain labels absent from T_f; training-restricted classifiers are the special case $V_f = T_f$. Write n_{fk} for fold-level test support and define

$$S = \left\{ k : \sum_f n_{fk} > 0 \right\}, \quad n_k = \sum_f n_{fk},$$
$$m_k = \sum_f n_{fk} \mathbf{1}\{k \in V_f\}, \quad \rho_k = m_k / n_k \ (k \in S).$$

The primary metric pools confusion counts and averages F1 over positive-test-support labels S. We also report the inferred union of true and predicted labels, the default label inventory when

scikit-learn's `f1_score` is called without an explicit `labels` argument. These conventions can differ when a legal output has no test support. Train-only or other output-only labels remain in the vocabulary input for both calculations.

Proposition 1. Coverage ceiling.
Every legal prediction vector satisfies

$$F \le C = \frac{1}{|S|} \sum_{k \in S} \frac{2\rho_k}{1 + \rho_k}.$$

Proof. A true positive needs a legal true label, hence $TP_k \le m_k$ and recall is at most ρ_k. Precision is at most one. Substitution in the increasing harmonic-mean expression for F1 proves the result. Equality needs every available row correct and no false positives entering a positive-m_k class.

Support-weighted F1 replaces $1/|S|$ with $n_k / \sum_j n_j$. Micro F1, with all true and predicted labels included, equals accuracy and is at most $\sum_k m_k / \sum_k n_k$. Balanced accuracy is at most $|S|^{-1} \sum_k \rho_k$. These are deterministic cohort limits, not confidence intervals.

For leave-one-group-out using all remaining groups as training and $V_f = T_f$, a label in one group has $\rho_k = 0$; a label in two or more groups has $\rho_k = 1$. Thus fractional pooled coverage requires another structure, such as a forward or restricted-window protocol. This explains both the severity and the simple form of the CICIDS2017 result.

Legal outputs and limited training support

A global head permitting every test label has $C = 1$, including when some labels have no training examples. This is the correct legal ceiling. It is not evidence that the missing classes can be learned. There is no distribution-free improvement based only on training counts: a feature can encode its correct global label, and a fixed classifier can decode it perfectly without any examples of that label. Conversely, the same counts can accompany uninformative features.

For sensitivity analysis, define $V_f(\tau) = \left\{k : N_{fk}^{\text{train}} \ge \tau\right\}$. Recomputing the bound describes how coverage changes with a declared support requirement. It is a hard ceiling only for a model that enforces this restricted vocabulary. Calling it a learnability ceiling for unrestricted networks would require additional assumptions about features, priors, side information and learning. The package therefore accepts legal vocabularies explicitly and uses training labels only as the default.

Vocabulary Oracle

The coverage ceiling counts unavailable true labels but assumes all available rows are classified correctly and creates no false positives. The exact vocabulary oracle O is the maximum pooled macro F1 under perfect classification of available rows and optimal legal destinations for unavailable rows; it includes false positives created by those destinations. When exact optimization is not run, the sandwich bounds $L \le O \le U$ use the sum and the maximum of the foldwise minimum destination costs, respectively. These quantities describe attainable-score limits, not model performance; their derivation and the grouped solver are in the supplement.

Evaluation Design

We use CICIDS2017 [19], the official UNSW-NB15 partitions [20], original-label NSL-KDD [21], and the UCI gas-sensor drift archive [22]. Counts, input hashes, membership manifests and confusion matrices accompany the code. Primary results use pooled positive-test-support macro F1 and source-training-label outputs; the NSL pipeline comparison also reports inferred-union scores. UNSW and NSL forests use 200 trees; CIC forests use 100 trees. Seeds 42–46 describe initialization variation on fixed cohorts, not independent networks or test sets.

We separately use the corrected DistriNet CICIDS2017 release, which supplies timestamped per-day CSVs and revised labels [5], [6]. Monday through Thursday form the training pool and Friday is the chronological test day. Flow identifiers, endpoint addresses and ports, timestamp, and label are excluded from features. We cap the training sample at 5,000 rows per observed label and seed (35,603 rows in the realized sample); all 21 training labels remain represented. Random Forest, Extra Trees, and SGD with log loss are each run with seeds 42–44 on the same full Friday cohort. These fits quantify model variation on this fixed split; they are not independent tests or a comparison isolating the effect of corrected labels.

CICIDS2017 compares five-fold stratified shuffled cross-validation with capture-day holdout. Numeric imputation uses training medians; web-label spelling variants are normalized. The local MachineLearningCVE CSVs contain no timestamps. A historical within-day row-order result is retained in the artifact but is not described as a verified temporal cutoff. All six archived forest configurations, including bootstrap weighting and that historical split, have separate fresh replication records agreeing with archived metrics to 10^{-12}.

NSL-KDD uses its named training and test files. Randomized pipelines were fit with seeds 42–46. GaussianNB and kNN are deterministic under these settings; GaussianNB was refit five times and kNN's identical deterministic predictions were reused. The forest retains its existing one-hot encoding; the five added pipelines use one-hot nominal encoding and training-fitted numeric standardization. The comparison therefore concerns complete pipelines, not isolated estimators. UNSW uses training-fitted ordinal nominal encoding. Its controlled study withholds every pair of the nine attack labels, retains all original test rows and repeats 36 pairs over five seeds. For ranking analysis we separately save confusion matrices on available and unavailable rows. Full scores retain all ten test labels; covered-only scores retain the labels with positive support in that subset. Comparisons across different pairs consequently change the covered target and are descriptive condition comparisons. A separate benign-only Isolation Forest uses the official UNSW-NB15 training partition: benign rows are divided into fit and calibration portions, and attack labels are withheld from both. Its threshold is set to the lower 1% calibration-score quantile; five seeds are evaluated on the untouched official test partition after mapping truth to BENIGN/ATTACK.

The gas study fits batch t and tests batch $t + 1$, for nine adjacent-batch folds, a protocol used in drift research [23]. The 19 fits span forests, MLPs, histogram boosting, logistic regression, SVM, kNN and CORAL logistic regression [24]. CORAL uses unlabeled target features and is transductive. It retains source labels. Ranking statistics use fixed predictions; shared rows and overlapping training conditions preclude iid significance claims.

Results

NSL-KDD: a natural partial-coverage split

Of the 38 test labels, 17 are unavailable to a training-restricted classifier. The positive-test-support ceiling and oracle are 0.55263. Two train-only labels can receive predictions without adding a class to that score's denominator. Under inferred-union scoring those destinations are scored as zero-F1 classes, and the exact oracle is 0.54837. Across five forest seeds, mean full-cohort F1 is 0.23953 (SD 0.00878); no unavailable test label is correctly predicted. The constraint is material to the attainable score, while model errors account for a large remaining gap.

The five-category mapping has ceiling one. This does not repair fine-grained recognition; it asks whether the system identifies a broader category. Reporting a high category score and a low fine-label score as interchangeable evidence would obscure this distinction.

Table 1: NSL-KDD forest scores on the same official test rows. Covered scoring removes unavailable rows and changes the scored label set.

Seed	Full support-scored F1	Covered support-scored F1
42	0.25456	0.48702
43	0.23488	0.45491
44	0.23764	0.45548
45	0.23850	0.45566
46	0.23205	0.45612

These five fits share one training file and one test file. Full scores range from 0.23205 to 0.25456; covered scores range from 0.45491 to 0.48702. We report the seed range as fit variation on this fixed cohort and do not interpret the small seed-level order changes as ranking stability or population uncertainty.

Prespecified pipeline comparison.

We compare all six prespecified pipelines on the same official NSL-KDD split. For the four randomized pipelines, table entries are means and standard deviations over seeds 42–46. GaussianNB and kNN are deterministic under these settings; each has one distinct prediction matrix, so their SD across the five seed labels is zero. GaussianNB was refit five times and kNN's identical deterministic predictions were reused. The forest and added pipelines use different preprocessing, so these results compare complete pipelines rather than estimator families. Full and covered-row scores target different label inventories; neither is a substitute for the other.

Table 2: NSL-KDD pipeline scores under positive-test-support scoring. Values are mean ± SD across five declared seeds.

Pipeline	Full F1	Covered F1
Random forest	0.23953 ± 0.00878	0.46184 ± 0.01409
Extra Trees	0.22314 ± 0.00162	0.45095 ± 0.00048
Decision tree	0.24664 ± 0.00825	0.50294 ± 0.00985
Gaussian NB	0.17968 ± 0.00000	0.34711 ± 0.00000
SGD logistic	0.20319 ± 0.01521	0.40073 ± 0.02966
kNN	0.25160 ± 0.00000	0.53995 ± 0.00000

Table 3: The same NSL-KDD predictions scored over the inferred union of true and predicted labels. Values are mean ± SD.

Pipeline	Full F1	Covered F1
Random forest	0.23338 ± 0.00855	0.44084 ± 0.01345
Extra Trees	0.21742 ± 0.00158	0.43046 ± 0.00046
Decision tree	0.24032 ± 0.00803	0.48007 ± 0.00940
Gaussian NB	0.17507 ± 0.00000	0.33133 ± 0.00000
SGD logistic	0.19588 ± 0.01274	0.37548 ± 0.02235
kNN	0.24515 ± 0.00000	0.51540 ± 0.00000

Among these six complete pipelines, kNN has the highest point estimate under both scoring conventions. On full positive-support scoring, its 0.25160 mean is 0.00496 above the decision tree's 0.24664, smaller than the tree's 0.00825 seed SD; kNN is deterministic here, so this comparison does not quantify model-to-model uncertainty. On covered rows its mean lead over the tree is 0.03701, while the covered-row task remains conditional and differs from full scoring. These results do not isolate estimator effects or establish a general performance ranking.

We also reaggregate each saved forest confusion matrix to the dataset's five broad categories without refitting. The fine-label mean remains 0.23953 (SD 0.00878) under a ceiling of 0.55263; the projected five-category mean is 0.48349 (SD 0.00549) under a ceiling of 1. The 3,750 rows carrying unavailable fine labels map to categories present in training. This paired calculation makes the role of label resolution concrete: category-level scoring accepts correct family predictions even when the exact attack subtype is unavailable. It is not a comparison between separately trained fine- and coarse-label models. The release records the full mapping for the 40-label train/test union; 38 labels have positive test support. For an operational mixed-resolution score, every attack family containing a test-only subtype must be grouped for both truth and prediction. All four NSL-KDD attack families contain at least one such subtype, so this coherent mixed taxonomy is identical to the five-category task above. Its inferred-union and positive-support scores are therefore equal at

0.48349 (SD 0.00549): all five output categories have positive test support, and the predictions map only to those five categories. It does not isolate a score change for only the 17 unavailable rows; changing their resolution alone while retaining fine labels for sibling attacks would not define one fixed output taxonomy for both truth and prediction.

Table 4: Label resolution changes the score and ceiling for the same five saved NSL-KDD forest prediction matrices. Both true and predicted labels are mapped to the five categories.

Target	Ceiling	Macro F1, mean ± SD
Fine attack subtype	0.55263	0.23953 ± 0.00878
Five attack categories	1.00000	0.48349 ± 0.00549

CICIDS2017: a day holdout changes the scoring task

Every attack class appears on one day. Benign traffic remains available whenever tested, giving $\rho_{\text{BENIGN}} = 1$; the 14 attack fractions are zero. Hence $F = F_{\text{BENIGN}}/15$ and $C = O = 0.06667$. The unweighted forest's score changes from 0.85347 in shuffled cross-validation to 0.06030 in day holdout. Under the latter protocol the attack F1 terms are fixed at zero, so their contribution cannot distinguish these training-restricted classifiers.




Figure 1: CICIDS2017 unweighted forest. Shuffled cross-validation has full label coverage; day holdout makes all fine-grained attack labels unavailable. The ceiling is a property of each protocol.

The day-held-out unweighted forest has benign recall 0.99858. Of the 557,646 unavailable attack rows, 475,727 are sent to benign and the remainder to other attack labels. Those other attack labels have zero covered support in the pooled score, so they provide free oracle destinations. This explains why the exact oracle equals the coverage ceiling here. The micro ceiling is 0.80300 because benign dominates the cohort. Merging web labels gives a 13-label ceiling of 0.07692;

the declared eight-family mapping gives 0.25; binary attack detection has ceiling one. These are different evaluation targets.

Corrected CICIDS2017: Friday labels are unavailable after earlier-day training

The corrected release contains 1,552,899 Monday–Thursday training rows and 547,915 Friday test rows. Its five test-positive labels are BENIGN, Bot, Bot - Attempted, DDoS, and PortScan. Only BENIGN occurs in the training vocabulary, so all four attack-label recalls are zero for any classifier restricted to observed training labels; the fine-label ceiling is $C = 1/5 = 0.20$. This is a result on the corrected, timestamped release and a separate split from the original-release LODO analysis above.

On the fixed Friday cohort, mean positive-support macro F1 is 0.15513 (SD 0.00168) for Random Forest, 0.15542 (SD 0.00122) for Extra Trees, and 0.17464 (SD 0.00728) for SGD log loss. The per-class training cap changes class priors, and model-specific calibration and thresholds also differ. We report these as fixed settings, not as a model-quality comparison. The cap and label variants affect fitting; this experiment does not estimate the isolated effect of relabeling because no matched old-release fit is included.

Table 5: Corrected CICIDS2017 Friday holdout: means and sample SDs over three seeds on one fixed test cohort. The attainment ratio F/C is about 0.78–0.87 but mostly reflects benign-class F1; it is not attack-detection quality. Binary scores appear in the summary table below.

Model setting	Fine macro F1	Ceiling (C)	(F/C)
Random Forest	0.15513 (0.00168)	0.20000	0.77566
Extra Trees	0.15542 (0.00122)	0.20000	0.77708
SGD log loss	0.17464 (0.00728)	0.20000	0.87320

The same unit ceiling can accompany very different attack detection. The summary table collects the binary results once; $C = 1$ in each row because BENIGN and ATTACK are legal outputs. Corrected-Friday scores use binary-collapsed predictions from the fine-label fits. Comparisons across fixed settings and datasets are descriptive.

Table 6: Binary detection results with legal-output ceiling one. Parentheses give sample SD across seeds where available. The published Alsaadi score is not our reproduction.

Case / setting	Model	Macro F1	Attack recall
CIC LODO, binary re-score	RF, one saved fit	0.57972	0.14690
CIC LODO, binary refit	RF, seed 42	0.58063	0.14782
CIC Friday, original release	RF, seed 42	0.61754	0.27894
Corrected Friday	RF, 3 seeds	0.64951 (0.02161)	0.35852 (0.03184)
Corrected Friday	Extra Trees, 3 seeds	0.65185 (0.01570)	0.36055 (0.02342)
Corrected Friday	SGD log loss, 3 seeds	0.85735 (0.04664)	0.80688 (0.08380)
UNSW-NB15	Isolation Forest, 5 seeds	0.48327 (0.02080)	0.18128 (0.02488)
CIC day holdout	Alsaadi et al. [25]	0.619	not reported

To show what target choice changes on the saved day-holdout predictions, we map truth and predicted labels to the declared eight-family taxonomy. The same matrix scores 0.06030 at 15 fine labels and 0.15630 at eight families, with ceilings 0.06667 and 0.25. The fine-label score is 90.5% of its ceiling because benign F1 is 0.90456 while all 14 attack-class F1 terms are zero. This attainment ratio is not a measure of attack detection. The binary re-score appears in the summary table; it removes the structural ceiling but retains low attack recall. This is a task comparison on fixed predictions, not a refit or estimate for a separately trained binary model.

Table 7: CICIDS2017 day-holdout predictions re-scored at two multiclass label resolutions using the same pooled confusion matrix. The binary result appears in the summary table above.

Target	Classes	Ceiling	Macro F1	F/C
Fine attack labels	15	0.06667	0.06030	0.90456
Declared attack families	8	0.25000	0.15630	0.62518

Alsaadi et al. explicitly label their whole-day CICIDS2017 result as binary. Both binary outputs occur in training, so its ceiling is one despite the held-out fine-grained attack names. The matching Monday-through-Thursday-to-Friday result in the summary table is a cross-study check, not an exact reproduction: preprocessing and hyperparameters may differ. Neither result evaluates attack-type attribution.

A second published example illustrates how methods text resolves a headline score. Biyouki et al. report macro F1 = 98.55% for CICIDS2017 leave-one-family-out with Web Attack excluded from training [26]. Their experimental setup defines CICIDS2017 as a binary Normal/Attack task and says CICIDS metrics are binary unless otherwise stated. Table 4 does not state a different inventory, so the reported result is compatible with a ceiling of one: BENIGN and ATTACK remain available because other attack families occur in training. This is a source-based interpretation, not an independent re-score; the paper does not release predictions. A 15-label or 13-label ceiling would apply only under a different multiclass target that the article does not specify.

We also re-scored one published artifact with saved predictions available. Franco-Valiente et al. release ten per-seed confusion matrices for a five-superclass CICIDS2017 connection-grouped evaluation [27]. Recomputing macro F1 from those matrices gives a mean of 0.90002 (sample SD 0.05143; 95% t-interval half-width 0.0368), matching the reported 0.900 ± 0.037. The study reports training support for all five classes, including 65 U2R flows, so the closed-set ceiling is 1 for each split. This is one independently checked paper and one compatible result, not the 10–20-paper survey needed to estimate how often published scores sit near their ceilings. The Nuako technical report lists macro F1 0.0435 against a conservative comparison ceiling of 0.25. Because its score is below that ceiling, it is not a violation; its denominator and target inventory remain unresolved.

Fixed-cohort withholding and rankings

The official UNSW-NB15 split has complete coverage. The unweighted forest's five-seed mean is 0.47144, with seed SD 0.00094. Training-label availability cannot explain that shortfall. Withholding two labels creates $C = 0.8$, but its oracle depends on their support and legal destinations. For Analysis plus Backdoor at seed 42, $O = 0.79833$ and $F = 0.47067$.

The benign-only Isolation Forest is a separate open-set binary detector. It sees no attack rows during fitting or calibration and predicts BENIGN/ATTACK; attack categories are only a descriptive breakdown. Its mean test false-positive rate is 0.00881 (SD 0.00262), with calibration false-positive rate 0.991%. Its macro F1 and attack recall appear in the summary table alongside the other binary settings.

The covered-row calculations use a different label inventory for each withheld pair, while full scoring retains all test labels. On this finite grid, 2,577 of 16,110 pair-seed comparisons and 97 of 630 pair-mean comparisons reverse order between the two scoring definitions. These counts are descriptive; they do not establish that either ranking is wrong. All 180 full scores match the earlier grid to absolute tolerance 10^{-12}, and the saved confusion matrices permit reconstruction of covered-row scores.

The post-hoc routing control is moved to the supplement. It uses the true availability status and illustrates how a prediction to an unscored label can affect support-scored F1; it is not evidence of improved recognition or a deployable unknown-attack rule.

Natural fractional coverage and model families

In adjacent-batch gas sensing, toluene is unavailable when batch 6 is tested. The batch-6 test fold contains 467 toluene rows; 1,759 is the pooled toluene support across all test batches. Thus 1,292 of 1,759 toluene test rows are in folds where toluene is available, giving $\rho = 1292/1759$. The other five classes have full coverage. Global label presence misses this fold-level restriction: all six labels occur somewhere in training.

Table 8: Different natural protocols retain their own targets. Only the NSL forest row is a five-seed mean ± sample SD; the other displayed rows are single saved fits. $O - F$ is a score shortfall, not a model-quality estimate; F/O divides the displayed score (the NSL mean) by O and is cohort-specific attainment.

Case	C	O	F	F/O
NSL original, forest (five-seed mean)	0.55263	0.55263	0.23953 ± 0.00878	0.43343
CIC day, forest	0.06667	0.06667	0.06030	0.90456
Gas, forest	0.97449	0.96222	0.57034	0.59274
Gas, logistic	0.97449	0.96222	0.61946	0.64378

The gas oracle is 0.01227 below the coverage ceiling. This difference is 3.0% of the forest's gap $C - F$ to the ceiling and 3.5% of logistic regression's gap; the denominator is the model's shortfall from C, not from one. It explains zero toluene hits in batch 6 but little of the pooled shortfall. Across all 19 gas fits, full and covered-only rankings agree exactly: Spearman and Kendall correlations are one, with 161 concordant comparisons and ten ties. The model-family contrast therefore provides no natural family-ranking reversal. CORAL logistic scores 0.63760 while retaining the same legal ceiling.

Algorithm checks and literature screening

Exhaustive row-level enumeration on 80 small seeded inputs agrees with both solvers under support and union scoring. Another 100 cases with explicitly supplied legal heads, including labels absent from training, agree with exhaustive predictions. A repeated-vocabulary check reduces 300 unavailable folds from 2^{100} candidate assignments to two. These checks validate implementation and edge cases; fitted scores lying below a theorem are not independent evidence of significance. Varied synthetic shapes still reach exact-search budgets, as documented in the supplement.

A local protocol was committed before collecting six Crossref searches, each retaining the first 100 relevance-ranked records dated 2017–2026. Title filtering and DOI deduplication yielded 385 candidates. NumPy seed 20261108 selected 50 without replacement. The public frame, source metadata, sample, checksum and coding sheet are retained. This is a prospective local freeze rather than external preregistration.

Screening confirmed three eligible evaluations, excluded fourteen records and left thirty-three eligibility decisions unresolved. Temporal neuron coding and split learning were frequent reasons not to infer evaluation timing from a title. Of the three confirmed cases, one binary source-to-target evaluation permits both labels and therefore has legal ceiling one; its exact F1 averaging remains unresolved. The other two lack verified vocabulary/support/scoring information. No complete incompatible-score comparison is established. The result is a candidate-screening pilot, not a survey of fifty confirmed temporal IDS papers or a field prevalence estimate. Accessible abstract evidence can establish eligibility without establishing a score convention; missing evidence is retained as missing. The separate targeted source checks and DOI verification are in the supplement and artifact.

Using the Diagnostic

Choose the evaluation target before optimizing a split. Stratified shuffled cross-validation can measure interpolation over a shared inventory but does not establish future-day generalization. A chronological or capture-group holdout addresses a different deployment question and should retain the availability audit. Leave-one-attack-class-out should specify a binary alarm or a scored unknown target when the aim is unfamiliar-attack detection. Exact identification of a withheld fine-grained label cannot measure that capability for a training-restricted output head.

The reporting sequence is short: preserve fold membership; state the legal vocabulary and per-class support; declare pooling and the scored labels; compute C, then O or its sandwich if destination loss matters; report full and covered-row scores with their respective inventories. State whether labels come from training or a global head. A ratio F/O, when $O > 0$, describes attainment on that cohort only and should accompany the absolute score. It cannot make different targets or populations comparable.

The package exposes fold-array and count-based interfaces, accepts an explicit legal vocabulary per fold, and supplies a CLI for count files. Reproduction commands and a table-to-file map accompany the release. Counts, software, manifests and checksums are public artifacts; raw traffic redistribution remains subject to dataset terms.

Limitations and Conclusion

The simple ceiling is a scoring corollary of legal-output constraints. It does not measure feature separability, rare-class learnability, calibration or deployment utility. The exact oracle adds unavoidable false-positive loss and admits a vocabulary-parameterized algorithm, but this correction is small in the natural examples considered. In the NSL-KDD complete-pipeline comparison, kNN has the highest point estimate, but its full-score margin over the decision tree is smaller than the tree's seed SD, and the pipelines use different preprocessing. These fixed-split results do not establish a general estimator ranking or a reanalysis of a published model comparison. Shared-cohort repetitions describe fit variation, not population uncertainty.

The literature screen remains a single-reviewer pilot, not the requested re-score of 10–20 published papers. We independently re-scored ten per-seed confusion matrices from one published paper and found a compatible score with a ceiling of one; the broader screen has not established an incompatible score. This does not estimate how often scores approach or exceed their ceilings. The corrected CICIDS2017 experiment uses one fixed Friday holdout and three seeds per model; its capped training sample and one benchmark do not support population-level uncertainty. Because there is no paired experiment on the original and corrected releases under identical features and splits, score differences cannot be attributed to label correction alone. A permanent DOI, an externally hosted anonymous artifact and independent reproduction also remain pending.

The practical contribution is a pre-fit audit that records the task the score actually measures: the label resolution, legal outputs, scoring convention, and resulting ceiling. On NSL-KDD, changing from subtype labels to five categories changes both the bound and the same-prediction macro F1. The corrected CICIDS2017 Friday experiment shows that binary attack detection can coexist with

a low fine-label ceiling when attack subtypes are absent from training. The gas case shows that a ceiling can also explain little. These cases demonstrate what the audit can and cannot resolve. They do not establish that published scores are generally invalid.

Data availability

Dataset sources are cited above. The accompanying code release contains aggregate results, split manifests, hashes, source coding and commands mapped to the manuscript. Original data terms continue to apply.

Declarations

This research received no funding. The author declares no financial or non-financial competing interests.

Use of generative AI

Generative AI assisted code development, mathematical exposition, literature screening, analysis planning and manuscript editing. Numerical results were computed with the released scripts. The author retains responsibility for the submitted work.

References

[1] A. Ayantayo *et al.*, "Network intrusion detection using feature fusion with deep learning," *Journal of Big Data*, vol. 10, no. 1, p. 167, 2023, doi: 10.1186/s40537-023-00834-0.

[2] R. Sommer and V. Paxson, "Outside the closed world: On using machine learning for network intrusion detection," in *IEEE symposium on security and privacy*, 2010, pp. 305–316. doi: 10.1109/SP.2010.25.

[3] D. Arp *et al.*, "Dos and don'ts of machine learning in computer security," in *31st USENIX security symposium*, 2022, pp. 3971–3988. Available: https://www.usenix.org/conference/usenixsecurity22/presentation/arp

[4] M. Ring, S. Wunderlich, D. Scheuring, D. Landes, and A. Hotho, "A survey of network-based intrusion detection data sets," *Computers & Security*, vol. 86, pp. 147–167, 2019, Available: https://www.sciencedirect.com/science/article/pii/S016740481930118X

[5] G. Engelen, V. Rimmer, and W. Joosen, "Troubleshooting an Intrusion Detection Dataset: the CICIDS2017 Case Study." 2021 IEEE Security and Privacy Workshops (SPW), 2021. Available: https://doi.org/10.1109/SPW53761.2021.00009

[6] M. Lanvin, P.-F. Gimenez, Y. Han, F. Majorczyk, L. Mé, and E. Totel, "Errors in the CICIDS2017 Dataset and the Significant Differences in Detection Performances It Makes." Risks and Security of Internet and Systems, 2023. Available: https://doi.org/10.1007/978-3-031-31108-6_2

[7] J. Opitz and S. Burst, "Macro F1 and macro F1." 2019. Available: https://arxiv.org/abs/1911.03347

[8] G. Forman and M. Scholz, "Apples-to-apples in cross-validation studies: Pitfalls in classifier performance measurement," *ACM SIGKDD Explorations Newsletter*, vol. 12, no. 1, pp. 49–57, 2010, Available: https://www.kdd.org/exploration_files/v12-1-p49-forman-sigkdd.pdf

[9] J. Opitz, "A closer look at classification evaluation metrics and a critical reflection of common evaluation practice," *Transactions of the Association for Computational Linguistics*, vol. 12, pp. 820–836, 2024, doi: 10.1162/tacl_a_00675.

[10] M. Sokolova and G. Lapalme, "A systematic analysis of performance measures for classification tasks," *Information Processing and Management*, vol. 45, no. 4, pp. 427–437, 2009, doi: 10.1016/j.ipm.2009.03.002.

[11] H. Narasimhan, H. Ramaswamy, A. Saha, and S. Agarwal, "Consistent multiclass algorithms for complex performance measures," in *International conference on machine learning*, 2015, pp. 2398–2407. Available: https://proceedings.mlr.press/v37/narasimhanb15.html

[12] Z. Lipton, Y.-X. Wang, and A. Smola, "Detecting and correcting for label shift with black box predictors," in *International conference on machine learning*, 2018, pp. 3122–3130. Available: https://proceedings.mlr.press/v80/lipton18a.html

[13] W. J. Scheirer, A. de Rezende Rocha, A. Sapkota, and T. E. Boult, "Toward open set recognition," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2013, doi: 10.1109/TPAMI.2012.256.

[14] C. Geng, S.-J. Huang, and S. Chen, "Recent advances in open set recognition: A survey," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 43, no. 10, pp. 3614–3631, 2021, doi: 10.1109/TPAMI.2020.2981604.

[15] C. K. Chow, "On optimum recognition error and reject tradeoff," *IEEE Transactions on Information Theory*, 1970, doi: 10.1109/TIT.1970.1054406.

[16] Y. Geifman and R. El-Yaniv, "SelectiveNet: A deep neural network with an integrated reject option," in *International conference on machine learning*, 2019. Available: https://proceedings.mlr.press/v97/geifman19a.html

[17] Y. Xian, B. Schiele, and Z. Akata, "Zero-shot learning: The good, the bad and the ugly," in *IEEE conference on computer vision and pattern recognition*, 2017. Available: https://openaccess.thecvf.com/content_cvpr_2017/html/Xian_Zero-Shot_Learning_-_CVPR_2017_paper.html

[18] F. Pendlebury, F. Pierazzi, R. Jordaney, J. Kinder, and L. Cavallaro, "TESSERACT: Eliminating experimental bias in malware classification across space and time," in *28th USENIX security symposium*, 2019, pp. 729–746. Available: https://www.usenix.org/conference/usenixsecurity19/presentation/pendlebury

[19] I. Sharafaldin, A. H. Lashkari, and A. A. Ghorbani, "Toward generating a new intrusion detection dataset and intrusion traffic characterization," in *International conference on information systems security and privacy*, 2018, pp. 108–116. doi: 10.5220/0006639801080116.

[20] N. Moustafa and J. Slay, "UNSW-NB15: A comprehensive data set for network intrusion detection systems," in *Military communications and information systems conference*, 2015. doi: 10.1109/MilCIS.2015.7348942.

[21] M. Tavallaee, E. Bagheri, W. Lu, and A. A. Ghorbani, "A detailed analysis of the KDD CUP 99 data set," in *IEEE symposium on computational intelligence for security and defense applications*, 2009. doi: 10.1109/CISDA.2009.5356528.

[22] A. Vergara, "Gas sensor array drift dataset." UCI Machine Learning Repository, 2012. doi: 10.24432/C5RP6W.

[23] X. Zhu, T. Liu, J. Chen, J. Cao, and H. Wang, "One-class drift compensation for an electronic nose," *Chemosensors*, vol. 9, no. 8, p. 208, 2021, doi: 10.3390/chemosensors9080208.

[24] B. Sun, J. Feng, and K. Saenko, "Return of frustratingly easy domain adaptation," in *Proceedings of the AAAI conference on artificial intelligence*, 2016. doi: 10.1609/aaai.v30i1.10306.

[25] M. S. Alsaadi, M. Imran, N. Fadhel, M. Al-Essa, I. S. Munteanu, and W. A. Ali, "Dataset-calibrated perturbation budgets for adversarial robustness evaluation of machine-learning network intrusion detection systems," *Technologies*, vol. 14, no. 10, p. 647, 2026, doi: 10.3390/technologies14100647.

[26] A. Biyouki, S. Lotfipour, and B. Haghi, "An enhanced deep learning framework for intrusion classification enterprise network using multi-branch CNN-attention architecture," *Scientific Reports*, vol. 16, p. 3962, 2026, doi: 10.1038/s41598-025-34166-1.

[27] J. M. Franco-Valiente, J. Calle-Cancho, A. Serrano-Martín, and J. M. Haut, "Scaling and validating a distributed training and retraining pipeline for network intrusion detection," *Electronics*, vol. 15, no. 18, p. 4074, 2026, doi: 10.3390/electronics15184074.