

Socket Programming in C/C++

Difficulty Level : Medium • Last Updated : 08 Jul, 2022


What is socket programming?

Socket programming is a way of connecting two nodes on a network to communicate with each other. One socket(node) listens on a particular port at an IP, while the other socket reaches out to the other to form a connection. The server forms the listener socket while the client reaches out to the server.

State diagram for server and client model



Start Your Coding Journey Now!

[Login](#)
[Register](#)


State diagram for server and client model of Socket

Stages for server

1. Socket creation:

Data Structures Algorithms Interview Preparation Topic-wise Practice C++ Java Python

```
int socket(int domain, int type, int protocol)
```

- **sockfd:** socket descriptor, an integer (like a file-handle)
- **domain:** integer, specifies communication domain. We use `AF_LOCAL` as defined in the POSIX standard for communication between processes on the same host. For



Start Your Coding Journey Now!

[Login](#)[Register](#)

- **type:** communication type
SOCK_STREAM: TCP(reliable, connection oriented)
SOCK_DGRAM: UDP(unreliable, connectionless)
- **protocol:** Protocol value for Internet Protocol(IP), which is 0. This is the same number which appears on protocol field in the IP header of a packet. (man protocols for more details)

2. Setsockopt: This helps in manipulating options for the socket referred by the file descriptor sockfd. This is completely optional, but it helps in reuse of address and port. Prevents error such as: "address already in use".

```
int setsockopt(int sockfd, int level, int optname, const void *optval, socklen_t optlen);
```

3. Bind:

```
int bind(int sockfd, const struct sockaddr *addr, socklen_t addrlen);
```

After creation of the socket, bind function binds the socket to the address and port number specified in addr(custom data structure). In the example code, we bind the server to the localhost, hence we use INADDR_ANY to specify the IP address.

4. Listen:

```
int listen(int sockfd, int backlog);
```

It puts the server socket in a passive mode, where it waits for the client to approach the server to make a connection. The backlog, defines the maximum length to which the queue of pending connections for sockfd may grow. If a connection request arrives when the queue is full, the client may receive an error with an indication of ECONNREFUSED.



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
int new_socket= accept(int sockfd, struct sockaddr *addr, socklen_t *addrlen);
```

It extracts the first connection request on the queue of pending connections for the listening socket, sockfd, creates a new connected socket, and returns a new file descriptor referring to that socket. At this point, connection is established between client and server, and they are ready to transfer data.

Stages for Client

- **Socket connection:** Exactly same as that of server's socket creation
- **Connect:** The connect() system call connects the socket referred to by the file descriptor sockfd to the address specified by addr. Server's address and port is specified in addr.

```
int connect(int sockfd, const struct sockaddr *addr, socklen_t addrlen);
```



C++ Foundation Course

Beginner to Advance Level ★★★★★

Learn the basics foundational skills of C++ even if you have no prior knowledge about programming and position yourself for the best C++ jobs in the industry.

[Explore Now](#)

Implementation

Here we are exchanging one hello message between server and client to demonstrate the client/server model.



Server.c



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// Server side C/C++ program to demonstrate Socket
// programming
#include <netinet/in.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <sys/socket.h>
#include <unistd.h>
#define PORT 8080
int main(int argc, char const* argv[])
{
    int server_fd, new_socket, valread;
    struct sockaddr_in address;
    int opt = 1;
    int addrlen = sizeof(address);
    char buffer[1024] = { 0 };
    char* hello = "Hello from server";

    // Creating socket file descriptor
    if ((server_fd = socket(AF_INET, SOCK_STREAM, 0))
        == 0) {
        perror("socket failed");
        exit(EXIT_FAILURE);
    }

    // Forcefully attaching socket to the port 8080
    if (setsockopt(server_fd, SOL_SOCKET,
        SO_REUSEADDR | SO_REUSEPORT, &opt,
        sizeof(opt))) {
        perror("setsockopt");
        exit(EXIT_FAILURE);
    }
    address.sin_family = AF_INET;
    address.sin_addr.s_addr = INADDR_ANY;
    address.sin_port = htons(PORT);

    // Forcefully attaching socket to the port 8080
    if (bind(server_fd, (struct sockaddr*)&address,
        sizeof(address))
        < 0) {
        perror("bind failed");
        exit(EXIT_FAILURE);
    }
    if (listen(server_fd, 3) < 0) {
        perror("listen");
        exit(EXIT_FAILURE);
    }
    if ((new_socket
        = accept(server_fd, (struct sockaddr*)&address,
        (socklen_t*)&addrlen)) < 0)
```

Start Your Coding Journey Now!

[Login](#)
[Register](#)

```

    }
    valread = read(new_socket, buffer, 1024);
    printf("%s\n", buffer);
    send(new_socket, hello, strlen(hello), 0);
    printf("Hello message sent\n");

// closing the connected socket
close(new_socket);
// closing the listening socket
shutdown(server_fd, SHUT_RDWR);
return 0;
}

```

• client.c

C

```

// Client side C/C++ program to demonstrate Socket
// programming
#include <arpa/inet.h>
#include <stdio.h>
#include <string.h>
#include <sys/socket.h>
#include <unistd.h>
#define PORT 8080

int main(int argc, char const* argv[])
{
    int sock = 0, valread, client_fd;
    struct sockaddr_in serv_addr;
    char* hello = "Hello from client";
    char buffer[1024] = { 0 };
    if ((sock = socket(AF_INET, SOCK_STREAM, 0)) < 0) {
        printf("\n Socket creation error \n");
        return -1;
    }

    serv_addr.sin_family = AF_INET;
    serv_addr.sin_port = htons(PORT);

    // Convert IPv4 and IPv6 addresses from text to binary
    // form
    if (inet_pton(AF_INET, "127.0.0.1", &serv_addr.sin_addr)
        <= 0) {
        printf(
            "\nInvalid address/ Address not supported \n");
        return -1;
    }
}

```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
    = connect(sock, (struct sockaddr*)&serv_addr,
              sizeof(serv_addr))
    < 0) {
    printf("\nConnection Failed \n");
    return -1;
}
send(sock, hello, strlen(hello), 0);
printf("Hello message sent\n");
valread = read(sock, buffer, 1024);
printf("%s\n", buffer);

// closing the connected socket
close(client_fd);
return 0;
}
```

Compiling:

```
gcc client.c -o client
gcc server.c -o server
```

Output:

```
Client:Hello message sent
Hello from server
Server:Hello from client
Hello message sent
```

Next: [Socket Programming in C/C++: Handling multiple clients on server without multi threading](#)

This article is contributed by **Akshat Sinha**. If you like GeeksforGeeks and would like to contribute, you can also write an article using [write.geeksforgeeks.org](https://www.geeksforgeeks.org/write-geeksforgeeks/) or mail your article to review-team@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



Start Your Coding Journey Now!

Login

Register

VIDEO AND PRACTICE PROBLEMS

GeeksforGeeks

Like 146

Previous

Next

AD

RECOMMENDED ARTICLES

Page : 1 2 3

01

Socket Programming in C/C++:
Handling multiple clients on server
without multi threading
29, Aug 16

05

C++: Methods of code shortening
in competitive programming
04, Sep 18

02

getchar_unlocked() – Faster Input
in C/C++ For Competitive
Programming
18, Apr 16

06

Comparison of Java with other
programming languages
16, Jan 19



Start Your Coding Journey Now!

[Login](#)[Register](#)**Beginners**

13, Jun 17

04**C++ Programming and STL Facts**

20, Mar 18

U /**08****Hello World Program : First program while learning Programming**

25, Nov 19

Article Contributed By :

**GeeksforGeeks**

Vote for difficulty

Current difficulty : [Medium](#)

Easy

Normal

Medium

Hard

Expert

Improved By : [lcmgcd](#), [MichaelThomasKloos](#), [introdynelco1](#), [harendrakumar123](#), [nehalnimkar](#)**Article Tags :** [CPP-Library](#), [C++](#)**Practice Tags :** [CPP](#)[Improve Article](#)[Report Issue](#)Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.[Load Comments](#)

Start Your Coding Journey Now!

Login

Register



A-143, 9th Floor, Sovereign Corporate Tower,
Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

Company

- About Us
- Careers
- In Media
- Contact Us
- Privacy Policy
- Copyright Policy

Learn

- Algorithms
- Data Structures
- SDE Cheat Sheet
- Machine learning
- CS Subjects
- Video Tutorials
- Courses

News

- Top News
- Technology
- Work & Career
- Business
- Finance
- Lifestyle
- Knowledge

Languages

- Python
- Java
- CPP
- Golang
- C#
- SQL
- Kotlin

Web Development

- Web Tutorials
- Django Tutorial
- HTML

Contribute

- Write an Article
- Improve an Article
- Pick Topics to Write



Start Your Coding Journey Now!

[Login](#)[Register](#)

ReactJS

Video Internship

NodeJS

@geeksforgeeks , Some rights reserved

