

Exploratory Data Analysis

Loading libraries

The below code chunk loads the libraries we will be using in our analysis:

Reading and cleaning data

First, we input our stock data.

Our stock data consists of the following indices between 2000 and 2021:

- S&P500
- NASDAQ
- NYSE100

Important: Before running the code below, make sure your Knit directory is 'Document Directory'. This can be done by clicking the drop-down menu next to Knit, going to Knit directory and clicking on Document Directory.

```
setwd("../")
sp<-read.csv("Data/sp500.csv")
ny<-read.csv("Data/nyse.csv")
nas<-read.csv("Data/nasdaq.csv")
```

Now we will change the 'caldt' column to the Date format in order to plot the time series for each index:

```
sp$caldt<-as.Date(sp$caldt, format="%d/%m/%Y")
ny$caldt<-as.Date(ny$caldt, format="%d/%m/%Y")
nas$caldt<-as.Date(nas$caldt, format="%d/%m/%Y")
```

```
str(sp)
```

```
## 'data.frame': 5032 obs. of 2 variables:
## $ caldt : Date, format: "2001-01-02" "2001-01-03" ...
## $ spindx: num 1283 1348 1333 1298 1296 ...
```

```
str(ny)
```

```
## 'data.frame': 5284 obs. of 2 variables:
## $ caldt : Date, format: "2000-01-03" "2000-01-04" ...
## $ spindx: num 1455 1399 1402 1403 1441 ...
```


```
str(nas)
```

```
## 'data.frame':  5284 obs. of  2 variables:  
## $ caldt : Date, format: "2000-01-03" "2000-01-04" ...  
## $ ncindx: num  4131 3902 3878 3727 3883 ...
```


Initial Plots

We will start off by making a basic of stock price against time for each index, to get an idea of what our data looks like:


```
plot(sp, type='l')
```



```
plot(ny, type='l')
```



```
plot(nas, type='l')
```




They all follow the same basic pattern, which is what we would expect, with the iconic fall in stock-price during the 2008-2009 period of the ‘Great Recession’.


However, the stock price directly does not give us much information. Instead, we will take at the **daily log stock returns**.

```
sp_logret <- diff(log(sp$spindx))
ny_logret <- diff(log(ny$spindx))
nas_logret <- diff(log(nas$ncindx))


plot(sp$caldt[-length(sp$caldt)],sp_logret,type='l')
```



```
plot(ny$caldt[-length(ny$caldt)],ny_logret, type='l')
```




```
plot(nas$caldt[-length(nas$caldt)],nas_logret, type='l')
```



We can see that the returns average around 0% with very high variability during 2008-2009 (caused by the Great Recession) and during 2020 (caused by COVID-19).


Let us now plot the density of the returns to try to understand the distribution which will be helpful when we try to model the returns later one:

```
plot(density(sp_logret))
```




```
plot(density(ny_logret))
```


density.default(x = ny_logret)



N = 5283 Bandwidth = 0.001279


```
plot(density(nas_logret))
```



The returns look like they follow a normal distribution. So, we will make qq-plots to further confirm this:


```
qqnorm(sp_logret)
qqline(sp_logret,col='red')
```

Normal Q-Q Plot




```
qqnorm(ny_logret)  
qqline(ny_logret,col='red')
```

Normal Q-Q Plot



```
qqnorm(nas_logret)  
qqline(nas_logret,col='red')
```



The log-returns have much heavier tails than the normal distribution, which suggests that it might follow a Student's t-distribution.

Calculating summary statistics

Let us now obtain some sample statistics of our data. We will first use `summary()`:

```
summary(sp_logret)
```

```
##      Min.    1st Qu.    Median      Mean    3rd Qu.      Max.
## -0.1276521 -0.0045195  0.0006476  0.0002135  0.0057220  0.1095720
```

```
summary(ny_logret)
```

```
##      Min.    1st Qu.    Median      Mean    3rd Qu.      Max.
## -0.1276521 -0.0047659  0.0005935  0.0001795  0.0058089  0.1095720
```

```
summary(nas_logret)
```

```
##      Min.    1st Qu.    Median      Mean    3rd Qu.      Max.
## -0.1314915 -0.0062893  0.0009564  0.0002154  0.0075183  0.1325465
```

Now we will calculate the skewness of our data:

```
skewness(sp_logret)
```

```
## [1] -0.4178326
```

```
skewness(ny_logret)
```

```
## [1] -0.393156
```

```
skewness(nas_logret)
```

```
## [1] -0.1333754
```

The skewness of our indexes are not equal to 0 which indicates that our log-returns might not be normally distributed. Let's also look at the tails of the distribution by calculating the sample kurtosis:

```
kurtosis(sp_logret)
```

```
## [1] 14.67896
```

```
kurtosis(ny_logret)
```

```
## [1] 13.94
```

```
kurtosis(nas_logret)
```

```
## [1] 9.621652
```

The sample kurtosis is much higher than 3 meaning our log-returns have much fatter tails than the normal distribution!

Doing basic time-series tests

We will carrying out tests to check if our series is stationary and auto-correlated.

We first test if our series is stationary:

```
lag.length = 25
```

```
Box.test(sp_logret, lag=lag.length, type="Ljung-Box")
```

```
##
```

```
## Box-Ljung test
```

```
##
```

```
## data: sp_logret
```

```
## X-squared = 182.6, df = 25, p-value < 2.2e-16
```

```
Box.test(ny_logret, lag=lag.length, type="Ljung-Box")
```

```
##  
## Box-Ljung test  
##  
## data: ny_logret  
## X-squared = 179.72, df = 25, p-value < 2.2e-16
```


```
Box.test(nas_logret, lag=lag.length, type="Ljung-Box")
```

```
##  
## Box-Ljung test  
##  
## data: nas_logret  
## X-squared = 133.38, df = 25, p-value < 2.2e-16
```


The p-value is very small which means we reject the null hypothesis that our correlations are 0. This means our data is not stationary and we might not use a GARCH model on log-returns directly.

We also plot the ACF of our indexes to see how our data is correlated:

```
acf(sp_logret)
```




```
acf(ny_logret)
```



```
acf(nas_logret)
```


Series nas_logret



As you can see above there is serious correlation on the first lag, again confirm that our series is not stationary. So instead, we will build a mean equation and try to convert our residuals into a stationary white noise.


Building a mean-equation

```
sp_ar <- arima(sp_logret , order = c(1, 0, 1))
sp_ar
```

```
##
## Call:
## arima(x = sp_logret, order = c(1, 0, 1))
##
## Coefficients:
##          ar1          ma1  intercept
##       -0.0631   -0.0578         2e-04
## s.e.    0.1056    0.1056         2e-04
##
## sigma^2 estimated as 0.0001533:  log likelihood = 14955.89,  aic = -29903.78
```

```
acf(residuals(sp_ar))
```

Series residuals(sp_ar)




```
ny_ar <- arima(ny_logret , order = c(1, 0, 1))
ny_ar
```

```
##
## Call:
## arima(x = ny_logret, order = c(1, 0, 1))
##
## Coefficients:
##      ar1      ma1  intercept
##    -0.0020 -0.1135      2e-04
## s.e.   0.1143   0.1136      2e-04
##
## sigma^2 estimated as 0.0001555:  log likelihood = 15667.19,  aic = -31326.38
```

```
acf(residuals(ny_ar))
```

Series residuals(ny_ar)




```
nas_ar <- arima(nas_logret , order = c(1, 0, 1))
nas_ar
```

```
##
## Call:
## arima(x = nas_logret, order = c(1, 0, 1))
##
## Coefficients:
##          ar1      ma1  intercept
##         0.2811 -0.3470        2e-04
## s.e.   0.2102   0.2065        2e-04
##
## sigma^2 estimated as 0.000255:  log likelihood = 14360.11,  aic = -28712.21
```

```
acf(residuals(nas_ar))
```

Series residuals(nas_ar)



```
lag.length = 25
```

```
Box.test(residuals(sp_ar), lag=lag.length, type="Ljung-Box")
```

```
##  
## Box-Ljung test  
##  
## data: residuals(sp_ar)  
## X-squared = 94.264, df = 25, p-value = 5.697e-10
```


```
Box.test(residuals(ny_ar), lag=lag.length, type="Ljung-Box")
```

```
##  
## Box-Ljung test  
##  
## data: residuals(ny_ar)  
## X-squared = 96.877, df = 25, p-value = 2.095e-10
```

```
Box.test(residuals(nas_ar), lag=lag.length, type="Ljung-Box")
```


```
##  
## Box-Ljung test  
##  
## data: residuals(nas_ar)  
## X-squared = 101.92, df = 25, p-value = 2.974e-11
```

```
acf(sp_logret^2)
```




```
acf(ny_logret^2)
```

Series ny_logret^2




```
acf(nas_logret^2)
```


Series nas_logret^2




```
pacf(sp_logret)
```



```
pacf(ny_logret)
```

```
pacf(nas_logret)
```



Outputting Files

```
setwd('..')  
write.csv(residuals(sp_ar), 'Data/sp_residual.csv', row.names=T)  
write.csv(residuals(ny_ar), 'Data/ny_residual.csv', row.names=T)  
write.csv(residuals(nas_ar), 'Data/nas_residual.csv', row.names=T)
```