Session – 11

Task-1.

Create a SQL query using a subquery in the WHERE clause to find all restaurants from a 'Restaurants' table whose average rating is higher than the average rating of all restaurants in the city.

Solution:

```
WHERE rating > (
  SELECT AVG(rating)
  FROM Restaurants
);
```

Task-2.

Write a SQL query that uses a subquery in the SELECT statement to display each user's name from a 'Users' table along with the total number of orders they have placed from an 'Orders' table, like a summary you might see in a Zomato user profile.

Solution:

```
SELECT
  u.name,
  (
    SELECT COUNT(*)
    FROM Orders o
    WHERE o.user_id = u.id
  )
FROM Users u;
```

Task-3.

Given a 'Movies' table and a 'Reviews' table, write a SQL query using IN with a subquery to list all movies that have at least one review with a rating of 5 stars, as seen in BookMyShow's top-rated section.

Solution:

```
WHERE id IN (
  SELECT movie_id
  FROM Reviews
```

```
  WHERE rating = 5
);
```

Task-4.

Write a nested SQL query to find the names of all sellers from a 'Sellers' table on a Flipkart-style platform who have sold products in every category listed in a 'Categories' table.

Hint: Use nested subqueries to compare seller's categories with the complete list of categories.

Solution:

```
WHERE NOT EXISTS (
  SELECT ...
  WHERE NOT EXISTS (
    SELECT ...
  )
);
```