Case Study

Task-1.

Write an SQL query to find the top 5 highest-rated restaurants in Koramangala that serve North Indian cuisine, using the Zomato Bangalore dataset.

Solution:

```
SELECT name, location, cuisines, rate

FROM restaurants

WHERE location = 'Koramangala'

  AND cuisines LIKE '%North Indian%'

ORDER BY rate DESC

LIMIT 5;
```

Task-2.

Using SQL, calculate the average cost for two people for each cuisine type and list the 3 most expensive cuisines to eat in Bangalore.

Solution:

```
SELECT

   cuisines,

   AVG(`approx_cost(for two people)`) AS avg_cost_for_two

FROM restaurants

WHERE cuisines IS NOT NULL

GROUP BY cuisines

ORDER BY avg_cost_for_two DESC

LIMIT 3;
```

Task-3.

Find all restaurants that offer online delivery but have a rating below 3.0, and suggest a marketing strategy to improve their ratings based on your findings.

Hint: Look for patterns in location, cuisine, or price that might explain the low ratings.

Solution:

```
SELECT

   name,
```

```
  location,
  cuisines,
  `approx_cost(for two people)` AS cost_for_two,
  rate
FROM restaurants
WHERE online_order = 'Yes'
 AND rate <> 'NEW'
 AND rate <> '-'
 AND CAST(SUBSTRING_INDEX(rate, '/', 1) AS DECIMAL(2,1)) < 3.0
ORDER BY rate ASC;
```

Task-4.

Write an SQL query to segment restaurants into three market segments based on average cost for two: budget (below 400), mid-range (400-800), and premium (above 800). Count how many restaurants fall into each segment.

Solution:

```
SELECT
  CASE
    WHEN `approx_cost(for two people)` < 400 THEN 'Budget'
    WHEN `approx_cost(for two people)` BETWEEN 400 AND 800 THEN 'Mid-Range'
    ELSE 'Premium'
  END AS market_segment,
  COUNT(*) AS restaurant_count
FROM restaurants
GROUP BY
  CASE
    WHEN `approx_cost(for two people)` < 400 THEN 'Budget'
    WHEN `approx_cost(for two people)` BETWEEN 400 AND 800 THEN 'Mid-Range'
    ELSE 'Premium'
  END;
```

Task-5.

Use ChatGPT or Copilot to help you write an SQL query that lists the top 10 most popular restaurant chains (by number of outlets) in the dataset, then run and validate the query yourself.

Hint: Search for 'SQL group by count example' if you get stuck.

Solution:

```
SELECT
   name AS restaurant_chain,
   COUNT(*) AS number_of_outlets
FROM restaurants
GROUP BY name
ORDER BY number_of_outlets DESC
LIMIT 10;
```