

```
In [1]: # MOVIE RATING ANALYTICS (ADVANCED VISULIZATION)
```

```
import pandas as pd
import os
```

```
In [2]: os.getcwd() # if you want to change the working directory
```

```
Out[2]: 'C:\\Users\\shaik'
```

```
In [3]: movies = pd.read_csv(r"C:\Users\shaik\Downloads\Movie-Rating.csv")
```

```
In [4]: movies
```

```
Out[4]:
```

	Film	Genre	Rotten Tomatoes Ratings %	Audience Ratings %	Budget (million \$)	Year of release
0	(500) Days of Summer	Comedy	87	81	8	2009
1	10,000 B.C.	Adventure	9	44	105	2008
2	12 Rounds	Action	30	52	20	2009
3	127 Hours	Adventure	93	84	18	2010
4	17 Again	Comedy	55	70	20	2009
...
554	Your Highness	Comedy	26	36	50	2011
555	Youth in Revolt	Comedy	68	52	18	2009
556	Zodiac	Thriller	89	73	65	2007
557	Zombieland	Action	90	87	24	2009
558	Zookeeper	Comedy	14	42	80	2011

559 rows × 6 columns

```
In [5]: len(movies)
```

```
Out[5]: 559
```

```
In [6]: movies.head()
```

Out[6]:

	Film	Genre	Rotten Tomatoes Ratings %	Audience Ratings %	Budget (million \$)	Year of release
0	(500) Days of Summer	Comedy	87	81	8	2009
1	10,000 B.C.	Adventure	9	44	105	2008
2	12 Rounds	Action	30	52	20	2009
3	127 Hours	Adventure	93	84	18	2010
4	17 Again	Comedy	55	70	20	2009

In [7]: `movies.tail()`

Out[7]:

	Film	Genre	Rotten Tomatoes Ratings %	Audience Ratings %	Budget (million \$)	Year of release
554	Your Highness	Comedy	26	36	50	2011
555	Youth in Revolt	Comedy	68	52	18	2009
556	Zodiac	Thriller	89	73	65	2007
557	Zombieland	Action	90	87	24	2009
558	Zookeeper	Comedy	14	42	80	2011

In [8]: `movies.columns`

Out[8]: Index(['Film', 'Genre', 'Rotten Tomatoes Ratings %', 'Audience Ratings %', 'Budget (million \$)', 'Year of release'], dtype='object')

In [9]: `movies.columns = ['Film', 'Genre', 'CriticRating', 'AudienceRating', 'BudgetMilli`In [10]: `movies.head() # Removed spaces & % removed noise characters`

Out[10]:

	Film	Genre	CriticRating	AudienceRating	BudgetMillions	Year
0	(500) Days of Summer	Comedy	87	81	8	2009
1	10,000 B.C.	Adventure	9	44	105	2008
2	12 Rounds	Action	30	52	20	2009
3	127 Hours	Adventure	93	84	18	2010
4	17 Again	Comedy	55	70	20	2009

In [11]: `movies.info()`

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 559 entries, 0 to 558
Data columns (total 6 columns):
#   Column                Non-Null Count  Dtype
---  ---
0   Film                   559 non-null   object
1   Genre                   559 non-null   object
2   CriticRating            559 non-null   int64
3   AudienceRating          559 non-null   int64
4   BudgetMillions          559 non-null   int64
5   Year                    559 non-null   int64
dtypes: int64(4), object(2)
memory usage: 26.3+ KB
```

```
In [12]: movies.describe()
# if you look at the year the data type is int but when you look at the mean val
# we have to change to category type
# also from object datatype we will convert to category datatypes
#
```

```
Out[12]:
```

	CriticRating	AudienceRating	BudgetMillions	Year
count	559.000000	559.000000	559.000000	559.000000
mean	47.309481	58.744186	50.236136	2009.152057
std	26.413091	16.826887	48.731817	1.362632
min	0.000000	0.000000	0.000000	2007.000000
25%	25.000000	47.000000	20.000000	2008.000000
50%	46.000000	58.000000	35.000000	2009.000000
75%	70.000000	72.000000	65.000000	2010.000000
max	97.000000	96.000000	300.000000	2011.000000

```
In [13]: movies['Film']
#movies['Audience Ratings %']
```

```
Out[13]: 0      (500) Days of Summer
1      10,000 B.C.
2      12 Rounds
3      127 Hours
4      17 Again
...
554     Your Highness
555     Youth in Revolt
556     Zodiac
557     Zombieland
558     Zookeeper
Name: Film, Length: 559, dtype: object
```

```
In [14]: movies.Film
```

```
Out[14]: 0      (500) Days of Summer
         1      10,000 B.C.
         2      12 Rounds
         3      127 Hours
         4      17 Again
         ...
        554      Your Highness
        555      Youth in Revolt
        556      Zodiac
        557      Zombieland
        558      Zookeeper
        Name: Film, Length: 559, dtype: object
```

```
In [15]: movies.Film = movies.Film.astype('category')
```

```
In [16]: movies.Film
```

```
Out[16]: 0      (500) Days of Summer
         1      10,000 B.C.
         2      12 Rounds
         3      127 Hours
         4      17 Again
         ...
        554      Your Highness
        555      Youth in Revolt
        556      Zodiac
        557      Zombieland
        558      Zookeeper
        Name: Film, Length: 559, dtype: category
        Categories (559, object): ['(500) Days of Summer ', '10,000 B.C.', '12 Rounds
        ', '127 Hours', ..., 'Youth in Revolt', 'Zodiac', 'Zombieland ', 'Zookeeper']
```

```
In [17]: movies.head()
```

```
Out[17]:
```

	Film	Genre	CriticRating	AudienceRating	BudgetMillions	Year
0	(500) Days of Summer	Comedy	87	81	8	2009
1	10,000 B.C.	Adventure	9	44	105	2008
2	12 Rounds	Action	30	52	20	2009
3	127 Hours	Adventure	93	84	18	2010
4	17 Again	Comedy	55	70	20	2009

```
In [18]: movies.info()

# now the same thing we will change genra to category & year to category
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 559 entries, 0 to 558
Data columns (total 6 columns):
#   Column                Non-Null Count  Dtype
---  -
0   Film                  559 non-null    category
1   Genre                 559 non-null    object
2   CriticRating          559 non-null    int64
3   AudienceRating        559 non-null    int64
4   BudgetMillions        559 non-null    int64
5   Year                  559 non-null    int64
dtypes: category(1), int64(4), object(1)
memory usage: 43.6+ KB
```

```
In [19]: movies.Genre = movies.Genre.astype('category')
         movies.Year = movies.Year.astype('category')
```

```
In [20]: movies.Genre
```

```
Out[20]: 0      Comedy
         1      Adventure
         2      Action
         3      Adventure
         4      Comedy
         ...
        554     Comedy
        555     Comedy
        556     Thriller
        557     Action
        558     Comedy
        Name: Genre, Length: 559, dtype: category
        Categories (7, object): ['Action', 'Adventure', 'Comedy', 'Drama', 'Horror', 'Romance', 'Thriller']
```

```
In [21]: movies.Year # is it real no. year you can take average,min,max but out come have
```

```
Out[21]: 0      2009
         1      2008
         2      2009
         3      2010
         4      2009
         ...
        554     2011
        555     2009
        556     2007
        557     2009
        558     2011
        Name: Year, Length: 559, dtype: category
        Categories (5, int64): [2007, 2008, 2009, 2010, 2011]
```

```
In [22]: movies.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 559 entries, 0 to 558
Data columns (total 6 columns):
#   Column                Non-Null Count  Dtype
---  -
0   Film                  559 non-null   category
1   Genre                 559 non-null   category
2   CriticRating          559 non-null   int64
3   AudienceRating        559 non-null   int64
4   BudgetMillions        559 non-null   int64
5   Year                  559 non-null   category
dtypes: category(3), int64(3)
memory usage: 36.5 KB
```

```
In [23]: movies.Genre.cat.categories
```

```
Out[23]: Index(['Action', 'Adventure', 'Comedy', 'Drama', 'Horror', 'Romance',
               'Thriller'],
              dtype='object')
```


```
In [24]: movies.describe()
#now when you see the descript you will get only integer value mean, standard de
```

```
Out[24]:
```

	CriticRating	AudienceRating	BudgetMillions
count	559.000000	559.000000	559.000000
mean	47.309481	58.744186	50.236136
std	26.413091	16.826887	48.731817
min	0.000000	0.000000	0.000000
25%	25.000000	47.000000	20.000000
50%	46.000000	58.000000	35.000000
75%	70.000000	72.000000	65.000000
max	97.000000	96.000000	300.000000


```
In [25]: #How to working with joint plots
from matplotlib import pyplot as plt
import seaborn as sns
%matplotlib inline
import warnings
warnings.filterwarnings('ignore')
```

```
In [26]: j = sns.jointplot( data = movies, x = 'CriticRating', y = 'AudienceRating')
plt.show()
# Audience rating is more dominant then critics rating
# Based on this we find out as most people are most liklihood to watch audience
# Let me explain the excel - if you filter audience rating & critic rating. crit
```



```
In [27]: j = sns.jointplot( data = movies, x = 'CriticRating', y = 'AudienceRating', kind
plt.show()


#j = sns.jointplot( data = movies, x = 'CriticRating', y = 'AudienceRating', kin
```



```
In [28]: #Histograms


# <<< chat1

m1 = sns.distplot(movies.AudienceRating)
plt.show()
#y - axis generated by seaborn automatically that is the powerfull of seaborn gal
```


```
In [29]: sns.set_style('darkgrid')
```

```
In [30]: m2 = sns.distplot(movies.AudienceRating, bins = 15)  
plt.show()
```




```
In [31]: #sns.set_style('darkgrid')  
n1 = plt.hist(movies.AudienceRating, bins=15)
```

```
plt.show()
```



```
In [32]: sns.set_style('white') #normal distribution & called as bell curve  
n1 = plt.hist(movies.AudienceRating, bins=20)  
plt.show()
```




```
In [33]: n1 = plt.hist(movies.CriticRating, bins=20) #uniform distribution
```

```
In [34]: # <<< chat - 2
```


```
# Creating stacked histograms & this is bit tough to understand
```

```
In [35]: #h1 = plt.hist(movies.BudgetMillions)

plt.hist(movies.BudgetMillions)
plt.show()
```



```
In [36]: plt.hist(movies[movies.Genre == 'Drama'].BudgetMillions)
plt.show()
```



In [37]: `movies.head()`


Out[37]:

	Film	Genre	CriticRating	AudienceRating	BudgetMillions	Year
0	(500) Days of Summer	Comedy	87	81	8	2009
1	10,000 B.C.	Adventure	9	44	105	2008
2	12 Rounds	Action	30	52	20	2009
3	127 Hours	Adventure	93	84	18	2010
4	17 Again	Comedy	55	70	20	2009


In [38]: `#movies.Genre.unique()`

In [39]: *# Below plots are stacked histogram becuae overlaped*

```
plt.hist(movies[movies.Genre == 'Action'].BudgetMillions, bins = 20)
plt.hist(movies[movies.Genre == 'Thriller'].BudgetMillions, bins = 20)
plt.hist(movies[movies.Genre == 'Drama'].BudgetMillions, bins = 20)
plt.legend()
plt.show()
```



```
In [40]: plt.hist([movies[movies.Genre == 'Action'].BudgetMillions, \
                  movies[movies.Genre == 'Drama'].BudgetMillions, \
                  movies[movies.Genre == 'Thriller'].BudgetMillions, \
                  movies[movies.Genre == 'Comedy'].BudgetMillions],
              bins = 20, stacked = True)
plt.show()
```




In [41]: *# if you have 100 categories you cannot copy & paste all the things*

```
for gen in movies.Genre.cat.categories:  
    print(gen)
```

Action
Adventure
Comedy
Drama
Horror
Romance
Thriller


In [42]: `vis1 = sns.lmplot(data=movies, x='CriticRating', y='AudienceRating',\n fit_reg=False)`

In [43]: `plt.show()`




```
In [44]: vis1 = sns.lmplot(data=movies, x='CriticRating', y='AudienceRating',\n                           fit_reg=False, hue = 'Genre')
```

```
In [45]: plt.show()
```



```
In [46]: vis1 = sns.lmplot(data=movies, x='CriticRating', y='AudienceRating',  
                           fit_reg=False, hue='Genre', height=10, aspect=1)
```

```
In [47]: plt.show()
```




```
In [48]: # Kernal Density Estimate plot ( KDE PLOT)
# how can i visulize audience rating & critics rating . using scatterplot
```

```
In [49]: k1 = sns.kdeplot(x=movies.CriticRating, y=movies.AudienceRating)


# where do u find more density and how density is distributed across from the the
# center point is kernal this is calld KDE & insteade of dots it visualize like
# we can able to clearly see the spread at the audience ratings
```

```
In [50]: plt.show()
```


```
In [53]: k1 = sns.kdeplot(x=movies.CriticRating, y=movies.AudienceRating, fill=True, cmap
```

```
In [54]: plt.show()
```




```
In [56]: k2 = sns.kdeplot(x=movies.CriticRating, y=movies.AudienceRating, fill=True, cmap
```

```
In [57]: plt.show()
```




```
In [59]: sns.set_style('dark')
k1 = sns.kdeplot(x=movies.BudgetMillions,y=movies.AudienceRating,shade_lowest=False)
```

```
In [60]: plt.show()
```




```
In [61]: sns.set_style('dark')
k1 = sns.kdeplot(x=movies.BudgetMillions,y=movies.AudienceRating)
```

```
In [62]: plt.show()
```



```
In [64]: k2 = sns.kdeplot(x=movies.BudgetMillions,y=movies.CriticRating)
```


```
In [65]: plt.show()
```



```
In [66]: #subplots

f, ax = plt.subplots(1,2, figsize =(12,6))
#f, ax = plt.subplots(3,3, figsize =(12,6))
```


```
In [67]: plt.show()
```



```
In [68]: f, axes = plt.subplots(1,2, figsize =(12,6))

k1 = sns.kdeplot(x=movies.BudgetMillions,y=movies.AudienceRating,ax=axes[0])
k2 = sns.kdeplot(x=movies.BudgetMillions,y=movies.CriticRating,ax = axes[1])
```

```
In [69]: plt.show()
```




```
In [70]: axes
```

```
Out[70]: array([<Axes: xlabel='BudgetMillions', ylabel='AudienceRating'>,
                <Axes: xlabel='BudgetMillions', ylabel='CriticRating'>],
              dtype=object)
```


In [77]: *#Box plots -*

```
w = sns.boxplot(data=movies, x='Genre', y = 'CriticRating')  
plt.show()
```




In [78]: *#violin plot*


```
z = sns.violinplot(data=movies, x='Genre', y = 'CriticRating')  
plt.show()
```



```
In [79]: w1 = sns.boxplot(data=movies[movies.Genre == 'Drama'], x='Year', y = 'CriticRating')
plt.show()
```




```
In [80]: z = sns.violinplot(data=movies[movies.Genre == 'Drama'], x='Year', y = 'CriticRating')
plt.show()
```




```
In [81]: # Createing a Facet grid
```


```
In [82]: g = sns.FacetGrid (movies, row = 'Genre', col = 'Year', hue = 'Genre') #kind of s  
plt.show()
```



```
In [83]: plt.scatter(movies.CriticRating,movies.AudienceRating)
plt.show()
```





```
In [84]: g = sns.FacetGrid (movies, row = 'Genre', col = 'Year', hue = 'Genre')
g = g.map(plt.scatter, 'CriticRating', 'AudienceRating' ) #scatterplots are mapped
plt.show()
```




In [85]: *# you can populated any type of chat.*

```
g = sns.FacetGrid (movies, row = 'Genre', col = 'Year', hue = 'Genre')
g = g.map(plt.hist, 'BudgetMillions') #scatterplots are mapped in facetgrid
plt.show()
```



```
In [86]: #
g = sns.FacetGrid (movies, row = 'Genre', col = 'Year', hue = 'Genre')
kws = dict(s=50, linewidth=0.5, edgecolor='black')
g = g.map(plt.scatter, 'CriticRating', 'AudienceRating', **kws ) #scatterplots are
plt.show()
```



```
In [88]: import seaborn as sns
import matplotlib.pyplot as plt

sns.set_style('darkgrid')
f, axes = plt.subplots(2, 2, figsize=(15, 15))

# KDE Plot 1
k1 = sns.kdeplot(
    x=movies.BudgetMillions,
    y=movies.AudienceRating,
```

```
    ax=axes[0, 0]
)

# KDE Plot 2
k2 = sns.kdeplot(
    x=movies.BudgetMillions,
    y=movies.CriticRating,
    ax=axes[0, 1]
)





k1.set(xlim=(-20, 160))
k2.set(xlim=(-20, 160))


# Violin plot for Drama genre
z = sns.violinplot(
    data=movies[movies.Genre == 'Drama'],
    x='Year',
    y='CriticRating',
    ax=axes[1, 0]
)

# KDE Plot 3 with fill
k4 = sns.kdeplot(
    x=movies.CriticRating,
    y=movies.AudienceRating,
    fill=True,
    cmap='Reds',
    thresh=0.05,
    ax=axes[1, 1]
)

# KDE contour Lines (optional overlay)
k4b = sns.kdeplot(
    x=movies.CriticRating,
    y=movies.AudienceRating,
    cmap='Reds',
    ax=axes[1, 1]
)

plt.tight_layout()
plt.show()
```





```
In [90]: import seaborn as sns
import matplotlib.pyplot as plt

# Set dark background and style
sns.set_style('dark', {'axes.facecolor': 'black'})

# Create subplot grid
f, axes = plt.subplots(2, 2, figsize=(15, 15))

# Plot [0,0] - Budget vs AudienceRating
k1 = sns.kdeplot(
    x=movies.BudgetMillions,
    y=movies.AudienceRating,
    fill=True,
    cmap='inferno',
    thresh=0.05,
    ax=axes[0, 0]
)
k1b = sns.kdeplot(
    x=movies.BudgetMillions,
    y=movies.AudienceRating,
    cmap='cool',
    ax=axes[0, 0]
)
```

```
# Plot [0,1] - Budget vs CriticRating
k2 = sns.kdeplot(
    x=movies.BudgetMillions,
    y=movies.CriticRating,
    fill=True,
    cmap='inferno',
    thresh=0.05,
    ax=axes[0, 1]
)

k2b = sns.kdeplot(
    x=movies.BudgetMillions,
    y=movies.CriticRating,
    cmap='cool',
    ax=axes[0, 1]
)





# Set x-limits for both top plots
k1.set(xlim=(-20, 160))
k2.set(xlim=(-20, 160))


# Plot [1,0] - Violin plot for Drama
z = sns.violinplot(
    data=movies[movies.Genre == 'Drama'],
    x='Year',
    y='CriticRating',
    palette='magma',
    ax=axes[1, 0]
)

# Plot [1,1] - Critic vs Audience rating
k4 = sns.kdeplot(
    x=movies.CriticRating,
    y=movies.AudienceRating,
    fill=True,
    cmap='Blues_r',
    thresh=0.05,
    ax=axes[1, 1]
)

k4b = sns.kdeplot(
    x=movies.CriticRating,
    y=movies.AudienceRating,
    cmap='gist_gray_r',
    ax=axes[1, 1]
)

# Final layout
plt.tight_layout()
plt.show()
```



In []: