

Name:
Roll No:

Practical 4:- To determine maximum temperature using Hadoop MapReduce

Map Reduce : works by breaking the processing into two phases: the map phase and the reduce phase. Each phase has key-value pairs as input and output, the types of which may be chosen by the programmer. The programmer also specifies two functions: the map function and the reduce function.

Hadoop MaxTemperature operation occurs in 3 stages –

Mapper Phase

Reducer Phase

Driver code

Dataset – temperature.txt

```
00670119909999991950051507004+68750+023550FM-  
12+038299999V0203301N00671220001CN9999999N9+00001+99999999999  
  
00430119909999991950051512004+68750+023550FM-  
12+038299999V0203201N00671220001CN9999999N9+00221+99999999999  
  
00430119909999991950051518004+68750+023550FM-  
12+038299999V0203201N00261220001CN9999999N9-00111+99999999999  
  
00430126509999991949032412004+62300+010750FM-  
12+048599999V0202701N00461220001CN0500001N9+01111+99999999999  
  
00430126509999991949032418004+62300+010750FM-  
12+048599999V0202701N00461220001CN0500001N9+00781+99999999999
```

These lines are presented to the map function as the key-value pairs

```
(0, 00670119909999991950051507004...9999999N9+00001+99999999999...) (106,  
00430119909999991950051512004...9999999N9+00221+99999999999...) (212,  
00430119909999991950051518004...9999999N9-00111+99999999999...) (318,  
00430126509999991949032412004...0500001N9+01111+99999999999...) (424,  
00430126509999991949032418004...0500001N9+00781+99999999999...)
```

The keys are the line offsets within the file, which we ignore in our map function. The map function merely extracts the year and the air temperature (indicated in bold text), and emits them as its output (the temperature values have been interpreted as integers):

(1950, 0)

(1950, 22)

Roll No:

(1949, [111, 78])

(1950, [0, 22, -11])

(1949, 111)


(1950, 22)

1) Open virtual box and then start cloudera quickstart



2) Open Eclipse present on the cloudera desktop


Name:
Roll No:




- 3) Create a new Java project clicking: **File -> New -> Project -> Java Project -> Next** (“**MaxTemp**” is the project name).

File	Edit	Source	Refactor	Navigate	Search	Project	Run	Window	Help
New	Shift+Alt+N					>	Java Project		
Open File...							Project...		
Close	Ctrl+W						Package		
Close All	Shift+Ctrl+W						Class		
Save	Ctrl+S						Interface		
Save As...							Enum		
Save All	Shift+Ctrl+S						Annotation		
Revert							Source Folder		
Move...							Java Working Set		
Rename...	F2						Folder		
Refresh	F5						File		
Convert Line Delimiters To						>	Untitled Text File		
							JUnit Test Case		




Name:
Roll No:



- 4) Adding the Hadoop libraries to the project Click on **Libraries** -> Add External JARs
Click on **File System** -> **usr** -> **lib** -> Hadoop Select all the **libraries (JAR Files)** -> click **OK** Click on **Add External jars**, -> **client** -> select all **jar files** -> **ok** -> **Finish**.






Name:
Roll No:




- 5) Right Click on the name of Project “MaxTemp” -> New -> class don’t write anything for package Write Name Textbox write “MaxTemp” -> Finish Then MaxTemp.java window will pop up.

Name:
Roll No:



Name:
Roll No:



Source code:

```
import java.io.IOException;

import java.util.*;

import org.apache.hadoop.fs.Path;

import org.apache.hadoop.io.LongWritable;

import org.apache.hadoop.io.Text;

import org.apache.hadoop.io.IntWritable;

import org.apache.hadoop.mapreduce.Reducer.Context;

import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;

import org.apache.hadoop.mapreduce.lib.input.TextInputFormat;

import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;

import org.apache.hadoop.mapreduce.lib.output.TextOutputFormat;

import org.apache.hadoop.mapreduce.lib.output.TextOutputFormat;

import org.apache.hadoop.mapreduce.lib.input.TextInputFormat;

import org.apache.hadoop.mapreduce.Job;

import org.apache.hadoop.mapreduce.Mapper;

import org.apache.hadoop.mapreduce.Reducer;

import org.apache.hadoop.conf.Configuration;
```

Name:
Roll No:

```
//import MaximumTemp.MaxTemperatureMapper;
//import MaxTemp.MaxTemperatureReducer;
public class MaxTemp {
// Mapper
/*MaxTemperatureMapper class is static
* And extends Mapper abstract class
* having four Hadoop generics type
* Long Writable, Text, Text, Text.
*/
public static class MaxTemperatureMapper extends
Mapper<LongWritable, Text, Text, IntWritable> {
// the data in our data set with
// this value is inconsistent data
//public static final int MISSING = 9999;

public void map(LongWritable key, Text value, Context context)
throws IOException, InterruptedException {
String line=value.toString();
String year=line.substring(15, 19);
int airtemp;
if(line.charAt(87)=='+')
{
airtemp=Integer.parseInt(line.substring(88,92));
}
else
airtemp=Integer.parseInt(line.substring(87,92));
String q=line.substring(92,93);
if(airtemp!=9999 && q.matches("[01459]"))
{

context.write(new Text(year), new IntWritable(airtemp));
}
}
```

MSc Part-I Sem-II

BDT

Name:
Roll No:

```
}  
}  
}  
  
// Reducer  
  
/*MaxTemperatureReducer class is static  
and extends Reducer abstract class  
having four Hadoop generics type  
Text, Text, Text, Text.  
*/  
  
public static class MaxTemperatureReducer extends  
Reducer<Text, IntWritable, Text, IntWritable> {  
/**  
 * @method reduce  
 * This method takes the input as key and  
 * list of values pair from the mapper,  
 * it does aggregation based on keys and  
 * produces the final context.  
 */  
  
public void reduce(Text key, Iterable<IntWritable> values, Context context)  
throws IOException, InterruptedException {  
    int maxvalue= Integer.MIN_VALUE;  
    for (IntWritable value : values) {  
        maxvalue=Math.max(maxvalue, value.get());  
    }  
    context.write(key, new IntWritable(maxvalue));  
}  
}  
  
/**  
 * @method main  
 * This method is used for setting  
MSc Part-I Sem-II
```

BDT

Name:
Roll No:

```
* all the configuration properties.  
* It acts as a driver for map-reduce  
* code.  
*/  
  
public static void main(String[] args) throws Exception {  
    // reads the default configuration of the  
    // cluster from the configuration XML files  
    Configuration conf = new Configuration();  
    // initializing the job with the  
    // default configuration of the cluster  
    // Job job = new Job(conf, "weather example");  
    Job job = Job.getInstance(conf, "weather example");  
    // Assigning the driver class name  
    job.setJarByClass(MaxTemp.class);  
    // Key type coming out of mapper  
    // job.setMapOutputKeyClass(Text.class);  
    // value type coming out of mapper  
    // job.setMapOutputValueClass(Text.class);  
    // Defining the mapper class name  
    job.setMapperClass(MaxTemperatureMapper.class);  
    // Defining the reducer class name  
    job.setReducerClass(MaxTemperatureReducer.class);  
    // defining input Format class which is  
    // responsible to parse the dataset  
    // into a key value pair  
    job.setInputFormatClass(TextInputFormat.class);  
    // Defining output Format class which is  
    // responsible to parse the dataset  
    // into a key value pair  
    job.setOutputFormatClass(TextOutputFormat.class);
```

Roll No:

```
job.setOutputKeyClass(Text.class);

job.setOutputValueClass(IntWritable.class);

FileInputFormat.addInputPath(job, new Path(args[0]));



FileOutputFormat.setOutputPath(job, new Path(args[1]));

System.exit(job.waitForCompletion(true) ? 0 : 1);



}

}
```


- 6) Right Click on the project name **MaxTemp** -> **Export** -> **Java** -> **JAR File** -> **Next** -> for select the export destination for **JAR** file: **browse** -> Name : **MaxTemp.jar** -> save in folder -> **cloudera** -> **Finish** -> **OK**



Name:
Roll No:




- 7) Open terminal & type `->hdfs dfs -ls /`
HDFS Command to display the list of Files and Directories in HDFS. It lists the contents of the directory specified by path, showing the names, permissions, owner, size and modification date for each entry.



Name:
Roll No:

- 8) Input file named as temperature which is present on desktop i.e. in local file system.



- 9) Now we have to move this input file to hdfs. For this we create a directory on hdfs using command
->hdfs dfs -mkdir /tempip.
So here I create tempip directory.

```
[cloudera@quickstart ~]$ hdfs dfs -mkdir /tempip  
[cloudera@quickstart ~]$ hdfs dfs -ls /tempip
```

Then we can verify whether this directory is created or not using ls command **hdfs dfs -ls /**

```
[cloudera@quickstart ~]$ hdfs dfs -ls /  
Found 16 items  
drwxrwxrwx - hdfs supergroup 0 2017-10-23 09:15 /benchmarks  
drwxr-xr-x - cloudera supergroup 0 2021-05-24 13:58 /forcopy  
drwxr-xr-x - hbase supergroup 0 2021-06-14 20:08 /hbase  
drwxr-xr-x - cloudera supergroup 0 2021-06-05 00:06 /inputdir  
drwxr-xr-x - cloudera supergroup 0 2021-06-06 02:14 /newdir  
drwxr-xr-x - cloudera supergroup 0 2021-06-05 06:34 /op1  
-rw-r--r-- 4 cloudera supergroup 155 2021-06-06 03:17 /output_abc  
drwxr-xr-x - cloudera supergroup 0 2021-06-06 02:28 /output_new  
drwxr-xr-x - cloudera supergroup 0 2021-06-05 00:37 /outputdir  
drwxr-xr-x - cloudera supergroup 0 2021-06-06 04:32 /rjc  
drwxr-xr-x - cloudera supergroup 0 2021-05-24 13:55 /solr  
drwxr-xr-x - cloudera supergroup 0 2021-06-20 11:36 /tempip  
-rw-r--r-- 1 cloudera supergroup 4049 2021-06-06 03:53 /test_1  
drwxrwxrwt - hdfs supergroup 0 2021-05-24 10:39 /tmp  
drwxr-xr-x - hdfs supergroup 0 2017-10-23 09:17 /user  
drwxr-xr-x - hdfs supergroup 0 2017-10-23 09:17 /var  
[cloudera@quickstart ~]$
```

- 10) Move the input file i.e. temperature to this directory created in hdfs by using either put command or copyFromLocal command.
hdfs dfs -put /home/cloudera/Desktop/temperature /tempip/

```
[cloudera@quickstart ~]$ hdfs dfs -put /home/cloudera/Desktop/temperature /tempip/  
[cloudera@quickstart ~]$
```

- 11) Now checking whether the “temperature” present in /tempip directory of hdfs or not using **hdfs dfs -ls/tempip** command


```
[cloudera@quickstart ~]$ hdfs dfs -ls /tempip  
Found 1 items  
-rw-r--r-- 1 cloudera supergroup 530 2021-06-20 11:50 /tempip/temperature  
[cloudera@quickstart ~]$
```

- 12) As we can see “temperature” file is present in /tempip directory of hdfs. Now we will see the content of this file using **hdfs dfs -cat /tempip/temperature** command.

Name:
Roll No:


```
[cloudera@quickstart ~]$ hdfs dfs -cat /tempip/temperature
0067011990999991950051507004+68750+023550FM-12+038299999V0203301N00671220001CN9999999N9+00001+9999999999
0043011990999991950051512004+68750+023550FM-12+038299999V0203201N00671220001CN9999999N9+00221+9999999999
0043011990999991950051518004+68750+023550FM-12+038299999V0203201N00671220001CN9999999N9+00111+9999999999
0043012650999991949032412004+62300+010750FM-12+048599999V0202701N00461220001CN0500001N9+01111+9999999999
0043012650999991949032418004+62300+010750FM-12+048599999V0202701N00461220001CN0500001N9+00781+9999999999
[cloudera@quickstart ~]$
```

- 13) Running Mapreduce Program on Hadoop, syntax is `hadoop jar jarFileName.jar ClassName /InputFileAddress /outputdir`
i.e. `hadoop jar /home/cloudera/MaximumTemp.jar MaxTemp /tempip/temperature /tempop1`



```
cloudera@quickstart:~$ hadoop jar /home/cloudera/MaximumTemp.jar MaxTemp /tempip/temperature /tempop1
21/06/20 12:30:05 INFO client.RMProxy: Connecting to ResourceManager at /0.0.0.0:8032
21/06/20 12:30:13 WARN mapreduce.JobResourceUploader: Hadoop command-line option parsing not performed. Implement the Tool interface a
nd execute your application with ToolRunner to remedy this.
21/06/20 12:30:17 INFO input.FileInputFormat: Total input paths to process : 1
21/06/20 12:30:18 INFO mapreduce.JobSubmitter: number of splits:1
21/06/20 12:30:22 INFO mapreduce.JobSubmitter: Submitting tokens for job: job_1624193345836_0001
21/06/20 12:30:53 INFO impl.YarnClientImpl: Submitted application 1624193345836_0001
21/06/20 12:30:53 INFO mapreduce.Job: The url to track the job: http://quickstart.cloudera:8088/proxy/application_1624193345836_0001/
21/06/20 12:30:53 INFO mapreduce.Job: Running job: job_1624193345836_0001
21/06/20 12:33:30 INFO mapreduce.Job: Job job_1624193345836_0001 running in uber mode : false
21/06/20 12:33:31 INFO mapreduce.Job: map 0% reduce 0%
21/06/20 12:35:47 INFO mapreduce.Job: map 100% reduce 0%
21/06/20 12:37:54 INFO mapreduce.Job: map 100% reduce 100%
21/06/20 12:37:59 INFO mapreduce.Job: Job job_1624193345836_0001 completed successfully
21/06/20 12:38:03 INFO mapreduce.Job: Counters: 49
File System Counters
  FILE: Number of bytes read=61
  FILE: Number of bytes written=207339
  FILE: Number of read operations=0
  FILE: Number of large read operations=0
  FILE: Number of write operations=0
  HDFS: Number of bytes read=645
  HDFS: Number of bytes written=17
  HDFS: Number of read operations=6
  HDFS: Number of large read operations=0
  HDFS: Number of write operations=2
Job Counters
  Launched map tasks=1
  Launched reduce tasks=1
```

Map-Reduce Framework



```
Map-Reduce Framework
Map input records=5
Map output records=5
Map output bytes=45
Map output materialized bytes=61
Input split bytes=115
Combine input records=0
Combine output records=0
Reduce input groups=2
Reduce shuffle bytes=61
Reduce input records=5
Reduce output records=2
Spilled Records=10
Shuffled Maps =1
Failed Shuffles=0
Merged Map outputs=1
GC time elapsed (ms)=1169
CPU time spent (ms)=5230
Physical memory (bytes) snapshot=307490008
Virtual memory (bytes) snapshot=301425868
Total committed heap usage (bytes)=152965128
Shuffle
  Errors
    BAD_ID=0
    CONNECTION=0
    IO_ERROR=0
    WRONG_LENGTH=0
    WRONG_MAP=0
    WRONG_REDUCE=0
File Input Format Counters
  Bytes Read=530
```

- 14) Verify the content of tempop1 directory and in that part-r file has the actual output by using the command `Hdfs dfs -cat /tempop1/part-r-00000`. This will give us final output. The same file can also be accessed using a browser. For every execution of this program we need to delete the output directory or give a new name to the output directory every time.

Name:

Roll No:

- checking whether the tempop1 directory is created in hdfs or not using command

-> **hdfs dfs -ls /**

```
[cloudera@quickstart ~]$ hdfs dfs -ls /
Found 17 items
drwxrwxrwx - hdfs supergroup 0 2017-10-23 09:15 /benchmarks
drwxr-xr-x - cloudera supergroup 0 2021-05-24 13:58 /forcopy
drwxr-xr-x - hbase supergroup 0 2021-06-14 20:08 /hbase
drwxr-xr-x - cloudera supergroup 0 2021-06-05 00:06 /inputdir
drwxr-xr-x - cloudera supergroup 0 2021-06-06 02:14 /newdir
drwxr-xr-x - cloudera supergroup 0 2021-06-05 06:34 /op1
-rw-r--r-- 4 cloudera supergroup 155 2021-06-06 03:17 /output_abc
drwxr-xr-x - cloudera supergroup 0 2021-06-06 02:28 /output_new
drwxr-xr-x - cloudera supergroup 0 2021-06-05 00:37 /outputdir
drwxr-xr-x - cloudera supergroup 0 2021-06-06 04:32 /rjc
drwxr-xr-x - cloudera supergroup 0 2021-05-24 13:55 /solr
drwxr-xr-x - cloudera supergroup 0 2021-06-20 11:50 /tempip
drwxr-xr-x - cloudera supergroup 0 2021-06-20 12:37 /tempop1
-rw-r--r-- 1 cloudera supergroup 4049 2021-06-06 03:53 /test_1
drwxrwxrwt - hdfs supergroup 0 2021-05-24 10:39 /tmp
drwxr-xr-x - hdfs supergroup 0 2017-10-23 09:17 /user
drwxr-xr-x - hdfs supergroup 0 2017-10-23 09:17 /var
[cloudera@quickstart ~]$
```

Check what we have inside this **tempop1** directory using command as

-> **hdfs dfs -ls/tempop1**

```
[cloudera@quickstart ~]$ hdfs dfs -ls /tempop1
Found 2 items
-rw-r--r-- 1 cloudera supergroup 0 2021-06-20 12:37 /tempop1/ SUCCESS
-rw-r--r-- 1 cloudera supergroup 17 2021-06-20 12:37 /tempop1/part-r-00000
[cloudera@quickstart ~]$
```

Now we want to read the content of the **part-r-00000** file which present inside the **tempop1** using command

➤ **hdfs dfs -cat /tempop1/part-r-00000**

```
[cloudera@quickstart ~]$ hdfs dfs -cat /tempop1/part-r-00000
1949 111
1950 22
[cloudera@quickstart ~]$
```


So the maximum temperature for the year 1949 is 111 and for the year 1950 is 22.

15) The same file can also be accessed using a browser.


Browse the Directory by

Hadoop->**HDFS Namenode**->**Utilities** ->**Browse the file system**

Name:
Roll No:




Permission	Owner	Group	Size	Last Modified	Replication	Block Size	Name
drwxr-xr-x	cloudera	supergroup	0 B	Sat Jun 05 06:34:49 -0700 2021	0	0 B	tmp1
-rw-r--r--	cloudera	supergroup	155 B	Sun Jun 06 03:17:44 -0700 2021	4	128 MB	output_abc
drwxr-xr-x	cloudera	supergroup	0 B	Sun Jun 06 02:28:28 -0700 2021	0	0 B	output_new
drwxr-xr-x	cloudera	supergroup	0 B	Sat Jun 05 00:37:29 -0700 2021	0	0 B	outputdir
drwxr-xr-x	cloudera	supergroup	0 B	Sun Jun 06 04:32:33 -0700 2021	0	0 B	rjc
drwxr-xr-x	cloudera	supergroup	0 B	Mon May 24 13:55:18 -0700 2021	0	0 B	sofr
drwxr-xr-x	cloudera	supergroup	0 B	Sun Jun 20 11:50:03 -0700 2021	0	0 B	tempip
drwxr-xr-x	cloudera	supergroup	0 B	Sun Jun 20 12:37:55 -0700 2021	1	128 MB	tempop1
-rw-r--r--	cloudera	supergroup	3.95 KB	Sun Jun 06 03:53:28 -0700 2021	1	128 MB	test_1
drwxrwxrwt	hdfs	supergroup	0 B	Mon May 24 10:39:39 -0700 2021	0	0 B	tmp
drwxr-xr-x	hdfs	supergroup	0 B	Mon Oct 23 09:17:33 -0700 2017	0	0 B	user
drwxr-xr-x	hdfs	supergroup	0 B	Mon Oct 23 09:17:24 -0700 2017	0	0 B	var



Permission	Owner	Group	Size	Last Modified	Replication	Block Size	Name
-rw-r--r--	cloudera	supergroup	0 B	Sun Jun 20 12:37:55 -0700 2021	1	128 MB	SUCCESS
-rw-r--r--	cloudera	supergroup	17 B	Sun Jun 20 12:37:52 -0700 2021	1	128 MB	part-r-00000

Now downloading the **part-r-00000** file.




Inside the **part-r-00000** file it will have the same output as we are getting after executing using command.

-hadoop jar /home/cloudera/MaximumTemp.jar MaxTemp /tempip/temperature/tempop1

Name:

Roll No:



NOTE: - For every execution of this program we need to delete the output directory or give a new name to the output directory every time.