Marwadi University

Faculty of Computer Applications

Enrolment No:		92500566013	
Student Name		Shaikriyana	
Subject	**DBMS-ii**	**Academic Year**	**2025-2026**
Subject Code	**05DS0204**	**Subject Type**	**Central Level**

Index

Sr. no	Details	Submission Date
1	Write a PL/SQL block that uses a cursor attribute SQL%ROWCOUNT to raise the basic salary of employees by 10% in department number 10 and also display the appropriate message based on the existence to the record in the EMP table (Use Implicit Cursor)	25-02-26
2	Write a PL/SQL block that uses a cursor attribute %ISOPEN and %NOTFOUND to raise the basic salary of employees of department number 20 by 5% and also display the appropriate message based on the existence to the record in the EMP table Whenever any such raise is given to the employees, a record for the same is maintained in the emp_update table (Perform using both Implicit and Explicit Cursor)	26-02-26

3	a cursor Write a PL/SQ block that uses attribute %ROWCOUN to displaythe name, department and basic salary of first 5	27-02-26

Marwadi University

Faculty of Computer Applications

	the highest basic salary (Use Explicit employees getting Cursor) L/SQL ng loop disp ay	
4	Write a P block usi a cursor FOR to name and the basic salary of top 3 highest paid employees. (Use Cursor For Loop)	28-02-26
5	Write a PL/SQL block using a parameterized cursor that displays the department wise basic salary of each employee and department wise total gross salary (Parameterized Cursor and Use Cursor For Loop)	1-03-2026

Definition 1:

Write a PL/SQL block that uses a cursor attribute SQL%ROWCOUNT to raise the basic salary of employees by 10% that are working in department number 10 and also display the appropriate message based on the existence to the record in the EMP table. (Use Implicit Cursor)

```
set serveroutput on

begin
update employee set BASICSAL=basicsal + (Basicsal
*0.10) where deptno=10;
dbms_output.put_line('Salary Updated..');
if SQL%FOUND then
dbms_output.put_line('total no of records
updated are:'||SQL%ROWCOUNT);
end if;
end;
/
```

Definition 2:

Write a PL/SQL block that uses a cursor attribute %ISOPEN and %NOTFOUND to raise the basic salary of employees of department number 20 by 5% and also display the appropriate message based on the existence to the record in the EMP table. Whenever any such raise is given to the employees, a record for the same is maintained in the emp_update table. (Perform using both Implicit and Explicit Cursor) --IMPLICIT CURSOR

```
serveroutput on
begin
    update employee set basicsal=basicsal+(basicsal*0.05) where deptno=20;
    if sql%isopen then
        dbms_output.put_line('cursor is open');
    end if;
    if sql%notfound then
        dbms_output.put_line('cursor is closed');
    else
    dbms_output.put_line('total updated
records:'||SQL%ROWCOUNT);
end if;

end;
/
```

Definition 2:

Write a PL/SQL block that uses a cursor attribute %ISOPEN and %NOTFOUND to raise the basic salary of employees of department number 20 by 5% and also display the appropriate message based on the existence to the record in the EMP table. Whenever any such raise is given to the employees, a record for the same is maintained in the emp_update table. (Perform using both Implicit and Explicit Cursor) --EXPLICIT CURSOR

```
set serveroutput on
declare
    cursor def2 is select basicsal from employee where
    deptno=10;
    sal employee.basicsal%type;
    increment number;
begin
open def2;
if def2%isopen then
loop
    fetch def2 into sal;
    exit when def2%notfound;
    increment:=sal*0.5;
    update employee set basicsal=sal+increment
    where deptno=10;
    end loop;
    dbms_output.put_line('salary is updated');
close def2;
else
    dbms_output.put_line('cursor is not open');
end if;
end;
/
```

Definition 3:

Write a PL/SQL block that uses a cursor attribute %ROWCOUNT to display the name, department and basic salary of first 5 employees getting the highest basic salary. (Use Explicit Cursor)

```
set serveroutput on
declare

cursor def3 IS select
name,DEPTNAME,basicsal from employee order by
basicsal desc;
nm employee.name%TYPE;
dnm employee.deptname%TYPE;
sal employee.basicsal%TYPE;
n number;
begin
open def3;
loop
fetch def3 into nm,dnm,sal;
exit when def3%NOTFOUND;
dbms_output.put_line('Name:'||nm);
dbms_output.put_line('Department
Name:'||dnm);
dbms_output.put_line('basic salaray:'||sal);
n:=def3%ROWCOUNT;
end loop;
close def3;
dbms_output.put_line('total rows:'||n);

end;
/
```

Definition 4:

Write a PL/SQL block using a cursor FOR loop to display name and the basic salary of top 3 highest paid employees. (Use Cursor For Loop)

```
set serveroutput on
begin
    for r1 in (select name,basicsal from (select name,basicsal from employee
order by basicsal DESC)where rownum<=3)
    loop
    dbms_output.put_line('name:'||r1.name);
    dbms_output.put_line('salary:'||r1.basicsal);
    end loop;

end;
/
```

Definition 5:

Write a PL/SQL block using a parameterized cursor that displays the department wise basic salary of each employee and department wise total gross salary. (Parameterized Cursor and Use Cursor For Loop)--parameterized cursor

```
set serveroutput on
DECLARE
Cursor c1(xdeptno number) IS
select name,deptno,basicsal,gross from employee
where deptno= xdeptno;
x c1%ROWTYPE; --rowtype then
BEGIN
Open c1(20);
loop
fetch c1 INTO x;
exit when C1%NOTFOUND;
dbms_output.put_line('name: '||
x.name||' Deptno: '|| x.deptno||'
salary: '|| x.basicsal||'gross salary:'||x.gross);
end loop;
close c1;
END;
/
```

Definition 5:
Write a PL/SQL block using a parameterized cursor that displays the department wise basic salary of each employee and department wise total gross salary. (Parameterized Cursor and Use Cursor For Loop)-- cursor for loop

```
set serveroutput on
declare

cursor cur2(dno number) IS select
name,deptno,basicsal,gross from employee
where deptno=dno;
begin
for r1 IN cur2(10)
loop
dbms_output.put_line('name: '||
r1.name||' Deptno: '|| r1.deptno||'
salary: '|| r1.basicsal||'gross salary:'||r1.gross);
end loop;
end;
/
```