

5.9 Lab: Configure Management VLAN Settings - CLI

Candidate: COMPTIA COMPTIA ()

Time Spent: 00:08

Score: 0%

Task Summary

Required Actions

-
- ✗ Set the IP address for the switch
-
- ✗ Set the default gateway address
-
- ✗ Save the changes [Show Details](#)
-

Explanation

Complete this lab as follows:

1. Configure the IP address and subnet mask for the VLAN 1 interface.
 - a. Select **Switch**.
 - b. From the switch terminal, press **Enter** to get started.
 - c. At the Switch> prompt, type **enable** and press **Enter**.
 - d. At the Switch# prompt, type **configure terminal** and press **Enter**.
 - e. At the Switch(config)# prompt, type **interface vlan1** and press **Enter**.
 - f. At the Switch(config-if)# prompt, type **ip address 192.168.11.250 255.255.255.0** and press **Enter**.
 - g. Type **exit** and press **Enter**.
2. Configure the default gateway.
 - a. At the Switch(config)# prompt, type **ip default-gateway 192.168.11.254** and press **Enter**.
 - b. At the prompt, type **exit** and press **Enter**.
3. Verify the configuration changes.
 - a. At the prompt, type **show run** and press **Enter**.
 - b. Press the **space bar** as needed to verify that the correct changes were made.
 - c. Type **any key** to exit show command.
4. Save your changes to the startup-config file.
 - a. At the Switch# prompt, type **copy run start** and press **Enter**.
 - b. Press **Enter** to begin building the configuration.
 - c. Press **Enter** to return to the prompt.