

3.7 LAB

Complete this lab as follows:

1. Log in to the CISCO switch.
 1. Maximize the Google Chrome window for better viewing.
 2. In the Username and Password fields, enter **cisco** (the password is case sensitive).
 3. Select **Log In**.
2. Enable Jumbo Frames.
 1. From the left pane, expand and select **Port Management > Port Settings**.
 2. For Jumbo Frames, select **Enable**.
 3. Select **Apply**.
3. Save the changes to the switch's startup configuration file.
 1. From the upper right of the switch window, select **Save**.
 2. For *Source File Name*, make sure **Running configuration** is selected.
 3. For *Destination File Name*, make sure **Startup configuration** is selected.
 4. Select **Apply**.
 5. Select **OK**.
 6. Select **Done**.
4. Reboot the switch.
 1. From the left pane, under *Administration*, select **Reboot**.
 2. Select **Reboot** to reboot the switch immediately.
 3. Select **OK**.
5. Log in to the Cisco switch and check switch statistics for any errors.
 1. In the Username and Password fields, enter **cisco** (the password is case sensitive).
 2. Select **Log In**.
 3. From the left pane, expand and select **Status and Statistics > RMON > Statistics**.
 4. For *Interface*, use the drop-down list to select **GE28**.
 5. Review the statistics for Undersize, Oversize, Jabbers, and Collisions.
 6. Answer the questions.